

IDEAL Version: ID14_0C_12
IDF

Format: VISION SERVICE RT 200MD Vertical Scale: 1:200 Graphics File Created: 24-May-2009 13:21

PIP SUMMARY

arcVISION Gamma Ray Delta-T Compressional, Real-Time
Resistivity ROBB (Density Bottom)
TNPH (Thermal Neutron Porosity)

ARC Gamma Ray, Real-Time (ARC_GR_RT) 0 (GAPI) 200		Thermal Neutron Porosity, Real-Time (TNPH_ADN_RT) 45 (PU) -15	
Average Borehole Diameter, Real-Time (ADIA_ADN_RT) 6 (IN) 16		ARC BHCorr Phase-Shift Resistivity 40-in. at 2 MHz, Real-Time (P40H_RT) 0.2 (OHMM) 2000	
MWD Collar RPM (CRPM_RT) (RPM) 0 250		Bulk Density, Bottom, Real-Time Computed Downhole (ROBB_DH_RT) 1.85 (G/C3) 2.85	
ROP*5 (ROP5) 200 (M/HR) 0		ARC BHCorr Phase-Shift Resistivity 28-in. at 2 MHz, Real-Time (P28H_RT) 0.2 (OHMM) 2000	
PKPK_RPM (Stick_RT) (RPM) 0 500		Photoelectric Factor, Bottom, Real-Time (PEB_RT) 0 (----) 10	
		Bulk Density Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_RT) -0.75 (G/C3) 0.25	
		Delta-T Compressional, Real-Time (DTCO_RT) 600 (US/M) 100	



























































































































