

Longtom-4 H LWD RT 500MD

IDEAL Version: ID13_OC_08 <MD> Vertical Scale: 1:500

Graphics File Created: 04-Aug-2008 05:11

PIP SUMMARY

Density Samples ▬

▬ Gamma Ray Samples

Neutron Samples ▬

▬ Resistivity Samples

Ultrasonic Caliper, Average Diameter, Real-Time, Computed Downhole (UCAV_DH_ECO_RT) (IN)			Thermal Neutron Porosity, Average, Real-Time (TNPH_ECO_RT) (PU)
6 ————— 16			45 ————— -15
Raw Formation Sigma, Average, Real-Time, Computed Downhole (RFSA_DH_ECO_RT) (CU)		ARC Phase Shift Resistivity 40 inch at 2 MHz, Real-Time (P40H_ECO_RT) (OHMM)	Bulk Density, Bottom, Real-Time, Computed Downhole (ROBB_DH_ECO_RT) (G/C3)
0 ————— 50		0.2 ————— 2000	1.85 ————— 2.85
Gamma Ray, Average, Real-Time (GRMA_ECO_RT) (GAPI)	MWD Collar RPM (CRPM_RT) (RPM)	ARC Phase Shift Resistivity 28 inch at 2 MHz, Real-Time (P28H_ECO_RT) (OHMM)	Photoelectric Factor, Bottom, Real-Time, Computed Downhole (PEB_DH_ECO_RT) (-----)
0 ————— 200	0 ————— 400	0.2 ————— 2000	0 ————— 10
ROP*5 (ROP5) (M/HR)	PKPK_RPM (Stick_RT) (RPM)	ARC Phase Shift Resistivity 16 inch at 2 MHz, Real-Time (P16H_ECO_RT) (OHMM)	Bulk Density Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_ECO_RT) (G/C3)
200 ————— 0	0 ————— 400	0.2 ————— 2000	-0.25 ————— 0.25







