

Madfish-1 EcoScope Service 500TVD RT

Format: Nero-2 ST1 Ecoscope Service – sonicVISIO      Vertical Scale: 1:500      Graphics File Created: 07-Dec-2008 07:48

|                                                                                                         |  |                                                                                                                   |  |                                                                                                  |                                                                                                           |
|---------------------------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Gamma Ray, Average, Real-Time, Computed Downhole (GRMA_DH_ECO_RT)</b><br>0 (GAPI) 200                |  | <b>Thermal Neutron Porosity, Average, Real-Time (TNPH_ECO_RT)</b><br>0.45 (V/V) -0.15                             |  | <b>Delta-T Compressional, Real Time (DTCO_RT)</b><br>140 (US/F) 40                               |                                                                                                           |
| <b>Ultrasonic Caliper, Average Diameter, Real-Time, Computed Downhole (UCAV_DH_ECO_RT)</b><br>6 (IN) 16 |  | <b>Eco Uncorrected Phase Shift Resistivity 40 inch at 2MHz, Real-Time (P40H_UNC_DH_ECO_RT)</b><br>0.2 (OHMM) 2000 |  | <b>Photoelectric Factor, Bottom, Real-Time, Computed Downhole (PEB_DH_ECO_RT)</b><br>0 (----) 10 | <b>Bulk Density Correction, Bottom, Real-Time Computed Downhole (DRHB_DH_ECO_RT) (G/C3)</b><br>-0.25 0.25 |
| <b>ROP*5 (ROP5) (M/HR)</b><br>200 0                                                                     |  | <b>Eco Uncorrected Phase Shift Resistivity 16 inch at 2MHz, Real-Time (P16H_UNC_DH_ECO_RT)</b><br>0.2 (OHMM) 2000 |  | <b>Bulk Density, Bottom, Real-Time, Computed Downhole (ROBB_DH_ECO_RT) (G/C3)</b><br>1.95 2.95   | <b>Downhole Annulus Temperature, Real Time, Computed Downhole (DHAT_DH_ECO_RT) (DEGC)</b><br>0 200        |
| <b>MWD Collar RPM (CRPM_RT) (RPM)</b><br>0 200                                                          |  |                                                                                                                   |  | <b>Coherence at Compressional Peak, Real-Time (CHCO_RT) (----)</b><br>1 -4                       |                                                                                                           |







