

DEPTH SUMMARY LISTING

Depth System Equipment

Depth Measuring Device	Tension Device	Logging Cable
------------------------	----------------	---------------

Depth Control Parameters	
--------------------------	--

Depth Control Remarks	
-----------------------	--

1. Schlumberger depth control policy followed 2. IDW used as primary depth control, Z-chart used for secondary depth control 3. Log correlated three times during coring program, as per client request 4. 5. 6.

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OS1:	HLRA-PEX-HNGS
OS2:	FMI-SS
OS3:	VSI-4
OS4:	Perfo
OS5:	

- Wombat 4 is an appraisal well in Gippsland Basin

- Toolstring run as per tool sketch.

- MSCT configured for small hole. Standoffs and bumpers removed.

- 33 cores attempted in total.

- Cores packed and inspected by drilling supervisor and wellsite geologist.

– Core logs presented in order that the cores were taken, not in order of depth.

DOWNHOLE EQUIPMENT			
LEH-QT LEH-QT 1183			12.97
SGT-P SGH-K 3037 SGC-V 10245 SGD-TAB	Gamma Ray		12.08
MSCT-AA MCEC-AA 181 ECH-KS 113 MCMU-AA 174 BIT-AA MCFU_1-AA 17			10.40

Tension MSCT

TOOL ZERO

TOOL BOTTOM

MAXIMUM STRING DIAMETER 5.25 IN
MEASUREMENTS RELATIVE TO TOOL ZERO
ALL LENGTHS IN METERS

Client: Lakes Oil

Well: Wombat 4

Field: Wombat

State: Victoria

Country: Australia

Rig Name: Hunt 2

Reference Datum: Derrick Floor

Elevation: 26.6 m

Production String	(in)		(m)		Well Schematic			(m)		(in)		Casing String
	OD	ID	MD					MD	OD	ID		
								0.0	7.000			Casing String
								0.0	9.625			Casing String
								299.0	9.625			Casing Shoe
								299.0	8.500			Borehole Segment
								1361.3	7.000			Casing Shoe

					1361.3 1361.0	8.500 6.125	Borehole Segment Bottom Borehole Segment
					2500.0	6.125	Borehole Segment Bottom

Schlumberger

MSCT Summary

MAXIS Field Log

MSCT CORE REPORT

Core	Depth	Time Coring Began	Remark
1	10.6 (M)	20:48:44	Surface Check
2	1006.3 (M)		Motor Check at 1000m
3	1975.0 (M)	22:34:42	Core
4	1946.0 (M)	22:41:01	Core
5	1888.0 (M)	22:51:23	Core
6	1849.0 (M)	22:59:26	Core
7	1833.0 (M)	23:04:17	Core
8	1804.0 (M)	23:10:09	Core
9	1762.0 (M)	23:15:58	Core

10	1729.0 (M)	23:21:05	Core
11	1636.0 (M)	23:32:29	Core
12	1632.0 (M)	23:38:02	Core
13	1560.0 (M)	23:51:49	Core
14	1500.0 (M)	23:59:29	Core
15	1467.0 (M)	00:12:23	Core
16	1467.7 (M)	00:17:58	Core
17	1436.0 (M)	00:26:14	Core
18	1424.0 (M)	00:31:24	Core
19	1426.8 (M)	00:36:27	Core
20	1406.0 (M)	00:42:11	Core
21	1406.5 (M)	00:48:08	Core
22	1405.5 (M)	00:54:17	Core
23	1383.0 (M)	01:00:12	Core
24	1384.9 (M)	01:05:40	Core
25	2460.0 (M)	02:22:38	Core
26	2445.0 (M)	02:28:54	Core
27	2371.0 (M)	02:47:04	Core
28	2363.0 (M)	02:58:10	Core
29	2302.0 (M)	03:10:39	Core
30	2227.0 (M)	03:23:37	Core
31	2209.0 (M)	03:34:43	Core
32	2190.0 (M)	03:43:24	Core
33	2149.0 (M)	03:50:01	Core
34	2075.0 (M)	03:58:16	Core
35	2040.0 (M)	04:03:49	Core



MSCT Station Logs

MAXIS Field Log

Company:

Well:

Output DLIS Files

DEFAULT

MSCT_011LTP

FN:10

PRODUCER


14-Nov-2009 22:33

1975.0 M

Elapsed Time (s)	Event Summary
205.2	Anchor Shoe Closed
145.6	Coring Stopped
95.2	Coring Started
52.8	Anchor Shoe Open
44.4	Marker 3
44.4	Core 3 at 1975.0(M)
0.0	Coring Stopped

PIP SUMMARY

Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
-----------	-------------	-------







Time Mark Every 60 S		
PIP SUMMARY		
Parameters		
DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN
Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 14-Nov-2009 22:39		
OP System Version: 17C0-154		
MSCT-AA	17C0-154	SGT-P 17C0-154
Output DLIS Files		
DEFAULT	MSCT_014LTP	FN:13 PRODUCER 14-Nov-2009 22:39

Company:	Well:
Output DLIS Files	
DEFAULT	MSCT_017LTP FN:16 PRODUCER 14-Nov-2009 22:49 1888.0 M

Elapsed Time (s)	Event Summary
242.0	Anchor Shoe Closed
177.6	Coring Stopped
96.0	Coring Started
66.0	Anchor Shoe Open
61.2	Marker 5
61.2	Core 5 at 1888.0(M)

PIP SUMMARY

Time Mark Every 60 S





500	(V)	1000			
PIP SUMMARY					
Time Mark Every 60 S					
Parameters					
DLIS Name		Description		Value	
MSCT-AA: Mechanical Sidewall Coring Tool SOFF		Standoff		0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S		Graphics File Created: 14-Nov-2009 22:49	
OP System Version: 17C0-154					
MSCT-AA		17C0-154		SGT-P 17C0-154	
Output DLIS Files					
DEFAULT		MSCT_017LTP		FN:16 PRODUCER 14-Nov-2009 22:49	


Company:

Well:

Output DLIS Files					
DEFAULT	MSCT_020LTP	FN:19	PRODUCER	14-Nov-2009 22:57	1849.0 M

Elapsed Time (s)	Event Summary
173.6	Anchor Shoe Closed
106.0	Coring Stopped
70.4	Coring Started
50.4	Anchor Shoe Open
43.2	Marker 6
43.2	Core 6 at 1849.0(M)

PIP SUMMARY				
Time Mark Every 60 S				
Hydraulic Motor Downhole Voltage (HMDV)				
500	(V)			
Coring Motor Downhole Voltage (CMDV)				
500	(V)			
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL		Limit Switch From D3T to MSCT_LSWI	Kinematics Pressure (RPPV) (PSIG)	
			0 5000	
(SSTA) (-----)	Hydraulic Motor Current (HMCU) (AMPS)	Elapsed Time (ETIM) (S)	Hydraulic Pump Pressure (HPPR) (PSIG)	Coring Motor Linear Position (CMLP) (IN)
0 10	0 2		0 5000	0 2.5
		189 180 171 162		Anchor Shoe Closed



PIP SUMMARY

Time Mark Every 60 S

Parameters				
DLIS Name		Description		Value
MSCT-AA: Mechanical Sidewall Coring Tool		Standoff		0 IN
SOFF				
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S		Graphics File Created: 14-Nov-2009 22:57
OP System Version: 17C0-154				
MSCT-AA		17C0-154		SGT-P 17C0-154
Output DLIS Files				
DEFAULT		MSCT_020LTP		FN:19 PRODUCER 14-Nov-2009 22:57

Company: Well:


Output DLIS Files				
DEFAULT	MSCT_022LTP	FN:21	PRODUCER	14-Nov-2009 23:02 1833.0 M


Elapsed Time (s)	Event Summary
187.2	Anchor Shoe Closed

128.4	Coring Stopped
78.0	Coring Started
62.4	Anchor Shoe Open
55.6	Marker 7
55.6	Core 7 at 1833.0(M)

PIP SUMMARY

Time Mark Every 60 S





(SSTA) 0 (----) 10		Hydraulic Motor Current (HMCU) 0 (AMPS) 2		Elapsed Time (ETIM) (S) Limit Switch From D3T to MSCT_LSWI	Hydraulic Pump Pressure (HPPR) 0 (PSIG) 5000		Coring Motor Linear Position (CMLP) 0 (IN) 2.5				
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL					Kinematics Pressure (RPPV) 0 (PSIG) 5000						
Coring Motor Downhole Voltage (CMDV) 500 (V) 1000											
Hydraulic Motor Downhole Voltage (HMDV) 500 (V) 1000											

PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 14-Nov-2009 23:08

OP System Version: 17C0-154

MSCT-AA	17C0-154	SGT-P	17C0-154
---------	----------	-------	----------

Output DLIS Files

DEFAULT	MSCT_025LTP	FN:24	PRODUCER	14-Nov-2009 23:08
---------	-------------	-------	----------	-------------------


Company: Well:

Output DLIS Files

DEFAULT	MSCT_028LTP	FN:27	PRODUCER	14-Nov-2009 23:14	1762.0 M
---------	-------------	-------	----------	-------------------	----------

Elapsed Time (s)	Event Summary
177.2	Anchor Shoe Closed
107.2	Coring Stopped

Time Mark Every 60 S



PIP SUMMARY				
Time Mark Every 60 S				
Parameters				
DLIS Name		Description		Value
SOFF		MSCT-AA: Mechanical Sidewall Coring Tool Standoff		0 IN
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S		Graphics File Created: 14-Nov-2009 23:20
OP System Version: 17C0-154				
MSCT-AA		17C0-154	SGT-P	17C0-154
Output DLIS Files				
DEFAULT		MSCT_031LTP	FN:30 PRODUCER	14-Nov-2009 23:19


Company:				Well:
Output DLIS Files				
DEFAULT	MSCT_034LTP	FN:33	PRODUCER	14-Nov-2009 23:30 1636.0 M

Elapsed Time (s)	Event Summary
218.8	Anchor Shoe Closed
156.4	Coring Stopped
67.6	Coring Started

97.6	Coring Started
83.2	Anchor Shoe Open
76.0	Marker 11
76.0	Core 11 at 1636.0(M)

PIP SUMMARY

Time Mark Every 60 S



PIP SUMMARY			
Time Mark Every 60 S			
Parameters			
DLIS Name	Description	Value	
MSCT-AA: Mechanical Sidewall Coring Tool SOFF	Standoff	0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	Graphics File Created: 14-Nov-2009 23:30
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_034LTP	FN:33	PRODUCER 14-Nov-2009 23:30

Company:



Well:

Output DLIS Files

DEFAULTMSCT_036LTPFN:35PRODUCER14-Nov-2009 23:361632.0 M

Elapsed Time (s)	Event Summary
217.2	Anchor Shoe Closed
150.8	Coring Stopped
98.8	Coring Started
62.8	Anchor Shoe Open
58.0	Marker 12
58.0	Core 12 at 1632.0(M)

Time Mark Every 60 S					
Hydraulic Motor Downhole Voltage (HMDV)					
500	(V)	1000			
Coring Motor Downhole Voltage (CMDV)					
500	(V)	1000			
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL		Limit Switch From D3T to MSCT_LSWI	Kinematics Pressure (RPPV) (PSIG)		
			0	5000	
(SSTA)	Hydraulic Motor Current (HMCU)	Elapsed Time (ETIM) (S)	Hydraulic Pump Pressure (HPPR) (PSIG)	Coring Motor Linear Position (CMLP) (IN)	
0	(-----) 10	0	5000	0	2.5
		240	Anchor Shoe Closed		
		234			
		225			
		216			
		207			
		108			



PIP SUMMARY

Time Mark Every 60 S

Parameters				
DLIS Name		Description		Value
MSCT-AA: Mechanical Sidewall Coring Tool SOFF		Standoff		0 IN
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S		Graphics File Created: 14-Nov-2009 23:36
OP System Version: 17C0-154				
MSCT-AA	17C0-154	SGT-P	17C0-154	
Output DLIS Files				
DEFAULT	MSCT_036LTP	FN:35	PRODUCER	14-Nov-2009 23:36


Company:				Well:
Output DLIS Files				
DEFAULT	MSCT_039LTP	FN:38	PRODUCER	14-Nov-2009 23:50 1560.0 M


Elapsed	
---------	--

Time (s)	Event Summary
187.2	Anchor Shoe Closed
118.8	Coring Stopped
85.6	Coring Started
54.4	Anchor Shoe Open
48.0	Marker 13
48.0	Core 13 at 1560.0(M)

PIP SUMMARY

Time Mark Every 60 S





(SSTA) (-----) 10		Hydraulic Motor Current (HMCU) (AMPS) 2	Elapsed Time (ETIM) (S)	Hydraulic Pump Pressure (HPPR) (PSIG) 5000	Coring Motor Linear Position (CMLP) (IN) 2.5
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL		Limit Switch From D3T to MSCT_LSWI			
Coring Motor Downhole Voltage (CMDV) (V) 500 1000					
Hydraulic Motor Downhole Voltage (HMDV) (V) 500 1000					

PIP SUMMARY

Time Mark Every 60 S

Parameters		
DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

OP System Version: 17C0-154

MSCT-AA 17C0-154 SGT-P 17C0-154

Output DLIS Files

DEFAULT MSCT_042LTP FN:41 PRODUCER 14-Nov-2009 23:58

Company: Well:


Output DLIS Files


DEFAULT MSCT_045LTP FN:44 PRODUCER 15-Nov-2009 00:11 1467.0 M

Elapsed Time (s)	Event Summary
166.8	Anchor Shoe Closed
91.2	Coring Stopped
71.6	Coring Started
55.6	Anchor Shoe Open
46.4	Marker 15
46.4	Core 15 at 1467.0(M)

PIP SUMMARY

Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Parameters		
DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool SOFF		0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 00:11

OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154

Output DLIS Files				
DEFAULT	MSCT_045LTP	FN:44	PRODUCER	15-Nov-2009 00:11

Company: Well:


Output DLIS Files				
DEFAULT	MSCT_047LTP	FN:46	PRODUCER	15-Nov-2009 00:16 1467.7 M

Elapsed Time (s)	Event Summary
216.8	Anchor Shoe Closed
156.0	Coring Stopped
59.6	Coring Started
42.4	Anchor Shoe Open
35.2	Marker 16
35.2	Core 16 at 1467.7(M)

PIP SUMMARY

Time Mark Every 60 S

Hydraulic Motor Downhole Voltage	
----------------------------------	--



PIP SUMMARY

Time Mark Every 60 S

Parameters


DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN


MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_047LTP	FN:46	PRODUCER 15-Nov-2009 00:16

Company:					Well:	
Output DLIS Files						
DEFAULT	MSCT_050LTP	FN:49	PRODUCER	15-Nov-2009 00:25	1436.0 M	

Elapsed Time (s)	Event Summary
190.4	Anchor Shoe Closed
120.4	Coring Stopped
64.4	Coring Started
48.8	Anchor Shoe Open
41.2	Marker 17
41.2	Core 17 at 1436.0(M)

PIP SUMMARY





PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 00:25

OP System Version: 17C0-154

MSCT-AA 17C0-154 SGT-P 17C0-154

Output DLIS Files

DEFAULT MSCT_050LTP FN:49 PRODUCER 15-Nov-2009 00:25


Company: Well:

Output DLIS Files

DEFAULT MSCT_052LTP FN:51 PRODUCER 15-Nov-2009 00:30 1424.0 M

Elapsed Time (s)	Event Summary
173.6	Anchor Shoe Closed
97.2	Coring Stopped
70.4	Coring Started
56.0	Anchor Shoe Open
46.0	Marker 18
46.0	Core 18 at 1424.0(M)

PIP SUMMARY



PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 00:30

OP System Version: 17C0-154


Company:


Well:

Output DLIS Files

DEFAULTMSCT_054LTPFN:53PRODUCER15-Nov-2009 00:351426.8 M

Elapsed Time (s)	Event Summary
176.8	Anchor Shoe Closed
111.2	Coring Stopped
57.6	Coring Started
42.0	Anchor Shoe Open
35.2	Marker 19
35.2	Core 19 at 1426.8(M)






Parameters			
DLIS Name	Description		Value
MSCT-AA: Mechanical Sidewall Coring Tool	SOFF		0 IN
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	Graphics File Created: 15-Nov-2009 00:35
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_054LTP	FN:53	PRODUCER 15-Nov-2009 00:35

Company:				Well:
Output DLIS Files				
DEFAULT	MSCT_057LTP	FN:56	PRODUCER	15-Nov-2009 00:41 1406.0 M
Event Summary				
Elapsed Time (s)				
224.8	Anchor Shoe Closed			
98.0	Coring Stopped			
66.8	Coring Started			
50.0	Anchor Shoe Open			
42.8	Marker 20			
42.8	Core 20 at 1406.0(M)			

PIP SUMMARY	
Time Mark Every 60 S	
Hydraulic Motor Downhole Voltage (HMDV)	



PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name

Description

Value

MSCT-AA: Mechanical Sidewall Coring Tool
SOFF Standoff


0 IN



Company:Well:

Output DLIS Files

DEFAULT MSCT_059LTP FN:58 PRODUCER 15-Nov-2009 00:47 1406.5 M

Elapsed Time (s)	Event Summary
164.8	Anchor Shoe Closed
102.0	Coring Stopped
64.8	Coring Started
50.0	Anchor Shoe Open
44.8	Marker 21
44.8	Core 21 at 1406.5(M)





PIP SUMMARY

Time Mark Every 60 S

Parameters		
DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 00:47

OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154

Output DLIS Files				
DEFAULT	MSCT_059LTP	FN:58	PRODUCER	15-Nov-2009 00:47


Company: Well:

Output DLIS Files				
DEFAULT	MSCT_061LTP	FN:60	PRODUCER	15-Nov-2009 00:53 1405.5 M

Elapsed Time (s)	Event Summary
180.0	Anchor Shoe Closed
118.8	Coring Stopped
74.0	Coring Started
59.2	Anchor Shoe Open
53.6	Marker 22
53.6	Core 22 at 1405.5(M)

PIP SUMMARY

Time Mark Every 60 S



PIP SUMMARY

Time Mark Every 60 S


Parameters		
DLIS Name	Description	Value
SOFF	MSCT-AA: Mechanical Sidewall Coring Tool Standoff	0 IN


Company: Well:

Output DLIS Files

DEFAULT MSCT_063LTP FN:62 PRODUCER 15-Nov-2009 00:58 1383.0 M

Elapsed Time (s)	Event Summary
160.8	Anchor Shoe Closed
93.2	Coring Stopped
74.8	Coring Started
56.4	Anchor Shoe Open
50.4	Marker 23
50.4	Core 23 at 1383.0(M)





PIP SUMMARY

Time Mark Every 60 S

Parameters		
DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 00:58

OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154

Output DLIS Files				
DEFAULT	MSCT_063LTP	FN:62	PRODUCER	15-Nov-2009 00:58

Company: Well:


Output DLIS Files				
DEFAULT	MSCT_065LTP	FN:64	PRODUCER	15-Nov-2009 01:04 1384.9 M

Elapsed Time (s)	Event Summary
185.6	Anchor Shoe Closed
120.4	Coring Stopped
90.0	Coring Started
73.6	Anchor Shoe Open
66.4	Marker 24
66.4	Core 24 at 1384.9(M)

PIP SUMMARY

Time Mark Every 60 S

Hydraulic Motor Downhole Voltage



PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 01:04

Company:

Well:

Output DLIS Files

DEFAULT

MSCT_068LTP


FN:67


PRODUCER

15-Nov-2009 02:20

2460.0 M

Elapsed Time (s)	Event Summary
269.2	Anchor Shoe Closed
200.0	Coring Stopped
115.6	Coring Started
75.6	Anchor Shoe Open
66.4	Marker 25
66.4	Core 25 at 2460.0(M)





PIP SUMMARY				
Time Mark Every 60 S				
Parameters				
DLIS Name		Description		Value
MSCT-AA: Mechanical Sidewall Coring Tool				
SOFF	Standoff		0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S		Graphics File Created: 15-Nov-2009 02:20
OP System Version: 17C0-154				
MSCT-AA	17C0-154		SGT-P	17C0-154
Output DLIS Files				
DEFAULT	MSCT_068LTP		FN:67 PRODUCER	15-Nov-2009 02:20

Company:					Well:	
Output DLIS Files						
DEFAULT	MSCT_070LTP	FN:69	PRODUCER	15-Nov-2009 02:27	2445.0 M	


Elapsed Time (s)	Event Summary
208.0	Anchor Shoe Closed
135.6	Coring Stopped
79.6	Coring Started
55.2	Anchor Shoe Open
46.8	Marker 26

46.8

Core 26 at 2445.0(M)

PIP SUMMARY


Time Mark Every 60 S





PIP SUMMARY



Time Mark Every 60 S

Parameters





Hydraulic Motor Downhole Voltage (HMDV) 500 (V) 1000			
Coring Motor Downhole Voltage (CMDV) 500 (V) 1000			
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL		Limit Switch From D3T to MSCT_LSWI	Kinematics Pressure (RPPV) 0 (PSIG) 5000
(SSTA) 0 (-----) 10	Hydraulic Motor Current (HMCU) 0 (AMPS) 2	Elapsed Time (ETIM) (S)	Hydraulic Pump Pressure (HPPR) 0 (PSIG) 5000
			Coring Motor Linear Position (CMLP) 0 (IN) 2.5
			Anchor Shoe Closed



PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S Graphics File Created: 15-Nov-2009 02:56

OP System Version: 17C0-154

DEFAULT	MSCT_074LTP	FN:73	PRODUCER	15-Nov-2009 02:56
---------	-------------	-------	----------	-------------------


Company: _____ Well: _____


DEFAULT	MSCT_077LTP	FN:76	PRODUCER	15-Nov-2009 03:09	2302.0 M
---------	-------------	-------	----------	-------------------	----------

Elapsed Time (s)	Event Summary
330.4	Anchor Shoe Closed
124.4	Coring Stopped
62.8	Coring Started
44.0	Anchor Shoe Open
37.6	Marker 29
37.6	Core 29 at 2302.0(M)

PIP SUMMARY

Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool		
SOFF	Standoff	0 IN

Format: MSCT_CUSTOMER_Station Vertical Scale: 1" per 60S

Graphics File Created: 15-Nov-2009 03:09

OP System Version: 17C0-154

MSCT-AA 17C0-154 SGT-P 17C0-154

Output DLIS Files

DEFAULT MSCT_077LTP FN:76 PRODUCER 15-Nov-2009 03:09

Company:


Well:


Output DLIS Files

DEFAULT MSCT_080LTP FN:79 PRODUCER 15-Nov-2009 03:22 2227.0 M

Elapsed Time (s)	Event Summary
384.8	Anchor Shoe Closed
168.0	Coring Stopped

76.0	Coring Stopped
54.8	Anchor Shoe Open
48.4	Marker 30
48.4	Core 30 at 2227.0(M)






PIP SUMMARY			
Time Mark Every 60 S			
Parameters			
DLIS Name	Description	Value	
SOFF	MSCT-AA: Mechanical Sidewall Coring Tool Standoff	0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	
		Graphics File Created: 15-Nov-2009 03:22	
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_080LTP	FN:79	PRODUCER 15-Nov-2009 03:22

Company:			Well:
Output DLIS Files			
DEFAULT	MSCT_082LTP	FN:81	PRODUCER 15-Nov-2009 03:33 2209.0 M
Elapsed Time (s)	Event Summary		
319.6	Anchor Shoe Closed		
120.4	Coring Stopped		
69.6	Coring Started		
47.6	Anchor Shoe Open		
42.0	Marker 31		
42.0	Core 31 at 2209.0(M)		

PIP SUMMARY			
Time Mark Every 60 S			
Hydraulic Motor Downhole Voltage (HMDV)			
500	(V)	1000	



Time Mark Every 60 S		PIP SUMMARY	
Parameters			
DLIS Name	Description	Value	
SOFF	MSCT-AA: Mechanical Sidewall Coring Tool Standoff	0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	Graphics File Created: 15-Nov-2009 03:33
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_082LTP	FN:81 PRODUCER	15-Nov-2009 03:33


Company:


Well:

Output DLIS Files

DEFAULTMSCT_084LTPFN:83PRODUCER15-Nov-2009 03:412190.0 M

Elapsed Time (s)	Event Summary
217.6	Anchor Shoe Closed
150.0	Coring Stopped
93.6	Coring Started
64.4	Anchor Shoe Open
57.6	Marker 32
57.6	Core 32 at 2190.0(M)





(SSTA) 0-----10	Hydraulic Motor Current (HMCU) 0(AMPS)2	Elapsed Time (ETIM) (S) Limit Switch From D3T to MSCT_LSWI	Hydraulic Pump Pressure (HPPR) 0(PSIG)5000	Coring Motor Linear Position (CMLP) 0(IN)2.5
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL			Kinematics Pressure (RPPV) 0(PSIG)5000	
Coring Motor Downhole Voltage (CMDV) 500(V)1000				
Hydraulic Motor Downhole Voltage (HMDV) 500(V)1000				

PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
MSCT-AA: Mechanical Sidewall Coring Tool SOFF	Standoff	0 IN
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S
		Graphics File Created: 15-Nov-2009 03:41

OP System Version: 17C0-154

MSCT-AA	17C0-154	SGT-P	17C0-154
---------	----------	-------	----------

Output DLIS Files

DEFAULT	MSCT_084LTP	FN:83	PRODUCER	15-Nov-2009 03:41
---------	-------------	-------	----------	-------------------

Company: Well:

Output DLIS Files


DEFAULT	MSCT_087LTP	FN:86	PRODUCER	15-Nov-2009 03:48	2149.0 M
---------	-------------	-------	----------	-------------------	----------

Elapsed
Time (s)

Event Summary

229.2	Anchor Shoe Closed
160.8	Coring Stopped
69.2	Coring Started
48.4	Anchor Shoe Open
41.2	Marker 33
41.2	Core 33 at 2149.0(M)

PIP SUMMARY




500 (CMDV) 1000			
Hydraulic Motor Downhole Voltage (HMDV)			
500 (V) 1000			
PIP SUMMARY			
Time Mark Every 60 S			
Parameters			
DLIS Name	Description	Value	
MSCT-AA: Mechanical Sidewall Coring Tool SOFF	Standoff	0 IN	
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	Graphics File Created: 15-Nov-2009 03:48
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_087LTP	FN:86	PRODUCER 15-Nov-2009 03:48

Company:		Well:	
Output DLIS Files			
DEFAULT	MSCT_090LTP	FN:89	PRODUCER 15-Nov-2009 03:56 2075.0 M


Elapsed Time (s)	Event Summary
181.2	Anchor Shoe Closed
110.0	Coring Stopped
72.4	Coring Started
47.2	Anchor Shoe Open
40.0	Marker 34
40.0	Core 34 at 2075.0(M)

PIP SUMMARY			
Time Mark Every 60 S			
Hydraulic Motor Downhole Voltage (HMDV)			
500 (V) 1000			
Coring Motor Downhole Voltage (CMDV)			
500 (V) 1000			
Motor Voltage Window From MSCT_LMVL to MSCT_UMVL		Limit Switch From D3T to MSCT_LSWI	Kinematics Pressure (RPPV) (PSIG) 0 5000
(SSTA) 0 (----) 10	Hydraulic Motor Current (HMCU) (AMPS) 0 2	Elapsed Time (ETIM)	Hydraulic Pump Pressure (HPPR) (PSIG) 0 5000
			Coring Motor Linear Position (CMLP) (IN) 0 2.5



PIP SUMMARY			
Time Mark Every 60 S			
Parameters			
DLIS Name	Description	Value	
MSCT-AA: Mechanical Sidewall Coring Tool			
SOFF	Standoff	0	IN
Format: MSCT_CUSTOMER_Station		Vertical Scale: 1" per 60S	Graphics File Created: 15-Nov-2009 03:56
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_090LTP	FN:89	PRODUCER 15-Nov-2009 03:56

Company:						Well:
Output DLIS Files						
DEFAULT	MSCT_092LTP	FN:91	PRODUCER	15-Nov-2009 04:02	2040.0 M	





2250

2275

Gamma Ray (GR) (GAPI)		Tension (TENS) (LBF)	
0	150	0	8000
Format: CORRELATION		Vertical Scale: 1:200	
Graphics File Created: 15-Nov-2009 03:16			
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154
Output DLIS Files			
DEFAULT	MSCT_079LUP	FN:78	PRODUCER 15-Nov-2009 03:16

Company:		Well:	
Output DLIS Files			
DEFAULT	MSCT_089LUP	FN:88	PRODUCER 15-Nov-2009 03:53
OP System Version: 17C0-154			
MSCT-AA	17C0-154	SGT-P	17C0-154






Format: CORRELATION Vertical Scale: 1:200 Graphics File Created: 15-Nov-2009 03:53


OP System Version: 17C0-154

MSCT-AA	17C0-154	SGT-P	17C0-154
---------	----------	-------	----------

Output DLIS Files

DEFAULT	MSCT_089LUP	FN:88	PRODUCER	15-Nov-2009 03:53
---------	-------------	-------	----------	-------------------





Format: CORRELATION		Vertical Scale: 1:200		Graphics File Created: 14-Nov-2009 23:41	
OP System Version: 17C0-154					
MSCT-AA	17C0-154	SGT-P		17C0-154	
Output DLIS Files					
DEFAULT	MSCT_038LUP	FN:37	PRODUCER	14-Nov-2009 23:41	



Calibrations

MAXIS Field Log

Calibration and Check Summary							
Measurement	Nominal	Master	Before	After	Change	Limit	Units
Mechanical Sidewall Coring Tool Wellsite Calibration – MSCT Piston Position Calibration							
Before: 14-Nov-2009 20:42							
Zero	0	N/A	0.5588	N/A	N/A	N/A	IN
Plus	2.140	N/A	2.676	N/A	N/A	N/A	IN
Scintillation Gamma-Ray – P Wellsite Calibration – Detector Calibration							
Before: 14-Nov-2009 20:54							
Gamma Ray (Jig – Bkg)	233.3	N/A	233.3	N/A	N/A	21.21	GAPI

Mechanical Sidewall Coring Tool / Equipment Identification		
Primary Equipment:		
Mechanical Sidewall Corer Fifty Core Uni	MCFU – AA	17
Mechanical Sidewall Corer Mechanical Uni	MCMU – AA	174
Mechanical Sidewall Corer Bit	BIT – AA	
Mechanical Sidewall Corer Electronics Ca	MCEC – AA	181
Auxiliary Equipment:		
Electronics Cartridge Housing	ECH – KS	113

Scintillation Gamma-Ray – P / Equipment Identification		
Primary Equipment:		
Scintillation Gamma Cartridge	SGC – V	10245
Scintillation Gamma Detector	SGD – TAB	
Auxiliary Equipment:		
Scintillation Gamma Housing	SGH – K	3037
Gamma Source Radioactive	GSR – U/Y	

Scintillation Gamma-Ray – P Wellsite Calibration														
Detector Calibration														
Phase	Gamma Ray Background		GAPI	Value	Phase	Gamma Ray (Jig – Bkg)		GAPI	Value	Phase	Gamma Ray (Calibrated)		GAPI	Value
Before				6.701	Before				233.3	Before				165.0
	0	30.00	120.0			212.1	233.3	254.5			150.0	165.0	180.0	
	(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)			(Minimum)	(Nominal)	(Maximum)	
Before: 14-Nov-2009 20:54														

Company:	Lakes Oil N.L.	
Well:	Wombat-4	
Field:	Wombat	
Rig:	Hunt #2	
Country:	Australia	
Mechanical Side Wall Coring Tool Log Run 4		