

EXPLORATION LOGGING DRILLING RATE AND DATA <input checked="" type="checkbox"/> FT/HR <input type="checkbox"/> MIN/FT  VISUAL POROSITY GD. FAIR TR. POOR FAIR TR. CORE TEST	DEPTH	LITHOLOGY	OIL TRACE GD. TRACE FAIR GOOD V. GOOD	DRILLING MUD				CUTTINGS				REMARKS AND LITHOLOGY DESCRIPTION	
				CONTINUOUS DITCH GAS		CHROMATOGRAPHIC ANALYSIS		GAS		GAS			
				OIL IN MUD TR. X FAIR XX GD. XXX	TOTAL GAS BACKUP SCALE 10X PETROL VAP	METHANE ETHANE PROPANE	BUTANES PENTANES M 1000	TOTAL GAS BACKUP SCALE 10X PETROL VAP	TOTAL GAS BACKUP SCALE 10X PETROL VAP	CUTTING FAIR GOOD	CUTTING FAIR GOOD		
20	40 60 80 100	100	1M	10M	40M	20	40 60 80 100	20	40 60 80 100				
400 300 200 100													
	900												
7/14-16 NBMS REED. Y13J													
	1000												
	1100												
	1200												
	1300												

DEPT. NAT. RES & ENV  
  
 PE603214

DRILLING 12 1/4" HOLE  
 LIMESTONE: GRAY, WHITE  
 VERY FRIABLE & FOSSILIFEROUS, PREDOMINANTLY BRYOZOA; MINERAL FLUORESCENCE.  
 MINOR CEMENT CONTAM.

CONTINUED CALCARENITE COQUINA LIMESTONE.

SANDY SILTSTONE  
 LIGHT-GRAY, FIRM  
 WITH SCATTERED GR  
 OF SILTY TO COARSE  
 ANGULAR TO SUBROUNDE  
 QUARTZ.