DEPT. NAT. RES & ENV
PE603763

EXPLORATION LOGGING

DRILLING RATE AND DATA

☒ FT/HR ☐ MIN/FT

VISUAL POROSITY

400 300 200 100 GD FAIR TR 0

CORE TEST

DEPTH

LITHOLOGY

OIL — TRACE, GD. TRACE, FAIR, GOOD, V GOOD

DRILLING MUD

CONTINUOUS DITCH GAS

OIL IN MUD: TR. x; FAIR xx; GD. xxx

TOTAL GAS _____ (BACKUP SCALE ÷ 10X)

PETROL VAP ___ ___

20 40 60 80 100

CHROMATOGRAPHIC ANALYSIS

METHANE _____ BUTANES ___4___

ETHANE ___2___ PENTANES ___5___

PROPANE ___3___ M = 1000

100 1M PPM IN AIR 10M 40M

CUTTINGS

CUT — FAIR, GOOD

GAS

TOTAL GAS _____ (BACKUP SCALE ÷ 10X)

PETROL VAP ___ ___

20 40 60 80 100

REMARKS AND LITHOLOGY DESCRIPTION

800

NB#3 Sec $3 SJ

900

DRILLING 9 5/8" HOLE.

NOTE: DRILLING RATE OBTAINED FROM RIG GEOLOGRAPH AND LITHOLOGY FROM CREW'S SAMPLES IN INTERVAL 830' TO 2140'.

LIMESTONE: LIGHT GREY, VERY FOSSILIFEROUS, MARLY, OCCAISONAL QUARTZ GRAINS.

~~STREAKS SANDY DOLOMITE.~~

1000

LIMESTONE: LIGHT GREY, GREY, COQUINA.

1°

1100

AS ABOVE, VERY MARLY.

DECREASING MARL.

1200

INCREASING MARL.

50 100 100 1M 10M 40M 50 100