



WRIXONDALE No.1



REGIONAL LINE : GB83A-26
THROUGH WRIXONDALE No.1 WITH
SYNTHETIC SEISMOGRAM.

Seiscom Delta Limited

PE605005

BEACH PETROLEUM NL.

Line: GB83A-26
S.P: 120-560
Survey: Bengworden-83
Location: PEP 107 : Gippsland Basin
Area: Victoria

N

Process: MIGRATE STACK

Acquisition: Geosource
PARTY NUMBER: 6812
DATE: JANUARY 1984

ENERGY SOURCE:
type: Dynamite
number of shooting: Single
shotpoint interval: 120 m.
source depth: 8–24 m.
source array: single holes
size: 1 kg.

RECORDING GEOMETRY:
fold of recording: 6001 type: split spread
no. of groups: 96 interval: 15 m.
spread: 742.5–37.5–0–37.5–742.5 m.

INSTRUMENTATION:
geophones: MD-79 10 Hz 12 in line over 30 m.
recording system: MDS-10
high cut: 125 Hz slope 72 dB/octave
record format: SEGB 1600 BPI P.E.
record length: 2 sec.
sample interval: 4 msec.
LVL Survey: Uphole Method.
Done : June 1983

Processing: SEISCOM DELTA INC.
CENTRE: MELBOURNE/AUSTRALIA
DATE: DECEMBER 1983
COMPUTER SYSTEM: MEGASIS

INITIAL PROCESS:
demultiplex: 2 sec.
EXPONENTIAL GAIN:
initial gain: +25 dB/sec. 4–400 msec.
TRACE EDIT:
DEPULSE:
source compensation: for instruments and geophones
TWO DIMENSIONAL FILTERING
in F-K domain:
apparent velocities: 240 m/sec – 2011 m/sec
PULSE COMPRESSION:
statistical wavelet shaping: 160 ms pulse over 15–100 Hz zero phase output
FREQUENCY DECONVOLUTION: 2 gate,bandwidth 15–100 Hz
DATUM STATICS:
static corrections: for source and receiver elevations
datum: 0 m.
refractor velocity: 1700 m/sec
weathering statics: based on delay time map provided by Beach
CDP GATHER
VELOCITY ANALYSES: from Seiscom s Dove Velocity Spectra
RESIDUAL STATICS (SWS): surface consistent velocities
VELOCITY ANALYSES: from Seiscom s Dove and Panel Velocity Spectra
NORMAL MOVEOUT CORRECTION:
RESIDUAL STATICS (PAST): sub-surface consistent solution
FRONT-END MUTE:

Offset	Time
203 m.	0. ms.
234 m.	200. ms.
400 m.	400. ms.
743 m.	600. ms.

SPHERICAL DIVERGENCE:
STACK:
type: true amplitude
fold: 6
TRACE EQUALISATION:
data length window:
WAVE EQUATION MIGRATION:
Kneller Operator
FILTER:
A) 0 ms 25/35–110/130 Hz
B) 500 ms 25/35–105/125 Hz
C) 1000 ms 20/30–100/120 Hz
D) 1500 ms 16/26–70/90 Hz
E) 2000 ms 15/25–50/50 Hz
RAW LEVEL SCALING:
average window: 250 msec.
DISPLAY SYSTEM: SEISCHROME II
type: trace equalised
vertical scale: 7.5 in/sec
horizontal scale: 31.2 in/in
polarity: reflection to the right, increase positive digital numbers, 851140

Geophysicist: Rob Slack SDU

0.5 km

1:6250

GIPPSLAND
REGIONAL LINE No.