

TABLE 3: CEMENT SUMMARY - BASKER-1

Date	Job Description	Hole Size / Depth	Casing Shoe	Cement Used (mT)	Slurry Wt (sg)	Mixwater/Additives	Remarks
21/4/83	30" casing	36"/240	234	Class G 14	1.56	Drill water plus 2% BWOC CaCl <sub>2</sub> , 2.5% BWOW Gel 13.8 m <sup>3</sup>	Returns to seabed observed by diving bell <u>Design Figures:</u>
				13	1.92	Neat seawater 6 m <sup>3</sup>	<u>Lead:</u> 1.29 m <sup>3</sup> slurry/mt cement 0.96 m <sup>3</sup> mixwater/mt cement <u>Tail:</u> 0.76 m <sup>3</sup> slurry/mt cement 0.44 m <sup>3</sup> water/mt cement
25/4/83	20" casing	26"/504	498	Class G 50	1.48	Drill water plus 2% BWOC CaCl <sub>2</sub> 3% BWOW Gel 54 m <sup>3</sup>	Return observed to seabed <u>Design Figures:</u>
				22	1.90	Seawater 10 m <sup>3</sup>	<u>Lead:</u> 1.46 m <sup>3</sup> slurry/mt cement 1.13 m <sup>3</sup> mixwater/mt cement <u>Tail:</u> 0.76 m <sup>3</sup> slurry/mt cement 0.44 m <sup>3</sup> water/mt cement
6/5/83	13-3/8" casing	17-1/2"/1110	1104	Class G 32.5	1.48	Drill water plus 3% BWOW Gel 37 m <sup>3</sup>	TOC 423m <u>Design Figures:</u>
				9.7	1.90	Seawater 7.4 m <sup>3</sup>	<u>Lead:</u> 1.46 m <sup>3</sup> slurry/mt cement 1.13 m <sup>3</sup> water/mt cement <u>Tail:</u> 0.76 m <sup>3</sup> slurry/mt cement 0.44 m <sup>3</sup> water/mt cement
21/5/83	9-5/8" casing	12-1/4"/2862	2853	Class G 45	1.5	Drill water plus 3% BWOW Gel, HR-7 0.5% BWOC 51 m <sup>3</sup>	TOC 954m <u>Design Figures:</u>
				5	1.9	Seawater plus 0.9% BWOC, HR-7 1.7 m <sup>3</sup>	<u>Lead:</u> 1.46 m <sup>3</sup> slurry/mt cement 1.13 m <sup>3</sup> water/mt cement <u>Tail:</u> 0.76 m <sup>3</sup> slurry/mt cement 0.44 m <sup>3</sup> water/mt cement
16/6/83	7" liner	8-1/2"	3287	Class G 16	1.9	Drill water plus 0.75% BWOC, CFR-2 0.8% BWOC, Halad 22A 0.4% BWOC, HR-12 8.4 m <sup>3</sup>	<u>Design Figures:</u> 0.76 m <sup>3</sup> slurry/mt cement 0.44 m <sup>3</sup> water/mt cement
16/6/83	<u>Abandonment</u> Plug 1	8-1/2"		Class G 10	1.9	HR-12L 50 litre/m <sup>3</sup> Drill water 4.8 m <sup>3</sup>	Plug 1: 3991-3820m
16/6/83	Plug 2	8-1/2"		8	1.9	HR-12L 7 litre/m <sup>3</sup> Drill water 4.5 m <sup>3</sup>	Plug 2: 3440-3280m
16/7/83	Plug 3	7" liner		5	1.9	0.15% HR-12 BWOC 2.2 m <sup>3</sup>	Plug 3: 3230-3030m
16/7/83	Plug 4	Liner lap 7" liner/9-5/8" csg		8	1.9	0.12% HR-12 BWOC 4.1 m <sup>3</sup>	Plug 4: 2525-2725m
6/9/83	Plug 5	9-5/8" csg		4	1.9	1.5% CaCl <sub>2</sub> BWOC Seawater	Plug 5 : 656-576m
6/9/83	Plug 6	9-5/8" csg		4	1.9	3% CaCl <sub>2</sub> BWOC Seawater	Plug 6 : 310-230m