

CHECKSHOT SURVEY STACK SUMMARY LISTING (TWO WAY CORRECTED TIMES)

Gun and Hydrophone Coordinates:

Gun Azimuth		115.0	DEG
Gun Offset		45.0	M
Gun Depth	From Schlumberger Zero	30.0	M
Hydrophone Depth	From Schlumberger Zero	35.0	M
SRD Depth	From Schlumberger Zero	25.0	M

Other VSP constants:

True Vertical Time Correction	YES
Surface Velocity	1524.00 M/s

Stack number	Measured Depth (1) (M)	Measured Trans Time (2) (MS)	True Vert. Depth from SRD (3) (M)	Corrected Trans Time (4) (MS)	Average Velocity (5) (M/S)
32	781.5	345.33	756.3	703.11	1405.75
32	796.9	356.28	771.7	725.02	2536.45
31	881.6	386.07	856.4	784.65	2856.15
31	897.1	391.24	871.9	794.99	2748.62
29	981.5	422.22	956.3	856.98	2754.17
29	996.9	427.23	971.7	867.01	2963.10
28	1081.6	455.92	1056.4	924.40	2954.27
28	1097.0	460.99	1071.8	934.55	2964.17
30	1099.5	462.04	1074.3	936.66	2964.17
30	1114.9	467.13	1089.7	946.83	2988.51
27	1181.5	489.36	1156.3	991.32	2983.30
27	1196.9	494.65	1171.7	1001.89	2810.16
26	1281.5	524.86	1256.3	1062.34	2829.50
26	1297.0	529.81	1271.8	1072.24	3097.49
25	1381.5	557.12	1356.2	1126.87	3079.24
25	1396.9	562.32	1371.6	1137.27	3059.08
24	1469.5	585.94	1444.2	1184.52	3040.47
23	1481.5	590.28	1456.2	1193.20	2839.47
24	1484.9	591.23	1459.6	1195.11	2839.47
23	1496.9	595.61	1471.6	1203.87	2860.54
22	1581.5	625.13	1556.2	1262.92	2880.77
22	1597.0	630.26	1571.7	1273.17	3038.83
21	1681.6	658.08	1656.3	1328.82	3042.41
21	1697.0	663.11	1671.7	1338.88	3037.80
20	1776.5	689.30	1751.2	1391.27	3062.64
20	1791.9	693.95	1766.6	1400.57	3347.88
19	1806.5	698.53	1781.2	1409.19	3121.98
19	1821.9	703.99	1796.6	1419.74	3027.97
18	1829.6	706.47	1804.3	1424.69	3209.78
17	1836.5	708.59	1811.2	1428.92	3209.78
18	1845.0	711.25	1819.7	1434.27	3272.35
17	1851.9	713.32	1826.6	1438.44	3272.35
16	1866.5	717.71	1841.2	1447.22	3467.75
16	1881.9	721.83	1856.6	1455.48	3581.07
15	1896.5	726.07	1871.2	1463.97	3676.76
15	1911.9	729.97	1886.6	1471.78	3740.69
14	1926.6	734.10	1901.3	1480.06	3609.81
14	1942.0	738.30	1916.7	1488.46	3694.70
13	1956.5	742.18	1931.1	1496.24	3785.31
13	1972.0	746.21	1946.6	1504.31	3784.13
12	1986.5	750.10	1961.1	1512.10	3809.76
12	2001.8	754.02	1976.4	1519.95	3729.13
11	2016.6	758.15	1991.2	1528.24	3772.11
11	2032.0	762.00	2006.6	1535.96	3585.72
10	2046.5	766.46	2021.1	1544.87	3594.21
10	2061.9	770.29	2036.5	1552.55	3998.69
9	2076.5	773.94	2051.1	1559.88	3780.43
8	2091.4	778.22	2066.0	1568.43	3688.18
9	2091.9	777.98	2066.5	1567.96	3688.18
7	2106.5	782.30	2081.1	1576.61	3734.35
8	2106.9	781.93	2081.5	1575.87	3734.35
6	2121.5	785.81	2096.1	1583.65	3931.46
7	2121.9	786.39	2096.5	1584.80	3931.46
5	2134.8	788.98	2109.4	1589.99	4021.92
6	2136.9	789.91	2111.5	1591.87	4021.92
5	2150.2	793.14	2124.8	1598.34	0.00

(1) Measured Depth is Cable Depth Referenced to Schlumberger Zero.

(2) TVD is referenced to SRD (5)

(3) TW Transit time with respect to SRD(5) corrected for Deviation

(4) Average Velocity corrected for Deviation.

Average Velocity computed on 150 FT across each level.

(5) SRD is Seismic Reference Depth.