

HORWOOD BAGSHAW LTD., Adelaide, South Aust.

WELL DRILLING CONTRACTORS AND HYDRAULIC ENGINEERS

DEPT. NAT. RES & ENV



PE603478

BORE LOG

W401

COBDENS
 Bore for MLAKES ENTRANCE OIL TRUST Location Lakes Entrance Victoria

Drillers J. Minoqua & J. Collins Name of Property Lease No. 5383

Commenced Oct. 7th 1935 Completed Feb. 22nd 1936 Depth Bored 1507'-0" T.D.

CASING IN BORE			Thickness of Strata		Strata as per drillers time sheets.	Section	Depth Feet	WATER STRUCK	
Diam	Length	Brand	Feet	Ins.				Struck at Feet from Surf	Rose to
			8		Sandy clay		8		
			19		Sandstone & hard layers		27		
			37		clay & gravel broken ground		64		
			11		Stone		75		
Shoe Used									
Casing Clamps									
	Size						100		
	Type								
PUMPING TEST									
	1st Test	2nd Test	Final Test						
Gallons per hour					Blue shell rock				
Water Level before Pumping							200		
Water Level when Pumping									
Duration of Test									
Depth to Pump									
Size of Pump used and Type				245			300		
REMARKS—							320		
WATER CEMENTED OFF & CASING WITHDRAWN			8		White shell rock		328		
							400		
			120				448		
					sticky clay				
			52				500		

Entered by W.H.C.

HORWOOD BAGSHAW LTD.
 MILE END, S.A.

DATE March 18th 1936

Approved W. J. Barker