BREAM – 2 — FIT DATA

FORMATION TESTER RECOVERY DATA

Header	Test No	Test Depth	Open Hole Test	Cased Hole Test	Gas (Total) cuft	Condensate cc	Oil cc	Water cc	Mud cc	Sand cc	Initial Shut in psi	Shut in Time min	Sampling psi	Sampling Time min	Final Shut in psi	Shut in Time min	Hydrostatic psi	Surface Chamber psi	Free Gas cuft	API Gravity @ °F	GOR	Rrf (Filtered) @ °F	Equivalent Cl ppm	Type of tool	Type of Sample shot	Sample Unit size cc	Choke size	Rmf @ °F	Equivalent Cl ppm	Rw @ °F	Equivalent Cl ppm	Remarks
BREAM – 2, FIT DATA, Run 1	1	6302	X		0.5	0	0	0	21,000	0	–	–	3600				3650		0.5	– @ –	–	@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Packers did not Seal. Mud Run. Reversefire
	2	6303	X		28.3	0	Scum	17000	500	0	–	–	2740	11.6	2920		3600	1700	28.3	@		1.36 @ 70	4500	FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Reversefire
SEGREGATOR	2	6302	X		0	0	0	0	2250	0	–	–					3600	1750	–	– @ –	–	@		–	–	2250	None	1.02 @ 67	5500	@		Lost Packer Seal.
	3	6347	X		44	0	15000	0	500	0	–	–	2820	Est 15	2820	Est 4.5	3650	1500	44	48.2 @ 60	420	@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Reversefire.
SEGREGATOR #21	3	6347	X								–	–		0.1	2820	0.5	3650			@		@		–	–	2250	None.	1.02 @ 68	5500	@		To be Transferred.
	4	5934	X		102.7	4000?	0				–	–	2680	11.5	2870	3.2	3410	1700	102.7	@		@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Reversefire
	5	6504	X		0	0	0	10000	8		3300	4.2	200	22.8	2840	10.5	3810	0	0	– @ –	–	0.39 @ 80	18 000	[illegible]	[illegible]	[illegible]	[illegible]	1.02 @ 61	5500	0.065 @ 164	60000	% Formation water [illegible]
	6	6292	X		94.3	+ gas cut mud 4000					–	–	2830	11	2900	2.5	3520	1650	94.3	@		@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Reversefire
SEGREGATOR #1	6	6292	X								–	–		0.1	2880	1.5	3540			@		@		–	–	2250	None	1.02 @ 67	5500	@		To be Transferred. Reversefire
	7	6306.5	X		106.4	+ mud 1200	0	0		0	3670	0.5	2790	Est 15	2790	Est 6.5	3630	1700	106.4	65 @ 60		– @ –	–	FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		To be Transferred.
Segregator #16	7	6306.5	X								–	–		0.1	2790	8.9	3630			@		@		–	–	2250	None.	1.02 @ 67	5500	@		
	8	6315	X		74	500	0		5500	0	–	–	1690	26.3		1	3600	1400	74	@		@		FIT Combo	HTF	22165		1.02 @ 67	5500	@		Reversefire
SEGREGATOR	8	6315	X		7	Trace	0	0	0	0	–	–	600		2940	1	3600	1500	7	@		– @ –	–	–	–	2250	None	1.02 @ 67	5500	@		
	9	6326	X		0	0	0	0	7000	0	–	–	3770	2	3770	0.8	3770	0	0	0 @ 0	0	@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Packer did not seal Mud Run. Reversefire
	10	6285	X		106.9	+ mud 7500	0	[illegible]		0	–	–	2485	13.5	2935	10	3575	1700	106.9	@		@		FIT Combo	HTF	22165	0.020	1.02 @ 67	5500	@		Reversefire
Bream – 2, Run 2, 9+10/4/1969	2	8957	X		2.5	0	0	20000	270	0	5000	0.5	2480	12.5	3900	2.5	5190	600	2.5	– @ –	–	0.86 @ 87	5600	FIT Combo	HTF	22165	0.020	0.80 @ 72	7300	@		
Segregator 26	2	8957			4.2	Trace	0	1750	0	0	–	–			3900		5190	1500	4.2	@		0.82 @ 80	7300			2250	None	0.80 @ 72	7300	@		
	3	8690	X		130	750	0	1000	250	0	5050	0.3	3680	Est 12	3680	Est 5.5	4930	2000	130	52 @ 60		0.91 @ 88	5200	FIT Combo	HTF	22165	0.020	0.80 @ 72	7300	@		
Segregator 24											–	–		0.2	3680	4.8	4930			@		@				2250	None	@		@		To be Transferred.
	4	8616	X		123	600	0	500	200	0	5000	0.5	3700	5.75	3880	8.75	4950	2000	123	@		0.99 @ 78	6000	FIT Combo	HTF	22165	0.030	0.80 @ 72	7300	@		
Segregator 22					14.5	50	0	0	50	0	–	–		0.2	3880	4.3	4950	2200	14.3	@		@				2250	None.	0.80 @ 72	7300	@		
	5	8533	X		0.5	0	0	21000	0	0	4980	1	2400	14	3450	3	5000	200				1.55 @ 64	3800	FIT Combo	HTF + 7/8 SC.	22165	0.020	0.80 @ 72	7300	@		Cable key seated.
Segregator						0	0	2100	0	0	–	–	0	0.3	3600	2.7	5000	200		– @ –	–	1.64 @ 64	3500	FIT		2250	None.	0.80 @ 72	7300	@		
Run 3	1	9178	X		0.1	0	0	20000	0	0	5230	1	2730	5.5	4110	2.5	5270			@		1.31 @ 78	4000	FIT Combo	HTF + 7/8 SC	22165	0.03	0.87 @ 70	7000	@		
Segregator					0	0	0	2200	0	0	–	–	0	0.3	4130	3.2	5270			@		@				2250	None.	0.87 @ 70	7000	– @		
	2	8564	X		0.1	0	0	1750	0	0	4870	1	0	7	3930	32.5	5070	0	0	– @ –	–	1.02 @ 85	4500	FIT Combo	HTF + 7/8 SC	22165	0.03	0.87 @ 70	7000	@		Test Tight.
	3	8411	X		39.7	Trace	0	14000	0	0	4860	1	3280	6	3840	2.5	4820	1700	39.7	– @ –	–	1.15 @ 84	4500	FIT Combo	HTF + 7/8 SC	22165	0.03	0.87 @ 70	7000	@		
	4	8156	X		80.3	600	0	8100	0	0	4590	1	3550	EST 6	3550	2	4550	1900	80.2	@	21000	1.20 @ 74	4700	FIT Combo	HTF + 7/8 SC	22165	0.03	0.87 @ 70	7000	@		
Bream – 2, Run No 4: 20-4-69	1	6315		X	129.5	900	0	0	0	0	–	–	2730	5.4	2850	5.6	3600	1950	129.4	61 @ 60		– @ –	–	FIT Combo	1 x 7/8 SC	22165	0.03	0.76 @ 66	8500	@		
	2	6325.5		X	25	0	4500	0	0	0	2900	0.5	420	43.5	2870	9.5	3740	500	24.7	48.7 @ 60	875	– @ –	–	FIT	2 x 7/8 SC	22165	0.03	0.76 @ 65	8500	@		
Segregator	2	6325.5		X	4.7	0	900	0	50	0		–		8			3740		4.7	@	830	– @ –		–		2250	None	0.76 @ 66	8500	@		

COMPANY: ESSO Standard Oil (Aust)

WELL: Bream 2

FIELD: Wildcat

COUNTRY: Australia STATE: Victoria

SCHLUMBERGER

FORMATION TESTER

DEPT. NAT. RES & ENV
PE903960