

| EXPLORATION LOGGING DRILLING RATE AND DATA <input checked="" type="checkbox"/> FT/HR <input type="checkbox"/> MIN/FT VISUAL POROSITY CORE TEST CO. FAIR TR. CO. FAIR TR. CO. V. GOOD | DEPTH | LITHOLOGY | OIL TRACE CO. TRACE FAIR GOOD V. GOOD | DRILLING MUD | | | | CUTTINGS | | | | REMARKS AND LITHOLOGY DESCRIPTION |
|--|-------|-----------|--|---|---|------------------------------|-------------------------------|----------|---|-----------------|-----|--|
| | | | | CONTINUOUS DITCH GAS | | CHROMATOGRAPHIC ANALYSIS | | CUT | GAS | | GAS | |
| | | | | OIL IN MUD TR. X FAIR XX CO. XXX | TOTAL GAS BACKUP SCALE 10X PETROL VAP | METHANE ETHANE PROPANE | BUTANES PENTANES M-1000 | | TOTAL GAS BACKUP SCALE 10X PETROL VAP | 20 40 60 80 100 | | |
| 20 40 60 80 100 | 100 | 1M | PPM IN AIR | 10M 40M | 20 40 60 80 100 | | | | | | | |
| 400 300 200 100 | 1400 | | | | | | | | | | | CONTINUED FORAMS, SHELL FRAGMENTS, & BRYOZOA. |
| | 1500 | | | | | | | | | | | LIMESTONE: COQUINA MARL, AS ABOVE, MEDIUM GRAY, FIRM, DENSER, DIRTIER, LESS FLUORESCENCE. 1 1/2° |
| | 1600 | | | | | | | | | | | SAND: TAN, CLEAR, GRAY, MEDIUM TO COARSE, SUB-ROUNDED TO ROUNDED, PITTED GRAINS OF SCATTERED QUARTZ. CHERTY. |
| | 1700 | | | | | | | | | | | CG 6 U CG 13 U CG 15 U CG 20 U CG 15 U CG 14 U W 9.1 v 28 STRONG SWEET ODOR AT DITCH, FROM UNWASHED CUTTINGS. W 9.5 v 33 |
| | 1800 | | | | | | | | | | | SHALE: DARK-GRAY, DARK RED-BROWN, FIRM, VERY FISSILE, SLIGHTLY SILTY, RUSTY STAIN ON FRACTURE PLANES. |

