

HORWOOD BAGSHAW LTD., Adelaide, South Aust.

WELL DRILLING CONTRACTORS AND HYDRAULIC ENGINEERS



BORE LOG

W401
COBDENS BORE-1

COBDENS

Bore for M LAKE'S ENTRANCE OIL TRUST Location Lake's Entrance Victoria

Drillers J. Minoque & J. Collins Name of Property Lease No 5383

Commenced Oct 7th 1935 Completed Feb 22nd 1936 Depth Bored 1507' 0"

| CASING IN BORE | | | Thickness of Strata | | Strata MS par drillers time sheets. | Section | Depth Feet | WATER STRUCK | | Supply |
|----------------------------|--------|-------|---------------------|------|---|---------|------------|--------------------------|---------|--------|
| Diam | Length | Brand | Feet | Ins. | | | | Struck at Feet from Surf | Rose to | |
| | | | | | | | | | | |
| | | | | | Blue sticky fossilized | | | | | |
| | | | | | clay | | | | | |
| Shoe Used | | | | | | | | | | |
| Casing Clamps | | | 120 | | | | 600 | | | |
| Size | | | | | | | 620 | | | |
| Type | | | | | | | | | | |
| PUMPING TEST | | | | | | | | | | |
| | | | 40 | | Very sticky blue fossilized clay | | | | | |
| Gallons per hour | | | | | | | 660 | | | |
| Water Level before Pumping | | | | | Gray marl traces of green & gas. | | | | | |
| Water Level when Pumping | | | 89 | | | | 700 | | | |
| Duration of Test | | | 4 | | White stone. | | | | | |
| Depth to Pump | | | | | | | 749 | | | |
| Size of Pump used and Type | | | | | | | 753 | | | |
| REMARKS— | | | | | | | | | | |
| | | | 87 | | Dark gray marl with hard bars. | | | | | |
| | | | 20 | | | | | | | |
| | | | 15 | | Gray marl | | | | | |
| | | | 5 | | Gray fossiliferous marl | | | | | |
| | | | | | | | 860 | | | |
| | | | | | | | 875 | | | |
| | | | | | | | 880 | | | |
| | | | | | | | 900 | | | |
| | | | | | Gray sticky marl. | | | | | |
| | | | 105 | | | | | | | |
| | | | | | | | 985 | | | |
| | | | | | " " " | | 1000 | | | |

Entered by W.H.C.

HORWOOD BAGSHAW LTD.
MILE END, S.A.

DATE March 18th 1936

Approved *W. J. Barker*