SCHLUMBERGER

Electrical Log

COUNTRY AUSTRALIA
FIELD or LOCATION PORT CAMPBELL
WELL 3
COMPANY FROME-BROKEN HILL

COMPANY FROME-BROKEN HILL COMPANY PTY. LTD.
WELL 3
FIELD PORT CAMPBELL
LOCATION
STATE VICTORIA
COUNTRY AUSTRALIA

Location of Well

Note: Depth Scale 1"/100'

Elevation: R.T.: 210' D.F.: 209' K.B.: 212' or G.L.: 195'

FILING No.

RUN No.	1	2	3	4	
Date	9/2/'61	15/2/'61	20/2/'61	25/2/'61	
First Reading	1262'	3289'	4407'	5530'	
Last Reading	46'	1284'	3089'	4207'	
Feet Measured	1216'	2005'	1318'	1323'	
Csg. Schlum.	46'	1284'	1284'		
Csg. Driller	47'	1286'	1286'	1286'	
Depth Reached	1263'	3290'	4408'	5531'	
Bottom Driller	1265'	3292'	4410'	5530'	
Depth Datum	R.T.	R.T.	R.T.	R.T.	
Mud Nat.	BENTONITE	NATURAL	NATURAL	CAUSTIC/BENTONITE	
" Density	8·6lbs	11·1 lbs	10·3lbs	10·3lbs	
" Viscosity	70 sec	42 sec	37 sec	58 sec	
" Resist.	1·50 @ 69 °F	1·46 @ 87 °F	1·40 @ 80 °F	0·92 @ 75 °F	@ °F
" Res. BHT	1·05 @ 102 °F	1·17 @ 114 °F	0·90 @ 124 °F	0·44 @ 138 °F	@ °F
" pH	@ °F	7·0 @ °F	7·0 @ °F	11·0 @ °F	@ °F
" Wtr. Loss	CC 30 min.	70 CC 30 min.	60 CC 30 min.	13·8 CC 30 min.	CC 30 min.
Max. Temp. °F	102	114	124	138	
Bit Size		12 1/4	12 1/4	12 1/4 4676. 8 3/4 5530'	
Spcgs.—AM	16"	16"	16"	16"	
A	64"	64"	64"	64"	
AO	18' 8"	18' 8"	18' 8"	18' 8"	
Opr. Rig Time	4·30hrs	2·30hrs	2·30hrs	2·30hrs	
Truck No.	SKW-D 215	SKW-D 215	SKW-D 215	SKW-D 215	
Recorded By	J. WHITE	J. WHITE	J. WHITE	J. WHITE	
Witness By	J. BAIN	J. BAIN	J. BAIN	J. BAIN	

LEGEND

- Coarse clastic congl.
- Sands of Wangerrip & Paaratte
- Sandstones of Waarre & Otway
- Thin bedded limestone.
- Ankerite or dolomite.
- Marl.
- Mudstone.
- Interbedded ankerite or dolomite.
- Siltstone.
- Coal.
- Interbedded sandstone.
- Interbedded limestone.
- Interbedded coal.
- Interbedded mudstone.
- Interbedded marl.
- Interbedded siltstone.

ACCESSORIES

- Glauconite.
- Pyrite
- Oxidized
- Macrofossil
- Microfossil
- Plant remains
- Cored.
- D.S.T.
- Casing
- Perf. not squeezed
- Perf. for squeeze
- Perf. tested and squeezed
- Cement plug.
- Bridge plug.

REMARKS

RUN No 1. Bit sizes 17" from 47' to 1952'; 12 1/4" from 952' to 1265'

RUN No 2. S.P. scale change to 15mv/div. S.P. ground return at torpedo connection.

WELLSITE GEOLOGISTS: J.S. BAIN, S. BENEDEK, A.A. WEEGAR. LOG PLOTTED BY: J.S. BAIN.

DEPT. NAT. RES & ENV
PE604798

F.B.H. PORT CAMPBELL No 3.

WELL COMPLETION LOG

Spud in: 31 JAN 1961.
Total depth reached: 25 FEB 1961.

Well Completion Report — Port Campbell No. 3
By J.S. Bain & S. Benedek.

F.BH Report No.: 7200-G-80.
PLATE 2