

Type		KCl/Polymer	KCl/Polymer	KCl/Polymer						
Mud weight	sg	1.30	1.30	1.31						
Solids	%vol	12.5	13.0	13.5						
Chlorides	mg/l	53,000	49,000	53,000						
Rm	ohm.m@degC	0.129@27	0.105@26	0.123@22						
Rmf	ohm.m@degC	0.093@27	0.088@26	0.083@22						
Rmc	ohm.m@degC	0.229@27	0.186@26	0.248@22						
Potassium	mg/l	45,000	44,000	44,000						
Environmental data										
GR										
Mud weight	sg	1.30	1.30	1.31						
Bit size	in	8.5	8.5	8.5						
Resistivity										
Neutron porosity										
Hole Size										
Mud weight										
Temperature										
Mud salinity										
Formation salinity										
Recording rate 1	SEC	10 sec	10 sec	10 sec	ARC GR					
Recording rate 2	SEC	10 sec	10 sec	10 sec	ARC RES					
Filtering GR		3 point	3 point	3 point						
Filtering density										
Filtering Neutron										
Company representative		D.Bell	M.Bilek	G.Westie						
Anadrill personnel		A.Strahan	L.Muskett							

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN1	OTHER SERVICES FOR RUN2	OTHER SERVICES FOR RUN3
MWD Surveys. DWOB/DTORQ. APWD monitoring.	MWD Surveys. DWOB/DTORQ. APWD monitoring.	MWD Surveys. DWOB/DTORQ. APWD monitoring.
REMARKS: RUN NUMBER 1 Rotary drilled from 1666-1814m. Environmental conditions applied:- ARC GR: K+, borehole size and mud weight ARC resistivity is borehole compensated but not environmentally corrected. 10 June 01 06:48 Initialise ARC#087 with 10sec GR, 2MHz and 400KHz resistivity configuration. 09:15 BHA below rotary table. 18:50 On bottom drilling new formation in the 8 1/2" hole at 1666m 11 June 01 01:10 Real-time data lost between 1648m-1689m due to corrupt surface software. 08:40 TD at 1814m for coring. 16:20 BHA above rotary table. Retrieve ARC recorded mode memory data.	REMARKS: RUN NUMBER 2 Ream logging data from 1814-1850m Rotary drilled from 1850-1907m. Environmental conditions applied:- ARC GR: K+, borehole size and mud weight ARC resistivity is borehole compensated but not environmentally corrected. 12 June 01 10:32 Initialise ARC#087 with 10sec GR, 2MHz and 400KHz resistivity configuration. 11:15 BHA below rotary table. 15:10 Ream down to acquire LWD data from 1814-1850m. 17:10 On bottom drilling at 1850m 21:00 TD at 1907m for coring 13 June 01 2:45 BHA above rotary table. Retrieve ARC recorded mode memory data.	REMARKS: RUN NUMBER 3 Ream logging data from 1907-1915m Rotary drilled from 1915-2430m. Environmental conditions applied:- ARC GR: K+, borehole size and mud weight ARC resistivity is borehole compensated but not environmentally corrected. 14 June 01 00:15 Initialise ARC#087 with 10sec GR, 2MHz and 400KHz resistivity configuration. 00:30 BHA below rotary table. 04:10 Ream down to acquire LWD data from 1907-1915m. 04:35 On bottom drilling at 1915m 16 June 01 01:20 TD at 2430m 16 June 01 ??:?? BHA above rotary table. Retrieve ARC recorded mode memory data.

EQUIPMENT DESCRIPTION

RUN1

RUN2

RUN3

DOWNHOLE EQ

DOWNHOLE E

DOWNHOLE EQ

PowerPulse MW

17.0

PowerPulse MW

17.1

PowerPulse MW

17.1

D&I

— 12.8

D&I

— 12.8

D&I

— 12.8

In-line Stabilis

8.63

In-line Stabilis

8.67

In-line Stabilis

8.67

ARC675

7.15

ARC675

7.19



ARC675

7.19

R-O P	—	4.89
T5	—	4.79
T3	—	4.48
T1	—	4.18
Gamma	///	3.75
Receiv	///	3.67
T2	///	3.52
T4	///	3.21
ARC AP	///	3.06

R-O P	—	4.93
T5	—	4.83
T3	—	4.52
T1	—	4.22
Gamma	///	3.79
Receiv	///	3.71
T2	///	3.56
T4	///	3.25
ARC AP	///	3.10

R-O P	—	4.93
T5	—	4.83
T3	—	4.52
T1	—	4.22
Gamma	///	3.79
Receiv	///	3.71
T2	///	3.56
T4	///	3.25
ARC AP	///	3.10

Float S		1.32	Float S		1.36	Float S		1.36
DOG S		0.46	DOG S		0.50	DOG S		0.50
Bit-PD		0.00 0.28	Bit-PD		0.00 0.32	Bit-PD		0.00 0.32
MAXIMUM STRING DI			MAXIMUM STRING DI			MAXIMUM STRING DI		
ALL LENGTHS I			ALL LENGTHS I			ALL LENGTHS I		

IDEAL Version: ID6_1C_03

IDF

ARC5_675

id6_1c_03

MWD_10

id6_1c_03

Format: ARC_Dual_Freq_Res

Vertical Scale: 1:200

Graphics File Created: 16-Jun-2001 18:20

Parameters

DLIS Name	Description	Value
AAPS	ARC5 Attenuation and Phase-Shift source	1_UPHOLE
APICG	ARC5 Gamma Ray API and Gain Combined Factor	1.091
ATRN	ARC5 Tool Run Number	GEOARC_IWARC675 / PP
ATSN	ARC5 Tool Serial Number	087
BHFCT_ARC	ARC5:GR Borehole Factor	1.740
BS_RM	Bit Size (RM)	8.500 in
DO	Depth Offset	0.0 m
KPER	ARC5:Potassium Concentration	44000.0
MST_RM	Mud Sample temperature (RM)	22.000 degC
MW_RM	Mud Weight (RM)	1.310 g/cm3
RMS_RM	Resistivity of Mud Sample (RM)	0.116 ohm.m
VERS_ARC	ARC5 Down hole software version Number	6.300
WRK	ARC5: Way to Report Potassium Concentration	POTASSIUM_BY_PARTS_PER_MILLION_IE_MG/KG


PIP SUMMARY

- └ ARC Gamma Ray Samples
- └ ARC Resistivity Samples


	ARC Non-BHCorr Phase-Shift Resistivity 40-in. at 2 MHz (P40H_UNC)	ARC Non-BHCorr Phase-Shift Resistivity 40-in. at 400 KHz (P40L_UNC)
	0.2 (OHMM) 2000	0.2 (OHMM) 2000
	ARC Non-BHCorr Phase-Shift Resistivity 34-in. at 2 MHz (P34H_UNC)	ARC Non-BHCorr Phase-Shift Resistivity 34-in. at 400 KHz (P34L_UNC)
	0.2 (OHMM) 2000	0.2 (OHMM) 2000
ARC Calibrated, Filtered Gamma Ray (GR_ARC_FILT)	ARC Non-BHCorr Phase-Shift Resistivity 28-in. at 2 MHz (P28H_UNC)	ARC Non-BHCorr Phase-Shift Resistivity 28-in. at 400 KHz (P28L_UNC)
0 (GAPI) 200	0.2 (OHMM) 2000	0.2 (OHMM) 2000
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)	ARC Non-BHCorr Phase-Shift Resistivity 22-in. at 2 MHz (P22H_UNC)	ARC Non-BHCorr Phase-Shift Resistivity 22-in. at 400 KHz (P22L_UNC)
200 (M/HR) 0	0.2 (OHMM) 2000	0.2 (OHMM) 2000



over Last 5ft (ROP5_RM)
200 (M/HR) 0



ARC Resistivity Time After Bit
(TAB_ARC_RES)
0 (HR) 10







Resistivity 22-in. at 2 MHz (P22H UNC) 0.2 (OHMM) 2000
Resistivity 34-in. at 2 MHz (A34H UNC) 0.2 (OHMM) 2000
Resistivity 22-in. at 400 KHz (P22L UNC) 0.2 (OHMM) 2000
ARC Non-BHCorr Phase-Shift Resistivity 16-in. at 2 MHz (P16H UNC) 0.2 (OHMM) 2000
ARC Non-BHCorr Attenuation Resistivity 28-in. at 2 MHz (A28H UNC) 0.2 (OHMM) 2000
ARC Non-BHCorr Phase-Shift Resistivity 16-in. at 400 KHz (P16L UNC) 0.2 (OHMM) 2000





















































2400



2425



TD at 2430m.

ARC Resistivity Time After Bit
(TAB_ARC_RES)
0 (HR) 10

Rate of Penetration, Averaged
over Last 5ft (ROP5_RM)
200 (M/HR) 0

ARC Calibrated, Filtered
Gamma Ray (GR_ARC_FILT)
0 (GAPI) 200

ARC Non-BHCorr Phase-Shift
Resistivity 16-in. at 2 MHz
(P16H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Attenuation
Resistivity 28-in. at 2 MHz
(A28H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 16-in. at 400 KHz
(P16L_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 22-in. at 2 MHz
(P22H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Attenuation
Resistivity 34-in. at 2 MHz
(A34H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 22-in. at 400 KHz
(P22L_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 28-in. at 2 MHz
(P28H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Attenuation
Resistivity 40-in. at 2 MHz
(A40H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 28-in. at 400 KHz
(P28L_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 34-in. at 2 MHz
(P34H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 34-in. at 400 KHz
(P34L_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 40-in. at 2 MHz
(P40H_UNC)
0.2 (OHMM) 2000

ARC Non-BHCorr Phase-Shift
Resistivity 40-in. at 400 KHz
(P40L_UNC)
0.2 (OHMM) 2000

PIP SUMMARY

ARC Gamma Ray Samples

└ ARC Gamma Ray Samples
└ ARC Resistivity Samples

IDEAL Version: ID6_1C_03
IDF

ARC5_675

id6_1c_03

MWD_10

id6_1c_03

6.75-in. Array Resistivity Compensated / Equipment Identification

Primary Equipment:
Tool Name and Serial Number
ARC675 Calibration Status

ARC - 675 #087
OK

Master: 25-APR-01

6.75-in. Array Resistivity Compensated Calibration

Resistivity: Air

Phase	Phase-Shift T1	DEG	Value	Phase	Phase-Shift T2	DEG	Value	Phase	Phase-Shift T3	DEG	Value
Master			-0.2200	Master			0.5200	Master			-0.3600
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T4	DEG	Value	Phase	Phase-Shift T5	DEG	Value	Phase	Phase-Shift T1 at 400KHz	DEG	Value
Master			0.4200	Master			-0.4200	Master			-0.5800
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T2 at 400KHz	DEG	Value	Phase	Phase-Shift T3 at 400KHz	DEG	Value	Phase	Phase-Shift T4 at 400KHz	DEG	Value
Master			0.6400	Master			-0.5800	Master			0.6400
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)
Phase	Phase-Shift T5 at 400KHz	DEG	Value								
Master			-0.5500								
	-3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)								

Master: 25-APR-01

6.75-in. Array Resistivity Compensated Calibration

Resistivity: Air

Phase	Attenuation T1	DB	Value	Phase	Attenuation T2	DB	Value	Phase	Attenuation T3	DB	Value
Master			8.550	Master			6.485	Master			5.159
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T4	DB	Value	Phase	Attenuation T5	DB	Value	Phase	Attenuation T1 at 400KHz	DB	Value
Master			4.329	Master			3.671	Master			8.510
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)		6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)
Phase	Attenuation T2 at 400KHz	DB	Value	Phase	Attenuation T3 at 400KHz	DB	Value	Phase	Attenuation T4 at 400KHz	DB	Value
Master			6.470	Master			5.110	Master			4.360
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz	DB	Value								
Master			3.670								
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)								

Master: 25-APR-01

6.75-in. Array Resistivity Compensated Calibration

Gamma Ray: Blanket

Gamma Ray: Blanket

Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS		Value
Master			5.237
	3.840 (Minimum)	4.800 (Nominal)	6.000 (Maximum)

ANADRILL

SCHLUMBERGER

Survey report 16-Jun-2001 18:27:28 Page 1 of 4

Client.....: Woodside Energy Limited
Field.....: Exploration

Well.....: Geographe-1
API number.....:
Engineer.....:

Spud date.....: 30May 01
Last survey date.....: 16-Jun-01
Total accepted surveys...: 61
MD of first survey.....: 110.00 m
MD of last survey.....: 2430.00 m

COUNTRY:.....: Australia
STATE:.....: Victoria

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Geomagnetic data -----
Magnetic model.....: BGM version 2000
Magnetic date.....: 07-Jun-2001
Magnetic field strength..: 1223.18 HCNT
Magnetic dec (+E/W-).....: 11.05 degrees
Magnetic dip.....: -70.29 degrees

----- Depth reference -----
Permanent datum.....: GROUND LEVEL
Depth reference.....:
GL above permanent.....: -15240.00 m
KB above permanent.....: -15240.00 m
DF above permanent.....: -15240.00 m

----- MWD survey Reference Criteria -----
Reference G.....: 1000.11 mGal
Reference H.....: 1223.18 HCNT
Reference Dip.....: -70.29 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Vertical section origin-----
Latitude (+N/S-).....: 0.00 m
Departure (+E/W-).....: 0.00 m

----- Corrections -----
Magnetic dec (+E/W-).....: 11.05 degrees
Grid convergence (+E/W-)..: 1.20 degrees
Total az corr (+E/W-).....: 9.85 degrees
(Total az corr = magnetic dec - grid conv)
Sag applied (Y/N).....: No degree: 0.00

----- Platform reference point-----
Latitude (+N/S-).....: -304.57 m
Departure (+E/W-).....: -304.57 m

Azimuth from rotary table to target: 0.00 degrees

[(c)2001 Anadrill IDEAL ID6_1C_03]
ANADRILL SCHLUMBERGER Survey Report

16-Jun-2001 18:27:28 Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool qual type
1	110.00	0.00	0.00	0.00	110.00	-6.20	-6.20	8.70	10.68	125.48	0.00	TIP	-
2	189.10	0.50	231.87	79.10	189.10	-6.41	-6.41	8.43	10.59	127.27	0.06	MS	-
3	218.10	0.56	238.20	29.00	218.10	-6.57	-6.57	8.21	10.51	128.66	0.03	MS	-
4	247.10	0.38	220.69	29.00	247.10	-6.71	-6.71	8.03	10.46	129.91	0.08	MS	-
5	276.10	0.35	249.81	29.00	276.10	-6.82	-6.82	7.88	10.42	130.86	0.06	MS	-
6	305.10	0.36	245.47	29.00	305.10	-6.89	-6.89	7.71	10.34	131.75	0.01	MS	-
7	334.10	0.36	242.38	29.00	334.10	-6.97	-6.97	7.55	10.27	132.69	0.01	MS	-
8	363.10	0.21	240.21	29.00	363.09	-7.03	-7.03	7.42	10.23	133.46	0.05	MS	-
9	392.10	0.28	233.99	29.00	392.09	-7.10	-7.10	7.32	10.20	134.14	0.03	MS	-
10	421.10	0.31	212.96	29.00	421.09	-7.21	-7.21	7.22	10.20	134.96	0.04	MS	-
11	450.10	0.24	173.99	29.00	450.09	-7.34	-7.34	7.18	10.27	135.60	0.07	MS	-
12	479.10	0.17	337.21	29.00	479.09	-7.36	-7.36	7.17	10.27	135.72	0.14	MS	-
13	508.10	0.22	183.67	29.00	508.09	-7.37	-7.37	7.15	10.27	135.87	0.13	MS	-
14	537.10	0.18	205.51	29.00	537.09	-7.47	-7.47	7.13	10.33	136.33	0.03	MS	-
15	560.10	0.13	125.20	23.00	560.09	-7.52	-7.52	7.14	10.36	136.49	0.09	MS	-
16	623.90	0.45	124.14	63.80	623.89	-7.70	-7.70	7.40	10.68	136.13	0.05	MS	-
17	652.80	0.42	116.52	28.90	652.79	-7.81	-7.81	7.59	10.89	135.82	0.02	MS	-
18	681.70	0.49	120.36	28.90	681.69	-7.92	-7.92	7.79	11.11	135.47	0.03	MS	-
19	710.70	0.51	109.34	29.00	710.69	-8.03	-8.03	8.02	11.35	135.02	0.03	MS	-
20	739.80	0.62	110.62	29.10	739.79	-8.12	-8.12	8.29	11.61	134.42	0.04	MS	-
21	768.70	0.79	99.81	28.90	768.69	-8.21	-8.21	8.63	11.92	133.57	0.07	MS	-
22	797.80	0.73	96.47	29.10	797.78	-8.27	-8.27	9.01	12.23	132.52	0.03	MS	-
23	826.90	0.71	102.56	29.10	826.88	-8.33	-8.33	9.38	12.54	131.61	0.03	MS	-
24	855.80	0.58	113.58	28.90	855.78	-8.43	-8.43	9.68	12.84	131.02	0.06	MS	-
25	884.70	0.50	169.10	28.90	884.68	-8.61	-8.61	9.84	13.07	131.17	0.18	MS	-
26	913.50	0.39	172.08	28.80	913.48	-8.83	-8.83	9.88	13.25	131.78	0.04	MS	-
27	942.60	0.10	201.84	29.10	942.58	-8.95	-8.95	9.88	13.33	132.16	0.11	MS	-
28	971.70	0.10	134.56	29.10	971.68	-8.99	-8.99	9.89	13.37	132.27	0.04	MS	-
29	1000.80	0.12	143.17	29.10	1000.78	-9.03	-9.03	9.93	13.42	132.30	0.01	MS	-
30	1029.90	0.19	237.08	29.10	1029.88	-9.08	-9.08	9.91	13.44	132.52	0.08	MS	-

[(c)2001 Anadrill IDEAL ID6_1C_03]

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool qual type
31	1059.00	0.15	220.33	29.10	1058.98	-9.14	-9.14	9.84	13.43	132.88	0.02	MS	-
32	1088.00	0.37	305.43	29.00	1087.98	-9.11	-9.11	9.74	13.34	133.10	0.13	MS	-
33	1116.50	0.39	285.43	28.50	1116.48	-9.03	-9.03	9.57	13.16	133.35	0.05	MS	-
34	1145.50	0.43	350.19	29.00	1145.48	-8.90	-8.90	9.46	12.99	133.26	0.15	MS	-
35	1174.00	0.23	282.58	28.50	1173.97	-8.78	-8.78	9.38	12.85	133.11	0.14	MS	-
36	1203.20	0.28	267.73	29.20	1203.17	-8.77	-8.77	9.26	12.75	133.47	0.03	MS	-
37	1232.50	0.41	270.75	29.30	1232.47	-8.77	-8.77	9.08	12.63	134.02	0.04	MS	-
38	1261.70	0.56	273.94	29.20	1261.67	-8.76	-8.76	8.83	12.44	134.78	0.05	MS	-
39	1290.60	0.65	250.61	28.90	1290.57	-8.81	-8.81	8.54	12.27	135.90	0.09	MS	-
40	1319.60	0.58	232.53	29.00	1319.57	-8.95	-8.95	8.26	12.18	137.29	0.07	MS	-
41	1348.80	0.40	236.73	29.20	1348.77	-9.10	-9.10	8.06	12.16	138.45	0.06	MS	-
42	1378.00	0.44	196.58	29.20	1377.97	-9.26	-9.26	7.95	12.20	139.37	0.10	MS	-
43	1406.60	0.39	315.22	28.60	1406.57	-9.30	-9.30	7.85	12.17	139.84	0.25	MS	-
44	1435.70	0.22	329.68	29.10	1435.67	-9.18	-9.18	7.75	12.01	139.84	0.06	MS	-
45	1464.50	0.74	239.16	28.80	1464.47	-9.23	-9.23	7.56	11.93	140.67	0.27	MS	-
46	1493.00	0.49	244.45	28.50	1492.96	-9.37	-9.37	7.29	11.88	142.12	0.09	MS	-
47	1522.30	0.27	290.71	29.30	1522.26	-9.40	-9.40	7.11	11.79	142.89	0.12	MS	-
48	1551.30	0.54	354.50	29.00	1551.26	-9.24	-9.24	7.04	11.62	142.72	0.17	MS	-
49	1580.60	0.73	23.01	29.30	1580.56	-8.93	-8.93	7.10	11.41	141.54	0.12	MS	-
50	1609.70	0.52	2.07	29.10	1609.66	-8.63	-8.63	7.17	11.22	140.27	0.11	MS	-
51	1629.00	0.60	320.28	19.30	1628.96	-8.47	-8.47	7.11	11.06	139.97	0.21	MS	-
52	1644.90	0.82	304.70	15.90	1644.86	-8.34	-8.34	6.97	10.86	140.12	0.18	MS	-
53	1712.56	1.32	331.60	67.66	1712.51	-7.38	-7.38	6.20	9.63	139.96	0.10	MWD	6-axis
54	1771.96	2.31	281.29	59.40	1771.88	-6.54	-6.54	4.70	8.05	144.31	0.30	MWD	6-axis
55	1858.15	2.75	285.30	86.19	1857.98	-5.65	-5.65	1.00	5.74	169.97	0.05	MWD	6-axis
56	1892.08	2.74	285.94	33.93	1891.88	-5.22	-5.22	-0.56	5.25	186.18	0.01	MWD	6-axis
57	1982.51	3.40	279.36	90.43	1982.18	-4.19	-4.19	-5.29	6.75	231.63	0.08	MWD	6-axis
58	2069.37	3.67	272.00	86.86	2068.87	-3.67	-3.67	-10.61	11.23	250.91	0.06	MWD	6-axis
59	2217.19	4.06	267.99	147.82	2216.35	-3.69	-3.69	-20.57	20.89	259.83	0.03	MWD	6-axis
60	2314.68	4.18	272.34	97.49	2313.59	-3.67	-3.67	-27.57	27.81	262.43	0.03	MWD	6-axis

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool qual type
61	2430.00	4.18	272.34	115.32	2428.61	-3.32	-3.32	-35.96	36.12	264.72	0.00	MWD	Proj

Company: Woodside Energy Limited

Well: Geographe-1 Exploration

Field: Permit VIC/P43

Rig: Ocean Bounty

State: Victoria

IDEAL services from Anadrill

VISION Resistivity – 2MHz & 400KHz
 Measured Depth
 Scale 1:200



