

Rig: **ISDL 453** State: **Victoria**

Bit Run Summary

[illegible]

Type	KCL/PHPA/GLYCOL									
Mud weight	ppg	10.3								
Solids	%vol	7.3								
Chlorides	mg/l	48,000								
Rm	Ohmm@degC	0.1419@20								
Rmf	Ohmm@degC	0.1046@20								
Rmc	Ohmm@degC	0.2120@20								
Potassium	%vol	4								
Environmental data										
GR										
Mud weight	ppg	10.3								
Bit size	in	8.5								
Resistivity										
Neutron porosity										
Hole Size	in	8.5								
Mud weight	ppg	10.3								
Temperature	DegC	75.29								
Mud salinity	mg/l	48,000								
Formation salinity										
Recording rate 1	SEC	10								
Recording rate 2	SEC	10								
Filtering GR		3 pt								
Filtering density		3 pt								
Filtering Neutron		3 pt								
Company representative	G. Cambell	B. Davies								
Anadrill personnel	J. Walta	L. Bon	W. Betheux							

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN3 Directional Surveys	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 3 8-1/2in Hole Section was logged from 829 m to 3206 m MD. Depth is referenced to the Driller's pipe tally. All data presented is from tool memory. GR corrected for mud weight, tool and bit size. RAB6 Resistivity is corrected for the bit size, mud resistivity and borehole temperature. Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehome salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure) Mud type is water based KCl/PHPA/GLYCOL. Barite is present in the mud. RAB6C Downhole Software 6C-V6.1 ADN6C Downhole Software 6.2B08	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

There were discrepancies in the pipe tally this run.


EQUIPMENT DESCRIPTION

RUN1

RUN

RUN

DOWNHOLE EQ



A675XP S/N 2179

0.78 deg bend



Bit-PDC

Geo-Diamond Model: S75HPX

MAXIMUM STRING DI

ALL LENGTHS I

0.19
0.00

IDEAL Version: ID7_OC_02

IDF

RAB
ADNIDEAL Version: ID7_OC_02
IDEAL Version: ID7_OC_02

MWD_10

IDEAL Version: ID7_OC_02

Format: A31 RM Density Neutron

Vertical Scale: 1:500

Graphics File Created: 21-Jul-2002 16:52

Parameters

DLIS Name	Description	Value
ADN_COLLAR_STR	ADN Collar Type String	ADDC-AA: Slick
ADN_STAB_STR	ADN Stabilizer Type String	None
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES
A_DHS	ADN Down Hole Software Version String	V6.2B
BHA_COEF_VER	RAB: BHA Coef Generator Version	62012.0
BHT_RM	Bottom Hole Temperature (RM)	75.290 degC
BSAL_RM	Mud Salinity (RM)	79.200 ppk
BS_RM	Bit Size (RM)	8.500 in
DEVI	Well Section Deviation	0.100 deg
DHS_VERSION	RAB: DownHole Software Version	6.101
DO	Depth Offset	0.0 m
DTMUD	Delta-T for Mud	630.0 us/m
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES
GRDC	Grid corr angle	-0.880 deg
LITHO_TYPE_ADN	Lithology (RM)	LIME
MST_RM	Mud Sample temperature (RM)	20.000 degC
MW_RM	Mud Weight (RM)	10.300 lbm/gal
OBM	RAB: Oil base Mud	NO
OBMF_RM	Oil Based Mud	NO
RAB_TEMP_SELECT	RAB Temperature Selection	MEAS
READOUT_PORT_MP	RAB: ROP to Bit Face Distance	14.700 m
RHOF_RM	Mud Filtrate Density (RM)	1.000 g/cm3
RHOM_RM	Matrix density (RM)	2.710 g/cm3
RMS_RM	Resistivity of Mud Sample (RM)	0.142 ohm.m
RWS_RM	Resistivity of Connate Water (RM)	1.000 ohm.m
SHT_RM	Surface Hole Temperature (RM)	15.000 degC
SSIZ_ADN	ADN Stabilizer Size	8.250 in
STAB	RAB: Run with Stabilizer	YES
TD_RM	Total Measured Depth (RM)	3220.0 m
TOOLTYPE	RAB: Azimuthal Tool	YES
TRPM_RM	Average Tool Rotational Speed	20.000 c/min
TSIZ_ADN	ADN Tool Size	6.750 in
TS_VERSION	RAB: ToolScope Software Version	6.101
TWS_RM	Temperature of Connate Water (RM)	23.889 degC
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.300 in
VERS_ADN	ADN Downhole Software Version	6.200
VRAB6	Rab Tool type (ENP/PILOT)	RAB6_C SERIES

PIP SUMMARY

Neutron Samples

PIP SUMMARY

└ Neutron Samples

Density Samples

└ Gamma Ray Samples

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)
200 (M/HR) 0

RAB Gamma Ray (GR_RAB)
0 (GAPI) 200

Density Time After Bit (TAB_DEN)
0 (HR) 10

Vertical Hole Diameter (VERD)
6 (IN) 16

Horizontal Hole Diameter (HORD)
6 (IN) 16

ADN
Rotational
Speed
(RPM_ADN)
(RPM)
0 200


Gas Area
From ROBB to TNPH

Bulk Density, Bottom (ROBB)
1.85 (G/C3) 2.85

Thermal Neutron Porosity (TNPH)
45 (PU) -15

Bulk Density (RHOB)
1.85 (G/C3) 2.85



Photoelectric Factor, Bottom (PEB)
0 (-----) 10
Bulk Density Correction, Bottom
(DRHB)
-0.25 (G/C3) 0.25







900



950



1000






































































<div><div>Horizontal Hole Diameter (HORD)</div><div>6 (IN) 16</div></div>	<div>ADN Rotational Speed (RPM_ADN) (RPM) 0 200</div>	<div><div>Photoelectric Factor, Bottom (PEB)</div><div>0 (----) 10</div></div>	<div><div>Bulk Density Correction, Bottom (DRHB) (G/C3)</div><div>-0.25 0.25</div></div>
<div><div>Vertical Hole Diameter (VERD)</div><div>6 (IN) 16</div></div>		<div><div>Bulk Density (RHOB) (G/C3)</div><div>1.85 2.85</div></div>	
<div><div>Density Time After Bit (TAB_DEN)</div><div>0 (HR) 10</div></div>		<div><div>Thermal Neutron Porosity (TNPH) (PU)</div><div>45 -15</div></div>	
<div><div>RAB Gamma Ray (GR_RAB)</div><div>0 (GAPI) 200</div></div>		<div><div>Bulk Density, Bottom (ROBB) (G/C3)</div><div>1.85 2.85</div></div>	
<div><div>Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR)</div><div>200 0</div></div>		<div><div>Gas Area From ROBB to TNPH</div></div>	

PIP SUMMARY	
+ Neutron Samples	Density Samples
+ Gamma Ray Samples	

IDEAL Version: ID7_0C_02 IDF			
RAB ADN	IDEAL Version: ID7_0C_02 IDEAL Version: ID7_0C_02	MWD_10	IDEAL Version: ID7_0C_02

6.75-in. Azimuthal Density Neutron / Equipment Identification			
Primary Equipment: Tool Name and Serial Number Neutron Logging Source Density Logging Source Stabilizer Size Calibration Status		ADN6 - CA NSR - M GSR - J/Z 8.25 - in. Valid	289 A161 A2125

Master: 5-MAY-2002 12:34				
6.75-in. Azimuthal Density Neutron Calibration				
Density: Magnesium Block				
Phase	LS window 3 - Mg CPS	Value	Phase	SS window 1 - Mg CPS
Master	1304	3005	Master	7415
250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)	700.0 (Minimum)	9350 (Nominal)
		18000 (Maximum)		23750 (Nominal)
				45000 (Maximum)

0.9000
(Minimum)

1.100
(Nominal)

1.300
(Maximum)

6.75-in. Resistivity At-the-Bit / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

RAB6 - CA

136

Calibration Status

Valid

Master: 10-JUN-2002 14:00

6.75-in. Resistivity At-the-Bit Calibration

Resistivity: Fixture

Phase	Ring/T1 factor ----	Value	Phase	Ring/T2 factor ----	Value	Phase	M0/T1 factor ----	Value
Master		0.9840	Master		0.9910	Master		0.9920
	0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)	
Phase	M0/T2 factor ----	Value	Phase	M2/T1 factor ----	Value	Phase	M2/T2 factor ----	Value
Master		0.9960	Master		0.9940	Master		0.9980
	0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)	
Phase	BTN shallow/T1 factor ----	Value	Phase	BTN shallow/T2 factor ----	Value	Phase	BTN medium/T1 factor ----	Value
Master		1.016	Master		1.017	Master		1.019
	0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)	
Phase	BTN medium/T2 factor ----	Value	Phase	BTN deep/T1 factor ----	Value	Phase	BTN deep/T2 factor ----	Value
Master		1.021	Master		1.018	Master		1.021
	0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)			0.9750 (Minimum) 1.000 (Nominal) 1.025 (Maximum)	

Master: Calibration date not found

6.75-in. Resistivity At-the-Bit Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor ----	Value
Master		0.8800
	0.7500 (Minimum) 1.000 (Nominal) 1.250 (Maximum)	

ANADRILL

SCHLUMBERGER

Survey report

16-Jul-2002 15:22:12

Page 1 of 6

Client.....: Esso Australia Ltd.
Field.....: Tuna

Well.....: A-31
API number.....:
Engineer.....: J. Walta

COUNTY.....: ISDL 453
STATE.....: Victoria

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: GROUND LEVEL
Depth reference.....: Driller's Pipe Tally
GL above permanent.....: -59.40 m
KB above permanent.....: 31.30 m
DF above permanent.....: 31.30 m

----- Vertical section origin-----

Spud date.....: 30-Jun-02
Last survey date.....: 16-Jul-02
Total accepted surveys...: 141
MD of first survey.....: 0.00 m
MD of last survey.....: 3220.00 m

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2001
Magnetic date.....: 27-Jun-2002
Magnetic field strength..: 1200.42 mGNT
Magnetic dec (+E/W-)....: 13.16 degrees
Magnetic dip.....: -68.69 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.02 mGal
Reference H.....: 1200.42 mGNT
Reference Dip.....: -68.69 degrees
Tolerance of G.....: (+/-) 2.50 mGal

----- Vertical section origin-----
Latitude (+N/S-).....: 1.86 m
Departure (+E/W-).....: 6.34 m

----- Platform reference point-----
Latitude (+N/S-).....: 1.86 m
Departure (+E/W-).....: 6.34 m

Azimuth from rotary table to target: 88.50 degrees

Reference Dip.....: -68.69 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 13.16 degrees
Grid convergence (+E/W-)..: -0.88 degrees
Total az corr (+E/W-).....: 14.04 degrees
(Total az corr = magnetic dec - grid conv)

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

16-Jul-2002 15:22:12

Page 2 of 6

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
1	0.00	0.00	0.00	0.00	0.00	0.00	1.86	6.34	0.00	73.65	0.00	TIP	-
2	12.07	0.07	344.00	12.07	12.07	0.00	1.87	6.34	0.01	73.59	0.06	GYR	-
3	17.07	0.15	344.00	5.00	17.07	0.00	1.88	6.34	0.02	73.50	0.16	GYR	-
4	22.07	0.14	312.50	5.00	22.07	-0.01	1.89	6.33	0.03	73.40	0.16	GYR	-
5	27.07	0.33	283.90	5.00	27.07	-0.03	1.89	6.31	0.04	73.29	0.44	GYR	-
6	32.07	0.48	276.70	5.00	32.07	-0.06	1.90	6.28	0.07	73.15	0.32	GYR	-
7	37.07	0.50	274.50	5.00	37.07	-0.10	1.90	6.23	0.11	73.01	0.05	GYR	-
8	42.07	0.49	276.00	5.00	42.07	-0.15	1.91	6.19	0.16	72.87	0.03	GYR	-
9	47.07	0.50	278.80	5.00	47.07	-0.19	1.91	6.15	0.20	72.71	0.05	GYR	-
10	52.07	0.36	277.40	5.00	52.07	-0.23	1.92	6.11	0.24	72.56	0.28	GYR	-
11	57.07	0.47	259.00	5.00	57.07	-0.26	1.92	6.07	0.27	72.48	0.34	GYR	-
12	62.07	0.41	247.50	5.00	62.07	-0.30	1.91	6.04	0.30	72.48	0.21	GYR	-
13	67.07	0.43	215.40	5.00	67.07	-0.33	1.88	6.01	0.33	72.59	0.47	GYR	-
14	72.07	0.51	202.50	5.00	72.07	-0.35	1.85	5.99	0.35	72.85	0.26	GYR	-
15	77.07	0.58	176.30	5.00	77.07	-0.36	1.80	5.99	0.36	73.23	0.51	GYR	-
16	82.07	0.73	162.00	5.00	82.07	-0.35	1.75	6.00	0.36	73.75	0.44	GYR	-
17	87.07	0.88	153.60	5.00	87.07	-0.32	1.68	6.02	0.36	74.39	0.38	GYR	-
18	92.07	1.13	141.90	5.00	92.07	-0.28	1.61	6.07	0.37	75.15	0.64	GYR	-
19	97.07	1.40	130.90	5.00	97.07	-0.20	1.53	6.15	0.38	76.02	0.72	GYR	-
20	102.07	1.84	120.70	5.00	102.06	-0.09	1.45	6.26	0.42	76.97	1.05	GYR	-
21	107.07	2.20	115.70	5.00	107.06	0.07	1.37	6.42	0.50	77.97	0.80	GYR	-
22	112.07	2.55	109.80	5.00	112.06	0.25	1.29	6.61	0.63	78.97	0.85	GYR	-
23	117.07	2.98	107.40	5.00	117.05	0.48	1.21	6.84	0.82	79.95	0.89	GYR	-
24	122.07	3.35	103.90	5.00	122.04	0.75	1.14	7.10	1.05	80.90	0.83	GYR	-
25	127.07	4.20	102.50	5.00	127.03	1.06	1.06	7.42	1.35	81.85	1.71	GYR	-
26	132.07	4.33	100.60	5.00	132.02	1.43	0.99	7.79	1.69	82.77	0.38	GYR	-
27	137.07	5.10	98.60	5.00	137.00	1.83	0.92	8.19	2.08	83.59	1.57	GYR	-
28	137.97	5.16	98.30	0.90	137.90	1.91	0.91	8.27	2.16	83.73	0.73	GYR	-
29	146.90	4.51	98.30	8.93	146.80	2.65	0.80	9.02	2.88	84.93	0.73	GYR	-
30	158.50	3.99	103.00	11.60	158.36	3.48	0.64	9.86	3.73	86.27	0.54	GYR	-

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

16-Jul-2002 15:22:12

Page 3 of 6

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
31	174.60	3.62	103.90	16.10	174.43	4.51	0.36	10.90	4.80	87.92	0.23	GYR	-
32	195.00	2.99	112.10	20.40	194.79	5.62	0.00	12.01	5.97	89.81	0.39	GYR	-
33	222.00	2.88	120.80	27.00	221.76	6.84	-0.61	13.25	7.34	92.47	0.17	GYR	-
34	241.10	3.91	130.60	19.10	240.83	7.73	-1.28	14.16	8.42	95.01	0.62	GYR	-
35	260.10	4.76	122.40	19.00	259.77	8.87	-2.13	15.31	9.82	97.85	0.55	GYR	-
36	279.30	5.31	103.40	19.20	278.90	10.39	-2.76	16.85	11.48	99.26	0.91	GYR	-
37	299.90	6.86	80.10	20.60	299.38	12.52	-2.77	18.99	13.47	98.27	1.40	GYR	-
38	316.15	10.55	72.73	16.25	315.44	14.92	-2.16	21.37	15.56	95.76	2.37	GYR	-
39	352.61	15.35	86.12	36.46	350.98	22.96	-0.84	29.38	23.19	91.56	1.54	MWD	6-axis
40	381.38	18.05	94.30	28.77	378.53	31.20	-0.92	37.62	31.40	91.40	1.24	MWD	6-axis
41	411.78	22.54	100.22	30.40	407.04	41.60	-2.31	48.06	41.93	92.70	1.62	MWD	6-axis
42	440.11	27.94	100.01	28.33	432.66	53.42	-4.42	59.95	53.97	94.18	1.91	MWD	6-axis
43	468.74	33.27	97.20	28.63	457.29	67.77	-6.58	74.35	68.54	95.08	1.93	MWD	6-axis
44	497.29	38.36	92.89	28.55	480.44	84.36	-8.01	90.99	85.22	95.00	1.99	MWD	6-axis
45	525.14	42.74	90.51	27.85	501.60	102.43	-8.53	109.08	103.26	94.45	1.67	MWD	6-axis
46	553.01	46.80	88.98	27.87	521.38	122.05	-8.43	128.70	122.79	93.73	1.51	MWD	6-axis
47	581.11	49.46	88.91	28.10	540.13	142.97	-8.04	149.62	143.62	93.06	0.95	MWD	6-axis
48	610.17	54.19	89.41	29.06	558.09	165.81	-7.71	172.45	166.39	92.55	1.63	MWD	6-axis
49	638.05	55.66	87.50	27.88	574.11	188.62	-7.09	195.26	189.13	92.07	0.77	MWD	6-axis
50	666.55	59.63	85.97	28.50	589.36	212.68	-5.72	219.29	213.08	91.48	1.46	MWD	6-axis
51	694.05	62.75	86.06	27.50	602.61	236.75	-4.04	243.32	237.06	91.04	1.13	MWD	6-axis
52	722.81	62.20	87.21	28.76	615.91	262.24	-2.54	268.78	262.48	90.53	0.40	MWD	6-axis
53	751.15	63.87	87.30	28.34	628.76	287.49	-1.33	294.01	287.69	90.25	0.59	MWD	6-axis
54	778.71	68.59	88.51	27.56	639.86	312.70	-0.42	319.21	312.88	90.07	1.76	MWD	6-axis
55	807.83	70.94	88.67	29.12	649.93	340.02	0.25	346.52	340.19	90.02	0.81	MWD	6-axis
56	812.33	71.08	88.93	4.50	651.40	344.28	0.34	350.78	344.44	89.94	0.63	MWD	6-axis
57	845.38	70.42	89.00	33.05	662.29	375.48	0.91	381.97	375.63	89.86	0.20	MWD	6-axis
58	874.18	71.18	89.28	28.80	671.77	402.67	1.32	409.17	402.83	89.81	0.28	MWD	6-axis
59	902.04	71.77	90.21	27.86	680.62	429.08	1.43	435.58	429.24	89.81	0.38	MWD	6-axis

58	874.18	71.18	89.28	28.80	671.77	402.67	1.32	409.17	402.83	89.81	0.28	MWD	6-axis
59	902.04	71.77	90.21	27.86	680.62	429.08	1.43	435.58	429.24	89.81	0.38	MWD	6-axis
60	931.93	71.89	89.41	29.89	689.94	457.48	1.53	463.98	457.64	89.81	0.26	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

16-Jul-2002 15:22:12

Page 4 of 6

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/-S (m)	Displ +E/-W (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
61	960.85	71.56	88.10	28.92	699.01	484.94	2.12	491.44	485.10	89.75	0.45	MWD	6-axis
62	989.81	70.75	87.66	28.96	708.36	512.34	3.14	518.82	512.49	89.65	0.31	MWD	6-axis
63	1018.64	69.68	87.09	28.83	718.12	539.46	4.38	545.92	539.59	89.54	0.42	MWD	6-axis
64	1047.42	68.84	87.34	28.78	728.31	566.37	5.69	572.81	566.48	89.43	0.30	MWD	6-axis
65	1076.22	70.95	88.00	28.80	738.21	593.41	6.79	599.83	593.51	89.35	0.76	MWD	6-axis
66	1104.92	71.26	88.33	28.70	747.50	620.57	7.65	626.97	620.65	89.30	0.15	MWD	6-axis
67	1133.56	70.77	88.57	28.64	756.82	647.65	8.39	654.04	647.73	89.26	0.19	MWD	6-axis
68	1162.76	69.60	88.22	29.20	766.72	675.12	9.16	681.50	675.20	89.23	0.42	MWD	6-axis
69	1192.29	70.68	87.70	29.53	776.75	702.89	10.15	709.25	702.96	89.18	0.40	MWD	6-axis
70	1220.68	70.21	87.93	28.39	786.25	729.64	11.17	735.99	729.71	89.13	0.18	MWD	6-axis
71	1249.53	71.42	88.09	28.85	795.74	756.89	12.11	763.22	756.95	89.09	0.42	MWD	6-axis
72	1278.47	70.83	88.55	28.94	805.10	784.27	12.91	790.59	784.33	89.06	0.25	MWD	6-axis
73	1307.78	70.41	88.78	29.31	814.82	811.92	13.56	818.23	811.98	89.05	0.16	MWD	6-axis
74	1336.76	71.90	87.82	28.98	824.18	839.35	14.37	845.65	839.40	89.02	0.60	MWD	6-axis
75	1365.54	71.58	88.03	28.78	833.20	866.67	15.36	872.96	866.72	89.01	0.13	MWD	6-axis
76	1394.99	70.65	87.88	29.45	842.73	894.54	16.36	900.81	894.58	89.01	0.32	MWD	6-axis
77	1423.91	71.30	88.18	28.92	852.16	921.88	17.30	928.13	921.92	88.93	0.25	MWD	6-axis
78	1453.13	70.73	88.04	29.22	861.67	949.51	18.21	982.91	976.73	88.91	0.20	MWD	6-axis
79	1482.00	69.94	87.98	28.87	871.38	976.69	19.15	982.91	976.73	88.88	0.27	MWD	6-axis
80	1511.29	71.58	88.27	29.29	881.03	1004.34	20.06	1010.55	1004.38	88.86	0.57	MWD	6-axis
81	1540.24	71.22	88.49	28.95	890.27	1031.78	20.83	1037.98	1031.81	88.85	0.14	MWD	6-axis
82	1569.45	71.83	88.59	29.21	899.52	1059.49	21.54	1065.67	1059.52	88.84	0.21	MWD	6-axis
83	1598.45	70.89	88.78	29.00	908.79	1086.96	22.17	1093.15	1086.99	88.84	0.33	MWD	6-axis
84	1627.03	70.31	88.62	28.58	918.29	1113.92	22.78	1120.10	1113.95	88.83	0.21	MWD	6-axis
85	1655.99	70.03	88.33	28.96	928.11	1141.16	23.51	1147.33	1141.19	88.82	0.13	MWD	6-axis
86	1684.63	70.80	88.15	28.64	937.71	1168.15	24.33	1174.30	1168.17	88.81	0.28	MWD	6-axis
87	1712.70	70.52	87.93	28.07	947.01	1194.63	25.24	1200.77	1194.66	88.79	0.12	MWD	6-axis
88	1741.50	70.18	87.75	28.80	956.69	1221.75	26.26	1227.87	1221.78	88.77	0.13	MWD	6-axis
89	1770.04	71.16	87.80	28.54	966.14	1248.68	27.31	1254.78	1248.70	88.75	0.34	MWD	6-axis
90	1798.12	71.43	87.83	28.08	975.14	1275.28	28.32	1281.36	1275.30	88.73	0.10	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

16-Jul-2002 15:22:12

Page 5 of 6

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/-S (m)	Displ +E/-W (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
91	1826.11	70.51	87.92	27.99	984.27	1301.73	29.30	1307.80	1301.75	88.71	0.33	MWD	6-axis
92	1854.99	70.21	88.08	28.88	993.97	1328.93	30.25	1334.99	1328.95	88.70	0.12	MWD	6-axis
93	1883.45	71.73	88.50	28.46	1003.25	1355.84	31.05	1361.88	1355.85	88.69	0.55	MWD	6-axis
94	1911.83	71.46	88.41	28.38	1012.22	1382.77	31.78	1388.80	1382.78	88.69	0.10	MWD	6-axis
95	1940.74	70.88	88.18	28.91	1021.55	1410.13	32.59	1416.15	1410.14	88.68	0.21	MWD	6-axis
96	1969.40	70.59	87.87	28.66	1031.01	1437.18	33.53	1443.18	1437.19	88.67	0.15	MWD	6-axis
97	1997.53	70.80	87.93	28.13	1040.31	1463.73	34.50	1469.71	1463.74	88.65	0.08	MWD	6-axis
98	2025.72	70.53	88.02	28.19	1049.64	1490.33	35.44	1496.30	1490.34	88.64	0.10	MWD	6-axis
99	2054.36	70.76	87.93	28.64	1059.13	1517.35	36.39	1523.30	1517.36	88.63	0.09	MWD	6-axis
100	2082.32	71.12	87.77	27.96	1068.26	1543.77	37.39	1549.71	1543.78	88.62	0.14	MWD	6-axis
101	2110.78	71.56	87.78	28.46	1077.37	1570.73	38.43	1576.65	1570.74	88.60	0.15	MWD	6-axis
102	2139.97	71.34	88.05	29.19	1086.66	1598.41	39.44	1604.31	1598.41	88.59	0.12	MWD	6-axis
103	2168.08	71.08	88.00	28.11	1095.71	1625.02	40.36	1630.91	1630.91	88.58	0.09	MWD	6-axis
104	2196.66	70.48	88.06	28.58	1105.12	1652.00	41.28	1657.88	1652.01	88.57	0.21	MWD	6-axis
105	2224.04	70.56	88.41	27.38	1114.25	1677.81	42.08	1683.68	1677.82	88.57	0.12	MWD	6-axis
106	2252.28	69.98	88.12	28.24	1123.78	1704.4	42.88	1710.25	1704.40	88.56	0.23	MWD	6-axis
107	2281.17	70.52	88.43	28.89	1133.54	1731.59	43.70	1737.42	1731.59	88.56	0.21	MWD	6-axis
108	2309.72	70.74	88.71	28.55	1143.01	1758.52	44.37	1764.35	1758.52	88.56	0.12	MWD	6-axis
109	2338.26	71.66	88.51	28.54	1152.21	1785.54	45.03	1791.36	1785.54	88.56	0.33	MWD	6-axis
110	2366.50	70.97	88.30	28.24	1161.26	1812.29	45.77	1818.10	1812.29	88.56	0.25	MWD	6-axis
111	2394.81	71.70	88.78	28.31	1170.32	1839.11	46.46	1844.91	1839.11	88.56	0.30	MWD	6-axis
112	2423.21	71.20	88.59	28.40	1179.35	1866.03	47.08	1871.83	1866.04	88.56	0.19	MWD	6-axis
113	2451.21	72.24	88.33	28.00	1188.14	1892.62	47.62	1898.41	1892.62	88.56	0.38	MWD	6-axis
114	2479.83	71.81	88.61	28.62	1196.97	1919.84	48.52	1925.62	1919.85	88.56	0.18	MWD	6-axis
115	2508.56	71.30	88.90	28.73	1206.06	1947.10	49.11	1952.87	1947.10	88.56	0.20	MWD	6-axis
116	2536.94	71.30	88.28	28.38	1215.16	1973.98	49.77	1979.74	1973.98	88.56	0.21	MWD	6-axis
117	2565.00	70.95	88.92	28.06	1224.23	2000.53	50.42	2006.28	2000.53	88.56	0.25	MWD	6-axis
118	2593.75	71.06	88.00	28.75	1233.59	2027.71	51.15	2033.46	2027.72	88.56	0.30	MWD	6-axis
119	2621.34	70.89	88.69	27.59	1242.59	2053.80	51.90	2059.53	2053.80	88.56	0.24	MWD	6-axis
120	2649.12	71.64	88.05	27.78	1251.51	2080.10	52.65	2085.83	2080.11	88.55	0.35	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
121	2677.65	71.61	87.32	28.53	1260.50	2107.18	53.75	2112.88	2107.18	88.54	0.24	MWD	6-axis
122	2706.95	71.20	87.67	29.30	1269.85	2134.94	54.96	2140.62	2134.94	88.53	0.18	MWD	6-axis
123	2734.92	71.02	87.18	27.97	1278.90	2161.40	56.15	2167.06	2161.40	88.51	0.18	MWD	6-axis
124	2763.51	70.88	87.43	28.59	1288.23	2188.42	57.42	2194.06	2188.42	88.50	0.10	MWD	6-axis
125	2791.53	70.61	87.84	28.02	1297.47	2214.87	58.51	2220.49	2214.87	88.49	0.17	MWD	6-axis
126	2820.22	70.49	88.27	28.69	1307.03	2241.92	59.43	2247.52	2241.92	88.48	0.15	MWD	6-axis
127	2849.03	70.21	88.69	28.81	1316.71	2269.05	60.15	2274.64	2269.05	88.48	0.17	MWD	6-axis
128	2876.04	70.13	89.20	27.01	1325.88	2294.46	60.62	2300.05	2294.46	88.49	0.18	MWD	6-axis
129	2904.05	71.38	88.95	28.01	1335.11	2320.90	61.04	2326.49	2320.90	88.50	0.45	MWD	6-axis
130	2931.57	72.04	88.48	27.52	1343.75	2347.03	61.63	2352.61	2347.03	88.50	0.29	MWD	6-axis
131	2957.82	72.11	88.37	26.25	1351.82	2372.01	62.32	2377.58	2372.01	88.50	0.05	MWD	6-axis
132	2988.58	72.86	87.28	30.76	1361.08	2401.34	63.43	2406.89	2401.34	88.49	0.42	MWD	6-axis
133	3016.69	72.05	87.25	28.11	1369.56	2428.14	64.71	2433.66	2428.14	88.48	0.29	MWD	6-axis
134	3044.23	71.27	87.17	27.54	1378.22	2454.27	65.98	2459.77	2454.27	88.46	0.28	MWD	6-axis
135	3072.08	71.29	87.84	27.85	1387.16	2480.64	67.13	2486.12	2480.64	88.45	0.23	MWD	6-axis
136	3100.54	70.27	88.02	28.46	1396.53	2507.51	68.10	2512.98	2507.51	88.45	0.36	MWD	6-axis
137	3128.49	69.94	88.36	27.95	1406.04	2533.80	68.93	2539.25	2533.80	88.44	0.16	MWD	6-axis
138	3156.30	70.71	88.09	27.81	1415.40	2559.98	69.74	2565.42	2559.98	88.44	0.29	MWD	6-axis
139	3184.71	71.86	87.90	28.41	1424.52	2586.89	70.68	2592.31	2586.89	88.44	0.41	MWD	6-axis
140	3197.86	72.24	87.73	13.15	1428.57	2599.40	71.16	2604.81	2599.40	88.43	0.31	MWD	6-axis
141	3220.00	72.50	87.60	22.14	1435.28	2620.50	72.02	2625.90	2620.50	88.43	0.13	Projection TD	

Company: Esso Australia Ltd.

Well: TNA A-31

Field: Tuna

Rig: ISDL 453

State: Victoria

IDEAL services from Anadrill

VISION Density Neutron
1:500 Measured Depth
Recorded Mode Log

Schlumberger