

[illegible]

Type		KCl/PHPA/Glycol									
Mud weight	ppg	9.5	9.7	9.6							
Solids	%	5.2	7.0	6.6							
Chlorides	mg/L	41000	38500	37000							
Rm	ohm-m	N/A	N/A	N/A							
Rmf	ohm-m	N/A	N/A	N/A							
Rmc	ohm-m	N/A	N/A	N/A							
Potassium	%	7.5	7.0	6.6							
Environmental data											
GR											
Mud weight	ppg	9.5	9.7	9.6							
Bit size	in	8.5	8.5	8.5							
Resistivity											
Neutron porosity											
Hole Size		N/A	N/A	N/A							
Mud weight		N/A	N/A	N/A							
Temperature		N/A	N/A	N/A							
Mud salinity		N/A	N/A	N/A							
Formation salinity		N/A	N/A	N/A							
Recording rate 1	SEC	N/A	N/A	N/A							
Recording rate 2	SEC	N/A	N/A	N/A							
Filtering GR		N/A	N/A	N/A							
Filtering density		N/A	N/A	N/A							
Filtering Neutron		N/A	N/A	N/A							
Company representative		R. Morris	B. Davis								
Anadrill personnel		J. Dolan	W. Gamlin	C. Soper	B. Manjenic						

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN1 Gamma Ray Directional Drilling Directional Surveys		OTHER SERVICES FOR RUN2 Gamma Ray Directional Drilling Directional Surveys		OTHER SERVICES FOR RUN3 Gamma Ray Directional Drilling Directional Surveys	
REMARKS: RUN NUMBER 1 8 1/2 in. hole section was drilled from 811 m to 2330 m. Depth is referenced to Driller's Depth. All data presented is Real Time data. Gamma Ray is corrected for Tool size, Bit size, Potassium content and Mud weight. Mud type is water-based KCl/PHPA/Glycol. Barite is present in the mud system. GR logged in casing to 803.5 m POOH at 2330 m for a bit change due to poor penetration rate.		REMARKS: RUN NUMBER 2 8 1/2 in. hole section was drilled from 2330 m to 2612 m. Depth is referenced to Driller's Depth. All data presented is Real Time data. Gamma Ray is corrected for Tool size, Bit size, Potassium content and Mud weight. Mud type is water-based KCl/PHPA/Glycol. Barite is present in the mud system. POOH at 2612 m for a bit change due to poor penetration rate.		REMARKS: RUN NUMBER 3 8 1/2 in. hole section was drilled from 2612 m to 2789 m. Depth is referenced to Driller's Depth. All data presented is Real Time data. Gamma Ray is corrected for Tool size, Bit size, Potassium content and Mud weight. Mud type is water-based KCl/PHPA/Glycol. Barite is present in the mud system. Reached TD of FLA A20a at 2789 m.	

Thank you for using Schlumberger.

RUN3

DOWNHOLE EQ


20.66 3/4 in. Pow
MDC Z40
MDI 11
MEC 11
MGR AA
DH software:

D&I	15.2
GR	14.6

12.26 1/8 in. NM
SN: DOTS
8 3/8 in. Stab


10.76 3/4 in. NM
SN: 9612

7.98 PowerPak* M
A675XP
SN: 023
1.15 deg
8 1/8 in. moto




GeoDiamond
8 1/2 in.
S73PX SN:

Maximum string diam
All lengths in



Smith Inse
8 1/2 in.
20GF SN: M

Maximum string diam
All lengths in



Smith Inse
8 1/2 in.
ER6027RP SN


Maximum string diam
All lengths in

FLA A20a RT 1:200TVD

IDEAL Version: ID8_OC_07 <TVD> Vertical Scale: 1:200 Graphics File Created: 19-Feb-2003 10:38


ROP*5 (ROP5)
(M/HR)


200 0




GR(TM) (GRM1)
(GAPI)

0 400










875
TVD






900
TVD













1125
TVD





1150
TVD




1175
TVD

1200
TVD






1225
TVD





1250
TVD







1275
TVD



1300
TVD



















1525
TVD



1550
TVD











1725
TVD

1750
TVD











1825
TVD


1850
TVD








1925
TVD






1950
TVD






1975
TVD


2000
TVD













2175
TVD


2200
TVD








2225
TVD

2250
TVD









2325
TVD

2350
TVD

2375







TVD

2400
TVD


2425
TVD










2450
TVD

2475
TVD










2600
TVD

2625
TVD



SCHLUMBERGER

Survey report 19-Feb-2003 07:30:37 Page 1 of 4

Client.....: ESSO Australia
Field.....: Flounder

Well.....: FLA A20a Spud date.....: 03-Feb-03
API number.....: Last survey date.....: 19-Feb-03
Engineer.....: J.Dolan Total accepted surveys...: 78
MD of first survey.....: 769.00 m
COUNTY.....: ISDL 453 MD of last survey.....: 2789.00 m
STATE.....: VICTORIA

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor
Magnetic field strength...: 1201.07 HCNT
----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's Depth
GL above permanent.....: -92.98 m
KB above permanent.....: 126.36 m
DF above permanent.....: 126.36 m
Reference Dip.....: -68.77 degrees
----- Vertical section origin-----
Latitude (+N/S-).....: -552.34 m
Departure (+E/W-).....: -337.96 m
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees
----- Platform reference point-----
Latitude (+N/S-).....: 5758713.10 m
Departure (+E/W-).....: 625838.70 m
Magnetic dec (+E/W-).....: 13.22 degrees
Grid convergence (+E/W-).....: -0.89 degrees
Total az corr (+E/W-).....: 14.11 degrees
Azimuth from rotary table to target: 211.38 degrees (Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2003 IDEAL ID8_OC_07]
SCHLUMBERGER Survey Report

19-Feb-2003 07:30:37 Page 2 of 4

Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	10m)	type	(deg)	
1	769.00	44.97	212.13	0.00	706.90	244.63	-210.89	-128.64	244.64	211.38	0.00	TIP	17.57G
2	775.00	45.42	212.33	6.00	711.13	248.89	-214.49	-130.91	248.90	211.40	2.36	GYR	-19.75G
3	780.00	45.88	212.10	5.00	714.62	252.46	-217.51	-132.81	252.48	211.41	2.93	GYR	-35.38G
4	785.00	46.36	211.63	5.00	718.09	256.07	-220.57	-134.71	256.08	211.41	3.53	GYR	-26.08G
5	790.00	47.14	211.11	5.00	721.52	259.71	-223.68	-136.61	259.72	211.41	5.20	GYR	-25.60G
6	795.00	48.20	210.43	5.00	724.88	263.40	-226.86	-138.50	263.42	211.40	7.04	GYR	-20.97G
7	800.00	48.71	210.17	5.00	728.20	267.14	-230.09	-140.39	267.16	211.39	3.28	GYR	-97.61G
8	805.00	48.70	210.07	5.00	731.50	270.90	-233.34	-142.27	270.91	211.37	0.45	GYR	-108.42G
9	807.00	48.69	210.03	2.00	732.82	272.40	-234.64	-143.03	272.41	211.36	0.48	GYR	-164.72G
10	836.80	41.23	206.93	29.80	753.89	293.41	-253.11	-153.09	293.41	211.17	7.83	GYR	-168.89G
11	877.02	38.12	205.94	40.22	784.85	318.97	-276.10	-164.53	318.79	210.79	2.37	MWD	-112.65G
12	905.52	37.93	205.19	28.50	807.30	336.42	-291.94	-172.10	336.44	210.52	0.53	MWD	95.45G
13	934.75	37.89	205.91	29.23	830.36	354.28	-308.14	-179.85	354.31	210.27	0.46	MWD	180.00G
14	964.06	37.48	205.91	29.31	853.55	372.10	-324.26	-187.68	372.17	210.06	0.42	MWD	-165.07G
15	992.37	34.99	204.75	28.31	876.39	388.73	-339.38	-194.84	388.83	209.86	2.74	MWD	-134.55G
16	1020.56	34.90	204.59	28.19	899.49	404.7	-354.0	-201.58	404.90	209.66	0.14	MWD	153.73G
17	1048.62	34.14	205.26	28.06	922.61	420.54	-368.47	-208.28	420.73	209.48	0.91	MWD	151.27G
18	1077.47	31.79	207.73	28.85	946.82	436.17	-382.52	-215.27	436.40	209.37	2.81	MWD	141.97G
19	1105.53	28.51	213.29	28.06	971.08	450.24	-394.67	-222.39	450.48	209.40	4.60	MWD	147.97G
20	1134.29	25.49	217.78	28.76	996.71	463.26	-405.30	-229.95	463.46	209.57	3.80	MWD	161.82G
21	1163.00	22.73	220.14	28.71	1022.91	474.89	-414.42	-237.31	475.05	209.80	3.05	MWD	171.92G
22	1191.38	20.51	221.04	28.38	1049.29	485.23	-422.37	-244.11	485.34	210.03	2.37	MWD	-180.00G

23	1220.17	17.92	221.01	28.79	1076.48	494.58	-429.51	-250.33	494.66	210.23	2.70	MWD	177.52G
24	1248.30	16.66	221.20	28.13	1103.34	502.83	-435.81	-255.83	502.89	210.41	1.35	MWD	-160.06G
25	1276.95	13.94	217.05	28.65	1130.97	510.32	-441.66	-260.61	510.36	210.54	3.07	MWD	-140.25G
26	1306.13	12.90	213.06	29.18	1159.35	517.07	-447.20	-264.51	517.11	210.60	1.43	MWD	129.19G
27	1335.52	11.50	222.68	29.39	1188.08	523.23	-452.10	-268.29	523.26	210.69	2.51	MWD	158.09G
28	1363.42	9.82	226.70	27.90	1215.50	528.26	-455.78	-271.90	528.28	210.82	1.97	MWD	162.35G
29	1392.66	7.72	231.75	29.24	1244.40	532.52	-458.70	-275.26	532.53	210.97	2.29	MWD	157.22G
30	1421.94	6.11	238.27	29.28	1273.46	535.76	-460.74	-278.13	535.76	211.12	1.83	MWD	177.97G

[(c)2003 IDEAL ID8_OC_07]
SCHLUMBERGER Survey Report

19-Feb-2003 07:30:37

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
31	1451.21	3.41	239.88	29.27	1302.63	537.92	-462.00	-280.21	537.92	211.24	2.77	MWD	-121.59M
32	1479.71	1.29	238.41	28.50	1331.10	538.96	-462.59	-281.21	538.96	211.30	2.23	MWD	-128.69M
33	1508.40	0.64	231.31	28.69	1359.79	539.39	-462.86	-281.61	539.39	211.32	0.69	MWD	-134.86M
34	1536.69	0.61	225.14	28.29	1388.08	539.69	-463.06	-281.84	539.69	211.33	0.08	MWD	-116.80M
35	1565.06	0.63	243.20	28.37	1416.45	539.97	-463.24	-282.09	539.97	211.34	0.21	MWD	-123.98M
36	1593.67	0.63	236.02	28.61	1445.05	540.25	-463.40	-282.36	540.25	211.36	0.08	MWD	-110.37M
37	1621.98	0.66	249.63	28.31	1473.36	540.52	-463.54	-282.64	540.52	211.37	0.17	MWD	-123.41M
38	1650.74	0.83	236.59	28.76	1502.12	540.84	-463.72	-282.97	540.84	211.39	0.25	MWD	-118.49M
39	1679.24	0.70	241.51	28.50	1530.62	541.18	-463.91	-283.30	541.18	211.41	0.15	MWD	-120.95M
40	1707.69	0.59	239.05	28.45	1559.06	541.46	-464.07	-283.58	541.46	211.43	0.12	MWD	-143.85M
41	1736.30	0.51	216.15	28.61	1587.67	541.72	-464.25	-283.78	541.72	211.44	0.24	MWD	-141.09M
42	1765.27	0.47	218.91	28.97	1616.64	541.96	-464.45	-283.93	541.96	211.44	0.05	MWD	-150.01M
43	1794.11	0.34	209.99	28.84	1645.48	542.16	-464.61	-284.05	542.17	211.44	0.15	MWD	-107.41M
44	1822.56	0.20	252.59	28.45	1673.93	542.29	-464.70	-284.14	542.29	211.44	0.25	MWD	-94.06M
45	1850.75	0.06	265.94	28.19	1702.12	542.33	-464.72	-284.20	542.33	211.45	0.15	MWD	-125.94M
46	1879.57	0.06	232.06	28.82	1730.94	542.36	-464.72	-284.22	542.36	211.45	0.03	MWD	-123.49M
47	1908.27	0.34	236.51	28.70	1759.64	542.45	-464.78	-284.31	542.45	211.45	0.29	MWD	-112.76M
48	1937.11	0.41	247.24	28.84	1788.48	542.61	-464.87	-284.47	542.61	211.46	0.10	MWD	-144.17M
49	1965.92	0.37	215.83	28.81	1817.29	542.79	-464.98	-284.62	542.79	211.47	0.22	MWD	-151.75M
50	1994.24	0.51	208.25	28.32	1845.61	543.00	-465.17	-284.74	543.00	211.47	0.16	MWD	-153.61M
51	2023.18	0.50	206.39	28.94	1874.55	543.26	-465.39	-284.85	543.26	211.47	0.02	MWD	-151.41M
52	2052.60	0.49	208.59	28.96	1903.97	543.51	-465.62	-284.97	543.51	211.47	0.02	MWD	-143.35M
53	2081.51	0.60	216.65	28.91	1932.88	543.78	-465.85	-285.12	543.79	211.47	0.14	MWD	-150.49M
54	2119.16	0.59	209.51	37.65	1970.52	544.17	-466.18	-285.33	544.18	211.47	0.06	MWD	-157.25M
55	2167.19	0.56	202.75	48.03	2018.55	544.65	-466.61	-285.55	544.65	211.47	0.05	MWD	-160.27M
56	2195.89	0.66	199.73	28.70	2047.25	544.95	-466.89	-285.66	544.95	211.46	0.11	MWD	177.62M
57	2223.99	0.73	177.62	28.10	2075.35	545.26	-467.22	-285.70	545.26	211.45	0.29	MWD	161.99M
58	2252.93	1.26	161.99	28.94	2104.28	545.62	-467.71	-285.60	545.62	211.41	0.61	MWD	169.50M

[(c)2003 IDEAL ID8_OC_07]
SCHLUMBERGER Survey Report

19-Feb-2003 07:30:37

Page 4 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
59	2281.95	2.44	169.50	23.02	2133.29	546.28	-468.62	-285.39	546.28	211.34	1.24	MWD	176.28M
60	2310.40	3.31	176.28	28.45	2161.70	547.40	-470.04	-285.22	547.40	211.25	0.98	MWD	-156.99M
61	2338.37	4.76	203.01	27.97	2189.60	549.20	-471.91	-285.62	549.20	211.18	2.51	MWD	-143.56M
62	2366.94	8.31	216.44	28.57	2217.98	552.43	-474.66	-287.31	552.44	211.19	4.03	MWD	6.86G
63	2396.06	10.57	217.92	29.11	2246.70	557.19	-478.47	-290.21	557.19	211.24	2.34	MWD	-2.58G
64	2425.11	12.16	217.58	29.06	2275.19	562.88	-482.99	-293.71	562.88	211.30	1.64	MWD	-39.34G
65	2454.01	12.97	214.68	28.90	2303.40	569.15	-488.07	-297.41	569.15	211.36	1.07	MWD	-159.12G
66	2482.80	12.43	213.72	28.79	2331.48	575.47	-493.31	-300.97	575.47	211.39	0.60	MWD	-25.62G
67	2510.32	13.06	212.39	27.52	2358.32	581.54	-498.39	-304.28	581.54	211.40	0.76	MWD	-76.45G
68	2539.20	13.20	210.04	28.88	2386.45	588.10	-504.00	-307.68	588.10	211.40	0.57	MWD	43.36G
69	2568.25	13.32	210.53	29.05	2414.72	594.76	-509.76	-311.04	594.76	211.39	0.17	MWD	53.58G
70	2596.81	13.53	211.73	28.56	2442.50	601.39	-515.43	-314.47	601.39	211.39	0.37	MWD	-30.75G
71	2625.84	13.73	211.23	29.03	2470.72	608.23	-521.27	-318.04	608.23	211.39	0.24	MWD	131.28G
72	2655.11	13.67	211.52	29.27	2499.15	615.16	-527.19	-321.65	615.16	211.39	0.09	MWD	124.26G
73	2682.30	13.63	211.77	27.19	2525.58	621.58	-532.65	-325.01	621.58	211.39	0.08	MWD	10.75G
74	2711.21	13.73	211.85	28.91	2553.67	628.42	-538.46	-328.62	628.42	211.40	0.11	MWD	154.32G

75	2740.15	12.71	214.10	28.94	2581.84	635.03	-544.01	-332.22	635.03	211.41	1.18	MWD	170.63G
76	2768.93	11.84	214.80	28.78	2609.96	641.14	-549.06	-335.68	641.14	211.44	0.92	MWD	-175.50G
77	2773.49	11.61	214.71	4.56	2614.43	642.07	-549.82	-336.20	642.07	211.44	1.52	MWD	174.12G
78	2789.00	11.25	214.90	15.51	2629.63	645.14	-552.34	-337.96	645.14	211.46	0.70	Projected to TD	

[(c)2003 IDEAL ID8_OC_07]

Company: **ESSO Australia Ltd.**

Schlumberger

Well: **FLA A20a**

Field: **Flounder**

Rig: **ISDL 453**

State: **VICTORIA**

Gamma Ray Service
1:200 True Vertical Depth
Real Time Log