

Rig: **ISDL 453** State: **Victoria**

Rig: ISDL 453 Field: Tuna Location: Bass Strait Well: TNA A-29 Company: Esso Australia Ltd.	GeoVISION Resistivity 1:200 Measured Depth Recorded Mode Log										
	Location	Total depth:		3075 m		Elevation	K.B.	Top Drive			
		Spud date:		27-July-02			G.L.	-59.4 m			
		Runs:		3 To 6			D.F.	31.3 m			
		Permanent datum:		Mean Sea Level		Elev.:	59.4 m				
		Log measured from:		Drill Floor		31.3 m above Perm. datum					
	Depth reference:		Driller's Pipe Tally								
	API serial no.		x = 5774225.50m (North) y = 624224.90m (East)		Longitude		Latitude				
					E 148 25 5.513		S 38 10 16.237				
	Depth logged:		928 m To 3075 m		Mag decl:		13.19°				
Date logged:		3-Aug-02 To 11-Aug-02		Mag dip:		-68.68°					
				Other services:		Directional Drilling					
Bore hole record				Casing record							
Hole size		from to		Size		Density					
12 1/4 in.		164.9 m 937 m		20 in.		84 lb/ft					
8 1/2 in.		928 m 3075 m		9 5/8 in.		47 lb/ft					
Mud record				Borehole deviation record							
Type		from to		Min		Max					
Seawater		164.9 m 937 m		6.35°		69.39°					
KCL/PHPA/GLYCOL		928 m 3075 m		67.92°		70.43°					
				26.61°		67.38°					
Surface equipment		Software record		IDEAL services from Anadrill							
Unit		OLU-FB-924						IDEAL Wis		ID6_1C_10r	
Depth system		PDA						SPM		ID6_1C_10r	
								LWD		see toolsketch	
								MWD		see toolsketch	

Bit Run Summary

Type		KCL/PHPA/GLYCOL	KCL/PHPA/GLYCOL							
Mud weight	ppg	9.4	10.55	10.4						
Solids	%vol	4.3	10.4	9.4						
Chlorides	mg/l	45,500	47,900	47,900						
Rm	Ohmms @ °C	0.0963@20	0.0945@20	0.1230@21						
Rmf	Ohmms @ °C	0.0878@20	0.1302@20	0.0880@21						
Rmc	Ohmms @ °C	0.0677@20	0.2170@21	0.3830@22						
Potassium	%vol	4	4	4						
Environmental data										
GR										
Mud weight	ppg	9.4	10.55	10.3						
Bit size	in	8.5	8.5	8.5						
Resistivity										
Neutron porosity										
Hole Size	in	8.5	8.5	8.5						
Mud weight	ppg	9.4	10.55	10.3						
Temperature	degC	47.1	78	75						
Mud salinity	mg/l	75,000	79,035	79,035						
Formation salinity										
Recording rate 1	SEC	10	10	10						
Recording rate 2	SEC	10	10	10						
Filtering GR		3 pt	3 pt	3 pt						
Filtering density		3 pt	3 pt	3 pt						
Filtering Neutron		3 pt	3 pt	3 pt						
Company representative		B. Davies	B. Steel	G. Campbell						
Anadrill personnel		J. Walta	L. Bon	J. Dolan						

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN3 Directional Surveys	OTHER SERVICES FOR RUN4 Directional Surveys	OTHER SERVICES FOR RUN6 Directional Surveys
<p>REMARKS: RUN NUMBER 3</p> <p>8-1/2in Hole Section was logged from 928m to 1192m MD</p> <p>Depth is referenced to driller's pipe tally</p> <p>All data is presented from tool memory</p> <p>Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature.</p> <p>Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure)</p> <p>Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.</p>	<p>REMARKS: RUN NUMBER 4</p> <p>8-1/2in Hole Section was logged from 1192m to 2797m MD</p> <p>Depth is referenced to driller's pipe tally</p> <p>All data is presented from tool memory</p> <p>Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature.</p> <p>Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure)</p> <p>Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.</p>	<p>REMARKS: RUN NUMBER 6</p> <p>8-1/2in Hole Section was logged from 2797m to 3075m MD</p> <p>Depth is referenced to driller's pipe tally</p> <p>All data is presented from tool memory</p> <p>Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature.</p> <p>Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure)</p> <p>Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.</p>

Barite is present in the mud.

RAB6C* Downhole Software 6.1B14
ADN6C* Downhole Software 6.2B08

Barite is present in the mud.

RAB6C* Downhole Software 6.1B14
ADN6C* Downhole Software 6.2B08

Barite is present in the mud.

RAB6C* Downhole Software 6.1B12
ADN6C* Downhole Software 6.1B01

EQUIPMENT DESCRIPTION

RUN3

RUN4


RUN6

DOWNHOLE EQ

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.2

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.8
27.6
26.8
26.7
26.3
25.5



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.4
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.7
13.6
13.4
13.2
13.1
12.9



Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B




DOWNHOLE E

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.2

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.7
27.6
26.7
26.6
26.2
25.4



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.3
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.6
13.5
13.3
13.2
13.0
12.8



Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B




DOWNHOLE EQ

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.1

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.6
27.5
26.6
26.5
26.1
25.4



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.3
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.6
13.5
13.3
13.2
13.0
12.8




Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B





IDEAL Version: ID7_0C_02

IDF

RAB	id6_1c_10	MWD_10	id6_1c_10
ADN	id6_1c_10		

Format: A-29 GeoVISION Resistivity Vertical Scale: 1:200 Graphics File Created: 18-Aug-2002 14:28


Parameters



DLIS Name	Description	Value
BDBHCA	RAB: Button Deep Borehole A Factor	0.004
BDBHCB	RAB: Button Deep Borehole B Factor	0.000
BHA_COEF_VER	RAB: BHA Coef Generator Version	2.000
BITBHCA	RAB: Bit A Borehole Factor	0.058
BITBHCB	RAB: Bit B Borehole Factor	0.000
BIT_K_FACTOR	RAB: Bit K Factor	15.703
BMBHCA	RAB: Button Medium Borehole A Factor	0.023
BMBHCB	RAB: Button Medium Borehole B Factor	0.000
BSBHCA	RAB: Button Shallow Borehole A Factor	0.023
BSBHCB	RAB: Button Shallow Borehole B Factor	0.000
BS_RM	Bit Size (RM)	8.500 in
BUT_KIMP_A	RAB: Button Impedance Coeff A	0.000
BUT_KIMP_B	RAB: Button Impedance Coeff B	0.000
DBUTTON_K_FACTOR	RAB: Button Deep K factor	0.005
DHS_VERSION	RAB: DownHole Software Version	V6.1 B
DO	Depth Offset	0.0 m
GRDC	Grid corr angle	-0.880 deg
MBUTTON_K_FACTOR	RAB: Button Medium K Factor	0.005
MST_RM	Mud Sample temperature (RM)	20.800 degC
MW_RM	Mud Weight (RM)	10.400 lbm/gal
OBM	RAB: Oil base Mud	NO
RABEC	RAB: Resistivity Env-Cor	YES
RAB_TEMP_SELECT	RAB Temperature Selection	MEAS
READOUT_PORT_MP	RAB: ROP to Bit Face Distance	13.070 m
RINGBHCA	RAB: Ring Borehole A Factor	0.160
RINGBHCB	RAB: Ring Borehole B Factor	0.000
RING_KIMP_A	RAB: Ring Impedance Coeff A	0.000
RING_KIMP_B	RAB: Ring Impedance Coeff B	0.000
RING_K_FACTOR	RAB: Ring K Factor	0.153
RMS_RM	Resistivity of Mud Sample (RM)	0.123 ohm.m
SBUTTON_K_FACTOR	RAB: Button Shallow K Factor	0.007
STAB	RAB: Run with Stabilizer	YES
TOOLTYPE	RAB: Azimuthal Tool	YES
TS_VERSION	RAB: ToolScope Software Version	V6.0 B017
VRAB6	Rab Tool type (ENP/PILOT)	RAB6_C_SERIES



PIP SUMMARY



Gamma Ray Samples



Deep Button Resistivity, Down (RES_BD_DN)

























1225



1250



































































































2450



2475













































PIP SUMMARY

Gamma Ray Samples

6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:
 Tool Name and Serial Number
 Neutron Logging Source
 Density Logging Source
 Stabilizer Size
 Calibration Status




ADN6 – CA
 NSR – M
 GSR – J/Z
 8.25 – in.
 Valid

289
 161
 2125

Master: 24-JUL-2002 8:49

6.75-in. Azimuthal Density Neutron Calibration




Density: Magnesium Block

Phase	LS window 3 – Mg CPS	Value	Phase	SS window 1 – Mg CPS	Value	Phase	SS window 3 – Mg CPS	Value
Master		1334	Master		3054	Master		7545
	250.0 (Minimum) 4125 (Nominal) 8000 (Maximum)			700.0 (Minimum) 9350 (Nominal) 18000 (Maximum)			2500 (Minimum) 23750 (Nominal) 45000 (Maximum)	

Master: 24-JUL-2002 8:49

6.75-in. Azimuthal Density Neutron Calibration




Density: Aluminum Block

Phase	LS window 3 – Al CPS	Value	Phase	SS window 1 – Al CPS	Value	Phase	SS window 3 – Al CPS	Value
Master		208.1	Master		1635	Master		4899
	50.00 (Minimum) 725.0 (Nominal) 1400 (Maximum)			500.0 (Minimum) 4250 (Nominal) 8000 (Maximum)			1500 (Minimum) 15750 (Nominal) 30000 (Maximum)	

Master: 24-JUL-2002 8:49

6.75-in. Azimuthal Density Neutron Calibration



Density: Background

Phase	LS window 3 – Background CPS	Value	Phase	SS window 1 – Background CPS	Value	Phase	SS window 3 – Background CPS	Value
Master		52.11	Master		125.8	Master		548.2
	15.00 (Minimum) 82.50 (Nominal) 150.0 (Maximum)			40.00 (Minimum) 220.0 (Nominal) 400.0 (Maximum)			150.0 (Minimum) 825.0 (Nominal) 1500 (Maximum)	

Master: 24-JUL-2002 8:49

6.75-in. Azimuthal Density Neutron Calibration









Density: Water Block Check

Phase	Long spacing water density G/C3	Value	Phase	Short spacing water density G/C3	Value
Master		1.035	Master		1.126
	1.011 (Minimum) 1.026 (Nominal) 1.041 (Maximum)			1.093 (Minimum) 1.118 (Nominal) 1.143 (Maximum)	

Master: 24-JUL-2002 8:49

6.75-in. Azimuthal Density Neutron Calibration

Neutron: Water Tank

Phase	Far 1 tube 1 gain	Value	Phase	Far 1 tube 1 offset CPS	Value
Master		1.106	Master		-0.8130
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 1 tube 2 gain	Value	Phase	Far 1 tube 2 offset CPS	Value
Master		1.054	Master		-0.9150
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 1 tube 3 gain	Value	Phase	Far 1 tube 3 offset CPS	Value
Master		1.064	Master		-0.8000
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 2 tube 1 gain	Value	Phase	Far 2 tube 1 offset CPS	Value
Master		1.106	Master		-0.7490
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	

Far 2 tube 2 gain			Far 2 tube 2 offset CPS		
Phase	Value		Phase	Value	
Master	1.005		Master	-0.8300	
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)	-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Far 2 tube 3 gain			Far 2 tube 3 offset CPS		
Phase	Value		Phase	Value	
Master	1.103		Master	-0.8040	
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)	-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Near 1 tube 1 gain					
Phase	Value				
Master	1.085				
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)			
Near 2 tube 1 gain					
Phase	Value				
Master	1.058				
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)			

6.75-in. Resistivity At-the-Bit / Equipment Identification

Primary Equipment:













Tool Name and Serial Number


Calibration Status

RAB6 – CA

136

Valid

Master: 28-JUL-2002 11:01														
6.75-in. Resistivity At-the-Bit Calibration														
Resistivity: Fixture														
Phase	Ring/T1 factor			Value	Phase	Ring/T2 factor			Value	Phase	M0/T1 factor			Value
Master				0.9850	Master				0.9970	Master				0.9930
0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)
Phase	M0/T2 factor			Value	Phase	M2/T1 factor			Value	Phase	M2/T2 factor			Value
Master				0.9970	Master				0.9980	Master				1.003
0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)
Phase	BTN shallow/T1 factor			Value	Phase	BTN shallow/T2 factor			Value	Phase	BTN medium/T1 factor			Value
Master				1.014	Master				1.020	Master				1.018
0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)
Phase	BTN medium/T2 factor			Value	Phase	BTN deep/T1 factor			Value	Phase	BTN deep/T2 factor			Value
Master				1.024	Master				1.015	Master				1.023
0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)			1.000 (Nominal)	1.025 (Maximum)

Master: 28-JUL-2002 11:01		
6.75-in. Resistivity At-the-Bit Calibration		
Gamma Ray: Blanket		
Phase	Gamma ray factor	Value
Master		0.9010
	0.7500 (Minimum)	1.000 (Nominal)
		1.250 (Maximum)

6.75-in. Azimuthal Density Neutron / Equipment Identification




Primary Equipment:
 Tool Name and Serial Number
 Neutron Logging Source
 Density Logging Source
 Stabilizer Size
 Calibration Status

ADN6 – CA 219
 NSR – M 161
 GSR – J/Z 2125
 8.25 – in.
 Valid

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration




Density: Magnesium Block

Phase	LS window 3 – Mg CPS	Value	Phase	SS window 1 – Mg CPS	Value	Phase	SS window 3 – Mg CPS	Value
Master		1294	Master		3056	Master		7448
	250.0 (Minimum) 4125 (Nominal) 8000 (Maximum)			700.0 (Minimum) 9350 (Nominal) 18000 (Maximum)			2500 (Minimum) 23750 (Nominal) 45000 (Maximum)	

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration




Density: Aluminum Block

Phase	LS window 3 – Al CPS	Value	Phase	SS window 1 – Al CPS	Value	Phase	SS window 3 – Al CPS	Value
Master		190.8	Master		1547	Master		4662
	50.00 (Minimum) 725.0 (Nominal) 1400 (Maximum)			500.0 (Minimum) 4250 (Nominal) 8000 (Maximum)			1500 (Minimum) 15750 (Nominal) 30000 (Maximum)	

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration



Density: Background

Phase	LS window 3 – Background CPS	Value	Phase	SS window 1 – Background CPS	Value	Phase	SS window 3 – Background CPS	Value
Master		58.08	Master		125.9	Master		543.1
	15.00 (Minimum) 82.50 (Nominal) 150.0 (Maximum)			40.00 (Minimum) 220.0 (Nominal) 400.0 (Maximum)			150.0 (Minimum) 825.0 (Nominal) 1500 (Maximum)	

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration









Density: Water Block Check

Phase	Long spacing water density G/C3	Value	Phase	Short spacing water density G/C3	Value
Master		1.043	Master		1.131
	1.016 (Minimum) 1.032 (Nominal) 1.047 (Maximum)			1.062 (Minimum) 1.107 (Nominal) 1.151 (Maximum)	

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration

Neutron: Water Tank

Phase	Far 1 tube 1 gain	Value	Phase	Far 1 tube 1 offset CPS	Value
Master		1.077	Master		-0.9260
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 1 tube 2 gain	Value	Phase	Far 1 tube 2 offset CPS	Value
Master		1.034	Master		-0.9100
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 1 tube 3 gain	Value	Phase	Far 1 tube 3 offset CPS	Value
Master		1.085	Master		-0.8150
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	
Phase	Far 2 tube 1 gain	Value	Phase	Far 2 tube 1 offset CPS	Value
Master		1.064	Master		-0.8090
	0.9000 (Minimum) 1.100 (Nominal) 1.300 (Maximum)			-1.200 (Minimum) -0.9000 (Nominal) -0.6000 (Maximum)	

(Minimum)	(Nominal)	(Maximum)		(Minimum)	(Nominal)	(Maximum)	
Phase	Far 2 tube 2 gain		Value	Phase	Far 2 tube 2 offset CPS		Value
Master			1.052	Master			-0.8120
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)	
Phase	Far 2 tube 3 gain		Value	Phase	Far 2 tube 3 offset CPS		Value
Master			1.081	Master			-0.7770
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)	
Phase	Near 1 tube 1 gain		Value				
Master			1.046				
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)					
Phase	Near 2 tube 1 gain		Value				
Master			1.011				
0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)					

6.75-in. Resistivity At-the-Bit / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

Calibration Status

RAB6 – CA

125

Valid

Master: 11-JUN-2002 15:39

6.75-in. Resistivity At-the-Bit Calibration

Resistivity: Fixture

Phase	Ring/T1 factor		Value	Phase	Ring/T2 factor		Value	Phase	M0/T1 factor		Value
Master			1.002	Master			0.9974	Master			1.004
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	
Phase	M0/T2 factor		Value	Phase	M2/T1 factor		Value	Phase	M2/T2 factor		Value
Master			0.9992	Master			0.9985	Master			0.9932
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	
Phase	BTN shallow/T1 factor		Value	Phase	BTN shallow/T2 factor		Value	Phase	BTN medium/T1 factor		Value
Master			1.003	Master			0.9977	Master			1.007
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	
Phase	BTN medium/T2 factor		Value	Phase	BTN deep/T1 factor		Value	Phase	BTN deep/T2 factor		Value
Master			1.001	Master			1.005	Master			0.9997
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	

Master: 11-JUN-2002 10:07

6.75-in. Resistivity At-the-Bit Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor		Value
Master			0.8760
0.7500 (Minimum)	1.000 (Nominal)	1.250 (Maximum)	

ANADRILL

SCHLUMBERGER

Survey report

11-Aug-2002 11:07:47

Page 1 of 5

Client.....: Esso Australia Ltd.
Field.....: TUNA

Well.....: A-29
API number.....:
Engineer.....: J. Walta

COUNTY.....: ISDL 453
STATE.....: Victoria

Spud date.....: 27-Jul-2002
Last survey date.....: 11-Aug-02
Total accepted surveys...: 106
MD of first survey.....: 156.07 m
MD of last survey.....: 3075.00 m

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: GROUND LEVEL
Depth reference.....: Driller's Pipe Tally
GL above permanent.....: -59.40 m
KB above permanent.....: 31.30 m
DF above permanent.....: 31.30 m

----- Vertical section origin-----
Latitude (+N/S-).....: 0.00 m
Departure (+E/W-).....: 0.00 m

----- Platform reference point-----
Latitude (+N/S-).....: 1.86 m
Departure (+E/W-).....: 6.34 m

Azimuth from rotary table to target: 277.51 degrees

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2001
Magnetic date.....: 27-Jul-2002
Magnetic field strength...: 1200.21 HCONT
Magnetic dec (+E/W-).....: 13.19 degrees
Magnetic dip.....: -68.68 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.02 mGal
Reference H.....: 1200.21 HCONT
Reference Dip.....: -68.68 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCONT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 13.19 degrees
Grid convergence (+E/W-)..: -0.88 degrees
Total az corr (+E/W-).....: 14.07 degrees
(Total az corr = magnetic dec - grid conv)
Sag applied (Y/N).....: No degree: 0.00

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 2 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
1	156.07	6.35	307.91	0.00	155.95	2.02	4.61	1.11	3.23	13.48	0.00	TIP	-
2	170.00	5.97	310.00	13.93	169.80	3.33	5.55	-0.06	4.64	359.41	0.32	GYR	-
3	180.00	6.25	311.20	10.00	179.74	4.26	6.25	-0.86	5.68	352.12	0.31	GYR	-
4	190.00	6.50	311.00	10.00	189.68	5.21	6.98	-1.70	6.77	346.39	0.25	GYR	-
5	199.00	7.95	302.40	9.00	198.61	6.23	7.64	-2.61	7.87	341.14	2.01	GYR	-
6	207.87	9.50	297.60	8.87	207.38	7.50	8.31	-3.78	9.16	335.55	1.93	GYR	-
7	257.64	15.09	289.75	49.77	255.99	17.84	12.41	-13.52	19.34	312.53	1.17	MWD	6-axis
8	286.91	18.18	284.12	29.27	284.03	26.16	14.81	-21.54	26.46	304.51	1.19	MWD	6-axis
9	316.01	22.01	284.09	29.10	311.36	36.14	17.25	-31.24	37.23	298.90	1.32	MWD	6-axis
10	344.67	26.97	284.20	28.66	337.43	48.00	20.15	-42.75	48.96	295.23	1.73	MWD	6-axis
11	373.47	32.36	282.80	28.80	362.45	62.23	23.46	-56.61	63.08	292.51	1.89	MWD	6-axis
12	402.99	38.21	282.39	29.52	386.53	79.26	27.17	-73.24	80.01	290.35	1.98	MWD	6-axis
13	430.93	41.02	283.93	27.94	408.06	97.06	31.24	-90.59	97.67	289.02	1.07	MWD	6-axis
14	460.99	45.41	281.38	30.06	429.96	117.62	35.72	-110.67	118.27	287.89	1.57	MWD	6-axis
15	488.83	49.30	278.57	27.84	448.82	138.09	39.25	-130.83	138.62	286.70	1.58	MWD	6-axis
16	518.55	53.78	276.06	29.72	467.30	161.31	42.20	-153.91	161.67	285.33	1.65	MWD	6-axis
17	546.96	58.08	276.70	28.41	483.21	184.77	44.82	-177.29	184.99	284.19	1.52	MWD	6-axis
18	576.09	62.87	277.64	29.13	497.56	201.07	47.99	-202.43	201.19	283.34	1.67	MWD	6-axis
19	604.84	65.59	277.64	28.75	510.06	232.92	51.43	-228.09	235.99	282.71	0.95	MWD	6-axis
20	633.75	69.39	278.17	28.91	521.13	260.59	55.10	-254.53	262.63	282.22	1.33	MWD	6-axis
21	662.68	69.86	277.82	28.93	531.20	289.68	58.87	-281.39	289.70	281.82	0.20	MWD	6-axis
22	691.52	69.82	277.82	28.84	541.14	316.72	62.56	-308.21	316.72	281.47	0.01	MWD	6-axis
23	720.51	69.92	277.99	28.99	551.12	343.90	66.30	-335.17	343.90	281.19	0.06	MWD	6-axis
24	749.83	69.95	278.05	29.32	561.18	371.41	70.14	-362.44	371.41	280.95	0.02	MWD	6-axis
25	778.98	69.97	278.33	29.15	571.16	398.77	74.04	-389.55	398.78	280.76	0.09	MWD	6-axis
26	807.96	69.69	278.22	28.98	581.16	425.95	77.96	-416.47	425.96	280.60	0.10	MWD	6-axis
27	836.68	69.70	278.05	28.72	591.12	452.86	81.77	-443.13	452.88	280.46	0.06	MWD	6-axis
28	865.69	69.28	277.61	29.01	601.29	480.00	85.47	-470.05	480.03	280.31	0.20	MWD	6-axis
29	894.90	69.07	277.19	29.21	611.67	507.25	88.99	-497.13	507.30	280.15	0.15	MWD	6-axis
30	912.12	68.72	277.44	17.22	617.87	523.29	91.04	-513.06	523.35	280.06	0.24	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 3 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
31	934.47	67.92	275.65	22.35	626.13	544.00	93.40	-533.69	544.09	279.93	0.83	MWD	6-axis
32	963.02	68.84	276.78	28.55	636.67	570.51	96.28	-560.12	570.63	279.75	0.49	MWD	6-axis
33	991.59	69.13	276.94	28.57	646.90	597.07	99.46	-586.55	597.22	279.62	0.11	MWD	6-axis
34	1019.91	69.09	276.77	28.32	656.99	623.47	102.62	-612.82	623.65	279.51	0.06	MWD	6-axis
35	1048.55	69.47	277.21	28.64	667.13	650.20	105.88	-639.41	650.42	279.40	0.20	MWD	6-axis
36	1076.12	68.94	276.89	27.57	676.91	675.92	109.04	-664.99	676.18	279.31	0.22	MWD	6-axis

36	1076.12	68.94	276.89	27.57	676.91	675.92	109.04	-664.99	676.18	279.31	0.22	MWD	6-axis
37	1104.52	69.75	277.83	28.40	686.93	702.45	112.45	-691.35	702.74	279.24	0.42	MWD	6-axis
38	1133.71	70.22	278.09	29.19	696.92	729.85	116.25	-718.51	730.16	279.19	0.18	MWD	6-axis
39	1162.50	69.60	277.75	28.80	706.82	756.86	119.97	-745.30	757.20	279.14	0.24	MWD	6-axis
40	1191.22	68.78	277.44	28.71	717.37	784.59	123.64	-772.83	784.97	279.09	0.30	MWD	6-axis
41	1219.65	69.73	277.16	28.43	727.09	810.20	126.90	-798.27	810.61	279.03	0.35	MWD	6-axis
42	1248.12	69.03	277.03	28.47	737.11	836.79	130.20	-824.71	837.24	278.97	0.25	MWD	6-axis
43	1276.77	70.00	277.74	28.65	747.14	863.59	133.65	-851.33	864.07	278.92	0.41	MWD	6-axis
44	1304.64	69.61	277.23	27.87	756.76	889.70	137.05	-877.26	890.22	278.88	0.22	MWD	6-axis
45	1333.27	68.53	276.72	28.63	766.99	916.38	140.30	-903.80	916.95	278.82	0.41	MWD	6-axis
46	1362.51	69.76	277.56	29.24	777.40	943.66	143.70	-930.91	944.26	278.78	0.50	MWD	6-axis
47	1390.59	69.10	277.80	28.08	787.26	969.91	147.21	-956.97	970.55	278.75	0.25	MWD	6-axis
48	1419.55	70.10	277.74	28.96	797.36	997.02	150.88	-983.86	997.69	278.72	0.35	MWD	6-axis
49	1447.26	69.14	277.71	27.71	807.01	1022.96	154.37	-1009.60	1023.66	278.69	0.35	MWD	6-axis
50	1475.75	70.48	277.78	28.49	816.84	1049.66	157.98	-1036.10	1050.50	278.67	0.47	MWD	6-axis
51	1504.20	69.80	277.36	28.45	826.51	1076.38	161.50	-1062.62	1077.15	278.64	0.28	MWD	6-axis
52	1532.83	68.89	276.77	28.63	836.60	1103.11	164.80	-1089.21	1103.93	278.60	0.37	MWD	6-axis
53	1562.01	70.11	277.19	29.18	846.82	1130.39	168.12	-1116.34	1131.25	278.56	0.44	MWD	6-axis
54	1590.59	69.57	277.20	28.58	856.67	1157.17	171.48	-1142.95	1158.08	278.53	0.19	MWD	6-axis
55	1619.04	69.80	279.22	28.45	866.55	1183.82	175.29	-1169.36	1184.76	278.53	0.67	MWD	6-axis
56	1647.25	68.42	278.44	28.21	876.61	1210.16	179.33	-1195.40	1211.11	278.53	0.55	MWD	6-axis
57	1676.33	69.58	277.93	29.08	887.03	1237.28	183.20	-1222.27	1238.26	278.52	0.43	MWD	6-axis
58	1705.18	69.52	277.87	28.85	897.11	1264.28	186.91	-1249.05	1265.29	278.51	0.03	MWD	6-axis
59	1734.51	69.49	278.30	29.33	907.38	1291.73	190.78	-1276.25	1292.67	278.50	0.14	MWD	6-axis
60	1762.84	70.02	278.16	28.33	917.18	1318.28	194.58	-1302.55	1319.34	278.50	0.19	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 4 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
61	1791.89	68.75	277.51	29.05	927.41	1345.44	198.29	-1329.49	1346.53	278.48	0.48	MWD	6-axis
62	1820.89	69.70	278.23	29.00	937.70	1372.52	202.00	-1356.35	1373.64	278.47	0.40	MWD	6-axis
63	1849.94	70.22	278.36	29.05	947.65	1399.78	205.94	-1383.35	1400.93	278.47	0.18	MWD	6-axis
64	1878.96	70.43	278.43	29.02	957.42	1427.09	209.93	-1410.39	1428.26	278.47	0.08	MWD	6-axis
65	1907.42	69.37	278.19	28.46	967.20	1453.79	213.79	-1436.83	1454.98	278.46	0.38	MWD	6-axis
66	1936.61	69.40	277.83	29.19	977.48	1481.08	217.60	-1463.89	1482.30	278.45	0.12	MWD	6-axis
67	1965.40	70.13	277.70	28.79	987.44	1508.46	221.25	-1490.65	1509.32	278.44	0.26	MWD	6-axis
68	1994.90	69.00	277.57	29.50	997.74	1535.66	224.92	-1518.05	1536.96	278.43	0.39	MWD	6-axis
69	2023.87	69.58	277.53	28.97	1007.98	1562.72	228.48	-1544.91	1564.05	278.41	0.20	MWD	6-axis
70	2053.01	70.40	277.19	29.14	1017.95	1590.05	231.99	-1572.07	1591.43	278.39	0.30	MWD	6-axis
71	2081.95	69.28	276.84	28.94	1027.93	1617.16	235.31	-1599.03	1618.59	278.37	0.40	MWD	6-axis
72	2110.89	69.88	276.72	28.94	1038.01	1644.18	238.51	-1625.92	1645.66	278.35	0.21	MWD	6-axis
73	2139.84	69.69	277.89	28.95	1048.03	1671.34	241.96	-1652.91	1672.86	278.33	0.38	MWD	6-axis
74	2168.61	68.47	277.69	28.77	1058.30	1698.18	245.61	-1679.53	1699.73	278.32	0.43	MWD	6-axis
75	2196.77	68.73	278.43	28.16	1068.58	1724.37	249.28	-1705.49	1725.95	278.32	0.26	MWD	6-axis
76	2225.63	69.28	277.51	28.86	1078.92	1751.28	253.02	-1732.17	1752.90	278.31	0.35	MWD	6-axis
77	2254.91	68.25	277.29	29.28	1089.52	1778.53	256.53	-1759.24	1780.18	278.30	0.36	MWD	6-axis
78	2283.60	69.15	277.10	28.69	1099.94	1805.21	259.86	-1785.76	1806.91	278.28	0.32	MWD	6-axis
79	2312.77	68.10	276.88	29.17	1110.57	1832.31	263.15	-1812.73	1834.07	278.26	0.37	MWD	6-axis
80	2341.36	68.69	277.40	28.59	1121.10	1858.48	266.45	-1839.10	1856.64	278.24	0.27	MWD	6-axis
81	2370.89	68.94	276.86	29.53	1131.77	1886.32	269.87	-1866.42	1888.17	278.23	0.19	MWD	6-axis
82	2399.55	69.12	277.90	28.66	1142.03	1913.04	273.30	-1892.96	1914.93	278.22	0.34	MWD	6-axis
83	2428.92	69.05	277.42	29.37	1152.51	1940.43	276.96	-1920.15	1942.37	278.21	0.15	MWD	6-axis
84	2457.83	69.47	277.99	28.91	1162.75	1967.43	280.59	-1946.94	1969.40	278.20	0.23	MWD	6-axis
85	2486.94	68.79	278.64	29.11	1173.12	1994.61	284.52	-1973.86	1956.60	278.20	0.31	MWD	6-axis
86	2515.88	67.38	279.85	28.94	1183.92	2021.45	288.83	-2000.36	2023.44	278.25	0.62	MWD	6-axis
87	2545.04	65.00	281.43	29.16	1195.70	2048.12	293.75	-2026.57	2050.09	278.25	0.95	MWD	6-axis
88	2573.83	62.39	283.61	28.79	1208.45	2073.92	299.34	-2051.76	2075.83	278.30	1.13	MWD	6-axis
89	2602.58	58.65	285.62	28.75	1222.60	2098.88	305.65	-2075.98	2100.70	278.38	1.44	MWD	6-axis
90	2631.33	56.13	286.51	28.75	1238.09	2122.99	312.35	-2099.25	2124.69	278.46	0.91	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 5 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
91	2659.69	54.32	286.63	28.36	1254.27	2146.16	318.99	-2121.58	2147.75	278.55	0.64	MWD	6-axis
92	2688.71	53.11	287.55	29.02	1271.44	2169.41	325.86	-2143.93	2170.88	278.64	0.49	MWD	6-axis
93	2718.07	51.22	289.76	29.36	1289.45	2192.37	333.27	-2165.90	2193.72	278.75	0.88	MWD	6-axis
94	2746.79	49.16	290.96	28.72	1307.84	2214.12	340.94	-2186.59	2215.33	278.86	0.79	MWD	6-axis
95	2776.50	47.88	292.40	29.71	1327.52	2235.97	349.16	-2207.27	2237.03	278.99	0.56	MWD	6-axis
96	2805.24	46.70	293.44	28.74	1347.01	2256.61	357.39	-2226.72	2257.53	279.12	0.49	MWD	6-axis
97	2833.96	43.73	298.05	28.72	1367.25	2273.28	366.22	-2245.08	2277.05	279.26	1.54	MWD	6-axis
98	2862.50	42.39	302.54	28.54	1388.10	2294.63	376.03	-2261.90	2295.24	279.44	1.17	MWD	6-axis
99	2891.25	40.70	305.19	28.75	1409.62	2312.16	386.65	-2277.73	2312.61	279.63	0.85	MWD	6-axis
100	2920.00	38.59	306.07	28.75	1431.76	2328.80	397.33	-2292.64	2329.10	279.83	0.76	MWD	6-axis
101	2948.89	36.50	309.17	28.89	1454.67	2344.50	408.06	-2306.59	2344.68	280.03	0.97	MWD	6-axis

101	2948.89	36.50	309.17	28.89	1454.67	2344.50	408.06	-2306.59	2344.68	280.03	0.97	MWD	6-axis
102	2977.95	33.86	311.42	29.06	1478.42	2359.06	418.88	-2319.36	2359.15	280.24	1.01	MWD	6-axis
103	3006.85	30.56	313.56	28.90	1502.87	2372.17	429.26	-2330.75	2372.30	280.44	1.21	MWD	6-axis
104	3036.40	27.10	314.14	29.55	1528.75	2384.11	439.10	-2341.04	2384.12	280.63	1.17	MWD	6-axis
105	3053.55	26.87	314.19	17.15	1544.03	2390.60	444.53	-2346.62	2390.60	280.73	0.13	MWD	6-axis
106	3075.00	26.61	314.25	21.45	1563.19	2398.65	451.26	-2353.54	2398.65	280.86	0.12	Projection	
[(c)2002 Anadrill IDEAL ID6_1C_10]													

Company:

Esso Australia Ltd.

Well:

TNA A-29

Field:

Tuna

Rig:

ISDL 453

State:

Victoria

GeoVISION Resistivity

1:200 Measured Depth

Recorded Mode Log

