

Rig: **ISDL 453** State: **Victoria**

Rig: ISDL 453 Field: Tuna Location: Bass Strait Well: TNA A-29 Company: Esso Australia Ltd.	VISION Density Neutron 1:500 Measured Depth Recorded Mode Log									
	Location	Total depth:		3075 m		Elevation	K.B.		Top Drive	
		Spud date:		27-July-02			G.L.		-59.4 m	
		Runs:		3 To 6			D.F.		31.3 m	
		Permanent datum:		Mean Sea Level		Elev.:		59.4 m		
		Log measured from:		Drill Floor		31.3 m		above Perm. datum		
	Depth reference:		Driller's Pipe Tally							
	API serial no.		x = 5774225.50m (North) y = 624224.90m (East)		Longitude		Latitude			
					E 148 25 5.513		S 38 10 16.237			
	Depth logged:		928 m To 3075 m		Mag decl: 13.19°		Other services:			
Date logged:		3-Aug-02 To 11-Aug-02		Mag dip: -68.68°		Directional Drilling				
Bore hole record				Casing record						
Hole size		from to		Size		Density		from to		
12 1/4 in.		164.9 m 937 m		20 in.		84 lb/ft		Surface 164.9 m		
8 1/2 in.		928 m 3075 m		9 5/8 in.		47 lb/ft		Surface 928 m		
Mud record				Borehole deviation record						
Type		from to		Min Max		from to				
Seawater		164.9 m 937 m		6.35° 69.39°		165 m 634 m				
KCL/PHPA/GLYCOL		928 m 3075 m		67.92° 70.43°		634 m 2515 m				
				26.61° 67.38°		2515 m 3075 m				
Surface equipment				Software record				IDEAL services from Anadrill		
Unit		OLU-FB-924		IDEAL Wis		ID6_1C_10r				
Depth system		PDA		SPM		ID6_1C_10r				
				LWD		see toolsketch				
				MWD		see toolsketch				

Bit Run Summary

[illegible]

Type		KCL/PHPA/GLYCOL	KCL/PHPA/GLYCOL							
Mud weight	ppg	9.4	10.55	10.4						
Solids	%vol	4.3	10.4	9.4						
Chlorides	mg/l	45,500	47,900	47,900						
Rm	Ohmms @ °C	0.0963@20	0.0945@20	0.1230@21						
Rmf	Ohmms @ °C	0.0878@20	0.1302@20	0.0880@21						
Rmc	Ohmms @ °C	0.0677@20	0.2170@21	0.3830@22						
Potassium	%vol	4	4	4						
Environmental data										
GR										
Mud weight	ppg	9.4	10.55	10.3						
Bit size	in	8.5	8.5	8.5						
Resistivity										
Neutron porosity										
Hole Size	in	8.5	8.5	8.5						
Mud weight	ppg	9.4	10.55	10.3						
Temperature	degC	47.1	78	75						
Mud salinity	mg/l	75,000	79,035	79,035						
Formation salinity										
Recording rate 1	SEC	10	10	10						
Recording rate 2	SEC	10	10	10						
Filtering GR		3 pt	3 pt	3 pt						
Filtering density		3 pt	3 pt	3 pt						
Filtering Neutron		3 pt	3 pt	3 pt						
Company representative		B. Davies	B. Steel	G. Campbell						
Anadrill personnel		J. Walta	L. Bon	J. Dolan						

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN3 Directional Surveys		OTHER SERVICES FOR RUN4 Directional Surveys		OTHER SERVICES FOR RUN6 Directional Surveys	
REMARKS: RUN NUMBER 3 8-1/2in Hole Section was logged from 928m to 1192m MD Depth is referenced to driller's pipe tally All data is presented from tool memory Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature. Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure) Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.		REMARKS: RUN NUMBER 4 8-1/2in Hole Section was logged from 1192m to 2797m MD Depth is referenced to driller's pipe tally All data is presented from tool memory Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature. Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure) Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.		REMARKS: RUN NUMBER 6 8-1/2in Hole Section was logged from 2797m to 3075m MD Depth is referenced to driller's pipe tally All data is presented from tool memory Button deep down resistivity is presented in replacement for absent ring resistivity. GR corrected for mud weight, tool and bit size. RAB6 resistivity is corrected for the bit size, mud resistivity and borehole temperature. Bottom quadrant density is presented. Neutron porosity is calculated with limestone matrix and is corrected for the bit size, borehole salinity, temperature and mud hydrogen index (from mud weight, temperature and pressure) Mud type is water based KCL/PHPA/GLYCOL Barite is present in the mud.	

Barite is present in the mud.

RAB6C* Downhole Software 6.1B14
ADN6C* Downhole Software 6.2B08

Barite is present in the mud.

RAB6C* Downhole Software 6.1B14
ADN6C* Downhole Software 6.2B08

Barite is present in the mud.

RAB6C* Downhole Software 6.1B12
ADN6C* Downhole Software 6.1B01

EQUIPMENT DESCRIPTION

RUN3

RUN4


RUN6

DOWNHOLE EQ

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.2

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.8
27.6
26.8
26.7
26.3
25.5



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.4
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.7
13.6
13.4
13.2
13.1
12.9



Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B




DOWNHOLE E

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.2

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.7
27.6
26.7
26.6
26.2
25.4



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.3
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.6
13.5
13.3
13.2
13.0
12.8



Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B




DOWNHOLE EQ

6-3/4" A
ADSE
8-1/4in
NSR-M
GSR-J A
Soft: 6.1

Neutron
Neutron
Density
Density
UltraSo
R-O P


27.6
27.5
26.6
26.5
26.1
25.4



6-3/4" Powe
MDC Z
MDI 116
MEC 115
Soft: 6.1

D&I
GR


19.3
18.7




6-3/4" G
S/N: 1
Soft: 6.1

Shallo
Medium
Deep
Ring R
R-O p
GR


13.6
13.5
13.3
13.2
13.0
12.8



Cross Over S
NM Pony
S/N ANA9



ADOS S/N
PowerPak* Mu
A675XP7850
1.15 deg bent B



1.15 deg bent B



1.15 deg bent B



1.15 deg bent B



Bit-PD

Hughes Model: HCM60

MAXIMUM STRING DI

ALL LENGTHS I

Bit-PD

GeoDIAMOND Model: S7

MAXIMUM STRING DI

ALL LENGTHS I

Bit-PD

GeoDIAMOND Model: S7

MAXIMUM STRING DI

ALL LENGTHS I

IDEAL Version: ID7_0C_02

IDF

RAB	id6_1c_10	MWD_10	id6_1c_10
ADN	id6_1c_10		

Format: A-29 GeoVISION Density Neutron

Vertical Scale: 1:500

Graphics File Created: 18-Aug-2002 13:48

Parameters

DLIS Name	Description	Value	
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES	
BHA_COEF_VER	RAB: BHA Coef Generator Version	2.000	
BHT_RM	Bottom Hole Temperature (RM)	75.000	degC
BSAL_RM	Mud Salinity (RM)	79.200	ppk
BS_RM	Bit Size (RM)	8.500	in
DEVI	Average angle of the hole (RM)	59.450	deg
DHS_VERSION	RAB: DownHole Software Version	V6.1B	
DO	Depth Offset	0.0	m
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES	
GRDC	Grid corr angle	-0.880	deg
LITHO_TYPE_ADN	Lithology (RM)	LIME	
MST_RM	Mud Sample temperature (RM)	20.800	degC
MW_RM	Mud Weight (RM)	10.400	lbm/gal
OBM	RAB: Oil base Mud	NO	
OBMF_RM	Oil Based Mud	NO	
RAB_TEMP_SELECT	RAB Temperature Selection	MEAS	
READOUT_PORT_MP	RAB: ROP to Bit Face Distance	13.070	m
RHOF_RM	Mud Filtrate Density (RM)	1.000	g/cm3
RHOM_RM	Matrix density (RM)	2.710	g/cm3
RMS_RM	Resistivity of Mud Sample (RM)	0.123	ohm.m
RWS_RM	Resistivity of Connate Water (RM)	1.000	ohm.m
SHT_RM	Surface Hole Temperature (RM)	10.000	degC
SSIZ_ADN	ADN:Stabilizer Size (RM)	8.250	in
STAB	RAB: Run with Stabilizer	YES	
TD_RM	Total Measured Depth (RM)	3075.0	m
TOOLTYPE	RAB: Azimuthal Tool	YES	
TRPM_RM	Average Tool rotational Speed (RM)	20.000	c/min
TSIZ_ADN	ADN:Tool Size (RM)	6.750	in
TS_VERSION	RAB: ToolScope Software Version	V6.0 B017	
TWS_RM	Temperature of Connate Water (RM)	23.889	degC
VERS_ADN	ADN downhole software	6.100	
VRAB6	Rab Tool type (ENP/PILOT)	RAB6_C_SERIES	

PIP SUMMARY

Density Ticks, 0.1 ft

Neutron Ticks, 0.1 ft

Gamma Ray Samples


LWD Spare Area

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)
200 (M/HR) 0

RAB Gamma Ray (GR_RAB)
0 (GAPI) 200

Density Time After Bit (TAB_DEN)
0 (HR) 10

ADN
Rotational
Speed
(RPM_ADN)
(RPM)
0 200



LWD Spare Area
From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH


Thermal Neutron Porosity (TNPH)
45 (PU) -15



Bulk Density, Bottom (ROBB)
1.85 (G/C3) 2.85



Bulk Density (RHOB)
1.85 (G/C3) 2.85



Photoelectric Factor, Bottom (PEB)
0 (----) 10



Bulk Density Correction, Bottom
(DRHB)
-0.25 (G/C3) 0.25






























































Density Time After Bit (TAB_DEN) (HR)		ADN Rotational Speed (RPM_ADN) (RPM)	Photoelectric Factor, Bottom (PEB) (----	Bulk Density Correction, Bottom (DRHB) (G/C3)
0	10	0	10	-0.25
RAB Gamma Ray (GR_RAB) (GAPI)		0	200	
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR)		200	0	
		Bulk Density (RHOB) (G/C3)		
		1.85		
		Bulk Density, Bottom (ROBB) (G/C3)		
		1.85		
		Thermal Neutron Porosity (TNPH) (PU)		
		45		
		LWDSpareArea From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH		




PIP SUMMARY		
+	Density Ticks, 0.1 ft	
+	Gamma Ray Samples	
		Neutron Ticks, 0.1 ft




IDEAL Version: ID7_OC_02 IDF			
RAB	id6_1c_10	MWD_10	id6_1c_10
ADN	id6_1c_10		



6.75-in. Azimuthal Density Neutron / Equipment Identification		
Primary Equipment:		
Tool Name and Serial Number	ADN6 – CA	289
Neutron Logging Source	NSR – M	161
Density Logging Source	GSR – J/Z	2125
Stabilizer Size	8.25 – in.	
Calibration Status	Valid	















Master: 24-JUL-2002 8:49														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Magnesium Block														
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value	Phase	SS window 3 – Mg CPS			Value
Master	<div><div></div></div>			1334	Master	<div><div></div></div>			3054	Master	<div><div></div></div>			7545
	250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)			700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)			2500 (Minimum)	23750 (Nominal)	45000 (Maximum)	

Master: 24–JUL–2002 8:49

6.75-in. Azimuthal Density Neutron Calibration														
Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				208.1	Master				1635	Master				4899
	50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)			500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)			1500 (Minimum)	15750 (Nominal)	30000 (Maximum)	

6.75-in. Azimuthal Density Neutron Calibration														
Density: Background														
Phase	LS window 3 – Background		CPS	Value	Phase	SS window 1 – Background		CPS	Value	Phase	SS window 3 – Background		CPS	Value
Master			52.11		Master			125.8		Master			548.2	
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

6.75-in. Azimuthal Density Neutron Calibration							
Density: Water Block Check							
Phase	Long spacing water density G/C3		Value	Phase	Short spacing water density G/C3		Value
Master			1.035	Master			1.126
	1.011 (Minimum)	1.026 (Nominal)	1.041 (Maximum)		1.093 (Minimum)	1.118 (Nominal)	1.143 (Maximum)

Neutron: Water Tank							
Phase	Far 1 tube 1 gain		Value	Phase	Far 1 tube 1 offset CPS		Value
Master			1.106	Master			-0.8130
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Far 1 tube 2 gain		Value	Phase	Far 1 tube 2 offset CPS		Value
Master			1.054	Master			-0.9150
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Far 1 tube 3 gain		Value	Phase	Far 1 tube 3 offset CPS		Value
Master			1.064	Master			-0.8000
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Far 2 tube 1 gain		Value	Phase	Far 2 tube 1 offset CPS		Value
Master			1.106	Master			-0.7490
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Far 2 tube 2 gain		Value	Phase	Far 2 tube 2 offset CPS		Value
Master			1.005	Master			-0.8300
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Far 2 tube 3 gain		Value	Phase	Far 2 tube 3 offset CPS		Value
Master			1.103	Master			-0.8040
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)		-1.200 (Minimum)	-0.9000 (Nominal)	-0.6000 (Maximum)
Phase	Near 1 tube 1 gain		Value				
Master			1.085				
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)				
Phase	Near 2 tube 1 gain		Value				
Master			1.058				
	0.9000 (Minimum)	1.100 (Nominal)	1.300 (Maximum)				

6.75-in. Resistivity At-the-Bit / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

RAB6 – CA

136













Calibration Status

Valid

Master: 28-JUL-2002 11:01

6.75-in. Resistivity At-the-Bit Calibration


Resistivity: Fixture

Phase	Ring/T1 factor	Value	Phase	Ring/T2 factor	Value	Phase	M0/T1 factor	Value
Master		0.9850	Master		0.9970	Master		0.9930
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	M0/T2 factor	Value	Phase	M2/T1 factor	Value	Phase	M2/T2 factor	Value
Master		0.9970	Master		0.9980	Master		1.003
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	BTN shallow/T1 factor	Value	Phase	BTN shallow/T2 factor	Value	Phase	BTN medium/T1 factor	Value
Master		1.014	Master		1.020	Master		1.018
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	BTN medium/T2 factor	Value	Phase	BTN deep/T1 factor	Value	Phase	BTN deep/T2 factor	Value
Master		1.024	Master		1.015	Master		1.023
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)

Master: 28-JUL-2002 11:01

6.75-in. Resistivity At-the-Bit Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor	Value
Master		0.9010
	0.7500 (Minimum)	1.000 (Nominal)
		1.250 (Maximum)

6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

ADN6 – CA

219

Neutron Logging Source

NSR – M

161

Density Logging Source

GSR – J/Z

2125

Stabilizer Size

8.25 – in.




Calibration Status

Valid

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration




Density: Magnesium Block

Phase	LS window 3 – Mg CPS	Value	Phase	SS window 1 – Mg CPS	Value	Phase	SS window 3 – Mg CPS	Value
Master		1294	Master		3056	Master		7448
	250.0 (Minimum)	4125 (Nominal)		700.0 (Minimum)	9350 (Nominal)		2500 (Minimum)	23750 (Nominal)
		8000 (Maximum)			18000 (Maximum)			45000 (Maximum)

Master: 23-JUL-2002 14:16




6.75-in. Azimuthal Density Neutron Calibration

6.75-in. Azimuthal Density Neutron Calibration

Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				190.8	Master				1547	Master				4662
50.00 (Minimum) 725.0 (Nominal) 1400 (Maximum)					500.0 (Minimum) 4250 (Nominal) 8000 (Maximum)					1500 (Minimum) 15750 (Nominal) 30000 (Maximum)				



Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration

Density: Background											
Phase	LS window 3 – Background CPS		Value	Phase	SS window 1 – Background CPS		Value	Phase	SS window 3 – Background CPS		Value
Master			58.08	Master			125.9	Master			543.1
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)		40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)		150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)















Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration

Density: Water Block Check									
Phase	Long spacing water density G/C3		Value	Phase	Short spacing water density G/C3		Value		
Master			1.043	Master			1.131		
	1.016 (Minimum)	1.032 (Nominal)	1.047 (Maximum)		1.062 (Minimum)	1.107 (Nominal)	1.151 (Maximum)		

Master: 23-JUL-2002 14:16

6.75-in. Azimuthal Density Neutron Calibration

Neutron: Water Tank									
Phase		Far 1 tube 1 gain		Value	Phase		Far 1 tube 1 offset CPS		Value
Master				1.077	Master				-0.9260
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Far 1 tube 2 gain		Value	Phase		Far 1 tube 2 offset CPS		Value
Master				1.034	Master				-0.9100
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Far 1 tube 3 gain		Value	Phase		Far 1 tube 3 offset CPS		Value
Master				1.085	Master				-0.8150
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Far 2 tube 1 gain		Value	Phase		Far 2 tube 1 offset CPS		Value
Master				1.064	Master				-0.8090
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Far 2 tube 2 gain		Value	Phase		Far 2 tube 2 offset CPS		Value
Master				1.052	Master				-0.8120
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Far 2 tube 3 gain		Value	Phase		Far 2 tube 3 offset CPS		Value
Master				1.081	Master				-0.7770
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)	-1.200 (Minimum)		-0.9000 (Nominal)		-0.6000 (Maximum)
Phase		Near 1 tube 1 gain		Value					
Master				1.046					
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)					
Phase		Near 2 tube 1 gain		Value					
Master				1.011					
0.9000 (Minimum)		1.100 (Nominal)		1.300 (Maximum)					

6.75-in. Resistivity At-the-Bit / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

RAB6 - CA

125













Calibration Status

Valid

Master: 11-JUN-2002 15:39

6.75-in. Resistivity At-the-Bit Calibration


Resistivity: Fixture

Phase	Ring/T1 factor	Value	Phase	Ring/T2 factor	Value	Phase	M0/T1 factor	Value
Master		1.002	Master		0.9974	Master		1.004
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	M0/T2 factor	Value	Phase	M2/T1 factor	Value	Phase	M2/T2 factor	Value
Master		0.9992	Master		0.9985	Master		0.9932
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	BTN shallow/T1 factor	Value	Phase	BTN shallow/T2 factor	Value	Phase	BTN medium/T1 factor	Value
Master		1.003	Master		0.9977	Master		1.007
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)
Phase	BTN medium/T2 factor	Value	Phase	BTN deep/T1 factor	Value	Phase	BTN deep/T2 factor	Value
Master		1.001	Master		1.005	Master		0.9997
	0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)		0.9750 (Minimum)	1.000 (Nominal)
		1.025 (Maximum)			1.025 (Maximum)			1.025 (Maximum)

Master: 11-JUN-2002 10:07

6.75-in. Resistivity At-the-Bit Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor	Value
Master		0.8760
	0.7500 (Minimum)	1.000 (Nominal)
		1.250 (Maximum)

ANADRILL

SCHLUMBERGER

Survey report

11-Aug-2002 11:07:47

Page 1 of 5

Client.....: Esso Australia Ltd.
Field.....: TUNA

Well.....: A-29
API number.....:
Engineer.....: J. Walta

COUNTY.....: ISDL 453
STATE.....: Victoria

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: GROUND LEVEL
Depth reference.....: Driller's Pipe Tally
GL above permanent.....: -59.40 m
KB above permanent.....: 31.30 m
DF above permanent.....: 31.30 m

----- Vertical section origin-----
Latitude (+N/S-).....: 0.00 m
Departure (+E/W-).....: 0.00 m

----- Platform reference point-----

Spud date.....: 27-Jul-2002
Last survey date.....: 11-Aug-02
Total accepted surveys...: 106
MD of first survey.....: 156.07 m
MD of last survey.....: 3075.00 m

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2001
Magnetic date.....: 27-Jul-2002
Magnetic field strength...: 1200.21 HCNT
Magnetic dec (+E/W-).....: 13.19 degrees
Magnetic dip.....: -68.68 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.02 mGal
Reference H.....: 1200.21 HCNT
Reference Dip.....: -68.68 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----

----- Platform reference point-----

Latitude (+N/S-).....: 1.86 m
Departure (+E/W-).....: 6.34 m

Azimuth from rotary table to target: 277.51 degrees

----- Corrections -----

Magnetic dec (+E/W-).....: 13.19 degrees
Grid convergence (+E/W-)..: -0.88 degrees
Total az corr (+E/W-).....: 14.07 degrees
(Total az corr = magnetic dec - grid conv)
Sag applied (Y/N).....: No degree: 0.00

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 2 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
1	156.07	6.35	307.91	0.00	155.95	2.02	4.61	1.11	3.23	13.48	0.00	TIP	-
2	170.00	5.97	310.00	13.93	169.80	3.33	5.55	-0.06	4.64	359.41	0.32	GYR	-
3	180.00	6.25	311.20	10.00	179.74	4.26	6.25	-0.86	5.68	352.12	0.31	GYR	-
4	190.00	6.50	311.00	10.00	189.68	5.21	6.98	-1.70	6.77	346.39	0.25	GYR	-
5	199.00	7.95	302.40	9.00	198.61	6.23	7.64	-2.61	7.87	341.14	2.01	GYR	-
6	207.87	9.50	297.60	8.87	207.38	7.50	8.31	-3.78	9.16	335.55	1.93	GYR	-
7	257.64	15.09	289.75	49.77	255.99	17.84	12.41	-13.52	19.34	312.53	1.17	MWD	6-axis
8	286.91	18.18	284.12	29.27	284.03	26.16	14.81	-21.54	26.46	304.51	1.19	MWD	6-axis
9	316.01	22.01	284.09	29.10	311.36	36.14	17.25	-31.24	37.23	298.90	1.32	MWD	6-axis
10	344.67	26.97	284.20	28.66	337.43	48.00	20.15	-42.75	48.96	295.23	1.73	MWD	6-axis
11	373.47	32.36	282.80	28.80	362.45	62.23	23.46	-56.61	63.08	292.51	1.89	MWD	6-axis
12	402.99	38.21	282.39	29.52	386.53	79.26	27.17	-73.24	80.01	290.35	1.98	MWD	6-axis
13	430.93	41.02	283.93	27.94	408.06	97.06	31.24	-90.59	97.67	289.02	1.07	MWD	6-axis
14	460.99	45.41	281.38	30.06	429.96	117.62	35.72	-110.67	118.27	287.89	1.57	MWD	6-axis
15	488.83	49.30	278.57	27.84	448.82	138.09	39.25	-130.83	138.62	286.70	1.58	MWD	6-axis
16	518.55	53.78	276.06	29.72	467.30	161.31	42.20	-153.91	161.67	285.33	1.65	MWD	6-axis
17	546.96	58.08	276.70	28.41	483.21	184.77	44.82	-177.29	184.99	284.19	1.52	MWD	6-axis
18	576.09	62.87	277.64	29.13	497.56	201.07	47.99	-202.43	201.19	283.34	1.67	MWD	6-axis
19	604.84	65.59	277.64	28.75	510.06	232.92	51.43	-228.09	235.99	282.71	0.95	MWD	6-axis
20	633.75	69.39	278.17	28.91	521.13	260.59	55.10	-254.53	262.63	282.22	1.33	MWD	6-axis
21	662.68	69.86	277.82	28.93	531.20	289.68	58.87	-281.39	289.70	281.82	0.20	MWD	6-axis
22	691.52	69.82	277.82	28.84	541.14	316.72	62.56	-308.21	316.72	281.47	0.01	MWD	6-axis
23	720.51	69.92	277.99	28.99	551.12	343.90	66.30	-335.17	343.90	281.19	0.06	MWD	6-axis
24	749.83	69.95	278.05	29.32	561.18	371.41	70.14	-362.44	371.41	280.95	0.02	MWD	6-axis
25	778.98	69.97	278.33	29.15	571.16	398.77	74.04	-389.55	398.78	280.76	0.09	MWD	6-axis
26	807.96	69.69	278.22	28.98	581.16	425.95	77.96	-416.47	425.96	280.60	0.10	MWD	6-axis
27	836.68	69.70	278.05	28.72	591.12	452.86	81.77	-443.13	452.88	280.46	0.06	MWD	6-axis
28	865.69	69.28	277.61	29.01	601.29	480.00	85.47	-470.05	480.03	280.31	0.20	MWD	6-axis
29	894.90	69.07	277.19	29.21	611.67	507.25	88.99	-497.13	507.30	280.15	0.15	MWD	6-axis
30	912.12	68.72	277.44	17.22	617.87	523.29	91.04	-513.06	523.35	280.06	0.24	MWD	6-axis

[(c)2002 Anadrill IDEAL ID6_1C_10]
ANADRILL SCHLUMBERGER Survey Report

11-Aug-2002 11:07:47

Page 3 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool qual type
31	934.47	67.92	275.65	22.35	626.13	544.00	93.40	-533.69	544.09	279.93	0.83	MWD	6-axis
32	963.02	68.84	276.78	28.55	636.67	570.51	96.28	-560.12	570.63	279.75	0.49	MWD	6-axis
33	991.59	69.13	276.94	28.57	646.90	597.07	99.46	-586.55	597.22	279.62	0.11	MWD	6-axis
34	1019.91	69.09	276.77	28.32	656.99	623.47	102.62	-612.82	623.65	279.51	0.06	MWD	6-axis
35	1048.55	69.47	277.21	28.64	667.13	650.20	105.88	-639.41	650.42	279.40	0.20	MWD	6-axis
36	1076.12	68.94	276.89	27.57	676.91	675.92	109.04	-664.99	676.18	279.31	0.22	MWD	6-axis
37	1104.52	69.75	277.83	28.40	686.93	702.45	112.45	-691.35	702.74	279.24	0.42	MWD	6-axis
38	1133.71	70.22	278.09	29.19	696.92	729.85	116.25	-718.51	730.16	279.19	0.18	MWD	6-axis
39	1162.50	69.60	277.75	28.80	706.82	756.86	119.97	-745.30	757.20	279.14	0.24	MWD	6-axis
40	1191.22	68.78	277.44	28.71	717.37	784.59	123.64	-772.83	784.97	279.09	0.30	MWD	6-axis
41	1219.65	69.73	277.16	28.43	727.09	810.20	126.90	-798.27	810.61	279.03	0.35	MWD	6-axis
42	1248.12	69.03	277.03	28.47	737.11	836.79	130.20	-824.71	837.24	278.97	0.25	MWD	6-axis
43	1276.77	70.00	277.74	28.65	747.14	863.59	133.65	-851.33	864.07	278.92	0.41	MWD	6-axis
44	1304.64	69.61	277.23	27.87	756.76	889.70	137.05	-877.26	890.22	278.88	0.22	MWD	6-axis
45	1333.27	68.53	276.72	28.63	766.99	916.38	140.30	-903.80	916.95	278.82	0.41	MWD	6-axis
46	1362.51	69.76	277.56	29.24	777.40	943.66	143.70	-930.91	944.26	278.78	0.50	MWD	6-axis
47	1390.59	69.10	277.80	28.08	787.26	969.91	147.21	-956.97	970.55	278.75	0.25	MWD	6-axis
48	1419.55	70.10	277.74	28.96	797.36	997.02	150.88	-983.86	997.69	278.72	0.35	MWD	6-axis
49	1447.26	69.14	277.71	27.71	807.01	1022.96	154.37	-1009.60	1023.66	278.69	0.35	MWD	6-axis
50	1475.75	70.48	277.78	28.49	816.84	1049.66	157.98	-1036.10	1050.50	278.67	0.47	MWD	6-axis
51	1504.20	69.80	277.36	28.45	826.51	1076.38	161.50	-1062.62	1077.15	278.64	0.28	MWD	6-axis
52	1532.83	68.89	276.77	28.63	836.60	1103.11	164.80	-1089.21	1103.93	278.60	0.37	MWD	6-axis
53	1562.01	70.11	277.19	29.18	846.82	1130.39	168.12	-1116.34	1131.25	278.56	0.44	MWD	6-axis
54	1590.59	69.57	277.20	28.58	856.67	1157.17	171.48	-1142.95	1158.08	278.53	0.19	MWD	6-axis
55	1619.04	69.80	279.22	28.45	866.55	1183.82	175.29	-1169.36	1184.76	278.53	0.67	MWD	6-axis
56	1647.25	68.42	278.44	28.21	876.61	1210.16	179.33	-1195.40	1211.11	278.53	0.55	MWD	6-axis
57	1676.33	69.58	277.93	29.08	887.03	1237.28	183.20	-1222.27	1238.26	278.52	0.43	MWD	6-axis
58	1705.18	69.52	277.87	28.85	897.11	1264.28	186.91	-1249.05	1265.29	278.51	0.03	MWD	6-axis
59	1734.51	69.49	278.30	29.33	907.38	1291.73	190.78	-1276.25	1292.67	278.50	0.14	MWD	6-axis
60	1762.84	70.02	278.16	28.33	917.18	1318.28	194.58	-1302.55	1319.34	278.50	0.19	MWD	6-axis

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool qual type
61	1791.89	68.75	277.51	29.05	927.41	1345.44	198.29	-1329.49	1346.53	278.48	0.48	MWD	6-axis
62	1820.89	69.70	278.23	29.00	937.70	1372.52	202.00	-1356.35	1373.64	278.47	0.40	MWD	6-axis
63	1849.94	70.22	278.36	29.05	947.65	1399.78	205.94	-1383.35	1400.93	278.47	0.18	MWD	6-axis
64	1878.96	70.43	278.43	29.02	957.42	1427.09	209.93	-1410.39	1428.26	278.47	0.08	MWD	6-axis
65	1907.42	69.37	278.19	28.46	967.20	1453.79	213.79	-1436.83	1454.98	278.46	0.38	MWD	6-axis
66	1936.61	69.40	277.83	29.19	977.48	1481.08	217.60	-1463.89	1482.30	278.45	0.12	MWD	6-axis
67	1965.40	70.13	277.70	28.79	987.44	1508.46	221.25	-1490.65	1509.32	278.44	0.26	MWD	6-axis
68	1994.90	69.00	277.57	29.50	997.74	1535.66	224.92	-1518.05	1536.96	278.43	0.39	MWD	6-axis
69	2023.87	69.58	277.53	28.97	1007.98	1562.72	228.48	-1544.91	1564.05	278.41	0.20	MWD	6-axis
70	2053.01	70.40	277.19	29.14	1017.95	1590.05	231.99	-1572.07	1591.43	278.39	0.30	MWD	6-axis
71	2081.95	69.28	276.84	28.94	1027.93	1617.16	235.31	-1599.03	1618.59	278.37	0.40	MWD	6-axis
72	2110.89	69.88	276.72	28.94	1038.01	1644.18	238.51	-1625.92	1645.66	278.35	0.21	MWD	6-axis
73	2139.84	69.69	277.89	28.95	1048.03	1671.34	241.96	-1652.91	1672.86	278.33	0.38	MWD	6-axis
74	2168.61	68.47	277.69	28.77	1058.30	1698.18	245.61	-1679.53	1699.73	278.32	0.43	MWD	6-axis
75	2196.77	68.73	278.43	28.16	1068.58	1724.37	249.28	-1705.49	1725.95	278.32	0.26	MWD	6-axis
76	2225.63	69.28	277.51	28.86	1078.92	1751.28	253.02	-1732.17	1752.90	278.31	0.35	MWD	6-axis
77	2254.91	68.25	277.29	29.28	1089.52	1778.53	256.53	-1759.24	1780.18	278.30	0.36	MWD	6-axis
78	2283.60	69.15	277.10	28.69	1099.94	1805.21	259.86	-1785.76	1806.91	278.28	0.32	MWD	6-axis
79	2312.77	68.10	276.88	29.17	1110.57	1832.31	263.15	-1812.73	1834.07	278.26	0.37	MWD	6-axis
80	2341.36	68.69	277.40	28.59	1121.10	1858.48	266.45	-1839.10	1856.64	278.24	0.27	MWD	6-axis
81	2370.89	68.94	276.86	29.53	1131.77	1886.32	269.87	-1866.42	1888.17	278.23	0.19	MWD	6-axis
82	2399.55	69.12	277.90	28.66	1142.03	1913.04	273.30	-1892.96	1914.93	278.22	0.34	MWD	6-axis
83	2428.92	69.05	277.42	29.37	1152.51	1940.43	276.96	-1920.15	1942.37	278.21	0.15	MWD	6-axis
84	2457.83	69.47	277.99	28.91	1162.75	1967.43	280.59	-1946.94	1969.40	278.20	0.23	MWD	6-axis
85	2486.94	68.79	278.64	29.11	1173.12	1994.61	284.52	-1973.86	1956.60	278.20	0.31	MWD	6-axis
86	2515.88	67.38	279.85	28.94	1183.92	2021.45	288.83	-2000.36	2023.44	278.25	0.62	MWD	6-axis
87	2545.04	65.00	281.43	29.16	1195.70	2048.12	293.75	-2026.57	2050.09	278.25	0.95	MWD	6-axis
88	2573.83	62.39	283.61	28.79	1208.45	2073.92	299.34	-2051.76	2075.83	278.30	1.13	MWD	6-axis
89	2602.58	58.65	285.62	28.75	1222.60	2098.88	305.65	-2075.98	2100.70	278.38	1.44	MWD	6-axis
90	2631.33	56.13	286.51	28.75	1238.09	2122.99	312.35	-2099.25	2124.69	278.46	0.91	MWD	6-axis

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool qual type
91	2659.69	54.32	286.63	28.36	1254.27	2146.16	318.99	-2121.58	2147.75	278.55	0.64	MWD	6-axis
92	2688.71	53.11	287.55	29.02	1271.44	2169.41	325.86	-2143.93	2170.88	278.64	0.49	MWD	6-axis
93	2718.07	51.22	289.76	29.36	1289.45	2192.37	333.27	-2165.90	2193.72	278.75	0.88	MWD	6-axis
94	2746.79	49.16	290.96	28.72	1307.84	2214.12	340.94	-2186.59	2215.33	278.86	0.79	MWD	6-axis
95	2776.50	47.88	292.40	29.71	1327.52	2235.97	349.16	-2207.27	2237.03	278.99	0.56	MWD	6-axis
96	2805.24	46.70	293.44	28.74	1347.01	2256.61	357.39	-2226.72	2257.53	279.12	0.49	MWD	6-axis
97	2833.96	43.73	298.05	28.72	1367.25	2273.28	366.22	-2245.08	2277.05	279.26	1.54	MWD	6-axis
98	2862.50	42.39	302.54	28.54	1388.10	2294.63	376.03	-2261.90	2295.24	279.44	1.17	MWD	6-axis
99	2891.25	40.70	305.19	28.75	1409.62	2312.16	386.65	-2277.73	2312.61	279.63	0.85	MWD	6-axis
100	2920.00	38.59	306.07	28.75	1431.76	2328.80	397.33	-2292.64	2329.10	279.83	0.76	MWD	6-axis
101	2948.89	36.50	309.17	28.89	1454.67	2344.50	408.06	-2306.59	2344.68	280.03	0.97	MWD	6-axis
102	2977.95	33.86	311.42	29.06	1478.42	2359.06	418.88	-2319.36	2359.15	280.24	1.01	MWD	6-axis
103	3006.85	30.56	313.56	28.90	1502.87	2372.17	429.26	-2330.75	2372.30	280.44	1.21	MWD	6-axis
104	3036.40	27.10	314.14	29.55	1528.75	2384.11	439.10	-2341.04	2384.12	280.63	1.17	MWD	6-axis
105	3053.55	26.87	314.19	17.15	1544.03	2390.60	444.53	-2346.62	2390.60	280.73	0.13	MWD	6-axis
106	3075.00	26.61	314.25	21.45	1563.19	2398.65	451.26	-2353.54	2398.65	280.86	0.12	Projection	

Company: Esso Australia Ltd.

Well: TNA A-29

Field: Tuna

Rig: ISDL 453

Victoria

State: **victoria**

IDEAL services from **Anadrill**

**VISION Density Neutron
1:500 Measured Depth
Recorded Mode Log**

Schlumberger