

Bit Run Summary

Run number	1	2	3	4	5
Bit size	8.5	8.5	8.5	8.5	8.5
Bit start depth	1362.6	2243.0	2391.0	2637.0	2748.0
Bit end depth	2243.0	2391.0	2637.0	2748.0	2803.0
Top interval logged	1343.9	2224.9	2372.9	2618.9	2729.9
Bottom interval logged	2225.0	2372.9	2618.9	2729.9	2784.9
Begin log: time	08:00	7:45	4:30	17:38	23:00
Begin log: date	04-Sep-03 07-Sep-03 10-Sep-03 12-Sep-03 14-Sep-03				
End log: time	15:46	16:30	21:20	23:00	10:13
End log: date	07-Sep-03 09-Sep-03 11-Sep-03 13-Sep-03 15-Sep-03				
Mud data					
Depth	2239.0	2389.0	2637.0	2747.0	2800.0

Type		KCl/PHPA/Glycol	KCl/PHPA/Glycol	KCl/PHPA/Glycol	KCl/PHPA/Glycol	KCl/PHPA/Glycol					
Mud weight	ppg	9.55	9.4	9.55	9.55	9.45					
Solids	%wt	4.7	4.3	5.6	5.3	5.2					
Chlorides	mg/L	47,500	46,000	43,000	46,500	42,500					
Rm											
Rmf											
Rmc											
Potassium											
Environmental data											
GR											
Mud weight	ppg	9.55	9.4	9.55	9.55	9.45					
Bit size	in	8.5	8.5	8.5	8.5	8.5					
Resistivity											
Neutron porosity											
Hole Size											
Mud weight											
Temperature											
Mud salinity											
Formation salinity											
Recording rate 1	SEC										
Recording rate 2	SEC										
Filtering GR		3pt	3pt	3pt	3pt	3pt					
Filtering density											
Filtering Neutron											
Company representative		G.Campbell	B.Steel								
Anadrill personnel		J.Dolan	O.Radicevic	C.Soper	B.Manjenic	D.Hastie					

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.











OTHER SERVICES FOR RUN1	OTHER SERVICES FOR RUN2	OTHER SERVICES FOR RUN3
Gamma Ray Directional Drilling Directional Surveys	Gamma Ray Directional Drilling Directional Surveys	Gamma Ray Directional Drilling Directional Surveys
REMARKS: RUN NUMBER 1 8-1/2 in. hole was drilled from 1362.6m to 2243.0m. Depth is referenced to the Driller's Depth. Gamma Ray is corrected for Tool Size, Bit Size, and Mud Weight. Mud type is KCl/PHPA/Glycol. Gamma Ray logged behind casing to 1351m. POOH due to bit change.	REMARKS: RUN NUMBER 2 8-1/2 in. hole was drilled from 2243.0m to 2391.0m. Depth is referenced to the Driller's Depth. Gamma Ray is corrected for Tool Size, Bit Size, and Mud Weight. Mud type is KCl/PHPA/Glycol. POOH due to bit change.	REMARKS: RUN NUMBER 3 8-1/2 in. hole was drilled from 2391.0m to 2637.0m. Depth is referenced to the Driller's Depth. Gamma Ray is corrected for Tool Size, Bit Size, and Mud Weight. Mud type is KCl/PHPA/Glycol. POOH due to bit change.

Thank you for using Schlumberger.

7.9

DOWNHOLE EQ

DOWNHOLE E

6-3/4 in. Pow MDC: 06 MEC: 61 MDI: 62 MGR: 29 DH software:		23.06-3/4 in. Pow MDC: 06 MEC: 61 MDI: 62 MGR: 29 DH software:		23.0
D&I GR		D&I GR		
18.7 — 18.1		18.7 — 18.1		
6-1/2 in. P S/N:GS9		14.86-1/2 in. P S/N:GS9		14.8
6-1/8 in. NM S/N: DOTS Stab OD: 8		12.26-1/8 in. NM S/N: DOTS Stab OD: 8		12.2
6-1/2 in. P S/N: ANA9		10.66-1/2 in. P S/N: ANA9		10.6
6-3/4 in. Power A675XP S/N: 02 1.15 deg. 8-3/8 in. Moto		7.936-3/4 in. Power A675XP S/N: 02 1.15 deg. 8-3/8 in. Moto		7.93

Smith Inse

8-1/2 in

FG20 S/N: M

Maximum string diam
All lengths in



0.00 0.25

Smith Inse

8-1/2 in

GFi30 S/N: M

Maximum string diam
All lengths in



0.00 0.25

FLA-A2a RT 1:200MD

IDEAL Version: ID8_OC_07 <MD> Vertical Scale: 1:200

Graphics File Created: 15-Sep-2003 14:50

PIP SUMMARY



GR(TM) PIP


ROP*5 (ROP5)
(M/HR)

200 0

GR(TM) (GRM1)
(GAPI)


0 400






1375

1400




GRM1



1425

1450







ROP5



GRM1



1525



1550









































2250

2275









ROP5




GRM1




2550

2575




2600

2625






See Remarks for Run 4






2650

2675









SCHLUMBERGER

Survey report 15-Sep-2003 11:02:46 Page 1 of 3

Client.....: ESSO Australia
Field.....: FLA GDA 94

Well.....: FLA-A2a Spud date.....: 03-Sep-03
API number.....: Last survey date.....: 15-Sep-03
Engineer.....: J.Dolan/O.Radicevic/D.Hastie Total accepted surveys...: 54
MD of first survey.....: 1350.00 m
RIG.....: ISDL 453 MD of last survey.....: 2803.00 m
STATE.....: VICTORIA

----- Survey calculation methods -----

Method for positions.....: Minimum curvature Magnetic model.....: BGGM version 2002
Method for DLS.....: Mason & Taylor Magnetic date.....: 02-Sep-2003
Magnetic field strength...: 1200.85 HCNT

----- Depth reference -----

Permanent datum.....: Mean Sea Level Magnetic dec (+E/W-).....: 13.22 degrees
Depth reference.....: Driller's Pipe Tally Magnetic dip.....: -68.76 degrees
GL above permanent.....: -93.00 m
KB above permanent.....: -15240.00 m
DF above permanent.....: 33.85 m

----- MWD survey Reference Criteria -----

Reference G.....: 1000.03 mGal
Reference H.....: 1200.85 HCNT
Reference Dip.....: -68.76 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----

Magnetic dec (+E/W-).....: 13.22 degrees
Grid convergence (+E/W-).....: -0.89 degrees
Total az corr (+E/W-).....: 14.11 degrees
Azimuth from rotary table to target: 297.15 degrees (Total az corr = magnetic dec - grid conv)

Survey Correction Type ...:

- I=Sag Corrected Inclination
- M=Schlumberger Magnetic Correction
- S=Shell Magnetic Correction
- F=Failed Axis Correction
- R=Magnetic Resonance Tool Correction
- D=Dmag Magnetic Correction

Seq Measured Incl Azimuth Course TVD Vertical Displ Displ Total At DLS Srvy Tool
depth angle angle length depth section +N/S- +E/W- displ Azim (deg/ tool Corr
- (m) (deg) (deg) (m) (m) (m) (m) (m) (deg) 10m) type (deg)

1	1350.00	16.46	221.99	0.00	1307.62	62.86	-215.88	-179.26	280.60	219.71	1.57	TIP	None
2	1374.40	13.55	232.15	24.40	1331.19	64.95	-220.20	-183.83	286.85	219.86	4.81	GYR	None
3	1411.73	9.13	256.70	37.33	1367.80	69.06	-223.57	-190.17	293.51	220.38	5.19	MWD	None
4	1440.12	8.96	275.09	28.39	1395.85	72.82	-223.90	-194.57	296.62	220.99	3.05	MWD	None
5	1469.06	9.09	292.17	28.94	1424.43	77.19	-222.83	-198.93	298.71	221.76	2.77	MWD	None
6	1497.91	8.97	296.87	28.85	1452.92	81.71	-220.95	-203.05	300.08	222.58	0.78	MWD	None
7	1526.50	10.31	309.60	28.59	1481.11	86.44	-218.32	-207.01	300.86	223.48	2.63	MWD	None
8	1555.14	11.41	326.61	28.64	1509.25	91.41	-214.32	-210.54	300.43	224.49	3.53	MWD	None
9	1584.00	11.80	331.76	28.86	1537.52	96.32	-209.33	-213.51	299.01	225.57	1.15	MWD	None
10	1612.87	11.87	331.37	28.87	1565.77	101.21	-204.13	-216.33	297.43	226.66	0.11	MWD	None
11	1641.74	11.93	331.51	28.87	1594.02	106.12	-198.90	-219.18	295.97	227.78	0.07	MWD	None
12	1670.80	11.79	331.23	29.06	1622.46	111.06	-193.66	-222.04	294.62	228.91	0.16	MWD	None
13	1699.15	11.74	330.47	28.35	1650.22	115.87	-188.61	-224.85	293.48	230.01	0.17	MWD	None
14	1728.09	11.53	329.93	28.94	1678.56	120.76	-183.54	-227.75	292.51	231.14	0.25	MWD	None
15	1757.04	11.41	329.44	28.95	1706.94	125.62	-178.57	-230.66	291.71	232.25	0.16	MWD	None
16	1785.60	11.25	327.87	28.56	1734.94	130.40	-173.78	-233.58	291.13	233.35	0.36	MWD	None
17	1814.31	11.16	332.62	28.71	1763.10	135.07	-168.94	-236.34	290.52	234.44	0.97	MWD	None
18	1843.05	11.19	331.76	28.74	1791.30	139.63	-164.02	-238.94	289.82	235.53	0.18	MWD	None
19	1871.62	11.06	331.55	28.57	1819.33	144.17	-159.16	-241.56	289.28	236.62	0.14	MWD	None
20	1900.06	10.82	332.11	28.44	1847.25	148.61	-154.41	-244.11	288.84	237.69	0.28	MWD	None
21	1928.69	11.77	330.34	28.63	1875.33	153.26	-149.49	-246.81	288.55	238.80	1.06	MWD	None
22	1957.49	11.60	329.37	28.80	1903.53	158.17	-144.45	-249.74	288.51	239.95	0.27	MWD	None
23	1986.11	12.40	330.46	28.62	1931.53	163.17	-139.30	-252.72	288.57	241.14	0.87	MWD	None
24	2015.06	12.13	330.42	28.95	1959.82	168.31	-133.95	-255.75	288.71	242.36	0.28	MWD	None
25	2043.78	13.10	330.59	28.72	1987.84	173.55	-128.49	-258.84	288.98	243.60	1.01	MWD	None
26	2072.44	14.31	331.30	28.66	2015.68	179.19	-122.56	-262.14	289.37	244.94	1.28	MWD	None
27	2101.06	14.00	330.94	28.62	2043.44	184.99	-116.43	-265.52	289.92	246.32	0.34	MWD	None
28	2129.96	15.19	332.71	28.90	2071.40	190.98	-110.00	-268.95	290.58	247.75	1.32	MWD	None
29	2159.25	18.21	334.37	29.29	2099.46	197.75	-102.47	-272.69	291.31	249.41	3.13	MWD	None
30	2187.25	21.60	334.98	28.00	2125.78	205.30	-93.85	-276.77	292.24	251.27	3.64	MWD	None

[(c)2003 IDEAL ID8_OC_07]
SCHLUMBERGER Survey Report

15-Sep-2003 11:02:46

Page 3 of 3

Seq	Measured depth	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim (deg)	DLS (deg)	Srvy tool	Tool Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	10m)	type	(deg)	
31	2215.89	24.11	332.81	28.64	2152.17	214.22	-83.87	-281.67	293.89	253.42	2.77	MWD	None
32	2244.50	26.55	331.20	28.61	2178.03	224.27	-73.06	-287.42	296.56	255.74	2.66	MWD	None
33	2272.84	28.75	329.07	28.34	2203.13	235.30	-61.67	-293.98	300.37	258.15	2.55	MWD	None
34	2301.31	32.66	329.75	28.47	2227.60	247.59	-49.15	-301.37	305.35	260.74	4.14	MWD	None
35	2329.86	36.22	329.93	28.55	2251.15	261.18	-35.19	-309.48	311.47	263.51	3.74	MWD	None
36	2359.02	38.38	330.45	29.16	2274.34	275.99	-19.86	-318.26	318.88	266.43	2.25	MWD	None
37	2371.48	38.87	333.19	12.46	2284.07	282.50	-13.10	-322.11	322.19	267.69	1.24	MWD	None
38	2388.13	38.50	329.86	16.65	2297.07	291.24	-4.09	-327.31	326.91	269.32	0.76	MWD	None
39	2416.83	42.45	331.83	28.70	2318.90	306.73	12.18	-336.37	336.18	272.12	4.34	MWD	None
40	2445.44	43.87	331.98	28.61	2339.77	322.78	29.47	-345.55	346.44	274.91	1.52	MWD	None
41	2474.07	38.51	335.08	28.63	2361.31	337.94	46.34	-353.93	356.64	277.50	5.95	MWD	None
42	2502.61	38.45	335.48	28.54	2383.65	351.91	62.48	-361.36	366.41	279.85	0.27	MWD	None
43	2531.19	39.29	335.30	28.58	2405.90	365.99	78.78	-368.82	376.85	282.10	0.89	MWD	None
44	2559.97	39.87	335.27	28.78	2428.08	380.42	95.44	-376.49	388.12	284.26	0.60	MWD	None
45	2589.01	38.93	335.13	29.04	2450.52	394.93	112.17	-384.22	399.99	286.31	0.98	MWD	None
46	2616.01	39.31	334.73	27.00	2471.47	408.40	127.60	-391.44	411.45	288.09	0.51	MWD	None
47	2643.54	39.80	334.52	27.53	2492.70	422.31	143.44	-398.95	423.70	289.81	0.51	MWD	None
48	2675.58	40.05	334.10	32.04	2517.27	438.70	161.97	-407.87	438.61	291.70	0.34	MWD	None
49	2704.02	40.51	333.56	28.44	2538.97	453.44	178.47	-415.98	452.41	293.26	0.61	MWD	None
50	2726.90	40.71	333.58	22.88	2556.33	465.43	191.81	-422.61	463.87	294.45	0.26	MWD	None
51	2733.21	40.62	333.55	6.31	2561.12	468.74	195.49	-424.44	467.06	294.77	0.44	MWD	None
52	2761.16	39.98	333.49	27.95	2582.44	483.29	211.67	-424.44	481.30	296.12	0.69	MWD	None
53	2783.99	38.26	333.88	22.83	2600.15	494.87	224.58	-438.88	492.79	297.14	2.28	MWD	None
54	2803.00	37.00	334.20	19.01	2615.20	504.15	235.02	-443.97	502.12	297.93	2.01	Projection to TD	

[(c)2003 IDEAL ID8_OC_07]

Well: **FLA-A2a**
Field: **Flounder GDA 94**
Rig: **ISDL 453**
State: **VICTORIA**

Gamma Ray Service
1:200 Measured Depth
Real Time Log