



**EWB Electromagnetic Wave Resistivity**  
**DGR Dual Gamma Ray**

[illegible]

## WELL INFORMATION

<b>MWD Run Number</b>	100	200			
<b>Date run completed</b>	16-Dec-03	20-Dec-03			
<b>Rig Bit Number</b>	100	200			
<b>Bit Size (mm)</b>	311	216			
<b>Tool Nominal OD (mm)</b>	203	171			
<b>Log Start Depth (MD, m)</b>	777.00	1,810.00			
<b>Log End Depth (MD, m)</b>	1,810.00	2,575.00			
<b>Drill or Wipe</b>	Drilling	Drilling			
<b>Drill/Wipe Start Date and Time</b>	15-Dec-03 06:00	18-Dec-03 19:06			
<b>Drill/Wipe End Date and Time</b>	16-Dec-03 13:10	20-Dec-03 01:34			
<b>Min Inc (deg) @ Depth (MD, m)</b>	0.12 @ 787.46	0.12 @ 2,266.83			
<b>Max Inc (deg) @ Depth (MD, m)</b>	1.04 @ 1,569.90	0.88 @ 1,830.94			
<b>Bit TFA(in2) / Bit Type</b>	0.65 / HC-605	0.55 / DSX104-HGN			
<b>Flow Rate (gpm)</b>	860	650			
<b>Max AV (mpm) / CV (mpm) @ MWD</b>	82.2 / 127.4	49.9 / 141.7			
<b>Fluid Type</b>	KCI/PHPA	KCI/PHPA			
<b>Density (sg) / Viscosity (spl)</b>	1.1 / 42.3	1.1 / 74.0			
<b>Filtrate CL (ppm)</b>	37000	42000			
<b>pH / Fluid Loss (cptm)</b>	8.8 / 7.0	9.5 / 0.25			
<b>PV (cp) / YP (pa)</b>	16 / 11.5	23 / 16.7			
<b>% Solids / % Sand</b>	6 / 0.6	9.5 / 0.25			
<b>% Oil / Oil:Water Ratio</b>	N/A / N/A:100	N/A / N/A:100			
<b>Rm @ Measured Temp (degC)</b>	0.11 @ 18.00	0.08 @ 18.00			
<b>Rmf @ Measured Temp (degC)</b>	0.10 @ 18.00	0.06 @ 18.00			
<b>Rmc @ Measured Temp (degC)</b>	0.12 @ 18.00	0.12 @ 18.00			
<b>Max Tool Temp (degC) / Source</b>	52.00 / EWR P4	70.00 / EWR-P4			
<b>Rm @ Max Tool Temp (degC)</b>	0.06 @ 52.00	0.03 @ 70.00			
<b>Lead MWD Engineer</b>	T.Oborne	T.Oborne			
<b>Customer Representative</b>	G.Howard	G.Howard			



## SENSOR INFORMATION

### Downhole Processor Information

Tool Type	HCIM	HCIM			
Software Version	66.37	66.37			
Sub Serial Number	198839	197931			
Insert Serial Number	170439	191774			
Logging String Serial Number	DM90033559XHGR8	DM90033562XHGR6			
Date and Time Initialized	14-Dec-03 18:30	18-Dec-03 12:37			
Date and Time Read	16-Dec-03 21:59	20-Dec-03 18:34			

### Directional Sensor Information

Tool Type	DM	DM			
Distance From Bit (m)	16.02	11.06			
Software Version	3.15	3.15			
Sub Serial Number	N/A	N/A			
Sonde Serial Number	103286	185534			
Sensor ID Number	N/A	N/A			
Survey String Serial Number	DM90026201F8	N/A			
Toolface Offset (deg)	N/A	N/A			

### Gamma Ray Sensor Information

Tool Type	DGR	DGR			
Distance From Bit (m)	12.49	7.51			
Recorded Sample Period (sec)	12	12			
Software Version	N/A	N/A			
Sub Serial Number	196051	078523			
Insert/Sonde Serial Number	188554	016131			

### Resistivity Sensor Information

Tool Type	EWR-P4	EWR-P4			
Distance From Bit (m)	9.46	4.47			
Recorded Sample Period (sec)	12	12			
Software Version	1.38	1.38			
Sub Serial Number	96508	134751			
Receiver Insert Serial Number	77242	130937			
Transmitter Insert Serial Number	135158	123469			
Receiver Orientation	Down	Down			


## REMARKS

1. All depths are bit depths and referenced to the drillers pipe tally.
2. AV/CV is calculated at the MWD collar using the Power Law for water based muds and the Bingham's Plastic Law for oil based muds.
3. Curve mnemonics are :
  - SGRC - Smoothed Gamma Ray Combined, api
  - SEXP - Smoothed Extra Shallow Phase-Shift Derived Resistivity, ohm-m
  - SESP - Smoothed Shallow Phase-Shift Derived Resistivity, ohm-m
  - SEMP - Smoothed Medium Phase-Shift Derived Resistivity, ohm-m
  - SEDP - Smoothed Deep Phase-Shift Derived Resistivity, ohm-m
  - SROP - Smoothed Rate of Penetration, m/hr
  - SFXE - Smoothed Formation Exposure Time, hr
  - STEM - Smoothed EWR-P4 Temperature, Deg C
4. Mud system changed from sea water and Hi-Vis sweeps to KCl/PHPA at 1435.0 mMDRT.




# WARRANTY

HALLIBURTON ENERGY SERVICES (HES) WILL USE ITS BEST EFFORTS TO FURNISH CUSTOMERS WITH ACCURATE INFORMATION AND INTERPRETATIONS THAT ARE PART OF, AND INCIDENT TO, THE SERVICES PROVIDED. HOWEVER, HES CANNOT AND DOES NOT WARRANT THE ACCURACY OR CORRECTNESS OF SUCH INFORMATION AND INTERPRETATIONS. UNDER NO CIRCUMSTANCES SHOULD ANY SUCH INFORMATION OR INTERPRETATION BE RELIED UPON AS THE SOLE BASIS FOR ANY DRILLING, COMPLETION, PRODUCTION, OR FINANCIAL DECISION OR ANY PROCEDURE INVOLVING ANY RISK TO THE SAFETY OF ANY DRILLING VENTURE, DRILLING RIG OR ITS CREW OR ANY OTHER THIRD PARTY. THE CUSTOMER HAS FULL RESPONSIBILITY FOR ALL DRILLING, COMPLETION AND PRODUCTION OPERATION. HES MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE SERVICES RENDERED. IN NO EVENT WILL HES BE LIABLE FOR FAILURE TO OBTAIN ANY PARTICULAR RESULTS OR FOR ANY DAMAGES, INCLUDING, BUT NOT LIMITED TO, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES, RESULTING FROM THE USE OF ANY INFORMATION OR INTERPRETATION PROVIDED BY HES.







790

800

810



820

830

840












910

920



930

940


950












1020

1030


1040

1050


1060

















1190

1200


1210

1220


1230




































1580

1590


1600

1610

1620







1630

1640

1650



1660

1670


1680
































1970

1980


1990

2000


2010



























2250

2260


2270

2280


2290
















2410


2420

2430


2440

2450


2460

















**Hill-1**

<i>Measured Depth (metres)</i>	<i>Inclination (degrees)</i>	<i>Direction (degrees)</i>	<i>Vertical Depth (metres)</i>	<i>Latitude (metres)</i>	<i>Departure (metres)</i>	<i>Vertical Section (metres)</i>	<i>Dogleg (deg/30m)</i>
1107.140	0.72	9.97	1107.124	2.604 N	1.992 E	3.007	0.08
1162.240	0.83	10.31	1162.219	3.336 N	2.123 E	3.749	0.06
1191.380	0.96	20.31	1191.355	3.773 N	2.246 E	4.203	0.21
1222.780	0.96	24.23	1222.751	4.261 N	2.446 E	4.725	0.06
1248.550	0.97	35.16	1248.517	4.636 N	2.660 E	5.141	0.21
1280.630	0.93	40.57	1280.593	5.055 N	2.985 E	5.625	0.09
1309.300	0.84	37.96	1309.259	5.397 N	3.265 E	6.025	0.10
1339.100	0.93	39.70	1339.056	5.754 N	3.553 E	6.441	0.09
1394.960	0.89	36.10	1394.909	6.452 N	4.097 E	7.249	0.04
1455.710	0.92	32.58	1455.651	7.244 N	4.638 E	8.148	0.03
1483.050	1.02	32.83	1482.987	7.634 N	4.888 E	8.587	0.11
1510.370	1.03	29.55	1510.303	8.051 N	5.141 E	9.053	0.06
1538.700	1.01	27.64	1538.628	8.494 N	5.382 E	9.541	0.04
1569.900	1.04	13.43	1569.823	9.013 N	5.576 E	10.091	0.24
1627.360	1.04	9.82	1627.274	10.030 N	5.785 E	11.129	0.03
1655.580	0.87	5.35	1655.490	10.496 N	5.848 E	11.596	0.19
1685.810	0.94	10.68	1685.716	10.969 N	5.916 E	12.072	0.11
1712.120	0.96	9.64	1712.023	11.399 N	5.993 E	12.507	0.03
1745.900	0.99	6.48	1745.798	11.968 N	6.073 E	13.079	0.06
1772.730	0.77	353.39	1772.625	12.379 N	6.079 E	13.479	0.33
1791.400	0.69	348.35	1791.293	12.615 N	6.041 E	13.699	0.17
1830.940	0.88	326.25	1830.829	13.101 N	5.824 E	14.118	0.27
1856.750	0.78	329.33	1856.637	13.418 N	5.624 E	14.378	0.12
1918.200	0.81	316.68	1918.081	14.094 N	5.113 E	14.911	0.09
1944.220	0.66	306.66	1944.099	14.316 N	4.867 E	15.067	0.22
1973.450	0.62	331.70	1973.327	14.556 N	4.657 E	15.249	0.29
2002.660	0.61	346.23	2002.535	14.846 N	4.546 E	15.504	0.16
2031.420	0.65	345.22	2031.294	15.153 N	4.467 E	15.783	0.04
2059.750	0.63	337.25	2059.622	15.453 N	4.366 E	16.049	0.10
2089.980	0.79	349.72	2089.849	15.811 N	4.264 E	16.373	0.21
2122.030	0.73	341.38	2121.897	16.220 N	4.160 E	16.744	0.12
2151.020	0.47	3.16	2150.885	16.513 N	4.108 E	17.016	0.35
2179.660	0.45	356.67	2179.524	16.741 N	4.108 E	17.238	0.06
2206.860	0.38	7.86	2206.724	16.936 N	4.114 E	17.428	0.12
2237.900	0.14	43.04	2237.763	17.064 N	4.153 E	17.562	0.27
2266.830	0.12	51.65	2266.693	17.109 N	4.201 E	17.617	0.02
2323.770	0.31	195.67	2323.633	16.996 N	4.207 E	17.509	0.22
2352.550	0.50	187.16	2352.412	16.796 N	4.170 E	17.306	0.20
2382.660	0.57	188.78	2382.521	16.519 N	4.131 E	17.028	0.07
2412.010	0.59	186.72	2411.869	16.226 N	4.091 E	16.734	0.03
2440.800	0.65	189.72	2440.658	15.918 N	4.046 E	16.424	0.08
2470.120	0.64	190.52	2469.976	15.592 N	3.988 E	16.093	0.01
2498.180	0.66	197.21	2498.034	15.281 N	3.911 E	15.773	0.08
2524.200	0.70	194.84	2524.052	14.983 N	3.825 E	15.463	0.06
2553.310	0.86	204.43	2553.160	14.611 N	3.689 E	15.070	0.21
2575.000	0.86	204.43	2574.847	14.315 N	3.555 E	14.750	0.00



**CALCULATION BASED ON MINIMUM CURVATURE METHOD**

**SURVEY COORDINATES RELATIVE TO WELL SYSTEM REFERENCE POINT  
TVD VALUES GIVEN RELATIVE TO DRILLING MEASUREMENT POINT**


**VERTICAL SECTION RELATIVE TO WELL HEAD  
VERTICAL SECTION IS COMPUTED ALONG A CLOSURE OF 13.95 DEGREES (GRID)  
A TOTAL CORRECTION OF 11.01 DEG FROM MAGNETIC NORTH TO GRID NORTH HAS BEEN APPLIED**

**HORIZONTAL DISPLACEMENT IS RELATIVE TO THE WELL HEAD.  
HORIZONTAL DISPLACEMENT(CLOSURE) AT 2575.000 METRES  
IS 14.750 METRES ALONG 13.95 DEGREES (GRID)**

**MWD RUN 100 - BHA**
**MWD RUN 100 - MWD**

	Component Length (m)	Cumulative Length (m)		Sensor Measure Point Distance To Bit (m)
		257.71		
HWDP	113.330		Sub	
Cross Over Sub	1.100	144.38		
		143.28		
Drill Collar	9.510		Directional	
Cross Over Sub	8.190	133.77		
		125.58		
Drill Collar	27.610			
		97.97	Processor	
Drilling Jars	9.770			
		88.20		
Drill Collar	65.760			
		22.44	Gamma Ray	
	2.010			





MWD RUN 200 - BHA

MWD RUN 200 - MWD

