

Schlumberger

Company: **ESSO Australia Pty. Ltd.**

12.25 in. Section

Well: West Moonfish-1

Field: **Moonfish**

Rig: ENSCO 102

State:

Victoria

PowerPulse* Gamma Ray
1:500 Measured Depth
Real Time Log

Location	
Total depth:	2532.0 m
Spud date:	05-Jan-05
Runs:	2 To 4
Permanent datum:	Mean Sea Level
Log measured from:	Drill Floor
Depth reference:	Driller's Depth
	Elev.: 0.0 m
	39.24 m above Perm. datum

ENSCO 102

Moonfish

Bass Strait

West Moonfish-1

Company: ESSO Australia Pty. Ltd.

Service Order no.
ASQ-04-12

x = 585687.25m (East)
y = 5777075.49m (North)

Longitude	Latitude
E 147° 58' 40.63"	S 38° 09' 0.48"

Depth logged: 755.4 m To 2518

Mag decl: 13.04 deg

Other services:

Date logged: 11-Jan-05 To 19-Jan-05

Mag dip: -68.70 deg

Directional Drilling, D&I Survey

Bore hole record				Casing record			
Hole size	from	to	Size	Density	from	to	
26.0 in.	Surface	160.0 m	20 in.	94.0 lb/ft	Surface	156.3 m	
17.5 in.	160.0 m	761.0 m	13.3/75 in.		Surface	755.4 m	
12.25 in.	761.0 m	2532.0 m					

Surface equipment		Software record		
Unit	OLU-JA-9602	IDEAL w/s	ID9_1C_01	
Depth system	PDA - DES-DA	SPM	hspm9_2c_08	
		LWD	N/A	
		MWD	V7.0c00	

























Bit Run Summary

Run number		2	3	4							
Bit size	in.	12.25	12.25	12.25							
Bit start depth	m	761.0	1737.0	2073.0							
Bit end depth	m	1737.0	2073.0	2532.0							
Top interval logged	m	755.4	1717.2	2053.2							
Bottom interval logged	m	1717.2	2053.2	2518.8							
Begin log: time		11:34	22:10	23:00							
Begin log: date			14-Jan-05	17-Jan-05							
End log: time		11:51	08:25	09:22							
End log: date		14-Jan-05	17-Jan-05	19-Jan-05							
Mud data											
Depth	m	1538.0	2037.0	2442.0							
Type		KCL/PHPA/Glycol	KCL/PHPA/Glycol	KCL/PHPA/Glycol							
Mud weight	ppg	9.5	9.65	9.75							
Solids	%	4.0	6.0	6.7							
Chlorides	mg/L	36500	42000	42000							
Rm	Ohm.m	N/A	N/A	N/A							
Rmf	Ohm.m	N/A	N/A	N/A							
Rmc	Ohm.m	N/A	N/A	N/A							


Potassium	%	7.0	7.0	7.0							
Environmental data											
GR											
Mud weight	ppg	9.5	9.65	9.75							
Bit size	in.	12.25	12.25	12.25							
Resistivity											
Neutron porosity											
Hole Size	in.	N/A	N/A	N/A							
Mud weight	ppg	N/A	N/A	N/A							
Temperature	°C	N/A	N/A	N/A							
Mud salinity	ppk	N/A	N/A	N/A							
Formation salinity											
Recording rate 1	SEC	8 sec.	8 sec.	8 sec.							
Recording rate 2	SEC	N/A	N/A	N/A							
Filtering GR		3 pt.	3 pt.	3 pt.							
Filtering density		N/A	N/A	N/A							
Filtering Neutron		N/A	N/A	N/A							
Company representative		R. Morris	G. Sharkey								
Anadrill personnel		J. Dolan	M. Y. Tan	C. Soper	D. Hay						


<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
OTHER SERVICES FOR RUN2 Directional Drilling D&I Survey Gamma Ray	OTHER SERVICES FOR RUN3 Directional Drilling D&I Survey Gamma Ray	OTHER SERVICES FOR RUN4 Directional Drilling D&I Survey Gamma Ray
REMARKS: RUN NUMBER 2 12 1/4 in. hole section was drilled from 761.0 m to 1737.0 m. Depth is referenced to Driller's Depth. All data presented was acquired in Real Time. GR corrected for Mud Weight, Tool and Bit Size. Mud type is KCL/PHPA/Glycol. Barite was present in the mud system. POOH at 1737.0 m to change bit. Intermittent loss of GR data caused by tool problems with flow rates. Thank you for choosing Schlumberger.	REMARKS: RUN NUMBER 3 12 1/4 in. hole section was drilled from 1737.0 m to 2073.0 m. Depth is referenced to Driller's Depth. All data presented was acquired in Real Time. GR corrected for Mud Weight, Tool and Bit Size. Mud type is KCL/PHPA/Glycol. Barite was present in the mud system. POOH at 2073.0 m to change bit. Thank you for choosing Schlumberger.	REMARKS: RUN NUMBER 4 12 1/4 in. hole section was drilled from 2073.0 m to 2532.0 m. Depth is referenced to Driller's Depth. All data presented was acquired in Real Time. GR corrected for Mud Weight, Tool and Bit Size. Mud type is KCL/PHPA/Glycol. Barite was present in the mud system. POOH at 2532.0 m due to section TD. Thank you for choosing Schlumberger.



EQUIPMENT DESCRIPTION		
RUN2	RUN3	RUN4

DOWNHOLE EQUIPMENT			DOWNHOLE EQUIPMENT			DOWNHOLE EQUIPMENT		
8–1/4 in. PowerPulse*		24.75	8 1/4 in. PowerPulse*		24.70	8–1/4 in. PowerPulse*		19.17
MDC 23326 MEC 612BB MDI 626BC MGR 295AA Software: V7.0C00			MDC 883 MEC 212BA MDI 1096BC MGR 503AA Software: V7.0C00			MDC 883 MEC 212BA MDI 1096BC MGR 503AA Software: V7.0C00		
D&I		20.44	D&I		20.41			
GR		19.80	GR		19.77			
8–1/4 in. NM Pony Collar		16.30	8–1/4 in. NM Pony Collar		16.30			
S/N: 6893C			S/N: 6893C					
11–7/8 in. Stabilizer		13.63	11–7/8 in. Stabilizer		13.63	8–1/4 in. NM Pony Collar		10.77
S/N: 6403			S/N: 6403			S/N: 6893C		
8 in. Float Sub		11.14	8 in. Float Sub		11.14	AnderGauge Stabilizer		8.10
S/N: ASQ990301			S/N: ASQ990301			OD 11–1/2 – 12–1/4 in S/N: S13–056		
PowerPak* Mud Motor		10.04	PowerPak* Mud Motor		10.04	8–1/4 in. NM Pony Collar		4.76
A962XP S/N: N7225 1.15 deg Bend 12–1/8 in. Motor Sleeve			A962XP S/N: N7225 1.15 deg Bend 12–1/8 in. Motor Sleeve			S/N: 7505		
Reed–Hycalog PDC Bit		0.00	Hughes Insert Bit		0.00	12–3/16 in. Near Bit Stabilizer		2.08
RHX192 S/N: 206985 OD 12–1/4 in.		0.33	MX20DX S/N: 6017688 OD 12–1/4 in.		0.33	S/N: DOTS3214		
Reed–Hycalog PDC Bit		0.00	Reed–Hycalog PDC Bit		0.00			0.25
RSX162 S/N: 206982 OD 12–1/4 in.								
Maximum string diameter 12.25 in. All lengths in Meters			Maximum string diameter 12.25 in. All lengths in Meters			Maximum string diameter 12.25 in. All lengths in Meters		

West Moonfish-1 RT 1:500MD








1050


1100




1150

1200

1250



Intermittent GR Between 889 – 1711 m. See Remarks.



1300

Intermittent GR Between 889 – 1711 m. See Remarks.

1350

Intermittent GR Between 889 – 1711 m. See Remarks.

1400

Intermittent GR Between 889 – 1711 m. See Remarks.


Handwritten green scribbles at the top of the page.



Handwritten green scribbles in the upper middle section.


Handwritten green scribbles in the middle section.

Handwritten green scribbles in the lower middle section.

Handwritten green scribbles at the bottom of the page.









1700



1750


1800













2300

2350





SCHLUMBERGER

Survey report

19-Jan-2005 20:58:52

Page 1 of 4

Client.....: ESSO Australia Pty. Ltd.
 Field.....: Moonfish

Well.....: West Moonfish-1
 API number.....:
 Engineer.....: J.Dolan / M.Y.Tan

Rig.....: ENSCO 102
 STATE.....: Victoria

Spud date.....: 05-Jan-05
 Last survey date.....: 19-Jan-05
 Total accepted surveys...: 86
 MD of first survey.....: 0.00 m
 MD of last survey.....: 2532.00 m

----- Survey calculation methods-----
 Method for positions.....: Minimum curvature
 Method for DLS.....: Mason & Taylor

----- Depth reference -----
 Permanent datum.....: Mean Sea Level
 Depth reference.....: Driller's Depth
 GL above permanent.....: -52.12 m
 KB above permanent.....: Top Drive
 DF above permanent.....: 39.24 m

----- Vertical section origin-----
 Latitude (+N/S-).....: 0.00 m
 Departure (+E/W-).....: 0.00 m

----- Platform reference point-----
 Latitude (+N/S-).....: 0.00 m
 Departure (+E/W-).....: 0.00 m

Azimuth from Vsect Origin to target: 171.73 degrees

----- Geomagnetic data -----
 Magnetic model.....: BGGM version 2004
 Magnetic date.....: 08-Jan-2005
 Magnetic field strength...: 1199.31 HCNT
 Magnetic dec (+E/W-).....: 13.04 degrees
 Magnetic dip.....: -68.70 degrees

----- MWD survey Reference Criteria -----
 Reference G.....: 1000.02 mGal
 Reference H.....: 1199.31 HCNT
 Reference Dip.....: -68.70 degrees
 Tolerance of G.....: (+/-) 2.50 mGal
 Tolerance of H.....: (+/-) 6.00 HCNT
 Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
 Magnetic dec (+E/W-).....: 13.04 degrees
 Grid convergence (+E/W-)..: -0.60 degrees
 Total az corr (+E/W-).....: 13.64 degrees
 (Total az corr = magnetic dec - grid conv)
 Survey Correction Type ...:
 I=Sag Corrected Inclination
 M=Schlumberger Magnetic Correction
 S=Shell Magnetic Correction
 F=Failed Axis Correction
 R=Magnetic Resonance Tool Correction
 D=Dmag Magnetic Correction

[(c)2005 IDEAL ID9_1C_01]
 SCHLUMBERGER Survey Report

19-Jan-2005 20:58:52

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool Corr (deg)
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	TIP	None
2	91.00	0.00	0.00	91.00	91.00	0.00	0.00	0.00	0.00	0.00	0.00	MWD_M	None
3	181.88	0.35	328.21	90.88	181.88	-0.25	0.24	-0.15	0.28	328.21	0.04	MWD	None
4	209.79	0.46	330.61	27.91	209.79	-0.44	0.41	-0.25	0.47	328.78	0.04	MWD	None
5	238.18	0.46	334.44	28.39	238.18	-0.65	0.61	-0.35	0.70	329.99	0.01	MWD	None
6	266.14	0.41	322.98	27.96	266.14	-0.85	0.79	-0.46	0.91	329.77	0.04	MWD	None
7	294.58	0.45	330.64	28.44	294.58	-1.04	0.97	-0.58	1.13	329.25	0.02	MWD	None
8	323.45	0.47	319.47	28.87	323.45	-1.25	1.16	-0.71	1.36	328.51	0.03	MWD	None
9	352.76	0.37	334.57	29.31	352.75	-1.44	1.33	-0.83	1.57	328.19	0.05	MWD	None
10	381.80	0.35	324.72	29.04	381.79	-1.61	1.49	-0.92	1.75	328.35	0.02	MWD	None
11	411.24	0.31	328.91	29.44	411.23	-1.76	1.63	-1.01	1.92	328.21	0.02	MWD	None
12	440.44	0.31	306.16	29.20	440.43	-1.89	1.75	-1.12	2.07	327.41	0.04	MWD	None
13	469.19	0.35	319.12	28.75	469.18	-2.02	1.86	-1.24	2.23	326.36	0.03	MWD	None
14	498.06	0.33	320.27	28.87	498.05	-2.16	1.99	-1.35	2.40	325.89	0.01	MWD	None
15	526.97	0.37	310.22	28.91	526.96	-2.30	2.11	-1.47	2.58	325.15	0.03	MWD	None
16	555.67	0.28	328.64	28.70	555.66	-2.44	2.23	-1.58	2.74	324.74	0.05	MWD	None
17	584.65	0.30	319.14	28.98	584.64	-2.57	2.35	-1.67	2.88	324.69	0.02	MWD	None
18	613.64	0.26	310.54	28.99	613.63	-2.68	2.45	-1.77	3.02	324.24	0.02	MWD	None
19	642.62	0.21	308.91	28.98	642.61	-2.77	2.53	-1.86	3.14	323.70	0.02	MWD	None
20	671.64	0.18	340.56	29.02	671.63	-2.85	2.60	-1.91	3.23	323.69	0.04	MWD	None
21	700.59	0.24	324.48	28.95	700.58	-2.95	2.70	-1.96	3.34	323.93	0.03	MWD	None
22	716.66	0.28	343.92	16.07	716.65	-3.02	2.76	-1.99	3.41	324.17	0.06	MWD	None
23	760.72	0.35	341.43	44.06	760.71	-3.26	2.99	-2.07	3.64	325.37	0.02	MWD	None
24	789.81	0.37	350.28	29.09	789.80	-3.44	3.17	-2.11	3.81	326.33	0.02	MWD	None
25	818.90	0.39	345.99	29.09	818.89	-3.63	3.36	-2.15	3.99	327.36	0.01	MWD	None
26	848.10	0.45	351.62	29.20	848.09	-3.85	3.57	-2.19	4.19	328.44	0.02	MWD	None
27	877.05	0.38	344.38	28.95	877.04	-4.05	3.77	-2.23	4.38	329.37	0.03	MWD	None
28	906.37	0.28	0.58	29.32	906.36	-4.22	3.94	-2.26	4.54	330.16	0.05	MWD	None
29	935.33	0.35	12.98	28.96	935.32	-4.37	4.09	-2.24	4.67	331.33	0.03	MWD	None
30	964.33	0.27	17.88	29.00	964.31	-4.52	4.25	-2.20	4.78	332.63	0.03	MWD	None

[(c)2005 IDEAL ID9_1C_01]
 SCHLUMBERGER Survey Report

19-Jan-2005 20:58:52

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool Corr (deg)
31	992.58	0.29	13.91	28.25	992.56	-4.64	4.38	-2.16	4.88	333.74	0.01	MWD	None

32	1021.76	0.36	9.73	29.18	1021.74	-4.80	4.54	-2.13	5.01	334.90	0.03	MWD	None
33	1050.63	0.30	18.15	28.87	1050.61	-4.95	4.70	-2.09	5.14	336.06	0.03	MWD	None
34	1079.82	0.33	13.33	29.19	1079.80	-5.10	4.86	-2.04	5.27	337.17	0.01	MWD	None
35	1108.59	0.28	27.98	28.77	1108.57	-5.23	5.00	-1.99	5.38	338.27	0.03	MWD	None
36	1137.86	0.28	33.98	29.27	1137.84	-5.34	5.12	-1.92	5.47	339.46	0.01	MWD	None
37	1166.83	0.29	28.94	28.97	1166.81	-5.46	5.24	-1.84	5.56	340.63	0.01	MWD	None
38	1195.74	0.29	56.71	28.91	1195.72	-5.54	5.35	-1.75	5.63	341.91	0.05	MWD	None
39	1224.73	0.34	48.47	28.99	1224.71	-5.62	5.45	-1.62	5.68	343.42	0.02	MWD	None
40	1253.76	0.28	53.99	29.03	1253.74	-5.70	5.54	-1.50	5.74	344.86	0.02	MWD	None
41	1282.95	0.28	76.24	29.19	1282.93	-5.74	5.60	-1.37	5.77	346.23	0.04	MWD	None
42	1312.43	0.35	69.81	29.48	1312.41	-5.77	5.65	-1.22	5.78	347.83	0.03	MWD	None
43	1341.45	0.49	75.67	29.02	1341.43	-5.80	5.71	-1.02	5.80	349.92	0.05	MWD	None
44	1370.44	0.54	77.71	28.99	1370.42	-5.82	5.77	-0.76	5.82	352.48	0.02	MWD	None
45	1399.38	0.57	80.90	28.94	1399.36	-5.83	5.82	-0.49	5.84	355.23	0.01	MWD	None
46	1428.34	0.57	72.23	28.96	1428.31	-5.86	5.89	-0.21	5.90	357.99	0.03	MWD	None
47	1457.45	0.71	75.91	29.11	1457.42	-5.90	5.98	0.11	5.98	1.02	0.05	MWD	None
48	1486.39	0.67	81.34	28.94	1486.36	-5.92	6.05	0.45	6.07	4.23	0.03	MWD	None
49	1515.33	0.64	84.68	28.94	1515.30	-5.91	6.09	0.78	6.14	7.26	0.02	MWD	None
50	1544.31	0.58	114.39	28.98	1544.28	-5.83	6.04	1.07	6.14	10.04	0.11	MWD	None
51	1573.33	0.68	130.93	29.02	1573.30	-5.62	5.87	1.33	6.02	12.80	0.07	MWD	None
52	1602.43	0.81	124.83	29.10	1602.39	-5.35	5.64	1.63	5.87	16.15	0.05	MWD	None
53	1630.64	0.88	126.64	28.21	1630.60	-5.06	5.40	1.97	5.74	20.06	0.03	MWD	None
54	1659.72	0.73	120.96	29.08	1659.68	-4.78	5.17	2.31	5.66	24.07	0.06	MWD	None
55	1688.54	0.77	115.92	28.82	1688.49	-4.56	4.99	2.64	5.64	27.89	0.03	MWD	None
56	1716.29	1.42	170.03	27.75	1716.24	-4.11	4.57	2.87	5.39	32.12	0.42	MWD	None
57	1747.14	3.39	168.14	30.85	1747.06	-2.82	3.30	3.12	4.54	43.41	0.64	MWD	None
58	1776.39	6.07	175.23	29.25	1776.21	-0.41	0.91	3.43	3.55	75.11	0.94	MWD	None
59	1803.97	9.73	177.60	27.58	1803.52	3.37	-2.87	3.65	4.64	128.22	1.33	MWD	None
60	1833.36	13.39	175.76	29.39	1832.31	9.23	-8.75	4.00	9.62	155.42	1.25	MWD	None
[(c) 2005 IDEAL ID9_1C_01]													
SCHLUMBERGER Survey Report													
19-Jan-2005 20:58:52													
Page 4 of 4													
Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
61	1863.43	16.85	168.96	30.07	1861.34	17.06	-16.50	5.09	17.27	162.84	1.29	MWD	None
62	1892.32	20.05	169.00	28.89	1888.74	26.19	-25.47	6.84	26.38	164.97	1.11	MWD	None
63	1921.31	23.60	171.03	28.99	1915.65	36.96	-36.09	8.70	37.12	166.45	1.25	MWD	None
64	1950.39	26.42	171.08	29.08	1942.00	49.26	-48.23	10.61	49.38	167.60	0.97	MWD	None
65	1980.01	28.74	171.62	29.62	1968.25	62.97	-61.79	12.67	63.07	168.42	0.79	MWD	None
66	2008.88	30.11	172.21	28.87	1993.40	77.15	-75.83	14.66	77.24	169.06	0.49	MWD	None
67	2037.15	31.81	172.17	28.27	2017.64	91.69	-90.24	16.64	91.76	169.55	0.60	MWD	None
68	2051.91	33.50	172.13	14.76	2030.06	99.66	-98.13	17.72	99.72	169.76	1.15	MWD	None
69	2066.15	33.78	171.23	14.24	2041.92	107.55	-105.93	18.87	107.60	169.90	0.40	MWD	None
70	2095.12	33.12	171.96	28.97	2066.09	123.51	-121.73	21.20	123.56	170.12	0.27	MWD	None
71	2124.15	33.36	172.51	29.03	2090.37	139.43	-137.50	23.35	139.47	170.36	0.13	MWD	None
72	2153.24	33.01	172.88	29.09	2114.72	155.35	-153.29	25.38	155.38	170.60	0.14	MWD	None
73	2181.81	32.54	173.18	28.56	2138.73	170.80	-168.64	27.25	170.82	170.82	0.17	MWD	None
74	2210.92	31.59	173.23	29.12	2163.41	186.26	-183.99	29.08	186.27	171.02	0.33	MWD	None
75	2240.12	31.28	173.54	29.20	2188.32	201.48	-199.11	30.84	201.49	171.20	0.12	MWD	None
76	2268.93	31.04	173.24	28.81	2212.98	216.38	-213.92	32.55	216.38	171.35	0.10	MWD	None
77	2298.13	31.01	173.23	29.20	2238.00	231.42	-228.87	34.32	231.43	171.47	0.01	MWD	None
78	2327.14	30.80	172.89	29.01	2262.89	246.32	-243.66	36.12	246.32	171.57	0.09	MWD	None
79	2356.90	30.47	172.50	29.76	2288.50	261.48	-258.70	38.05	261.48	171.63	0.13	MWD	None
80	2385.70	30.69	172.74	28.80	2313.29	276.13	-273.23	39.93	276.13	171.68	0.09	MWD	None
81	2414.71	30.89	172.94	29.01	2338.21	290.98	-287.96	41.78	290.98	171.74	0.08	MWD	None
82	2443.86	30.53	172.62	29.15	2363.27	305.86	-302.73	43.66	305.86	171.79	0.14	MWD	None
83	2472.51	30.38	172.52	28.65	2387.97	320.38	-317.13	45.53	320.38	171.83	0.06	MWD	None
84	2500.10	30.49	173.16	27.59	2411.76	334.36	-331.00	47.28	334.36	171.87	0.12	MWD	None
85	2513.76	30.10	173.67	13.66	2423.55	341.24	-337.84	48.07	341.25	171.90	0.34	MWD	None
86	2532.00	30.10	173.70	18.24	2439.33	350.39	-346.94	49.07	350.39	171.95	0.01	Projection To CSG Point	
[(c) 2005 IDEAL ID9_1C_01]													

Company:

ESSO Australia Pty. Ltd.

Schlumberger

Well:

West Moonfish–1

Field:

Moonfish

Rig:

ENSCO 102

12.25 in. Section

State:

Victoria

PowerPulse* Gamma Ray

1:500 Measured Depth

Real Time Log

