

Bit Run Summary

Type		KCL/PHPA/Glycol	KCL/PHPA/Glycol								
Mud weight	ppg	10.0	10.0								
Solids	%	7.1	7.1								
Chlorides	mg/L	31000	31000								
Rm	ohm.m@°C	0.14@24.1	0.14@24.1								
Rmf	ohm.m@°C	0.12@23.5	0.12@23.5								
Rmc	ohm.m@°C	0.23@24.5	0.23@24.5								
Potassium	%	6.0	6.0								
Environmental data											
GR											
Mud weight	ppg	10.0	10.0								
Bit size	in.	8.5	8.5								
Resistivity											
Neutron porosity											
Hole Size	in.	8.5	8.5								
Mud weight	ppg	10.0	10.0								
Temperature	°C	70.6	70.6								
Mud salinity	ppm	45746	45746								
Formation salinity											
Recording rate 1	SEC	10 sec.	10 sec.								
Recording rate 2	SEC	10 sec.	10 sec.								
Filtering GR		3 pt.	3 pt.								
Filtering density		3 pt.	3 pt.								
Filtering Neutron		3 pt.	3 pt.								
Company representative		B. Steel	M. Jackson	A. Bassett							
Anadrill personnel		K. Handley	M. Y. Tan	R. Burns	K. Wilson	D. Hay					

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN2 Directional Drilling D&I Survey	OTHER SERVICES FOR RUN3 Directional Drilling D&I Survey	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 2 8-1/2 in. hole section was drilled from 851.0 m to 2108.0 m. Depth is referenced to Driller's Depth. All data presented is from tool memory. GR corrected for mud weight, tool and bit size. GVR*6 resistivity is corrected for bit size, mud resistivity and borehole temperature. Neutron porosity is calculated with a limestone matrix and is corrected for bit size, borehole salinity, temperature and mud hydrogen index. Ultrasonic Caliper not available during sliding intervals.	REMARKS: RUN NUMBER 3 8-1/2 in. hole section was reamed from 1570.0 m to 1625.0 m. Depth is referenced to Driller's Depth. All data presented is from tool memory. GR corrected for mud weight, tool and bit size. GVR*6 resistivity is corrected for bit size, mud resistivity and borehole temperature. Neutron porosity is calculated with a limestone matrix and is corrected for bit size, borehole salinity, temperature and mud hydrogen index. PEF readings were affected by the presence of Barite in the mud system.	REMARKS: RUN NUMBER

sliding intervals.

PEF readings were affected by the presence of Barite in the mud system.

Data density compromised at high ROP.

POOH due to drill plug.

Barite in the mud system.

POOH to change BHA.

EQUIPMENT DESCRIPTION



RUN2


RUN3

RUN

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT





IDEAL Version: ID8_0C_07
IDF

Format: GeoVISION Density Neutron Log

Vertical Scale: 1:500

Graphics File Created: 07-Mar-2005 12:28

PIP SUMMARY

Neutron Samples

Density Samples

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)
100 (M/HR) 0

RAB Gamma Ray (GR_RAB)
0 (GAPI) 200

Vertical Hole Diameter (VERD)
6 (IN) 16

Horizontal Hole Diameter (HORD)
6 (IN) 16

Density Time After Bit (TAB_DEN)
0 (HR) 10

ADN
Rotational
Speed
(RPM_ADN)
(RPM)
200 0

Gas Area
From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH




Thermal Neutron Porosity (TNPH)
45 (PU) -15



Bulk Density, Bottom (ROBB)
1.85 (G/C3) 2.85



Bulk Density (RHOB)
1.85 (G/C3) 2.85



Photoelectric Factor, Bottom (PEB)
0 (----) 10



Bulk Density Correction, Bottom
(DRHB)
(G/C3)
-0.75 0.25





































Density Time After Bit (TAB_DEN)
(HR)

Horizontal Hole Diameter (HORD)
(IN)

Vertical Hole Diameter (VERD)
(IN)



ADN
Rotational
Speed
(RPM_ADN)
(RPM)



Photoelectric Factor, Bottom (PEB)
(-----)

Bulk Density Correction, Bottom
(DRHB)
(G/C3)

Bulk Density (RHOB)
(G/C3)

Bulk Density, Bottom (ROBB)
(G/C3)

RAB Gamma Ray (GR_RAB)		
0	(GAPI)	200
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)		
100	(M/HR)	0

Thermal Neutron Porosity (TNPH)		
45	(PU)	-15
Gas Area		
From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH		

PIP SUMMARY		
Density Samples		Neutron Samples
IDEAL Version: ID8_OC_07		
IDF		

6.75-in. Azimuthal Density Neutron / Equipment Identification		
Primary Equipment:		
Tool Name and Serial Number	ADN6 - CA	FE55
Collar Type and Serial Number	ADDC - AA	FE53
Chassis Type and Serial Number	ADSE - EA	380
Neutron Logging Source	NSR - M	202
Density Logging Source	GSR - J/Z	1994
Stabilizer Size	8.25 - in.	
Calibration Status	Valid	

















Master: 4-Jan-2005 21:40				
6.75-in. Azimuthal Density Neutron Calibration				
Density: Magnesium Block				
Phase	LS window 3 - Mg CPS	Value	Phase	SS window 1 - Mg CPS
Master		1041	Master	
250.0	4125	8000	700.0	9350
(Minimum)	(Nominal)	(Maximum)	(Minimum)	(Nominal)


Master: 4-Jan-2005 21:40				
6.75-in. Azimuthal Density Neutron Calibration				
Density: Aluminum Block				
Phase	LS window 3 - Al CPS	Value	Phase	SS window 1 - Al CPS
Master		156.5	Master	
50.00	725.0	1400	500.0	4250
(Minimum)	(Nominal)	(Maximum)	(Minimum)	(Nominal)

Master: 4-Jan-2005 21:40				
6.75-in. Azimuthal Density Neutron Calibration				
Density: Background				
Phase	LS window 3 - Background CPS	Value	Phase	SS window 1 - Background CPS
Master		51.03	Master	
15.00	82.50	150.0	40.00	220.0
(Minimum)	(Nominal)	(Maximum)	(Minimum)	(Nominal)




Master: 4-Jan-2005 21:40				
6.75-in. Azimuthal Density Neutron Calibration				
Density: Water Block Check				
Phase	Long spacing water density G/C3	Value	Phase	Short spacing water density G/C3
Master		1.029	Master	
1.024	1.039	1.054	1.096	1.126
(Minimum)	(Nominal)	(Maximum)	(Minimum)	(Nominal)

Master: 4-Jan-2005 21:40				
6.75-in. Azimuthal Density Neutron Calibration				
Neutron: Water Tank				
Phase	For 1 tube 1 gain	Value	Phase	For 1 tube 1 offset CPS

Phase	Far 1 tube 1 gain	Value	Phase	Far 1 tube 1 offset CPS	Value
Master		1.068	Master		0.06511
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Far 1 tube 2 gain	Value	Phase	Far 1 tube 2 offset CPS	Value
Master		1.013	Master		-0.03114
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Far 1 tube 3 gain	Value	Phase	Far 1 tube 3 offset CPS	Value
Master		1.039	Master		0.01313
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Far 2 tube 1 gain	Value	Phase	Far 2 tube 1 offset CPS	Value
Master		1.096	Master		0.07837
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Far 2 tube 2 gain	Value	Phase	Far 2 tube 2 offset CPS	Value
Master		0.9974	Master		-0.1285
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Far 2 tube 3 gain	Value	Phase	Far 2 tube 3 offset CPS	Value
Master		1.042	Master		0.1064
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-1.000 (Minimum) 0 (Nominal) 1.000 (Maximum)	
Phase	Near 1 tube 1 gain	Value	Phase	Near 1 tube 1 offset CPS	Value
Master		0.9812	Master		-40.77
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-100.0 (Minimum) 0 (Nominal) 100.0 (Maximum)	
Phase	Near 2 tube 1 gain	Value	Phase	Near 2 tube 1 offset CPS	Value
Master		0.9674	Master		-32.21
	0.8000 (Minimum) 1.050 (Nominal) 1.300 (Maximum)			-100.0 (Minimum) 0 (Nominal) 100.0 (Maximum)	

Master: 4-Jan-2005 21:40		
6.75-in. Azimuthal Density Neutron Calibration		
Neutron: Water Block Check		
Phase	Far Neutron water porosity PU	Value
Master		103.2
	90.00 (Minimum) 100.0 (Nominal) 125.0 (Maximum)	

6.75-in. Resistivity At-the-Bit / Equipment Identification			
Primary Equipment:			
Tool Name and Serial Number		RAB6 – CA	191
Calibration Status		Valid	

Master: 28-Jan-2005 18:29								
6.75-in. Resistivity At-the-Bit Calibration								
Resistivity: Fixture								
Phase	Ring/T1 factor	Value	Phase	Ring/T2 factor	Value	Phase	M0/T1 factor	Value
Master		0.0007	Master		0.0010	Master		1.007

Master		0.9967	Master		0.9942	Master		1.007
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	M0/T2 factor	Value	Phase	M2/T1 factor	Value	Phase	M2/T2 factor	Value
Master		1.004	Master		1.007	Master		1.004
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	BTN shallow/T1 factor	Value	Phase	BTN shallow/T2 factor	Value	Phase	BTN medium/T1 factor	Value
Master		1.003	Master		0.9999	Master		0.9950
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	BTN medium/T2 factor	Value	Phase	BTN deep/T1 factor	Value	Phase	BTN deep/T2 factor	Value
Master		0.9919	Master		1.012	Master		1.009
0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)

Master: 28-Jan-2005 18:29		
6.75-in. Resistivity At-the-Bit Calibration		
Gamma Ray: Blanket		
Phase	Gamma ray factor	Value
Master		0.9256
0.7500 (Minimum)	1.000 (Nominal)	1.250 (Maximum)

SCHLUMBERGER

Survey report

6-Mar-2005 15:10:58

Page 1 of 4

Client..... ESSO
Field..... Barracouta

Well..... BTA-A4A
API number.....
Engineer..... K.Handley, M.Y.Tan, R.Burns
Rig:..... ENSCO 102
STATE:..... Victoria

Spud date..... 24-Feb-05
Last survey date..... 06-Mar-05
Total accepted surveys... 63
MD of first survey..... 344.00 m
MD of last survey..... 2108.00 m

----- Survey calculation methods-----
Method for positions..... Minimum curvature
Method for DLS..... Mason & Taylor

----- Geomagnetic data -----
Magnetic model..... BGGM version 2004
Magnetic date..... 22-Feb-2005
Magnetic field strength... 1201.43 HCNT
Magnetic dec (+E/W-)..... 12.97 degrees
Magnetic dip..... -68.87 degrees

----- Depth reference -----
Permanent datum..... Mean Sea Level
Depth reference..... Driller's Depth
GL above permanent..... -45.70 m
KB above permanent..... Top Drive
DF above permanent..... 56.00 m

----- MWD survey Reference Criteria -----
Reference G..... 1000.03 mGal
Reference H..... 1201.43 HCNT
Reference Dip..... -68.87 degrees
Tolerance of G..... (+/-) 2.50 mGal
Tolerance of H..... (+/-) 6.00 HCNT
Tolerance of Dip..... (+/-) 0.45 degrees

----- Vertical section origin-----
Latitude (+N/S-)..... 0.85 m
Departure (+E/W-)..... 8.53 m

----- Platform reference point-----
Latitude (+N/S-)..... -304.57 m
Departure (+E/W-)..... -304.57 m

----- Corrections -----
Magnetic dec (+E/W-)..... 12.97 degrees
Grid convergence (+E/W-).. -0.42 degrees
Total az corr (+E/W-)..... 13.39 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

Azimuth from Vsect Origin to target: 76.22 degrees

[(c)2005 IDEAL ID9_1C_02]
SCHLUMBERGER Survey Report

6-Mar-2005 15:10:58

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr
1	344.00	0.25	235.37	0.00	343.99	0.73	0.55	9.36	9.38	86.64	0.00	TIP	None
2	351.60	3.14	130.65	7.60	351.59	0.84	0.40	9.50	9.51	87.56	4.23	GYR	None
3	371.56	6.26	115.73	16.06	371.48	2.00	0.42	10.00	10.01	88.22	1.67	GYR	None

3	371.30	6.20	115.73	19.90	371.40	2.00	-0.42	10.90	10.91	92.23	1.07	MWD	None
4	400.60	10.44	98.23	29.04	400.21	5.66	-1.49	14.93	15.01	95.69	1.67	GYR	None
5	430.00	13.39	92.42	29.40	428.97	11.40	-2.01	20.97	21.07	95.48	1.08	MWD	None
6	458.41	16.35	82.38	28.41	456.43	18.54	-1.62	28.22	28.27	93.29	1.38	MWD	None
7	487.44	19.21	75.25	29.03	484.08	27.38	0.14	36.90	36.90	89.79	1.24	MWD	None
8	516.58	22.78	75.14	29.14	511.28	37.82	2.80	46.99	47.07	86.58	1.23	MWD	None
9	545.52	27.31	73.86	28.94	537.49	50.06	6.09	58.79	59.10	84.09	1.58	MWD	None
10	574.63	31.33	72.34	29.11	562.87	64.29	10.24	72.42	73.14	81.95	1.40	MWD	None
11	603.86	34.81	75.42	29.23	587.36	80.22	14.65	87.74	88.95	80.52	1.32	MWD	None
12	632.38	38.27	75.46	28.52	610.27	97.19	18.92	104.17	105.88	79.71	1.21	MWD	None
13	661.80	41.30	75.07	29.42	632.87	116.01	23.71	122.38	124.65	79.04	1.03	MWD	None
14	691.10	45.16	74.90	29.30	654.22	136.07	28.91	141.76	144.67	78.47	1.32	MWD	None
15	719.99	48.91	74.32	28.89	673.90	157.20	34.52	162.13	165.77	77.98	1.31	MWD	None
16	749.12	52.83	74.48	29.13	692.28	179.78	40.59	183.89	188.32	77.55	1.35	MWD	None
17	778.33	56.53	75.07	29.21	709.17	203.61	46.85	206.89	212.13	77.24	1.28	MWD	None
18	806.73	58.42	75.06	28.40	724.44	227.54	53.02	230.02	236.05	77.02	0.67	MWD	None
19	826.51	60.05	75.43	19.78	734.56	244.54	57.35	246.46	253.04	76.90	0.84	MWD	None
20	857.08	60.11	75.02	30.57	749.80	271.03	64.11	272.08	279.53	76.74	0.12	MWD	None
21	885.76	61.34	74.96	28.68	763.83	296.04	70.58	296.24	304.53	76.60	0.43	MWD	None
22	914.88	60.95	74.82	29.12	777.88	321.54	77.23	320.86	330.03	76.47	0.14	MWD	None
23	943.53	60.68	75.21	28.65	791.85	346.55	83.70	345.03	355.03	76.36	0.15	MWD	None
24	972.56	59.77	76.43	29.03	806.27	371.74	89.87	369.45	380.23	76.33	0.48	MWD	None
25	1001.50	59.54	77.10	28.94	820.89	396.72	95.59	393.77	405.20	76.35	0.22	MWD	None
26	1030.64	59.11	76.93	29.14	835.76	421.78	101.22	418.19	430.26	76.39	0.16	MWD	None
27	1059.78	57.85	76.77	29.14	850.99	446.61	106.87	442.38	455.10	76.42	0.43	MWD	None
28	1089.10	58.34	76.70	29.32	866.49	471.50	112.59	466.60	479.99	76.43	0.17	MWD	None
29	1118.03	59.62	78.08	28.93	881.39	496.29	118.00	490.80	504.78	76.48	0.60	MWD	None
30	1147.18	61.65	77.56	29.15	895.69	521.68	123.36	515.63	530.18	76.55	0.71	MWD	None

[(c)2005 IDEAL ID9_1C_02]
SCHLUMBERGER Survey Report

6-Mar-2005 15:10:58

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
31	1176.44	62.74	77.42	29.26	909.34	547.56	128.96	540.89	556.06	76.59	0.37	MWD	None
32	1205.78	63.29	77.18	29.34	922.65	573.70	134.71	566.40	582.20	76.62	0.20	MWD	None
33	1234.53	63.22	77.02	28.75	935.59	599.37	140.44	591.43	607.87	76.64	0.06	MWD	None
34	1263.41	63.32	74.80	28.88	948.58	625.16	146.72	616.44	633.66	76.61	0.69	MWD	None
35	1292.28	62.74	73.74	28.87	961.67	650.88	153.70	641.21	659.37	76.52	0.38	MWD	None
36	1321.68	61.29	72.83	29.40	975.47	676.80	161.16	666.07	685.29	76.40	0.56	MWD	None
37	1350.51	60.59	72.52	28.83	989.47	701.95	168.67	690.13	710.44	76.27	0.26	MWD	None
38	1379.66	60.36	72.02	29.15	1003.84	727.26	176.39	714.29	735.75	76.13	0.17	MWD	None
39	1408.57	60.11	72.24	28.91	1018.19	752.29	184.09	738.18	760.78	76.00	0.11	MWD	None
40	1437.70	60.53	73.72	29.13	1032.61	777.56	191.50	762.37	786.06	75.90	0.46	MWD	None
41	1466.67	60.32	73.21	28.97	1046.91	802.72	198.67	786.53	811.23	75.82	0.17	MWD	None
42	1494.99	59.98	74.68	28.32	1061.01	827.27	205.46	810.13	835.78	75.77	0.47	MWD	None
43	1524.16	60.08	76.01	29.17	1075.58	852.53	211.85	834.58	861.05	75.76	0.40	MWD	None
44	1553.56	60.34	75.95	29.40	1090.19	878.05	218.04	859.33	886.56	75.76	0.09	MWD	None
45	1582.31	59.93	76.35	28.75	1104.50	902.98	224.00	883.54	911.49	75.77	0.19	MWD	None
46	1611.11	60.27	75.83	28.80	1118.86	927.95	230.01	907.77	936.46	75.78	0.20	MWD	None
47	1640.37	60.83	76.43	29.26	1133.25	953.42	236.11	932.51	961.94	75.79	0.26	MWD	None
48	1669.37	61.92	76.44	29.00	1147.14	978.88	242.08	957.25	987.39	75.81	0.38	MWD	None
49	1697.95	61.74	77.55	28.58	1160.63	1004.07	247.75	981.80	1012.58	75.84	0.35	MWD	None
50	1727.34	61.10	76.95	29.39	1174.69	1029.88	253.45	1006.98	1038.38	75.87	0.28	MWD	None
51	1756.52	60.74	76.03	29.18	1188.87	1055.38	259.41	1031.77	1063.88	75.89	0.30	MWD	None
52	1785.84	61.68	75.81	29.32	1202.99	1081.07	265.66	1056.69	1089.58	75.89	0.33	MWD	None
53	1814.73	60.60	74.63	28.89	1216.94	1106.37	272.11	1081.16	1114.88	75.87	0.52	MWD	None
54	1843.93	59.17	75.44	29.20	1231.59	1131.62	278.63	1105.56	1140.13	75.85	0.55	MWD	None
55	1873.01	60.22	75.24	29.08	1246.26	1156.72	284.99	1129.85	1165.24	75.84	0.37	MWD	None
56	1901.51	60.30	75.12	28.50	1260.40	1181.47	291.32	1153.77	1189.98	75.83	0.05	MWD	None
57	1930.50	59.14	74.53	28.99	1275.02	1206.49	297.87	1177.93	1215.01	75.81	0.44	MWD	None
58	1959.59	60.04	74.44	29.09	1289.74	1231.57	304.58	1202.11	1240.09	75.78	0.31	MWD	None
59	1988.62	60.66	73.85	29.03	1304.10	1256.78	311.47	1226.37	1265.31	75.75	0.28	MWD	None
60	2017.48	61.16	73.65	28.86	1318.14	1281.98	318.53	1250.59	1290.51	75.71	0.18	MWD	None

[(c)2005 IDEAL ID9_1C_02]
SCHLUMBERGER Survey Report

6-Mar-2005 15:10:58

Page 4 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
61	2046.69	59.38	74.45	29.21	1332.62	1307.32	325.50	1274.97	1315.87	75.68	0.65	MWD	None
62	2075.98	59.44	74.58	29.29	1347.53	1332.52	332.24	1299.27	1341.08	75.66	0.04	MWD	None
63	2108.00	59.44	74.48	32.02	1363.81	1360.08	339.59	1325.84	1368.64	75.63	0.03	Projection to TD	

[(c)2005 IDEAL ID9_1C_02]

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **BTA-A4A**

Field: **Barracouta**

Rig: **ENSCO 102**

8.5 in. Section

State: **Victoria**

**GeoVISION Density Neutron
1:500 Measured Depth
Recorded Mode Log**