

Bit Run Summary

Type		KCL/PHPA/Glycol	KCL/PHPA/Glycol								
Mud weight	ppg	10.0	10.0								
Solids	%	7.1	7.1								
Chlorides	mg/L	31000	31000								
Rm	ohm.m@°C	0.14@24.1	0.14@24.1								
Rmf	ohm.m@°C	0.12@23.5	0.12@23.5								
Rmc	ohm.m@°C	0.23@24.5	0.23@24.5								
Potassium	%	6.0	6.0								
Environmental data											
GR											
Mud weight	ppg	10.0	10.0								
Bit size	in.	8.5	8.5								
Resistivity											
Neutron porosity											
Hole Size	in.	8.5	8.5								
Mud weight	ppg	10.0	10.0								
Temperature	°C	70.6	70.6								
Mud salinity	ppm	45746	45746								
Formation salinity											
Recording rate 1	SEC	10 sec.	10 sec.								
Recording rate 2	SEC	10 sec.	10 sec.								
Filtering GR		3 pt.	3 pt.								
Filtering density		3 pt.	3 pt.								
Filtering Neutron		3 pt.	3 pt.								
Company representative		B. Steel	M. Jackson	A. Bassett							
Anadrill personnel		K. Handley	M. Y. Tan	R. Burns	K. Wilson	D. Hay					

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN2 Directional Drilling D&I Survey	OTHER SERVICES FOR RUN3 Directional Drilling D&I Survey	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 2 8-1/2 in. hole section was drilled from 851.0 m to 2108.0 m. Depth is referenced to Driller's Depth. All data presented is from tool memory. GR corrected for mud weight, tool and bit size. GVR*6 resistivity is corrected for bit size, mud resistivity and borehole temperature. Neutron porosity is calculated with a limestone matrix and is corrected for bit size, borehole salinity, temperature and mud hydrogen index. Ultrasonic Caliper not available during sliding intervals.	REMARKS: RUN NUMBER 3 8-1/2 in. hole section was reamed from 1570.0 m to 1625.0 m. Depth is referenced to Driller's Depth. All data presented is from tool memory. GR corrected for mud weight, tool and bit size. GVR*6 resistivity is corrected for bit size, mud resistivity and borehole temperature. Neutron porosity is calculated with a limestone matrix and is corrected for bit size, borehole salinity, temperature and mud hydrogen index. PEF readings were affected by the presence of Barite in the mud system.	REMARKS: RUN NUMBER

sliding intervals.

PEF readings were affected by the presence of Barite in the mud system.

Data density compromised at high ROP.

POOH due to drill plug.

Barite in the mud system.

POOH to change BHA.


EQUIPMENT DESCRIPTION

RUN2


RUN3







RUN


DOWNHOLE EQUIPMENT








DOWNHOLE EQUIPMENT




<p>PowerPak* Mud Motor A700GT S/N: 7062 1.15 deg Bend 8-3/8 in. Motor Sleeve</p>  <p>Reed Hycalog PDC Bit RSX272 S/N: 110936 OD 8-1/2 in.</p>  <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>6-3/4 in. NM Pony Collar S/N: SBD1651</p>  <p>8-1/4 in. Stabilizer S/N: S11773</p>  <p>6-13/16 in. Bit Sub S/N: E102-25</p>  <p>Reed Hycalog PDC Bit DSX210GUW S/N: 110575 OD 8-1/2 in.</p>  <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>9.18</p> <p>3.08</p> <p>1.22</p> <p>0.30</p>
--	--	---














850
TVD

875
TVD















950
TVD





975
TVD

















TVD

1225
TVD



1250
TVD






1275
TVD


1300
TVD





1325
TVD

1350
TVD





PIP SUMMARY	
- Density Samples	
IDEAL Version: ID8_0C_07 IDF	
True Vertical Depth Log	

Master: 4-Jan-2005 21:40											
6.75-in. Azimuthal Density Neutron Calibration											
Density: Magnesium Block											
Phase	LS window 3 – Mg CPS		Value	Phase	SS window 1 – Mg CPS		Value	Phase	SS window 3 – Mg CPS		Value
Master	<div></div>		1041	Master	<div></div>		2505	Master	<div></div>		6228


250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)	700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)	2500 (Minimum)	23750 (Nominal)	45000 (Maximum)
--------------------	-------------------	-------------------	--------------------	-------------------	--------------------	-------------------	--------------------	--------------------


Master: 4-Jan-2005 21:40														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				156.5	Master				1275	Master				3922
	50.00	725.0	1400		500.0	4250	8000		1500	15750	30000			
	(Minimum)	(Nominal)	(Maximum)		(Minimum)	(Nominal)	(Maximum)		(Minimum)	(Nominal)	(Maximum)			

Master: 4-Jan-2005 21:40														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Background														
Phase	LS window 3 – Background		CPS	Value	Phase	SS window 1 – Background		CPS	Value	Phase	SS window 3 – Background		CPS	Value
Master				51.03	Master				129.8	Master				563.0
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	













Master: 4-Jan-2005 21:40									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Water Block Check									
Phase	Long spacing water density G/C3		Value	Phase	Short spacing water density G/C3		Value		
Master			1.029	Master			1.116		
	1.024 (Minimum)	1.039 (Nominal)	1.054 (Maximum)		1.096 (Minimum)	1.126 (Nominal)	1.156 (Maximum)		


Master: 4-Jan-2005 21:40									
6.75-in. Azimuthal Density Neutron Calibration									
Neutron: Water Tank									
Phase	Far 1 tube 1 gain		Value	Phase	Far 1 tube 1 offset CPS		Value		
Master			1.068	Master			0.06511		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Far 1 tube 2 gain		Value	Phase	Far 1 tube 2 offset CPS		Value		
Master			1.013	Master			-0.03114		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Far 1 tube 3 gain		Value	Phase	Far 1 tube 3 offset CPS		Value		
Master			1.039	Master			0.01313		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Far 2 tube 1 gain		Value	Phase	Far 2 tube 1 offset CPS		Value		
Master			1.096	Master			0.07837		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Far 2 tube 2 gain		Value	Phase	Far 2 tube 2 offset CPS		Value		
Master			0.9974	Master			-0.1285		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Far 2 tube 3 gain		Value	Phase	Far 2 tube 3 offset CPS		Value		
Master			1.042	Master			0.1064		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-1.000 (Minimum)	0 (Nominal)	1.000 (Maximum)		
Phase	Near 1 tube 1 gain		Value	Phase	Near 1 tube 1 offset CPS		Value		
Master			0.9812	Master			-40.77		
	0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)		-100.0 (Minimum)	0 (Nominal)	100.0 (Maximum)		
Phase	Near 2 tube 1 gain		Value	Phase	Near 2 tube 1 offset CPS		Value		

Master		0.9674	Master		-32.21
0.8000 (Minimum)	1.050 (Nominal)	1.300 (Maximum)	-100.0 (Minimum)	0 (Nominal)	100.0 (Maximum)

Master: 4-Jan-2005 21:40					
6.75-in. Azimuthal Density Neutron Calibration					
Neutron: Water Block Check					
Phase	Far Neutron water porosity PU				Value
Master					103.2
	90.00 (Minimum)	100.0 (Nominal)	125.0 (Maximum)		

6.75-in. Resistivity At-the-Bit / Equipment Identification					
Primary Equipment:					
Tool Name and Serial Number			RAB6 - CA	191	
Calibration Status			Valid		

Master: 28-Jan-2005 18:29											
6.75-in. Resistivity At-the-Bit Calibration											
Resistivity: Fixture											
Phase	Ring/T1 factor		Value	Phase	Ring/T2 factor		Value	Phase	M0/T1 factor		Value
Master			0.9967	Master			0.9942	Master			1.007
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	M0/T2 factor		Value	Phase	M2/T1 factor		Value	Phase	M2/T2 factor		Value
Master			1.004	Master			1.007	Master			1.004
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	BTN shallow/T1 factor		Value	Phase	BTN shallow/T2 factor		Value	Phase	BTN medium/T1 factor		Value
Master			1.003	Master			0.9999	Master			0.9950
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)
Phase	BTN medium/T2 factor		Value	Phase	BTN deep/T1 factor		Value	Phase	BTN deep/T2 factor		Value
Master			0.9919	Master			1.012	Master			1.009
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)		0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)

Master: 28-Jan-2005 18:29					
6.75-in. Resistivity At-the-Bit Calibration					
Gamma Ray: Blanket					
Phase	Gamma ray factor				Value
Master					0.9256
	0.7500 (Minimum)	1.000 (Nominal)	1.250 (Maximum)		

Client.....: ESSO
Field.....: Barracouta

Well.....: BTA-A4A
API number.....
Engineer.....: K.Handley, M.Y.Tan, R.Burns

Rig.....: ENSCO 102
STATE.....: Victoria

Spud date.....: 24-Feb-05
Last survey date.....: 06-Mar-05
Total accepted surveys....: 63
MD of first survey.....: 344.00 m
MD of last survey.....: 2108.00 m

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's Depth
GL above permanent.....: -45.70 m
KB above permanent.....: Top Drive
DF above permanent.....: 56.00 m

----- Vertical section origin-----
Latitude (+N/S-).....: 0.85 m
Departure (+E/W-).....: 8.53 m

----- Platform reference point-----
Latitude (+N/S-).....: -304.57 m
Departure (+E/W-).....: -304.57 m

Azimuth from Vsect Origin to target: 76.22 degrees

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2004
Magnetic date.....: 22-Feb-2005
Magnetic field strength...: 1201.43 HCNT
Magnetic dec (+E/W-).....: 12.97 degrees
Magnetic dip.....: -68.87 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.03 mGal
Reference H.....: 1201.43 HCNT
Reference Dip.....: -68.87 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 12.97 degrees
Grid convergence (+E/W-)..: -0.42 degrees
Total az corr (+E/W-).....: 13.39 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2005 IDEAL ID9_1C_02]
SCHLUMBERGER Survey Report

6-Mar-2005 15:10:58

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
1	344.00	0.25	235.37	0.00	343.99	0.73	0.55	9.36	9.38	86.64	0.00	TIP	None
2	351.60	3.14	130.65	7.60	351.59	0.84	0.40	9.50	9.51	87.56	4.23	GYR	None
3	371.56	6.26	115.73	19.96	371.48	2.00	-0.42	10.90	10.91	92.23	1.67	MWD	None
4	400.60	10.44	98.23	29.04	400.21	5.66	-1.49	14.93	15.01	95.69	1.67	GYR	None
5	430.00	13.39	92.42	29.40	428.97	11.40	-2.01	20.97	21.07	95.48	1.08	MWD	None
6	458.41	16.35	82.38	28.41	456.43	18.54	-1.62	28.22	28.27	93.29	1.38	MWD	None
7	487.44	19.21	75.25	29.03	484.08	27.38	0.14	36.90	36.90	89.79	1.24	MWD	None
8	516.58	22.78	75.14	29.14	511.28	37.82	2.80	46.99	47.07	86.58	1.23	MWD	None
9	545.52	27.31	73.86	28.94	537.49	50.06	6.09	58.79	59.10	84.09	1.58	MWD	None
10	574.63	31.33	72.34	29.11	562.87	64.29	10.24	72.42	73.14	81.95	1.40	MWD	None
11	603.86	34.81	75.42	29.23	587.36	80.22	14.65	87.74	88.95	80.52	1.32	MWD	None
12	632.38	38.27	75.46	28.52	610.27	97.19	18.92	104.17	105.88	79.71	1.21	MWD	None
13	661.80	41.30	75.07	29.42	632.87	116.01	23.71	122.38	124.65	79.04	1.03	MWD	None
14	691.10	45.16	74.90	29.30	654.22	136.07	28.91	141.76	144.67	78.47	1.32	MWD	None
15	719.99	48.91	74.32	28.89	673.90	157.20	34.52	162.13	165.77	77.98	1.31	MWD	None
16	749.12	52.83	74.48	29.13	692.28	179.78	40.59	183.89	188.32	77.55	1.35	MWD	None
17	778.33	56.53	75.07	29.21	709.17	203.61	46.85	206.89	212.13	77.24	1.28	MWD	None
18	806.73	58.42	75.06	28.40	724.44	227.54	53.02	230.02	236.05	77.02	0.67	MWD	None
19	826.51	60.05	75.43	19.78	734.56	244.54	57.35	246.46	253.04	76.90	0.84	MWD	None
20	857.08	60.11	75.02	30.57	749.80	271.03	64.11	272.08	279.53	76.74	0.12	MWD	None
21	885.76	61.34	74.96	28.68	763.83	296.04	70.58	296.24	304.53	76.60	0.43	MWD	None
22	914.88	60.95	74.82	29.12	777.88	321.54	77.23	320.86	330.03	76.47	0.14	MWD	None
23	943.53	60.68	75.21	28.65	791.85	346.55	83.70	345.03	355.03	76.36	0.15	MWD	None
24	972.56	59.77	76.43	29.03	806.27	371.74	89.87	369.45	380.23	76.33	0.48	MWD	None
25	1001.50	59.54	77.10	28.94	820.89	396.72	95.59	393.77	405.20	76.35	0.22	MWD	None
26	1030.64	59.11	76.93	29.14	835.76	421.78	101.22	418.19	430.26	76.39	0.16	MWD	None
27	1059.78	57.85	76.77	29.14	850.99	446.61	106.87	442.38	455.10	76.42	0.43	MWD	None
28	1089.10	58.34	76.70	29.32	866.49	471.50	112.59	466.60	479.99	76.43	0.17	MWD	None
29	1118.03	59.62	78.08	28.93	881.39	496.29	118.00	490.80	504.78	76.48	0.60	MWD	None
30	1147.18	61.65	77.56	29.15	895.69	521.68	123.36	515.63	530.18	76.55	0.71	MWD	None

[(c)2005 IDEAL ID9_1C_02]
SCHLUMBERGER Survey Report

6-Mar-2005 15:10:58

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
31	1176.44	62.74	77.42	29.26	909.34	547.56	128.96	540.89	556.06	76.59	0.37	MWD	None
32	1205.78	63.29	77.18	29.34	922.65	573.70	134.71	566.40	582.20	76.62	0.20	MWD	None
33	1234.53	63.22	77.02	28.75	935.59	599.37	140.44	591.43	607.87	76.64	0.06	MWD	None
34	1263.41	63.32	74.80	28.88	948.58	625.16	146.72	616.44	633.66	76.61	0.69	MWD	None
35	1292.20	63.74	72.74	28.97	961.67	650.90	152.70	641.21	659.27	76.52	0.20	MWD	None

35	1222.28	62.74	73.74	28.87	901.87	650.88	133.70	841.21	639.37	76.32	0.38	MWD	None
36	1321.68	61.29	72.83	29.40	975.47	676.80	161.16	666.07	685.29	76.40	0.56	MWD	None
37	1350.51	60.59	72.52	28.83	989.47	701.95	168.67	690.13	710.44	76.27	0.26	MWD	None
38	1379.66	60.36	72.02	29.15	1003.84	727.26	176.39	714.29	735.75	76.13	0.17	MWD	None
39	1408.57	60.11	72.24	28.91	1018.19	752.29	184.09	738.18	760.78	76.00	0.11	MWD	None
40	1437.70	60.53	73.72	29.13	1032.61	777.56	191.50	762.37	786.06	75.90	0.46	MWD	None
41	1466.67	60.32	73.21	28.97	1046.91	802.72	198.67	786.53	811.23	75.82	0.17	MWD	None
42	1494.99	59.98	74.68	28.32	1061.01	827.27	205.46	810.13	835.78	75.77	0.47	MWD	None
43	1524.16	60.08	76.01	29.17	1075.58	852.53	211.85	834.58	861.05	75.76	0.40	MWD	None
44	1553.56	60.34	75.95	29.40	1090.19	878.05	218.04	859.33	886.56	75.76	0.09	MWD	None
45	1582.31	59.93	76.35	28.75	1104.50	902.98	224.00	883.54	911.49	75.77	0.19	MWD	None
46	1611.11	60.27	75.83	28.80	1118.86	927.95	230.01	907.77	936.46	75.78	0.20	MWD	None
47	1640.37	60.83	76.43	29.26	1133.25	953.42	236.11	932.51	961.94	75.79	0.26	MWD	None
48	1669.37	61.92	76.44	29.00	1147.14	978.88	242.08	957.25	987.39	75.81	0.38	MWD	None
49	1697.95	61.74	77.55	28.58	1160.63	1004.07	247.75	981.80	1012.58	75.84	0.35	MWD	None
50	1727.34	61.10	76.95	29.39	1174.69	1029.88	253.45	1006.98	1038.38	75.87	0.28	MWD	None
51	1756.52	60.74	76.03	29.18	1188.87	1055.38	259.41	1031.77	1063.88	75.89	0.30	MWD	None
52	1785.84	61.68	75.81	29.32	1202.99	1081.07	265.66	1056.69	1089.58	75.89	0.33	MWD	None
53	1814.73	60.60	74.63	28.89	1216.94	1106.37	272.11	1081.16	1114.88	75.87	0.52	MWD	None
54	1843.93	59.17	75.44	29.20	1231.59	1131.62	278.63	1105.56	1140.13	75.85	0.55	MWD	None
55	1873.01	60.22	75.24	29.08	1246.26	1156.72	284.99	1129.85	1165.24	75.84	0.37	MWD	None
56	1901.51	60.30	75.12	28.50	1260.40	1181.47	291.32	1153.77	1189.98	75.83	0.05	MWD	None
57	1930.50	59.14	74.53	28.99	1275.02	1206.49	297.87	1177.93	1215.01	75.81	0.44	MWD	None
58	1959.59	60.04	74.44	29.09	1289.74	1231.57	304.58	1202.11	1240.09	75.78	0.31	MWD	None
59	1988.62	60.66	73.85	29.03	1304.10	1256.78	311.47	1226.37	1265.31	75.75	0.28	MWD	None
60	2017.48	61.16	73.65	28.86	1318.14	1281.98	318.53	1250.59	1290.51	75.71	0.18	MWD	None
[(c)2005 IDEAL ID9_1C_02]													
SCHLUMBERGER Survey Report													
6-Mar-2005 15:10:58							Page		4 of 4				
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
Seq	Measured	Incl	Azimuth	Course	TVD	Vertical	Displ	Displ	Total	At	DLS	Srvy	Tool
#	depth	angle	angle	length	depth	section	+N/S-	+E/W-	displ	Azim	(deg/	tool	Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(m)	(deg)	10m)	type	(deg)
===	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
61	2046.69	59.38	74.45	29.21	1332.62	1307.32	325.50	1274.97	1315.87	75.68	0.65	MWD	None
62	2075.98	59.44	74.58	29.29	1347.53	1332.52	332.24	1299.27	1341.08	75.66	0.04	MWD	None
63	2108.00	59.44	74.48	32.02	1363.81	1360.08	339.59	1325.84	1368.64	75.63	0.03	Projection to TD	
[(c)2005 IDEAL ID9_1C_02]													

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **BTA-A4A**

Field: **Barracouta**

Rig: **ENSCO 102**

8.5 in. Section

State: **Victoria**

**GeoVISION Quadrant Density
1:200 True Vertical Depth
Recorded Mode Log**

