

Bit Run Summary

Type		Petrofree SBM									
Mud weight	ppg	10.05									
Solids	%	13.3									
Chlorides	mg/L	204100									
Rm	ohm.m@°C	n/a									
Rmf	ohm.m@°C	n/a									
Rmc	ohm.m@°C	n/a									
Potassium	%	0.0									
Environmental data											
GR											
Mud weight	ppg	10.05									
Bit size	in.	8.5									
Resistivity											
Neutron porosity											
Hole Size	in.	8.5									
Mud weight	ppg	10.05									
Temperature	°C	120.0									
Mud salinity	ppm	27227									
Formation salinity											
Recording rate 1	SEC	5 sec.									
Recording rate 2	SEC	5 sec.									
Filtering GR		3 pt.									
Filtering density		3 pt.									
Filtering Neutron		3 pt.									
Company representative	B. Steel	T. Paltridge	R. Bain								
Schlumberger D&M Personnel	J. Dolan	M. Y. Tan	D. Hastie	T. Auger	C. Soper	B. Hanson					

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN2

Xceed* RSS
D&I Survey

REMARKS: RUN NUMBER 2

8-1/2 in. hole section was drilled from 845.0 m to 4955.0 m.

Depth is referenced to Driller's Depth.

All data presented is from tool memory.

GR corrected for mud weight, tool and bit size.

ARC*6 resistivity is corrected for bit size, mud resistivity and borehole temperature.

Neutron porosity is calculated with a limestone matrix and is corrected for bit size, borehole salinity, temperature and mud hydrogen index.

PEF readings were affected by the presence of Barite in the mud system.

Caliper data spikes are due to stick and slip while drilling.

Mud type is Petrofree SBM.

POOH due to TD.

EQUIPMENT DESCRIPTION

RUN2

DOWNHOLE EQUIPMENT

6-3/4 in. ADN*6C	Neutron F	34.72	36.69
S/N: 0403	Neutron N	34.57	
8-1/4 in. Stabiliser	Density S	33.70	
NSR-M A202	Density L	33.60	
GSR-J A1994	UltraSonic	33.22	
Software: V8.3A02	R-O Port	32.46	
6-3/4 in. Sonic*6			30.09
S/N: 34641	Receiver	27.03	
Software: V6.4B01	R-O Port	26.63	
	Transmitter	23.59	
6-3/4 in. PowerPulse*			22.80
MDC FA28	D&I	18.55	
MEC 1080			
MDI 491			
MVC 095			
Software: V8.0C00			
	R-O Port	11.48	
8-3/8 in. In Line Stabiliser T5	T3	11.38	14.89
S/N: S15535-2	T1	11.07	
6-3/4 in. ARC*6	Gamma Ray	10.77	13.79
S/N: 669	Receiver	10.41	
Software: V9.0B00	T2	10.36	
	T4	10.11	
	ARC APRS	9.80	
		9.65	
6-3/4 in. Xceed* RSS			7.88

S/N: 059



Reed Hycalog PDC Bit
RSX 162 S/N: 209390
OD 8-1/2 in.

0.00

0.23

Maximum string diameter 8.50 in.
All lengths in Meters

IDEAL Version: ID10_0C_04
IDF

Format: VISION Density Neutron Log Vertical Scale: 1:200 Graphics File Created: 26-Jul-2005 11:23


Rate of Penetration, Averaged over Last
5ft (ROP5_RM)
200 (M/HR) 0

ARC Gamma Ray (GR_ARC)
0 (GAPI) 200


Vertical Hole Diameter (VERD)
6 (IN) 16

Horizontal Hole Diameter (HORD)
6 (IN) 16

Density Time After Bit (TAB_DEN)
0 (HR) 10



ADN
Rotational
Speed
(RPM_ADN)
(RPM)
250 0



Gas Area
From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH


Thermal Neutron Porosity (TNPH)
45 (PU) -15



Bulk Density, Bottom (ROBB)
1.85 (G/C3) 2.85


Bulk Density (RHOB)
1.85 (G/C3) 2.85

Photoelectric Factor, Bottom (PEB)
0 (----) 10

Bulk Density Correction, Bottom
(DRHB)
(G/C3) -0.75 0.25









750
TVD


775
TVD






800
TVD


825
TVD







850
TVD



875
TVD




900
TVD

925
TVD









1000
TVD


1025
TVD









1050
TVD

1075
TVD









1150
TVD


1175
TVD






1200
TVD


1225
TVD






1250
TVD


1275
TVD






1300
TVD


1325
TVD






1350
TVD


1375
TVD






1400
TVD


1425
TVD






1450
TVD

1475
TVD







1500
TVD

1525
TVD

1550











TVD



1575
TVD



1600
TVD

























1875
TVD

1900
TVD











2050
TVD


2050
TVD








2075
TVD

2100
TVD









2175
TVD


2200
TVD












2225
TVD


2250
TVD













2425
TVD


2450
TVD












2475
TVD




2500
TVD























2825
TVD

2850
TVD

Density Time After Bit (TAB_DEN)	
0	10
(HR)	
Horizontal Hole Diameter (HORD)	
6	16
(IN)	
Vertical Hole Diameter (VERD)	
6	16
(IN)	
ARC Gamma Ray (GR_ARC)	
0	200
(GAPI)	
Rate of Penetration, Averaged over Last	
5ft (ROP5_RM)	
200	0
(M/HR)	



<div>Photoelectric Factor, Bottom (PEB) (-----)</div> <div>010</div>		<div>Bulk Density Correction, Bottom (DRHB) (G/C3)</div> <div>-0.750.25</div>
<div>Bulk Density (RHOB) (G/C3)</div> <div>1.852.85</div>		
<div>Bulk Density, Bottom (ROBB) (G/C3)</div> <div>1.852.85</div>		
<div>Thermal Neutron Porosity (TNPH) (PU)</div> <div>45-15</div>		
<div>Gas Area From ADN/ROBB/DEPTH to ADN/TNPH/DEPTH</div>		

6.75-in. Azimuthal Density Neutron / Equipment Identification




Primary Equipment:
Tool Name and Serial Number
Collar Type and Serial Number
Chassis Type and Serial Number
Stabilizer Type and Serial Number
Neutron Logging Source
Density Logging Source
Stabilizer Size
Calibration Status

ADN6 – CA 0403
ADDC – AA 0403
ADSE – EA 18
Clamp-On Stabiliser 689198
NSR – M 202
CSR – J/Z 1994
8.25 – in.
Valid

Master: 21-Jun-2005 11:22

6.75-in. Azimuthal Density Neutron Calibration




Density: Magnesium Block

Phase	LS window 3 – Mg CPS		Value	Phase	SS window 1 – Mg CPS		Value	Phase	SS window 3 – Mg CPS		Value
Master			1052	Master			2361	Master			6156
	250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)		700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)		2500 (Minimum)	23750 (Nominal)	45000 (Maximum)

Master: 21-Jun-2005 11:22

6.75-in. Azimuthal Density Neutron Calibration




Density: Aluminum Block

Phase	LS window 3 – AI CPS			Value	Phase	SS window 1 – AI CPS			Value	Phase	SS window 3 – AI CPS			Value
Master				163.3	Master				1238	Master				3922
	50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)			500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)			1500 (Minimum)	15750 (Nominal)	30000 (Maximum)	

Master: 21-Jun-2005 11:22

6.75-in. Azimuthal Density Neutron Calibration



Density: Background

Phase	LS window 3 – Background CPS		Value	Phase	SS window 1 – Background CPS		Value	Phase	SS window 3 – Background CPS		Value
Master			33.84	Master			106.5	Master			474.2
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)		40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)		150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)

Master: 21-Jun-2005 11:22

6.75-in. Azimuthal Density Neutron Calibration













Density: Water Block Check













Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value
Master				1.030	Master				1.120
	1.024 (Minimum)	1.039 (Nominal)	1.054 (Maximum)			1.096 (Minimum)	1.126 (Nominal)	1.156 (Maximum)	


Master: 21-Jun-2005 11:22

6.75-in. Azimuthal Density Neutron Calibration











Neutron: 3-Point Calibration

Phase	Far 1 tube 1 Air Point Measure	CPS	Value	Phase	Far 1 tube 1 Rod Point Measure	CPS	Value	Phase	Far 1 tube 1 H2O Point Measure	CPS	Value
Master			17.01	Master			4.142	Master			2.060
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)		4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)		1.900 (Minimum)	2.363 (Nominal)	2.700 (Maximum)
Phase	Far 1 tube 2 Air Point Measure	CPS	Value	Phase	Far 1 tube 2 Rod Point Measure	CPS	Value	Phase	Far 1 tube 2 H2O Point Measure	CPS	Value
Master			18.12	Master			4.335	Master			2.137
	16.00 (Minimum)	19.05 (Nominal)	22.00 (Maximum)		4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)		1.900 (Minimum)	2.363 (Nominal)	2.800 (Maximum)
Phase	Far 1 tube 3 Air Point Measure	CPS	Value	Phase	Far 1 tube 3 Rod Point Measure	CPS	Value	Phase	Far 1 tube 3 H2O Point Measure	CPS	Value
Master			17.15	Master			4.188	Master			2.066
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)		4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)		1.900 (Minimum)	2.363 (Nominal)	2.700 (Maximum)
Phase	Far 2 tube 1 Air Point Measure	CPS	Value	Phase	Far 2 tube 1 Rod Point Measure	CPS	Value	Phase	Far 2 tube 1 H2O Point Measure	CPS	Value
Master			17.52	Master			4.365	Master			2.173
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)		4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)		1.900 (Minimum)	2.363 (Nominal)	2.700 (Maximum)











Phase 1 Far 2 tube 2 Air Point Measure CPS Value				Phase 2 Far 2 tube 2 Rod Point Measure CPS Value				Phase 3 Far 2 tube 2 H2O Point Measure CPS Value									
Master			18.07	Master			4.211	Master			1.982						
16.00 (Minimum)		19.05 (Nominal)		22.00 (Maximum)		4.000 (Minimum)		4.857 (Nominal)		5.500 (Maximum)		1.900 (Minimum)		2.363 (Nominal)		2.800 (Maximum)	
Phase 1 Far 2 tube 3 Air Point Measure CPS Value				Phase 2 Far 2 tube 3 Rod Point Measure CPS Value				Phase 3 Far 2 tube 3 H2O Point Measure CPS Value									
Master			17.03	Master			4.348	Master			2.060						
15.00 (Minimum)		19.05 (Nominal)		21.00 (Maximum)		4.000 (Minimum)		4.857 (Nominal)		5.500 (Maximum)		1.900 (Minimum)		2.363 (Nominal)		2.700 (Maximum)	
Phase 1 Near 1 tube 1 Air Point Measure CPS Value				Phase 2 Near 1 tube 1 Rod Point Measure CPS Value				Phase 3 Near 1 tube 1 H2O Point Measure CPS Value									
Master			458.8	Master			722.7	Master			319.9						
400.0 (Minimum)		487.5 (Nominal)		540.0 (Maximum)		610.0 (Minimum)		768.8 (Nominal)		850.0 (Maximum)		270.0 (Minimum)		343.7 (Nominal)		390.0 (Maximum)	
Phase 1 Near 2 tube 1 Air Point Measure CPS Value				Phase 2 Near 2 tube 1 Rod Point Measure CPS Value				Phase 3 Near 2 tube 1 H2O Point Measure CPS Value									
Master			454.0	Master			727.3	Master			320.0						
400.0 (Minimum)		487.5 (Nominal)		540.0 (Maximum)		610.0 (Minimum)		768.8 (Nominal)		850.0 (Maximum)		270.0 (Minimum)		343.7 (Nominal)		390.0 (Maximum)	

Master: 21-Jun-2005 11:22			
6.75-in. Azimuthal Density Neutron Calibration			
Neutron: Water Block Check			
Phase	Far Neutron water porosity PU		Value
Master			92.83
	90.00 (Minimum)	100.0 (Nominal)	125.0 (Maximum)


6.75–in. Array Resistivity Compensated / Equipment Identification		
Primary Equipment:		
Tool Name and Serial Number	ARC6 – BA	669
ARC675 Calibration Status	Valid	

Master: 21–Jun–2005 17:38														
6.75–in. Array Resistivity Compensated Calibration														
Resistivity: Air														
Phase	Phase–Shift T1			Value	Phase	Phase–Shift T2			Value	Phase	Phase–Shift T3			Value
Master				1.268	Master				–1.170	Master				1.197
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			
Phase	Phase–Shift T4			Value	Phase	Phase–Shift T5			Value	Phase	Phase–Shift T1 at 400KHz			Value
Master				–1.217	Master				1.178	Master				–0.01753
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			
Phase	Phase–Shift T2 at 400KHz			Value	Phase	Phase–Shift T3 at 400KHz			Value	Phase	Phase–Shift T4 at 400KHz			Value
Master				–0.06656	Master				0.006531	Master				–0.06732
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)		–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			
Phase	Phase–Shift T5 at 400KHz			Value										
Master				–0.002529										
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)											

Master: 21-Jun-2005 17:38

6.75-in. Array Resistivity Compensated Calibration											
Resistivity: Air											
Phase	Attenuation T1		Value	Phase	Attenuation T2		Value	Phase	Attenuation T3		Value
Master			8.679	Master			6.273	Master			5.309
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)
Phase	Attenuation T4		Value	Phase	Attenuation T5		Value	Phase	Attenuation T1 at 400KHz		Value
Master			4.192	Master			3.867	Master			8.755
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)		6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)
Phase	Attenuation T2 at 400KHz		Value	Phase	Attenuation T3 at 400KHz		Value	Phase	Attenuation T4 at 400KHz		Value
Master			6.204	Master			5.371	Master			4.116
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz		Value								
Master			3.943								
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)								

Master: 21-Jun-2005 14:57

6.75-in. Array Resistivity Compensated Calibration											
Gamma Ray: Blanket											
Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS										Value
Master											5.205
	2.780 (Minimum)		4.800 (Nominal)		6.000 (Maximum)						

SCHLUMBERGER

Survey report

21-Jul-2005 00:25:19

Page 1 of 7

Client.....: ESSO Australia Pty. Ltd.
Field.....: Bream B

Well.....: BMB-B17
API number.....:
Engineer.....: J.Dolan, M.Y.Tan, D.Hastie

RIG:.....: ENSCO 102
STATE:.....: Victoria

Spud date.....: 03-Jul-05
Last survey date.....: 20-Jul-05
Total accepted surveys...: 166
MD of first survey.....: 176.60 m
MD of last survey.....: 4955.00 m

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2004
Magnetic date.....: 07-Jul-2005
Magnetic field strength...: 1202.98 HCNT
Magnetic dec (+E/W-).....: 13.13 degrees
Magnetic dip.....: -69.03 degrees

----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's Depth
GL above permanent.....: -61.00 m
KB above permanent.....: Top Drive
DF above permanent.....: 47.17 m

----- MWD survey Reference Criteria -----
Reference G.....: 1000.05 mGal
Reference H.....: 1202.98 HCNT
Reference Dip.....: -69.03 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Vertical section origin-----
Latitude (+N/S-).....: -8.30 m
Departure (+E/W-).....: 1.90 m

----- Corrections -----
Magnetic dec (+E/W-).....: 13.13 degrees
Grid convergence (+E/W-)..: -0.52 degrees
Total az corr (+E/W-).....: 13.65 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

----- Platform reference point-----
Latitude (+N/S-).....:
Departure (+E/W-).....:

Azimuth from Vsect Origin to target: 262.95 degrees

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
1	176.60	0.04	183.64	0.00	176.60	-0.02	-8.30	1.92	8.52	166.98	0.00	TIP	None
2	184.83	1.13	182.03	8.23	184.83	-0.01	-8.38	1.92	8.60	167.12	4.04	GYR	None
3	213.43	3.56	179.37	28.60	213.40	0.14	-9.55	1.92	9.74	168.66	2.59	GYR	None
4	223.59	3.72	184.92	10.16	223.54	0.24	-10.20	1.89	10.37	169.47	1.04	GYR	None
5	242.62	4.46	196.22	19.03	242.52	0.65	-11.52	1.64	11.64	171.88	1.80	GYR	None
6	271.64	8.75	218.77	29.02	271.35	2.68	-14.32	-0.05	14.32	180.21	5.18	GYR	None
7	300.55	10.26	241.47	28.91	299.87	6.65	-17.27	-3.69	17.66	192.07	4.23	GYR	None
8	329.43	14.91	265.50	28.88	328.07	12.76	-18.79	-9.66	21.12	207.21	7.28	GYR	None
9	358.38	18.09	268.20	28.95	355.83	20.96	-19.22	-17.87	26.24	222.91	3.45	GYR	None
10	376.71	19.26	267.42	18.33	373.19	26.80	-19.45	-23.73	30.68	230.67	1.99	MWD	None
11	405.38	22.00	267.42	28.67	400.02	36.87	-19.90	-33.82	39.24	239.53	2.91	MWD	None
12	434.55	26.55	267.16	29.17	426.60	48.83	-20.47	-45.80	50.16	245.92	4.76	MWD	None
13	463.47	30.39	267.57	28.92	452.02	62.57	-21.10	-59.57	63.19	250.49	4.05	MWD	None
14	492.68	34.12	269.90	29.21	476.72	78.07	-21.43	-75.15	78.14	254.08	4.10	MWD	None
15	521.56	37.60	271.58	28.88	500.12	94.83	-21.20	-92.06	94.47	257.03	3.82	MWD	None
16	550.51	41.70	271.67	28.95	522.41	113.09	-20.68	-110.52	112.44	259.40	4.32	MWD	None
17	579.54	44.80	271.95	29.03	543.55	132.74	-20.05	-130.40	131.93	261.26	3.26	MWD	None
18	608.87	48.46	271.91	29.33	563.69	153.80	-19.33	-151.70	152.93	262.74	3.80	MWD	None
19	638.03	52.67	271.80	29.16	582.21	176.04	-18.60	-174.21	175.20	263.90	4.40	MWD	None
20	667.20	55.95	271.13	29.17	599.22	199.47	-18.00	-197.89	198.71	264.80	3.47	MWD	None
21	695.98	60.12	271.59	28.78	614.46	223.62	-17.42	-222.29	222.97	265.52	4.44	MWD	None
22	725.38	64.35	273.81	29.40	628.15	249.25	-16.18	-248.27	248.80	266.27	4.83	MWD	None
23	754.29	64.78	274.68	28.91	640.57	274.85	-14.25	-274.31	274.68	267.03	0.94	MWD	None
24	783.25	65.32	275.18	28.96	652.78	300.53	-11.99	-300.47	300.70	267.71	0.74	MWD	None
25	818.77	67.01	273.50	35.52	667.14	332.38	-9.54	-332.86	333.00	268.36	1.96	MWD	None
26	854.11	67.18	274.13	35.34	680.89	364.35	-7.37	-365.34	365.42	268.84	0.52	MWD	None
27	883.53	67.37	274.24	29.42	692.26	390.97	-5.39	-392.41	392.44	269.21	0.22	MWD	None
28	912.19	67.47	274.39	28.66	703.26	416.91	-3.40	-418.79	418.81	269.53	0.18	MWD	None
29	941.56	67.64	274.39	29.37	714.47	443.52	-1.32	-445.86	445.86	269.83	0.18	MWD	None
30	970.95	67.57	274.58	29.39	725.67	470.14	0.80	-472.95	472.95	270.10	0.20	MWD	None

[(c)2005 IDEAL ID10_2B_08]
SCHLUMBERGER Survey Report

21-Jul-2005 00:25:19

Page 3 of 7

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
31	1000.05	67.26	274.68	29.10	736.85	496.45	2.97	-499.73	499.74	270.34	0.34	MWD	None
32	1029.41	66.85	275.24	29.36	748.29	522.90	5.31	-526.66	526.69	270.58	0.68	MWD	None
33	1057.37	66.83	275.77	27.96	759.29	547.99	7.77	-552.25	552.31	270.81	0.53	MWD	None
34	1087.17	65.53	276.46	29.80	771.33	574.53	10.68	-579.36	579.46	271.06	1.48	MWD	None
35	1115.97	65.95	276.52	28.80	783.16	600.06	13.65	-605.45	605.60	271.29	0.45	MWD	None
36	1144.88	66.14	276.01	28.91	794.90	625.77	16.53	-631.71	631.93	271.50	0.53	MWD	None
37	1173.62	66.62	273.57	28.74	806.41	651.54	18.73	-657.95	658.21	271.63	2.42	MWD	None
38	1202.81	66.84	271.28	29.19	817.95	677.99	19.86	-684.74	685.02	271.66	2.21	MWD	None
39	1231.62	66.76	271.15	28.81	829.30	704.19	20.42	-711.21	711.50	271.64	0.15	MWD	None
40	1260.58	66.85	271.17	28.96	840.70	730.54	20.96	-737.82	738.12	271.63	0.10	MWD	None
41	1289.26	66.39	271.05	28.68	852.08	756.60	21.47	-764.14	764.45	271.61	0.50	MWD	None
42	1318.24	66.25	271.26	28.98	863.72	782.87	22.01	-790.68	790.98	271.59	0.25	MWD	None
43	1347.08	66.51	270.71	28.84	875.28	809.03	22.46	-817.10	817.41	271.57	0.60	MWD	None
44	1376.15	67.18	270.40	29.07	886.71	835.52	22.72	-843.82	844.13	271.54	0.76	MWD	None
45	1405.05	67.15	270.07	28.90	897.92	861.94	22.83	-870.46	870.76	271.50	0.32	MWD	None
46	1434.14	67.43	269.66	29.09	909.15	888.58	22.76	-897.29	897.58	271.45	0.49	MWD	None
47	1462.93	67.01	268.80	28.79	920.30	914.97	22.41	-923.84	924.11	271.39	0.95	MWD	None
48	1492.22	67.44	268.83	29.29	931.64	941.83	21.85	-950.84	951.09	271.32	0.45	MWD	None
49	1521.04	67.82	268.79	28.82	942.61	968.34	21.30	-977.48	977.71	271.25	0.40	MWD	None
50	1549.99	67.58	268.90	28.95	953.59	994.99	20.76	-1004.26	1004.48	271.18	0.27	MWD	None
51	1579.01	68.11	269.05	29.02	964.54	1021.72	20.28	-1031.13	1031.33	271.13	0.58	MWD	None
52	1608.07	68.31	269.31	29.06	975.33	1048.54	19.89	-1058.11	1058.30	271.08	0.33	MWD	None
53	1636.95	68.63	269.58	28.88	985.92	1075.23	19.63	-1084.98	1085.16	271.04	0.43	MWD	None
54	1666.13	68.90	270.38	29.18	996.49	1102.23	19.62	-1112.18	1112.35	271.01	0.83	MWD	None
55	1695.25	68.90	271.14	29.12	1006.98	1129.14	19.98	-1139.34	1139.52	271.00	0.74	MWD	None
56	1724.30	69.09	271.81	29.05	1017.39	1155.96	20.68	-1166.45	1166.64	271.02	0.69	MWD	None
57	1753.32	69.21	272.75	29.02	1027.72	1182.72	21.76	-1193.55	1193.75	271.04	0.93	MWD	None
58	1782.48	69.09	272.97	29.15	1038.09	1209.56	23.12	-1220.76	1220.98	271.08	0.25	MWD	None
59	1811.46	69.33	273.59	28.99	1048.38	1236.22	24.67	-1247.81	1248.06	271.13	0.66	MWD	None
60	1840.15	69.21	274.40	28.69	1058.54	1262.56	26.54	-1274.58	1274.86	271.19	0.81	MWD	None

[(c)2005 IDEAL ID10_2B_08]
SCHLUMBERGER Survey Report

21-Jul-2005 00:25:19

Page 4 of 7

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
61	1869.23	69.00	274.33	29.08	1068.91	1289.19	28.60	-1301.67	1301.98	271.26	0.23	MWD	None

62	1897.95	68.96	274.92	28.72	1079.21	1315.44	30.77	-1328.39	1328.75	271.33	0.59	MWD	None
63	1926.96	68.73	275.07	29.01	1089.68	1341.90	33.12	-1355.34	1355.75	271.40	0.28	MWD	None
64	1956.12	68.62	275.18	29.16	1100.29	1368.45	35.55	-1382.40	1382.86	271.47	0.16	MWD	None
65	1985.11	68.49	275.64	28.99	1110.89	1394.80	38.09	-1409.26	1409.78	271.55	0.47	MWD	None
66	2013.72	68.42	275.77	28.61	1121.39	1420.75	40.74	-1435.74	1436.32	271.63	0.15	MWD	None
67	2043.27	68.42	276.11	29.55	1132.26	1447.53	43.58	-1463.07	1463.72	271.71	0.33	MWD	None
68	2072.90	68.54	276.03	29.63	1143.13	1474.37	46.50	-1490.48	1491.21	271.79	0.15	MWD	None
69	2101.21	68.59	276.22	28.31	1153.47	1500.03	49.31	-1516.68	1517.48	271.86	0.20	MWD	None
70	2130.32	68.73	276.28	29.11	1164.07	1526.42	52.26	-1543.64	1544.52	271.94	0.16	MWD	None
71	2159.55	68.71	275.76	29.23	1174.68	1552.95	55.12	-1570.72	1571.69	272.01	0.51	MWD	None
72	2187.89	68.23	275.09	28.34	1185.08	1578.69	57.61	-1596.97	1598.01	272.07	0.85	MWD	None
73	2217.05	67.62	273.94	29.16	1196.04	1605.16	59.74	-1623.91	1625.00	272.11	1.28	MWD	None
74	2246.05	67.18	272.93	29.00	1207.18	1631.49	61.34	-1650.63	1651.77	272.13	1.08	MWD	None
75	2275.35	67.02	272.33	29.30	1218.58	1658.09	62.58	-1677.59	1678.76	272.14	0.60	MWD	None
76	2303.96	66.99	272.08	28.61	1229.76	1684.09	63.59	-1703.91	1705.09	272.14	0.25	MWD	None
77	2333.53	66.77	271.98	29.57	1241.37	1710.94	64.56	-1731.09	1732.29	272.14	0.25	MWD	None
78	2362.66	66.57	271.60	29.13	1252.91	1737.37	65.39	-1757.82	1759.04	272.13	0.42	MWD	None
79	2391.16	66.42	271.10	28.50	1264.27	1763.23	66.01	-1783.95	1785.17	272.12	0.52	MWD	None
80	2420.52	66.29	270.97	29.36	1276.05	1789.86	66.49	-1810.84	1812.06	272.10	0.18	MWD	None
81	2449.48	66.28	270.92	28.96	1287.70	1816.11	66.93	-1837.35	1838.57	272.09	0.05	MWD	None
82	2478.43	65.90	271.06	28.95	1299.43	1842.32	67.39	-1863.81	1865.03	272.07	0.42	MWD	None
83	2507.38	65.86	271.31	28.95	1311.26	1868.47	67.93	-1890.23	1891.45	272.06	0.24	MWD	None
84	2536.36	65.70	271.62	28.98	1323.15	1894.60	68.61	-1916.65	1917.88	272.05	0.34	MWD	None
85	2565.38	65.56	271.63	29.02	1335.12	1920.74	69.36	-1943.07	1944.31	272.04	0.15	MWD	None
86	2594.40	65.45	271.70	29.02	1347.15	1946.84	70.13	-1969.47	1970.72	272.04	0.13	MWD	None
87	2623.43	65.17	271.70	29.03	1359.28	1972.91	70.91	-1995.83	1997.09	272.03	0.29	MWD	None
88	2652.00	64.93	271.51	28.57	1371.33	1998.52	71.63	-2021.73	2023.00	272.03	0.32	MWD	None
89	2681.57	64.64	272.01	29.57	1383.93	2024.95	72.46	-2048.47	2049.75	272.03	0.55	MWD	None
90	2710.44	64.64	271.97	28.87	1396.29	2050.72	73.36	-2074.54	2075.84	272.03	0.04	MWD	None

[(c)2005 IDEAL ID10_2B_08]
SCHLUMBERGER Survey Report

21-Jul-2005 00:25:19

Page 5 of 7

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
91	2739.43	65.30	272.01	28.99	1408.56	2076.66	74.27	-2100.79	2102.10	272.02	0.69	MWD	None
92	2768.43	65.78	271.99	29.00	1420.57	2102.73	75.20	-2127.17	2128.50	272.02	0.50	MWD	None
93	2797.42	66.38	272.44	28.99	1432.32	2128.88	76.22	-2153.65	2155.00	272.03	0.76	MWD	None
94	2826.48	66.53	272.48	29.06	1443.93	2155.16	77.36	-2180.27	2181.64	272.03	0.16	MWD	None
95	2855.34	66.71	272.69	28.86	1455.38	2181.27	78.56	-2206.73	2208.13	272.04	0.28	MWD	None
96	2884.25	67.03	272.95	28.91	1466.74	2207.47	79.87	-2233.29	2234.71	272.05	0.42	MWD	None
97	2913.38	67.05	273.01	29.13	1478.10	2233.88	81.26	-2260.07	2261.53	272.06	0.06	MWD	None
98	2942.34	67.73	273.21	28.96	1489.24	2260.19	82.71	-2286.77	2288.26	272.07	0.74	MWD	None
99	2971.33	68.13	273.23	28.99	1500.13	2286.63	84.22	-2313.59	2315.12	272.08	0.42	MWD	None
100	3000.41	68.89	273.44	29.08	1510.78	2313.24	85.79	-2340.60	2342.17	272.10	0.82	MWD	None
101	3029.44	69.28	273.36	29.03	1521.15	2339.91	87.40	-2367.67	2369.28	272.11	0.42	MWD	None
102	3058.81	69.90	273.38	29.37	1531.39	2366.98	89.02	-2395.15	2396.80	272.13	0.64	MWD	None
103	3088.07	69.80	273.29	29.26	1541.47	2394.00	90.62	-2422.57	2424.27	272.14	0.14	MWD	None
104	3116.50	69.65	273.74	28.43	1551.32	2420.22	92.25	-2449.19	2450.93	272.16	0.48	MWD	None
105	3145.03	69.35	274.06	28.53	1561.31	2446.45	94.07	-2475.85	2477.64	272.18	0.45	MWD	None
106	3174.90	69.05	274.28	29.87	1571.92	2473.84	96.10	-2503.70	2505.55	272.20	0.37	MWD	None
107	3203.62	69.10	274.16	28.72	1582.17	2500.15	98.08	-2530.45	2532.35	272.22	0.13	MWD	None
108	3231.95	69.12	273.82	28.33	1592.28	2526.13	99.92	-2556.86	2558.81	272.24	0.34	MWD	None
109	3261.85	69.20	274.34	29.90	1602.91	2553.55	101.91	-2584.73	2586.74	272.26	0.50	MWD	None
110	3290.76	69.38	274.16	28.91	1613.14	2580.07	103.91	-2611.70	2613.77	272.28	0.26	MWD	None
111	3320.19	68.08	272.09	29.43	1623.81	2607.06	105.41	-2639.08	2641.18	272.29	2.41	MWD	None
112	3348.99	66.80	269.60	28.80	1634.86	2633.40	105.80	-2665.67	2667.77	272.27	2.79	MWD	None
113	3378.00	65.47	267.82	29.01	1646.60	2659.79	105.21	-2692.19	2694.25	272.24	2.21	MWD	None
114	3406.72	64.01	265.64	28.72	1658.86	2685.71	103.73	-2718.12	2720.10	272.19	2.60	MWD	None
115	3436.65	62.50	263.31	29.93	1672.33	2712.42	101.16	-2744.72	2746.58	272.11	2.62	MWD	None
116	3465.56	61.00	260.46	28.91	1686.01	2737.88	97.57	-2769.93	2771.65	272.02	3.08	MWD	None
117	3493.87	59.97	257.54	28.31	1699.96	2762.45	92.87	-2794.11	2795.65	271.90	2.95	MWD	None
118	3522.76	58.80	254.12	28.89	1714.68	2787.12	86.79	-2818.21	2819.55	271.76	3.34	MWD	None
119	3551.72	57.78	250.60	28.96	1729.90	2811.33	79.33	-2841.68	2842.79	271.60	3.33	MWD	None
120	3580.80	56.75	246.98	29.08	1745.63	2835.04	70.49	-2864.48	2865.35	271.41	3.37	MWD	None

[(c)2005 IDEAL ID10_2B_08]
SCHLUMBERGER Survey Report

21-Jul-2005 00:25:19

Page 6 of 7

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
121	3609.60	55.55	243.69	28.80	1761.68	2857.84	60.51	-2886.22	2886.85	271.20	3.16	MWD	None
122	3638.76	54.93	240.03	29.16	1778.31	2880.18	49.22	-2907.34	2907.75	270.97	3.21	MWD	None
123	3667.68	54.16	235.71	28.92	1795.09	2901.51	36.70	-2927.28	2927.51	270.72	3.80	MWD	None
124	3696.68	53.30	231.28	29.00	1812.25	2921.86	22.80	-2946.07	2946.16	270.44	3.86	MWD	None
125	3725.76	53.25	227.13	29.08	1829.64	2941.24	7.58	-2963.71	2963.72	270.15	3.49	MWD	None
126	3754.65	53.96	223.06	28.89	1846.79	2959.59	-8.83	-2980.17	2980.18	269.83	3.54	MWD	None

127	3783.54	54.77	220.16	28.89	1863.62	2977.21	-26.39	-2995.76	2995.87	269.50	2.63	MWD	None
128	3812.61	56.01	216.05	29.07	1880.14	2994.17	-45.21	-3010.51	3010.85	269.14	3.78	MWD	None
129	3841.38	57.08	212.30	28.77	1896.00	3009.98	-65.07	-3023.99	3024.69	268.77	3.50	MWD	None
130	3870.13	58.41	211.89	28.75	1911.35	3025.32	-85.67	-3036.90	3038.11	268.38	1.46	MWD	None
131	3899.29	57.91	210.71	29.16	1926.73	3040.69	-106.83	-3049.77	3051.64	267.99	1.17	MWD	None
132	3928.90	57.02	210.67	29.61	1942.65	3055.97	-128.30	-3062.51	3065.20	267.60	0.92	MWD	None
133	4015.78	53.81	210.04	86.88	1991.96	3099.42	-190.01	-3098.66	3104.48	266.49	1.14	MWD	None
134	4044.33	51.58	209.51	28.55	2009.27	3113.03	-209.72	-3109.94	3117.00	266.14	2.42	MWD	None
135	4073.26	50.24	207.64	28.93	2027.51	3126.11	-229.43	-3120.68	3129.11	265.80	2.08	MWD	None
136	4102.29	46.16	206.56	29.03	2046.85	3138.27	-248.69	-3130.54	3140.41	265.46	4.37	MWD	None
137	4131.17	40.46	206.33	28.88	2067.86	3149.20	-266.42	-3139.37	3150.65	265.15	6.02	MWD	None
138	4159.95	38.23	206.44	28.78	2090.12	3159.25	-282.76	-3147.47	3160.15	264.87	2.36	MWD	None
139	4188.95	34.73	205.10	29.00	2113.43	3168.60	-298.28	-3154.98	3169.04	264.60	3.77	MWD	None
140	4217.63	33.53	204.72	28.68	2137.17	3177.12	-312.88	-3161.75	3177.20	264.35	1.30	MWD	None
141	4246.94	29.53	204.89	29.31	2162.15	3185.20	-326.79	-3168.18	3184.99	264.11	4.16	MWD	None
142	4275.84	25.05	205.43	28.90	2187.82	3192.26	-338.78	-3173.81	3191.84	263.91	4.73	MWD	None
143	4304.81	21.47	206.80	28.97	2214.44	3198.51	-349.05	-3178.83	3197.94	263.73	3.81	MWD	None
144	4333.81	16.56	208.03	29.00	2241.85	3203.84	-357.44	-3183.17	3203.18	263.59	5.18	MWD	None
145	4362.92	15.37	209.00	29.11	2269.83	3208.50	-364.48	-3186.99	3207.77	263.48	1.28	MWD	None
146	4391.85	14.29	210.79	28.93	2297.80	3212.94	-370.90	-3190.68	3212.16	263.37	1.24	MWD	None
147	4420.81	13.66	214.12	28.96	2325.90	3217.39	-376.80	-3194.43	3216.57	263.27	1.07	MWD	None
148	4450.08	13.49	215.04	29.27	2354.35	3221.95	-382.46	-3198.32	3221.11	263.18	0.29	MWD	None
149	4478.92	13.79	215.54	28.84	2382.38	3226.53	-388.01	-3202.25	3225.68	263.09	0.34	MWD	None
150	4507.60	13.77	217.99	28.68	2410.23	3231.26	-393.48	-3206.34	3230.40	263.00	0.62	MWD	None

[(c)2005 IDEAL ID10_2B_08]
SCHLUMBERGER Survey Report

21-Jul-2005 00:25:19

Page 7 of 7

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
151	4536.72	13.73	218.40	29.12	2438.52	3236.18	-398.92	-3210.62	3235.31	262.92	0.11	MWD	None
152	4565.55	13.24	221.77	28.82	2466.55	3241.10	-404.06	-3214.94	3240.24	262.84	0.98	MWD	None
153	4594.41	12.52	224.81	28.87	2494.69	3246.05	-408.75	-3219.35	3245.20	262.76	1.04	MWD	None
154	4623.34	11.59	227.49	28.93	2522.98	3250.88	-412.94	-3223.70	3250.04	262.70	1.14	MWD	None
155	4652.25	10.43	224.62	28.91	2551.36	3255.30	-416.76	-3227.68	3254.48	262.64	1.35	MWD	None
156	4681.21	9.15	221.43	28.96	2579.90	3259.08	-420.36	-3231.05	3258.28	262.59	1.46	MWD	None
157	4710.37	8.01	218.08	29.16	2608.73	3262.26	-423.69	-3233.84	3261.47	262.54	1.30	MWD	None
158	4739.18	7.04	216.13	28.81	2637.29	3264.89	-426.70	-3236.12	3264.13	262.49	1.06	MWD	None
159	4768.38	6.52	215.64	29.20	2666.29	3267.23	-429.49	-3238.14	3266.49	262.44	0.55	MWD	None
160	4797.13	5.98	217.69	28.75	2694.87	3269.40	-432.00	-3240.00	3268.68	262.41	0.62	MWD	None
161	4826.21	5.62	212.03	29.08	2723.80	3271.36	-434.41	-3241.68	3270.66	262.37	0.71	MWD	None
162	4855.07	5.36	211.06	28.86	2752.53	3273.08	-436.76	-3243.13	3272.41	262.33	0.29	MWD	None
163	4883.83	5.16	209.56	28.76	2781.16	3274.68	-439.04	-3244.46	3274.03	262.29	0.26	MWD	None
164	4913.00	5.07	210.11	29.17	2810.22	3276.24	-441.29	-3245.75	3275.62	262.26	0.11	MWD	None
165	4934.41	4.85	211.39	21.41	2831.55	3277.38	-442.88	-3246.70	3276.77	262.23	0.35	MWD	None
166	4955.00	4.80	211.50	20.59	2852.07	3278.46	-444.36	-3247.60	3277.86	262.21	0.08	Projection to TD	

[(c)2005 IDEAL ID10_2B_08]

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **BMB-B17**

Field: **Bream B**

Rig: **ENSCO 102**

8.5 in. Section

State: **Victoria**

**VISION Density Neutron
1:200 True Vertical Depth
Recorded Mode Log**

