



Potassium	%	n.a									
Environmental data											
GR											
Mud weight	ppg	11.60									
Bit size	in	12.25									
Resistivity											
Neutron porosity											
Hole Size	in	n.a									
Mud weight	ppg	n.a									
Temperature	°C	n.a									
Mud salinity	ppk	n.a									
Formation salinity		n.a									
Recording rate 1	SEC	6 (ARC)									
Recording rate 2	SEC	n.a									
Filtering GR		3 pts.									
Filtering density		n.a									
Filtering Neutron		n.a									
Company representative		G. Doty	A. Zernov								
Anadrill personnel		M. Amarasena	B. Low	D. B. Khanh	C. Soper						

<p style="text-align: center;"><b>DISCLAIMER</b></p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
<b>OTHER SERVICES FOR RUN2</b> Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations	<b>OTHER SERVICES FOR RUN</b>	<b>OTHER SERVICES FOR RUN</b>
<b>REMARKS: RUN NUMBER 2</b> Depth is referenced to Driller's depth  Gamma ray is corrected for mud weight, tool size and bit size  Resistivity is borehole compensated and environmentally corrected  POOH due to reaching TD of 12.25	<b>REMARKS: RUN NUMBER</b>	<b>REMARKS: RUN NUMBER</b>

EQUIPMENT DESCRIPTION		
RUN2	RUN	RUN
DOWNHOLE EQUIPMENT		

DOWNHOLE EQUIPMENT

8-1/4  
DHS: 9.2C02  
S/N: VR50

23.88

D&I  
MVC

19.51  
18.87

8-1/4  
DHS: V9.3B  
S/N: 1877

14.84

Gamma Ray  
Resistivity

11.47  
11.42

ARC APRS

10.71

9  
S/N: BN9-002

8.94

12-1/4  
S/N: 218463

0.00 0.29

Maximum string diameter 12.25 in.  
All lengths in Meters

Variable Name	Variable Description	Run Name & Value	
	Run Number		2
	General Information		
BHT_RM	Bottom Hole Temperature (RM)	DEGC	94.000
BSAL_RM	Mud Salinity (RM)	PPK	0.000
BS_RM	Bit Size (RM)	IN	12.250
COEF_M	User Defined FEXP in Clean Sand	----	1.650
C_WS	Overpressure correction to Sw and M	----	1.000
FEXP	Formation Factor Exponent (RM)	----	2.000
FNUM	Formation Factor Enumerator (RM)	----	1.000
FPHI_RM	Formation Factor Porosity Source (RM)	----	XPLOT
MST_RM	Mud Sample temperature (RM)	DEGC	23.889
MW_RM	Mud Weight (RM)	LB/G	11.600
OBMF_RM	Oil Based Mud (RM)	----	YES
RHOF_RM	Mud Filtrate Density (RM)	G/C3	1.000
RHOM_RM	Matrix density (RM)	G/C3	2.710
RMS_RM	Resistivity of Mud Sample (RM)	OHMM	1000.000
RWA_COMP_M	Rwa computation model		
RWA_DEN_AD	Rwa Density Input ADN		
RWA_DEN_CD	Rwa Density Input CDN		
RWA_DEN_IN	Rwa Density Input		
RWA_FORM_M	Rwa computation formation model		
RWA_RES_IN	Rwa computation resistivity input		
RWS_RM	Resistivity of Connate Water (RM)	OHMM	1.000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	DEGC	10.000
TD_RM	Total Measured Depth (RM)	M	4365.000
TWS_RM	Temperature of Connate Water (RM)	DEGC	23.889
VF_ILLI	Fraction of illite in shales	----	0.500
VF_KAOL	Fraction of kaolinite in shales	----	0.500
VF_MONT	Fraction of montmorillonite in shales	----	0.000
XPDM_RM	Cross plot density porosity multiplier	----	0.675
XPNM_RM	Cross plot neutron porosity multiplier	----	0.325
	ARC		
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	DB	8.245
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	DB	8.243
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	DB	6.420
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	DB	6.433
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	DB	4.966
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	DB	4.958
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	DB	4.370
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	DB	4.379
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	DB	3.558
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	DB	3.559
ABNT	Abnormal Transmitter Indicator	----	No_Tx_Failed
ADHS	ARC Down Hole Software Version	----	9.3B
AM2A	ARC Air Cal Amplitude Offset at 2 MHz	----	-50000.000
ANISO_COMPUTE	Anisotropy Computation Option	----	YES
APICG	ARC5 Gamma Ray Gain Factor	----	1.052
APIG	ARC Gamma Ray API Gain Factor	----	-1.000
ARC_DATA_FIX	ARC: Create A Corrected ARC Time Data File	----	NO
ARC_DATA_LTB	ARC: Create An ARC LTB Data File	----	NO
ATMP_ARC	ARC Select Temperature Channel	----	Annulus_Temp
ATRN	ARC Tool Run Number	----	2
ATSN	ARC Tool Serial Number	----	1877
AZMF	Formation DIP Azimuth	DEG	0.000
BH_COMPUTE	Borehole Inversion Computation Option	----	YES
CALG	ARC Gamma Ray Cal Gain Factor	----	1.052
CALI_SLCT_ARC	ARC Caliper Selection	----	BITSIZE
CDPTH_ARC	Process Start Depth	M	30.480
DIELEC_COMPUTE	Dielectric Computation Option	----	YES
DIPF	Formation DIP Angle	DEG	0.000
ERRCT	Percentage Error Cutoff	----	4.500
GRSH	GR Shale (Invasion Computation Cutoff)	GAPI	1000.000
HIGH_BLEND	High Resistivity Threshold for Blending	OHMM	2.000
INCLIN_B0	ARC Bias Constant (mg)	----	0.000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	----	0.000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	----	0.000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	----	0.000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	----	1.000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	----	0.000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	----	0.000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	----	0.000
INVAS_COMPUTE	Invasion Computation Option	----	YES
JSD_ARC	ARC Acquisition start date	----	15-Sep-08
KPER	Potassium Concentration (RM)	----	0.000
LOW_BLEND	Low Resistivity Threshold for Blending	OHMM	1.000
MSWS	ARC Wizard Model Switch Window	M	1.524
MULTIEFFECT_COM	Multi Effect Option	----	YES
P11AC_RM	ARC: Air Calibration For Phase T1 to R1	DEG	-999.250
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	DEG	1.653
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	DEG	0.001
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	DEG	-1.561
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	DEG	-0.096
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	DEG	1.576
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	DEG	0.036
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	DEG	-1.570
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	DEG	-0.102
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	DEG	1.519
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	DEG	0.013

POFFSET_ARC	ARC: Pressure Offset	PSI	0.000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	----	P34B
PSOF_ADJ_T1	ARC: User Input Phase offset	DEG	0.000
RESTIK	ARC resistivity tick source	----	Phase
RSD	LWD run start date dd-mmm-yy	OHMM	1000.000
RWA_COMP_MOD	Rwa computation model	----	BASIC
RWA_DEN_ADN	Rwa Density Input	----	RHOB
RWA_DEN_CDN	Rwa Density Input	----	RHOB
RWA_DEN_INPUT	Rwa Density Input	----	RHOB
RWA_FORM_MOD	Rwa computation formation model	----	CLASTIC
RWA_RES_INPUT	Rwa computation resistivity input	----	RT
SHIG	ARC High Shock Risk Level	CPS	0.500
SMED	ARC Medium Shock Risk Level	CPS	0.330
SMIN	ARC Minimum Shock Risk Level	CPS	0.160
SUPD	ARC Real Time Shock Update Rate	S	30.000
TCODE_ARC	ARC Tool File Code	S	30.000
TSIZ_ARC	ARC Tool Size	IN	8.250
UNIFORM_COMPUTE	Uniform Rock Option	----	YES
VERS_ARC	ARC Down hole software version Number	----	9.300
WRK	to Report Potassium Concentration (RM)	----	K_by_Wgt_%

IDEAL Version: ID14\_0C\_02

IDF

Format: VISION Resistivity 2MHz

Vertical Scale: 1:500

Graphics File Created: 11-Nov-2008 09:22


PIP SUMMARY


- └


ARC Gamma Ray Samples
- └

ARC Resistivity Samples

	ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)	ARC Attenuation Resistivity 40-in. at 2 MHz (A40H)
0.2 (OHMM) 2000	0.2 (OHMM) 2000	0.2 (OHMM) 2000
ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)	ARC Attenuation Resistivity 34-in. at 2 MHz (A34H)	
0.2 (OHMM) 2000	0.2 (OHMM) 2000	
ARC Phase-Shift Resistivity 28-in. at 2 MHz (P28H)	ARC Attenuation Resistivity 28-in. at 2 MHz (A28H)	
0.2 (OHMM) 2000	0.2 (OHMM) 2000	
ARC Phase-Shift Resistivity 22-in. at 2 MHz (P22H)	ARC Attenuation Resistivity 22-in. at 2 MHz (A22H)	
0.2 (OHMM) 2000	0.2 (OHMM) 2000	
ARC Phase-Shift Resistivity 16-in. at 2 MHz (P16H)	ARC Attenuation Resistivity 16-in. at 2 MHz (A16H)	
0.2 (OHMM) 2000	0.2 (OHMM) 2000	









1200


1250


1300






























2300



2350


2400













2750

2800






2850

2900

2950








3000


3050

3100











3450

3500







3550



3600



3650




















## 8.25-in. Array Resistivity Compensated Calibration

## Gamma Ray: Blanket

Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS			Value
Master				7.575
	4.960 (Minimum)	7.200 (Nominal)	9.650 (Maximum)	

SCHLUMBERGER

Survey report

5-Nov-2008 04:06:21

Client.....: ESSO AUSTRALIA PTY LTD.  
Field.....: SNAPPER

Well.....: SNA A11A-ST  
API number.....: 08ASQ0028  
Engineer.....: MA/BL/DOB/DP

Spud date.....: 09-Sep-08  
Last survey date.....: 28-Oct-08  
Total accepted surveys....: 320  
MD of first survey.....: 0.00 m  
MD of last survey.....: 5204.00 m

RIG:.....: ISDL 175  
STATE:.....: VICTORIA

----- Survey calculation methods-----  
Method for positions.....: Minimum curvature  
Method for DLS.....: Mason & Taylor

----- Depth reference -----  
Permanent datum.....: Mean Sea Level  
Depth reference.....: Driller's Depth  
GL above permanent.....: -55.00 m  
KB above permanent.....: Top Drive  
DF above permanent.....: 41.70 m

----- Vertical section origin-----  
Latitude (+N/S-).....: -1.85 m  
Departure (+E/W-).....: 2.38 m

----- Platform reference point-----  
Latitude (+N/S-).....:  
Departure (+E/W-).....:

Azimuth from Vsect Origin to target: 225.66 degrees

----- Geomagnetic data -----  
Magnetic model.....: BGGM version 2008  
Magnetic date.....: 21-Oct-2008  
Magnetic field strength...: 1198.04 HCNT  
Magnetic dec (+E/W-).....: 13.00 degrees  
Magnetic dip.....: -68.69 degrees

----- MWD survey Reference Criteria -----  
Reference G.....: 1000.02 mGal  
Reference H.....: 1198.04 HCNT  
Reference Dip.....: -68.69 degrees  
Tolerance of G.....: (+/-) 2.50 mGal  
Tolerance of H.....: (+/-) 6.00 HCNT  
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----  
Magnetic dec (+E/W-).....: 13.00 degrees  
Grid convergence (+E/W-)..: -0.63 degrees  
Total az corr (+E/W-).....: 13.63 degrees  
(Total az corr = magnetic dec - grid conv)  
Survey Correction Type ...:  
I=Sag Corrected Inclination  
M=Schlumberger Magnetic Correction  
S=Shell Magnetic Correction  
F=Failed Axis Correction  
R=Magnetic Resonance Tool Correction  
D=Dmag Magnetic Correction

[(c)2008 IDEAL ID14\_OC\_02]  
SCHLUMBERGER Survey Report

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	0.00	0.00	0.00	0.00	0.00	0.00	-1.85	2.38	3.01	127.86	0.00	TIP	None
2	9.08	0.00	0.00	9.08	9.08	0.00	-1.85	2.38	3.01	127.86	0.00	MWD	None
3	64.08	0.64	256.16	55.00	64.08	0.26	-1.92	2.08	2.83	132.74	0.35	MWD	None
4	69.08	0.63	260.84	5.00	69.08	0.31	-1.93	2.03	2.80	133.66	0.32	MWD	None
5	74.08	0.65	250.94	5.00	74.08	0.36	-1.95	1.97	2.77	134.63	0.68	MWD	None
6	79.08	0.64	252.60	5.00	79.08	0.41	-1.97	1.92	2.75	135.67	0.13	MWD	None
7	84.08	0.66	258.82	5.00	84.08	0.46	-1.98	1.87	2.72	136.71	0.45	MWD	None
8	89.08	0.67	251.56	5.00	89.08	0.51	-1.99	1.81	2.69	137.79	0.52	MWD	None
9	94.08	0.60	249.24	5.00	94.08	0.56	-2.01	1.76	2.67	138.89	0.45	MWD	None
10	99.08	0.58	241.17	5.00	99.08	0.61	-2.03	1.71	2.66	139.95	0.52	MWD	None
11	104.08	0.62	228.30	5.00	104.08	0.66	-2.06	1.67	2.65	141.07	0.85	MWD	None
12	109.08	0.70	211.44	5.00	109.08	0.72	-2.11	1.63	2.67	142.27	1.27	MWD	None
13	114.08	0.89	192.04	5.00	114.08	0.78	-2.17	1.61	2.70	143.50	1.99	MWD	None
14	119.08	1.08	185.88	5.00	119.07	0.85	-2.26	1.59	2.76	144.76	1.32	MWD	None
15	124.08	1.46	178.13	5.00	124.07	0.93	-2.37	1.59	2.85	146.09	2.54	MWD	None
16	129.08	1.89	174.10	5.00	129.07	1.02	-2.51	1.60	2.98	147.48	2.72	MWD	None
17	134.08	2.10	170.15	5.00	134.07	1.12	-2.69	1.63	3.14	148.80	1.53	MWD	None
18	139.08	2.49	169.82	5.00	139.06	1.24	-2.88	1.66	3.33	150.04	2.38	MWD	None
19	144.08	2.77	169.43	5.00	144.06	1.36	-3.11	1.70	3.54	151.29	1.71	MWD	None
20	149.08	3.04	169.81	5.00	149.05	1.51	-3.36	1.75	3.79	152.49	1.65	MWD	None
21	154.08	3.26	170.56	5.00	154.05	1.66	-3.63	1.80	4.05	153.68	1.36	MWD	None
22	159.08	3.50	173.03	5.00	159.04	1.84	-3.92	1.84	4.33	154.89	1.71	MWD	None

	23	164.08	3.80	175.77	5.00	164.03	2.03	-4.24	1.87	4.63	156.21	2.11	MWD	None
	24	169.08	3.96	177.49	5.00	169.01	2.26	-4.58	1.89	4.95	157.58	1.21	MWD	None
	25	174.08	4.35	183.02	5.00	174.00	2.51	-4.94	1.89	5.28	159.10	3.41	MWD	None
	26	179.08	4.62	185.30	5.00	178.99	2.80	-5.33	1.86	5.64	160.78	1.97	MWD	None
	27	184.08	4.97	188.80	5.00	183.97	3.13	-5.74	1.81	6.02	162.55	2.78	MWD	None
	28	189.08	5.34	192.30	5.00	188.95	3.50	-6.18	1.72	6.42	164.43	2.96	MWD	None
	29	194.08	5.61	194.26	5.00	193.93	3.90	-6.65	1.61	6.84	166.36	2.00	MWD	None
	30	199.08	5.84	193.73	5.00	198.90	4.33	-7.13	1.49	7.29	168.18	1.44	MWD	None
	31	204.08	6.01	195.66	5.00	203.87	4.77	-7.63	1.36	7.75	169.89	1.60	MWD	None
	32	209.08	6.40	199.47	5.00	208.84	5.25	-8.14	1.20	8.23	171.64	3.46	MWD	None
	33	214.08	6.67	202.29	5.00	213.81	5.76	-8.68	0.99	8.73	173.46	2.56	MWD	None
	34	219.08	6.96	204.15	5.00	218.78	6.31	-9.22	0.76	9.25	175.29	2.22	MWD	None
	35	224.08	7.40	207.94	5.00	223.74	6.90	-9.78	0.49	9.79	177.16	3.94	MWD	None
	36	229.08	7.84	209.45	5.00	228.69	7.53	-10.36	0.17	10.37	179.08	2.95	MWD	None
	37	234.08	8.37	211.17	5.00	233.64	8.21	-10.97	-0.19	10.97	180.99	3.55	MWD	None
	38	239.08	8.88	212.23	5.00	238.59	8.94	-11.61	-0.58	11.62	182.88	3.26	MWD	None
	39	244.08	9.43	212.07	5.00	243.52	9.71	-12.28	-1.01	12.32	184.68	3.36	MWD	None
	40	249.08	10.25	212.50	5.00	248.45	10.55	-13.01	-1.46	13.09	186.42	5.02	MWD	None
	41	254.08	10.81	212.64	5.00	253.37	11.44	-13.78	-1.95	13.91	188.08	3.42	MWD	None
	42	259.08	11.55	212.86	5.00	258.27	12.38	-14.59	-2.48	14.80	189.64	4.52	MWD	None
	43	264.08	12.12	212.88	5.00	263.16	13.38	-15.45	-3.04	15.75	191.12	3.47	MWD	None
	44	269.08	12.69	212.49	5.00	268.05	14.43	-16.36	-3.62	16.75	192.47	3.51	MWD	None
	45	274.08	13.36	212.57	5.00	272.92	15.52	-17.31	-4.22	17.81	193.71	4.09	MWD	None
	46	279.08	14.13	212.66	5.00	277.78	16.68	-18.31	-4.86	18.94	194.87	4.70	MWD	None
	47	284.08	14.63	212.45	5.00	282.62	17.89	-19.35	-5.53	20.13	195.95	3.06	MWD	None
	48	289.08	15.27	212.31	5.00	287.45	19.15	-20.44	-6.22	21.37	196.93	3.91	MWD	None
	49	294.08	16.00	211.97	5.00	292.26	20.46	-21.58	-6.94	22.67	197.82	4.48	MWD	None
	50	299.08	16.98	211.90	5.00	297.06	21.84	-22.79	-7.69	24.05	198.64	5.98	MWD	None
	51	304.08	17.56	211.94	5.00	301.83	23.28	-24.05	-8.47	25.50	199.41	3.54	MWD	None
	52	309.08	18.41	211.96	5.00	306.59	24.78	-25.36	-9.29	27.01	200.12	5.18	MWD	None
	53	314.08	19.09	211.99	5.00	311.32	26.34	-26.72	-10.14	28.58	200.78	4.15	MWD	None
	54	319.08	19.84	211.85	5.00	316.04	27.96	-28.14	-11.02	30.22	201.39	4.58	MWD	None
	55	324.08	20.38	211.77	5.00	320.73	29.63	-29.60	-11.93	31.91	201.95	3.30	MWD	None
	56	329.08	21.36	211.76	5.00	325.41	31.36	-31.11	-12.87	33.67	202.47	5.97	MWD	None
	57	334.08	22.08	211.69	5.00	330.05	33.15	-32.69	-13.84	35.49	202.95	4.39	MWD	None
	58	339.08	22.85	211.55	5.00	334.67	35.00	-34.31	-14.84	37.38	203.39	4.71	MWD	None
	59	344.08	23.62	211.57	5.00	339.27	36.92	-35.99	-15.87	39.34	203.80	4.69	MWD	None
	60	349.08	24.89	211.82	5.00	343.82	38.91	-37.74	-16.95	41.37	204.19	7.77	MWD	None
	61	354.08	25.22	211.39	5.00	348.35	40.97	-39.54	-18.06	43.47	204.55	2.30	MWD	None
	62	359.08	26.19	211.56	5.00	352.86	43.07	-41.39	-19.19	45.63	204.88	5.93	MWD	None
	63	364.08	26.52	211.53	5.00	357.34	45.22	-43.29	-20.36	47.83	205.19	2.01	MWD	None
	64	369.08	26.97	211.34	5.00	361.80	47.40	-45.21	-21.53	50.07	205.47	2.79	MWD	None
	65	374.08	27.48	211.43	5.00	366.25	49.62	-47.16	-22.72	52.35	205.72	3.12	MWD	None
	66	379.08	28.09	211.41	5.00	370.67	51.88	-49.15	-23.94	54.67	205.97	3.72	MWD	None
	67	384.08	28.40	211.27	5.00	375.08	54.17	-51.17	-25.17	57.02	206.19	1.93	MWD	None
	68	389.08	28.95	211.53	5.00	379.46	56.50	-53.22	-26.42	59.41	206.40	3.44	MWD	None
	69	394.08	29.37	211.43	5.00	383.83	58.86	-55.29	-27.69	61.84	206.60	2.58	MWD	None
	70	399.08	29.94	211.44	5.00	388.18	61.26	-57.40	-28.98	64.30	206.79	3.47	MWD	None
	71	404.08	30.23	211.47	5.00	392.50	63.69	-59.54	-30.29	66.80	206.96	1.77	MWD	None
	72	409.08	30.54	211.55	5.00	396.82	66.14	-61.70	-31.61	69.32	207.13	1.91	MWD	None
	73	414.08	30.93	211.56	5.00	401.11	68.62	-63.88	-32.95	71.87	207.28	2.38	MWD	None
	74	419.08	31.27	211.61	5.00	405.39	71.12	-66.08	-34.30	74.45	207.43	2.08	MWD	None
	75	424.08	31.61	211.56	5.00	409.66	73.65	-68.30	-35.66	77.05	207.57	2.08	MWD	None
	76	429.08	31.97	211.57	5.00	413.91	76.21	-70.54	-37.04	79.68	207.71	2.19	MWD	None
	77	434.08	32.35	211.61	5.00	418.14	78.79	-72.81	-38.44	82.33	207.83	2.32	MWD	None
	78	439.08	32.76	211.64	5.00	422.36	81.40	-75.10	-39.85	85.02	207.95	2.50	MWD	None
	79	444.08	33.16	211.66	5.00	426.55	84.04	-77.42	-41.28	87.73	208.07	2.44	MWD	None
	80	449.08	33.49	211.84	5.00	430.73	86.70	-79.75	-42.72	90.47	208.18	2.10	MWD	None
	81	454.08	33.93	211.75	5.00	434.89	89.40	-82.11	-44.18	93.24	208.28	2.70	MWD	None
	82	459.08	34.32	211.71	5.00	439.03	92.12	-84.50	-45.66	96.04	208.39	2.38	MWD	None
	83	464.08	34.71	211.67	5.00	443.15	94.87	-86.91	-47.15	98.87	208.48	2.38	MWD	None
	84	469.08	35.15	211.63	5.00	447.25	97.65	-89.34	-48.65	101.73	208.57	2.69	MWD	None
	85	474.08	35.60	211.64	5.00	451.33	100.45	-91.81	-50.17	104.62	208.65	2.74	MWD	None
	86	479.08	36.06	211.71	5.00	455.38	103.29	-94.30	-51.70	107.54	208.74	2.82	MWD	None
	87	484.08	36.50	211.72	5.00	459.41	106.17	-96.82	-53.26	110.50	208.82	2.68	MWD	None
	88	489.08	36.99	211.72	5.00	463.42	109.07	-99.36	-54.83	113.49	208.89	2.99	MWD	None
	89	494.08	37.46	211.80	5.00	467.40	112.01	-101.93	-56.42	116.51	208.97	2.88	MWD	None
	90	499.08	37.90	211.80	5.00	471.35	114.97	-104.53	-58.03	119.56	209.04	2.68	MWD	None
	91	504.08	38.35	211.81	5.00	475.29	117.97	-107.15	-59.66	122.64	209.11	2.74	MWD	None
	92	509.08	38.99	211.91	5.00	479.19	121.00	-109.81	-61.31	125.76	209.18	3.92	MWD	None
	93	514.08	39.45	211.97	5.00	483.07	124.08	-112.49	-62.98	128.92	209.24	2.81	MWD	None
	94	519.08	39.98	211.97	5.00	486.91	127.18	-115.20	-64.67	132.11	209.31	3.23	MWD	None
	95	524.08	40.39	212.08	5.00	490.73	130.31	-117.93	-66.39	135.34	209.38	2.54	MWD	None
	96	529.08	40.95	212.15	5.00	494.52	133.48	-120.69	-68.12	138.59	209.44	3.43	MWD	None
	97	534.08	41.48	212.20	5.00	498.28	136.69	-123.48	-69.87	141.88	209.50	3.24	MWD	None
	98	539.08	41.93	212.23	5.00	502.02	139.92	-126.30	-71.65	145.20	209.57	2.75	MWD	None
	99	544.08	42.36	212.26	5.00	505.73	143.19	-129.14	-73.44	148.56	209.63	2.62	MWD	None
	100	549.08	42.84	212.31	5.00	509.41	146.48	-132.00	-75.24	151.94	209.68	2.93	MWD	None
	101	554.08	43.36	212.39	5.00	513.06	149.80	-134.88	-77.07	155.35	209.74	3.19	MWD	None
	102	559.08	43.91	212.47	5.00	516.67	153.16	-137.79	-78.92	158.80	209.80	3.37	MWD	None



103	564.08	44.39	212.54	5.00	520.26	156.55	-140.73	-80.79	162.27	209.86	2.94	MWD	None
104	569.08	44.88	212.59	5.00	523.82	159.97	-143.69	-82.68	165.78	209.92	2.99	MWD	None
105	574.08	45.35	212.68	5.00	527.35	163.43	-146.68	-84.59	169.32	209.97	2.89	MWD	None
106	579.08	45.99	212.81	5.00	530.84	166.91	-149.68	-86.53	172.89	210.03	3.94	MWD	None
107	584.08	46.34	212.87	5.00	534.31	170.43	-152.71	-88.49	176.50	210.09	2.15	MWD	None
108	589.08	46.91	212.92	5.00	537.74	173.97	-155.77	-90.46	180.13	210.15	3.48	MWD	None
109	594.08	47.52	212.90	5.00	541.14	177.55	-158.85	-92.45	183.79	210.20	3.72	MWD	None
110	599.08	48.11	212.89	5.00	544.49	181.17	-161.96	-94.46	187.49	210.25	3.60	MWD	None
111	604.08	48.55	212.90	5.00	547.82	184.81	-165.09	-96.49	191.22	210.31	2.68	MWD	None
112	609.08	48.99	212.94	5.00	551.11	188.48	-168.25	-98.54	194.98	210.36	2.69	MWD	None
113	614.08	49.61	213.03	5.00	554.37	192.17	-171.43	-100.60	198.77	210.41	3.80	MWD	None
114	619.08	49.96	213.14	5.00	557.60	195.90	-174.63	-102.68	202.58	210.46	2.19	MWD	None
115	624.08	50.61	213.13	5.00	560.80	199.65	-177.85	-104.79	206.42	210.51	3.96	MWD	None
116	629.08	51.13	213.28	5.00	563.95	203.44	-181.09	-106.91	210.30	210.56	3.25	MWD	None
117	634.08	51.57	213.33	5.00	567.07	207.26	-184.36	-109.06	214.20	210.61	2.69	MWD	None
118	639.08	52.25	213.45	5.00	570.16	211.10	-187.64	-111.22	218.13	210.66	4.19	MWD	None
119	644.08	52.76	213.55	5.00	573.20	214.98	-190.95	-113.41	222.09	210.71	3.15	MWD	None
120	649.08	53.34	213.68	5.00	576.21	218.89	-194.28	-115.62	226.08	210.76	3.59	MWD	None
121	654.08	53.70	213.68	5.00	579.18	222.82	-197.62	-117.85	230.10	210.81	2.19	MWD	None
122	659.08	54.45	213.76	5.00	582.11	226.78	-200.99	-120.10	234.14	210.86	4.59	MWD	None
123	664.08	54.97	213.82	5.00	585.00	230.78	-204.38	-122.37	238.22	210.91	3.18	MWD	None
124	669.08	55.76	213.80	5.00	587.84	234.80	-207.80	-124.66	242.33	210.96	4.82	MWD	None
125	674.08	56.38	213.73	5.00	590.64	238.86	-211.25	-126.96	246.47	211.01	3.80	MWD	None
126	679.08	56.97	213.77	5.00	593.38	242.95	-214.73	-129.29	250.64	211.05	3.60	MWD	None
127	684.08	57.55	213.86	5.00	596.09	247.07	-218.22	-131.63	254.84	211.10	3.57	MWD	None
128	689.08	58.12	213.83	5.00	598.75	251.21	-221.73	-133.98	259.07	211.14	3.48	MWD	None
129	694.08	58.80	213.81	5.00	601.36	255.38	-225.27	-136.36	263.33	211.19	4.15	MWD	None
130	699.08	59.51	213.82	5.00	603.93	259.58	-228.84	-138.74	267.62	211.23	4.33	MWD	None
131	704.08	60.06	213.82	5.00	606.44	263.81	-232.43	-141.15	271.93	211.27	3.35	MWD	None
132	709.08	60.74	213.81	5.00	608.91	268.06	-236.04	-143.57	276.28	211.31	4.15	MWD	None
133	714.08	61.41	213.80	5.00	611.33	272.35	-239.68	-146.00	280.65	211.35	4.08	MWD	None
134	719.08	62.00	213.77	5.00	613.70	276.66	-243.34	-148.45	285.05	211.39	3.60	MWD	None
135	724.08	62.60	213.80	5.00	616.03	280.99	-247.02	-150.91	289.47	211.42	3.66	MWD	None
136	729.08	63.20	213.78	5.00	618.30	285.34	-250.72	-153.39	293.92	211.46	3.66	MWD	None
137	734.08	63.89	213.68	5.00	620.53	289.72	-254.44	-155.87	298.39	211.49	4.24	MWD	None
138	739.08	64.17	213.74	5.00	622.72	294.12	-258.18	-158.37	302.88	211.53	1.74	MWD	None
139	744.08	64.56	213.70	5.00	624.88	298.53	-261.93	-160.87	307.39	211.56	2.39	MWD	None
140	749.08	64.79	213.71	5.00	627.02	302.95	-265.69	-163.38	311.90	211.59	1.40	MWD	None
141	754.08	64.83	213.72	5.00	629.15	307.38	-269.45	-165.89	316.42	211.62	0.25	MWD	None
142	759.08	64.85	213.69	5.00	631.28	311.81	-273.22	-168.40	320.95	211.65	0.21	MWD	None
143	764.08	64.76	213.66	5.00	633.41	316.23	-276.98	-170.91	325.47	211.68	0.57	MWD	None
144	769.08	64.66	213.65	5.00	635.54	320.65	-280.75	-173.42	329.99	211.70	0.61	MWD	None
145	774.08	64.49	213.66	5.00	637.69	325.07	-284.50	-175.92	334.50	211.73	1.04	MWD	None
146	779.08	64.35	213.70	5.00	639.85	329.48	-288.26	-178.42	339.01	211.76	0.88	MWD	None
147	784.08	64.25	213.74	5.00	642.01	333.89	-292.00	-180.92	343.51	211.78	0.65	MWD	None
148	789.08	64.16	213.77	5.00	644.19	338.30	-295.75	-183.42	348.01	211.81	0.57	MWD	None
149	794.08	64.18	213.81	5.00	646.37	342.70	-299.49	-185.93	352.51	211.83	0.25	MWD	None
150	799.08	64.02	213.83	5.00	648.55	347.10	-303.22	-188.43	357.00	211.86	0.98	MWD	None
151	804.08	63.78	213.83	5.00	650.75	351.50	-306.95	-190.93	361.49	211.88	1.46	MWD	None
152	809.08	63.63	213.83	5.00	652.97	355.88	-310.68	-193.42	365.97	211.91	0.91	MWD	None
153	814.08	63.55	213.85	5.00	655.19	360.27	-314.40	-195.92	370.44	211.93	0.50	MWD	None
154	819.08	63.63	213.90	5.00	657.42	364.65	-318.12	-198.41	374.92	211.95	0.56	MWD	None
155	824.08	63.72	213.95	5.00	659.63	369.04	-321.83	-200.91	379.40	211.98	0.61	MWD	None
156	829.08	63.97	213.97	5.00	661.84	373.43	-325.56	-203.42	383.88	212.00	1.53	MWD	None
157	834.08	64.27	213.98	5.00	664.02	377.84	-329.29	-205.94	388.38	212.02	1.83	MWD	None
158	839.08	64.53	213.97	5.00	666.18	382.25	-333.03	-208.46	392.89	212.04	1.59	MWD	None
159	844.08	65.01	214.01	5.00	668.31	386.68	-336.78	-210.98	397.41	212.07	2.93	MWD	None
160	849.08	65.47	214.01	5.00	670.41	391.13	-340.54	-213.52	401.95	212.09	2.80	MWD	None
161	854.08	65.90	214.04	5.00	672.46	395.59	-344.32	-216.07	406.50	212.11	2.63	MWD	None
162	859.08	66.47	214.04	5.00	674.48	400.07	-348.11	-218.63	411.07	212.13	3.47	MWD	None
163	864.08	66.94	214.05	5.00	676.46	404.57	-351.91	-221.21	415.66	212.15	2.87	MWD	None
164	869.08	67.48	214.10	5.00	678.40	409.09	-355.73	-223.79	420.27	212.17	3.30	MWD	None
165	874.08	67.94	214.10	5.00	680.29	413.62	-359.56	-226.38	424.89	212.19	2.80	MWD	None
166	879.08	68.48	214.12	5.00	682.15	418.17	-363.41	-228.99	429.53	212.22	3.29	MWD	None
167	884.08	68.97	214.15	5.00	683.96	422.74	-367.26	-231.60	434.19	212.24	2.99	MWD	None
168	889.08	69.43	214.15	5.00	685.74	427.32	-371.13	-234.22	438.86	212.26	2.80	MWD	None
169	894.08	69.84	214.17	5.00	687.48	431.91	-375.01	-236.86	443.54	212.28	2.50	MWD	None
170	899.08	70.11	214.19	5.00	689.19	436.51	-378.90	-239.49	448.24	212.30	1.65	MWD	None
171	904.08	70.37	214.22	5.00	690.88	441.12	-382.79	-242.14	452.94	212.32	1.59	MWD	None
172	909.08	70.40	214.29	5.00	692.56	445.74	-386.68	-244.79	457.65	212.34	0.44	MWD	None
173	914.08	70.50	214.38	5.00	694.23	450.36	-390.57	-247.45	462.36	212.36	0.80	MWD	None
174	929.77	69.92	213.75	15.69	699.55	464.82	-402.80	-255.72	477.12	212.41	1.61	MWD	None
175	958.90	70.38	217.36	29.13	709.44	491.79	-425.09	-271.65	504.47	212.58	3.59	MWD	None
176	1031.43												

182	1207.68	73.11	251.09	29.12	785.45	721.03	-556.70	-463.55	724.43	219.78	2.75	MWD	None
183	1236.43	73.19	255.64	28.75	793.79	745.27	-564.35	-489.98	747.37	220.97	3.60	MWD	None
184	1265.97	73.19	259.34	29.54	802.33	769.29	-570.47	-517.58	770.28	222.22	3.65	MWD	None
185	1295.26	75.10	260.12	29.29	810.33	792.63	-575.49	-545.30	792.81	223.46	2.14	MWD	None
186	1324.52	77.31	260.06	29.26	817.31	816.07	-580.38	-573.29	815.79	224.65	2.30	MWD	None
187	1353.14	80.46	259.60	28.62	822.83	839.30	-585.34	-600.93	838.89	225.75	3.39	MWD	None
188	1382.46	83.82	258.62	29.32	826.84	863.53	-590.83	-629.45	863.30	226.81	3.64	MWD	None
189	1411.86	84.45	254.99	29.40	829.84	888.56	-597.50	-657.92	888.74	227.76	3.80	MWD	None
190	1438.99	84.34	253.00	27.13	832.49	912.32	-604.95	-683.87	913.04	228.50	2.23	MWD	None
191	1469.73	84.22	251.43	30.74	835.56	939.68	-614.29	-712.99	941.12	229.25	1.55	MWD	None
192	1495.08	83.10	249.56	25.35	838.36	962.55	-622.70	-736.74	964.65	229.80	2.61	MWD	None
193	1524.61	83.35	248.29	29.53	841.84	989.48	-633.25	-764.10	992.40	230.35	1.33	MWD	None
194	1557.55	81.71	246.72	32.94	846.12	1019.80	-645.74	-794.28	1023.65	230.89	2.09	MWD	None
195	1586.20	81.97	245.06	28.65	850.19	1046.41	-657.32	-820.16	1051.07	231.29	1.77	MWD	None
196	1615.69	82.06	242.94	29.49	854.29	1074.13	-670.13	-846.41	1079.57	231.63	2.17	MWD	None
197	1645.11	82.29	241.37	29.42	858.29	1102.07	-683.74	-872.18	1108.24	231.91	1.63	MWD	None
198	1674.05	82.03	240.31	28.94	862.24	1129.74	-697.71	-897.21	1136.57	232.13	1.14	MWD	None
199	1703.12	82.32	238.35	29.07	866.20	1157.72	-712.40	-921.98	1165.15	232.31	2.06	MWD	None
200	1732.30	82.20	236.84	29.18	870.13	1186.01	-727.89	-946.39	1193.94	232.44	1.57	MWD	None
201	1761.47	82.34	235.21	29.17	874.05	1214.44	-744.05	-970.36	1222.79	232.52	1.69	MWD	None
202	1790.91	82.17	232.75	29.44	878.02	1243.30	-761.20	-993.96	1251.95	232.55	2.53	MWD	None
203	1819.75	82.34	230.57	28.84	881.91	1271.72	-778.92	-1016.37	1280.52	232.53	2.29	MWD	None
204	1849.17	82.20	228.35	29.42	885.86	1300.81	-797.87	-1038.52	1309.63	232.47	2.28	MWD	None
205	1878.57	82.21	225.34	29.40	889.85	1329.93	-817.79	-1059.77	1338.62	232.34	3.09	MWD	None
206	1907.72	83.13	222.85	29.15	893.57	1358.83	-838.56	-1079.89	1367.23	232.17	2.76	MWD	None
207	1936.37	83.16	219.37	28.65	896.99	1387.18	-859.98	-1098.59	1395.16	231.95	3.68	MWD	None
208	1965.65	83.33	216.22	29.28	900.44	1415.98	-882.96	-1116.40	1423.36	231.66	3.26	MWD	None
209	1994.86	83.27	219.15	29.21	903.85	1444.70	-905.91	-1134.13	1451.53	231.38	3.04	MWD	None
210	2024.29	83.27	221.55	29.43	907.30	1473.80	-928.19	-1153.06	1480.23	231.17	2.47	MWD	None
211	2053.19	83.24	220.75	28.90	910.69	1502.41	-949.80	-1171.94	1508.50	230.98	0.84	MWD	None
212	2082.34	82.86	221.32	29.15	914.22	1531.26	-971.62	-1190.94	1537.01	230.79	0.71	MWD	None
213	2111.43	82.87	221.69	29.09	917.83	1560.04	-993.24	-1210.07	1565.50	230.62	0.38	MWD	None
214	2140.76	82.95	221.72	29.33	921.45	1589.08	-1014.97	-1229.43	1594.26	230.46	0.09	MWD	None
215	2169.42	83.04	221.71	28.66	924.95	1617.46	-1036.20	-1248.36	1622.38	230.31	0.10	MWD	None
216	2198.60	82.92	221.88	29.18	928.51	1646.36	-1057.80	-1267.66	1651.03	230.16	0.22	MWD	None
217	2227.83	82.95	222.43	29.23	932.11	1675.31	-1079.30	-1287.13	1679.76	230.02	0.57	MWD	None
218	2257.56	83.07	223.04	29.73	935.73	1704.78	-1100.97	-1307.15	1709.03	229.89	0.63	MWD	None
219	2286.54	82.81	223.64	28.98	939.29	1733.52	-1121.89	-1326.89	1737.61	229.79	0.68	MWD	None
220	2315.08	82.92	223.72	28.54	942.83	1761.82	-1142.37	-1346.45	1765.77	229.69	0.14	MWD	None
221	2344.40	82.93	223.65	29.32	946.44	1790.90	-1163.41	-1366.55	1794.71	229.59	0.07	MWD	None
222	2373.54	82.81	224.10	29.14	950.06	1819.80	-1184.26	-1386.59	1823.48	229.50	0.48	MWD	None
223	2402.26	82.90	224.09	28.72	953.63	1848.28	-1204.72	-1406.42	1851.85	229.42	0.10	MWD	None
224	2431.99	82.78	224.18	29.73	957.34	1877.77	-1225.89	-1426.96	1881.23	229.33	0.15	MWD	None
225	2461.30	83.07	224.67	29.31	960.95	1906.85	-1246.67	-1447.32	1910.21	229.26	0.59	MWD	None
226	2490.43	82.98	224.61	29.13	964.49	1935.76	-1267.24	-1467.64	1939.03	229.19	0.11	MWD	None
227	2519.16	82.90	225.31	28.73	968.02	1964.27	-1287.41	-1487.78	1967.47	229.13	0.74	MWD	None
228	2548.71	82.84	225.23	29.55	971.68	1993.59	-1308.05	-1508.61	1996.72	229.07	0.10	MWD	None
229	2576.88	82.89	224.82	28.17	975.18	2021.54	-1327.81	-1528.39	2024.61	229.02	0.44	MWD	None
230	2606.68	83.04	223.80	29.80	978.83	2051.11	-1348.97	-1549.05	2054.08	228.95	1.05	MWD	None
231	2635.65	82.75	223.17	28.97	982.42	2079.84	-1369.83	-1568.83	2082.70	228.87	0.73	MWD	None
232	2665.14	83.07	222.28	29.49	986.06	2109.06	-1391.32	-1588.68	2111.80	228.79	0.97	MWD	None
233	2694.34	82.87	221.77	29.20	989.63	2137.98	-1412.85	-1608.09	2140.58	228.70	0.57	MWD	None
234	2723.69	83.10	221.82	29.35	993.22	2167.05	-1434.57	-1627.50	2169.50	228.61	0.24	MWD	None
235	2752.63	82.64	221.29	28.94	996.81	2195.69	-1456.06	-1646.55	2198.01	228.51	0.74	MWD	None
236	2781.37	83.01	221.24	28.74	1000.40	2224.12	-1477.49	-1665.36	2226.30	228.42	0.40	MWD	None
237	2810.86	83.04	221.21	29.49	1003.98	2253.31	-1499.51	-1684.65	2255.34	228.33	0.04	MWD	None
238	2840.20	83.07	221.43	29.34	1007.53	2282.35	-1521.38	-1703.88	2284.25	228.24	0.23	MWD	None
239	2868.83	83.12	221.37	28.63	1010.97	2310.69	-1542.70	-1722.67	2312.47	228.15	0.08	MWD	None
240	2898.20	82.98	221.17	29.37	1014.52	2339.76	-1564.62	-1741.90	2341.42	228.07	0.25	MWD	None
241	2926.78	82.87	221.21	28.58	1018.04	2368.04	-1585.96	-1760.58	2369.58	227.99	0.12	MWD	None
242	2956.18	83.01	221.48	29.40	1021.66	2397.13	-1607.86	-1779.86	2398.56	227.91	0.31	MWD	None
243	2984.65	82.72	221.70	28.47	1025.19	2425.31	-1628.99	-1798.61	2426.64	227.83	0.39	MWD	None
244	3014.30	83.21	223.15	29.65	1028.82	2454.69	-1650.71	-1818.46	2455.94	227.77	1.56	MWD	None
245	3043.56	82.55	223.31	29.26	1032.45	2483.70	-1671.87	-1838.34	2484.88	227.72	0.71	MWD	None
246	3073.02	83.12	223.13	29.46	1036.12	2512.90	-1693.17	-1858.36	2514.03	227.66	0.62	MWD	None
247	3112.02	82.84	222.53	39.00	1040.89	2551.56	-1721.55	-1884.68	2552.60	227.59	0.51	MWD	None
248	3131.41	82.98	222.60	19.39	1043.28	2570.77	-1735.73	-1897.69	2571.77	227.55	0.25	MWD	None
249	3160.44	83.13	223.05	29.03	1046.79	2599.55	-1756.86	-1917.28	2600.49	227.50	0.49	MWD	None
250	3198.90	82.95	223.10	38.46	1051.45	2637.69	-1784.75	-1943.35	2638.55	227.44	0.15	MWD	None
251	3228.02	82.72	222.88	29.12	1055.09	2666.55	-1805.88	-1963.05	2667.36	227.39			

262	3539.69	83.04	222.63	28.95	1093.35	2975.52	-2032.20	-2173.89	2975.84	226.93	0.00	MWD	None
263	3568.44	83.04	222.48	28.75	1096.83	3004.02	-2053.23	-2193.19	3004.30	226.89	0.16	MWD	None
264	3598.02	82.98	222.36	29.58	1100.43	3033.33	-2074.90	-2212.99	3033.57	226.84	0.14	MWD	None
265	3627.49	82.92	222.68	29.47	1104.05	3062.54	-2096.46	-2232.76	3062.74	226.80	0.33	MWD	None
266	3656.73	83.01	222.80	29.24	1107.63	3091.52	-2117.77	-2252.46	3091.68	226.77	0.16	MWD	None
267	3685.30	82.90	222.67	28.57	1111.13	3119.83	-2138.60	-2271.70	3119.97	226.73	0.18	MWD	None
268	3714.76	82.81	222.80	29.46	1114.80	3149.03	-2160.07	-2291.53	3149.13	226.69	0.16	MWD	None
269	3743.85	82.92	222.70	29.09	1118.41	3177.86	-2181.26	-2311.13	3177.93	226.66	0.16	MWD	None
270	3772.89	82.90	222.71	29.04	1121.99	3206.63	-2202.44	-2330.67	3206.68	226.62	0.02	MWD	None
271	3802.03	82.78	222.85	29.14	1125.63	3235.51	-2223.66	-2350.31	3235.52	226.59	0.19	MWD	None
272	3831.57	82.95	222.73	29.54	1129.30	3264.79	-2245.17	-2370.22	3264.77	226.55	0.21	MWD	None
273	3860.84	82.93	222.76	29.27	1132.89	3293.80	-2266.50	-2389.94	3293.76	226.52	0.04	MWD	None
274	3890.43	83.01	222.65	29.59	1136.52	3323.12	-2288.08	-2409.86	3323.06	226.48	0.14	MWD	None
275	3918.61	83.10	222.98	28.18	1139.92	3351.06	-2308.60	-2428.87	3350.98	226.45	0.37	MWD	None
276	3948.60	82.95	222.88	29.99	1143.56	3380.80	-2330.40	-2449.14	3380.69	226.42	0.18	MWD	None
277	3977.32	83.01	222.99	28.72	1147.07	3409.27	-2351.27	-2468.56	3409.14	226.39	0.13	MWD	None
278	4006.70	82.69	222.84	29.38	1150.73	3438.39	-2372.62	-2488.41	3438.24	226.36	0.37	MWD	None
279	4036.26	81.37	222.53	29.56	1154.83	3467.62	-2394.14	-2508.25	3467.45	226.33	1.40	MWD	None
280	4066.07	77.51	221.67	29.81	1160.29	3496.87	-2415.87	-2527.90	3496.67	226.30	4.04	MWD	None
281	4095.39	73.91	220.89	29.32	1167.53	3525.19	-2437.22	-2546.64	3524.97	226.26	3.82	MWD	None
282	4123.52	70.84	220.51	28.13	1176.04	3551.90	-2457.54	-2564.12	3551.65	226.22	3.35	MWD	None
283	4153.05	68.11	220.64	29.53	1186.40	3579.44	-2478.55	-2582.11	3579.17	226.17	2.82	MWD	None
284	4182.48	65.88	220.41	29.43	1197.90	3606.42	-2499.14	-2599.71	3606.13	226.13	2.32	MWD	None
285	4211.99	62.57	221.14	29.51	1210.73	3632.89	-2519.26	-2617.06	3632.59	226.09	3.49	MWD	None
286	4241.13	58.93	221.72	29.14	1224.96	3658.24	-2538.32	-2633.88	3657.92	226.06	3.84	MWD	None
287	4270.18	55.34	222.42	29.05	1240.73	3682.59	-2556.43	-2650.22	3682.26	226.03	3.82	MWD	None
288	4299.75	51.76	223.11	29.57	1258.29	3706.34	-2573.89	-2666.37	3706.00	226.01	3.73	MWD	None
289	4328.84	50.02	223.66	29.09	1276.64	3728.90	-2590.30	-2681.87	3728.55	226.00	1.88	MWD	None
290	4343.75	49.03	223.86	14.91	1286.32	3740.23	-2598.49	-2689.72	3739.88	225.99	2.05	MWD	None
291	4375.03	46.72	224.47	31.28	1307.30	3763.42	-2615.13	-2705.88	3763.07	225.98	2.29	MWD	None
292	4409.02	44.64	229.95	33.99	1331.06	3787.71	-2631.65	-2723.69	3787.36	225.98	3.98	MWD	None
293	4439.57	42.43	234.55	30.55	1353.21	3808.60	-2644.54	-2740.31	3808.27	226.02	3.85	MWD	None
294	4467.26	40.39	234.69	27.69	1373.97	3826.69	-2655.15	-2755.24	3826.38	226.06	2.25	MWD	None
295	4496.80	38.49	228.76	29.54	1396.79	3845.33	-2666.74	-2769.97	3845.03	226.09	4.35	MWD	None
296	4525.38	35.88	222.81	28.58	1419.57	3862.59	-2678.76	-2782.36	3862.29	226.09	4.74	MWD	None
297	4554.24	31.86	216.90	28.86	1443.53	3878.57	-2691.06	-2792.69	3878.26	226.06	5.48	MWD	None
298	4583.39	30.81	215.42	29.15	1468.43	3893.53	-2703.30	-2801.63	3893.19	226.02	1.36	MWD	None
299	4612.48	28.25	214.95	29.09	1493.74	3907.62	-2715.01	-2809.90	3907.28	225.98	2.69	MWD	None
300	4641.67	27.28	217.64	29.19	1519.57	3921.04	-2725.97	-2817.94	3920.68	225.95	1.65	MWD	None
301	4670.31	28.09	221.37	28.64	1544.93	3934.26	-2736.23	-2826.40	3933.89	225.93	2.04	MWD	None
302	4699.87	29.95	224.25	29.56	1570.78	3948.58	-2746.74	-2836.15	3948.21	225.92	2.40	MWD	None
303	4728.68	28.23	221.81	28.81	1595.96	3962.57	-2756.97	-2845.72	3962.20	225.91	2.21	MWD	None
304	4758.13	28.58	221.72	29.45	1621.86	3976.54	-2767.42	-2855.05	3976.17	225.89	0.36	MWD	None
305	4786.95	28.82	221.74	28.82	1647.14	3990.35	-2777.75	-2864.26	3989.97	225.88	0.25	MWD	None
306	4816.25	29.13	222.14	29.30	1672.77	4004.52	-2788.31	-2873.75	4004.13	225.86	0.38	MWD	None
307	4845.55	28.83	222.33	29.30	1698.40	4018.69	-2798.82	-2883.29	4018.30	225.85	0.33	MWD	None
308	4874.56	28.62	222.20	29.01	1723.84	4032.60	-2809.14	-2892.66	4032.21	225.84	0.23	MWD	None
309	4903.59	28.33	221.77	29.03	1749.36	4046.42	-2819.42	-2901.92	4046.02	225.83	0.37	MWD	None
310	4932.77	28.30	221.56	29.18	1775.05	4060.22	-2829.76	-2911.12	4059.83	225.81	0.11	MWD	None
311	4961.88	28.49	221.34	29.11	1800.66	4074.03	-2840.14	-2920.29	4073.63	225.80	0.23	MWD	None
312	4991.15	27.69	220.96	29.27	1826.48	4087.77	-2850.52	-2929.36	4087.37	225.78	0.85	MWD	None
313	5019.77	27.96	221.01	28.62	1851.79	4101.08	-2860.60	-2938.12	4100.68	225.77	0.29	MWD	None
314	5049.02	27.60	221.26	29.25	1877.67	4114.67	-2870.87	-2947.09	4114.27	225.75	0.39	MWD	None
315	5078.44	27.22	221.04	29.42	1903.79	4128.17	-2881.07	-2956.00	4127.77	225.74	0.41	MWD	None
316	5107.87	26.88	221.08	29.43	1930.00	4141.52	-2891.16	-2964.79	4141.11	225.72	0.35	MWD	None
317	5136.34	26.35	221.16	28.47	1955.45	4154.23	-2900.77	-2973.18	4153.82	225.71	0.57	MWD	None
318	5165.69	26.07	220.89	29.35	1981.78	4167.15	-2910.55	-2981.69	4166.74	225.69	0.32	MWD	None
319	5179.82	25.80	220.52	14.13	1994.49	4173.31	-2915.23	-2985.72	4172.90	225.68	0.68	MWD	None
320	5204.00	25.60	220.25	24.18	2016.28	4183.75	-2923.22	-2992.51	4183.34	225.67	0.29	Proj.	to TD

[(c) 2008 IDEAL ID14\_OC\_02]

Company:

ESSO Australia Pty Ltd

Well:

SNA A11A–ST

Field:

Snapper

Rig:

ISDL 175

State:

Victoria

VISION\* Resistivity

1:500 Measured Depth

Schlumberger

12.25 In. Section

