




SNA A11A-ST DrillMech RM 500TVD Run 2


IDEAL Version: ID14_OC_02 <TVD> Vertical Scale: 1:500


Graphics File Created: 11-Nov-2008 13:57











ARC Gamma Ray (GR_ARC) (GAPI) 200	Local comp 1 6in (LCOMP1) (PSI) 100000	MWD Lateral Vib (VIBLAT_RT) (G) 5	Surface RPM (RPM) (RPM) 0 200	CONT_INC (INCL_CONT_ RT) (DEG) 90	Equivalent Circulating Density (ECD_ARC) (LB/G) 14
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) (M/HR) 200 0	MWD Vib X-Axis (VIBX_ RT) (G) 5 0	STOR (TQA) (KFLB) 50	MWD Shock Peak (SHKP K_RT) (G) 0 200	CONT_AZIM (AZIM_CONT_ RT) (DEG) -180 180	Annulus Temperature (ATMP) (DEGC) 200
	SWOB (SWOB) (KLBF) 100		MWD Collar RPM (CRPM RT) (RPM)	PKPK RPM (Stick_RT) (RPM) 400	Standpipe Pressure (SPPA) (PSI) 5000

	(RPM)	
0	400	

	TUR_RPM (TRPM_RT)	
0	(RPM)	5000

	T_FLOW (TFLO)	
0	(GPM)	800