



PERFORM – DrillMech RT

IDEAL Version: ID14_OC_02 <TVD> Vertical Scale: 1:200


Graphics File Created: 08–Nov–2008 15:26








1325
TVD


1350
TVD



































ARC Gamma Ray (GR_ARC) 0 (GAPI) 200	Local comp 1 6in (LCOMP1) 0 (KPSI) 200	MWD Lateral Vib (VIBLAT_RT) 5 (G) 0	Surface RPM (RPM) 0 200	CONT_INC (INCL_CONT_ RT) 0 (DEG) 90	Equivalent Circulating Density (ECD_ARC) 9 (LB/G) 14
Rate of Penetration, Averaged over Last 5ft (ROP5_RM) 200 (M/HR) 0	MWD Vib X-Axis (VIBX_ RT) 5 (G) 0	STOR (TQA) 0 (KFLB) 50	MWD Shock Peak (SHKP K_RT) (G) 0 200	CONT_AZIM (AZIM_CONT_ RT) -180 (DEG) 180	Annulus Temperature (ATMP) 0 (DEGC) 200
	SWOB (SWOB) 0 (KLBF) 100		MWD Collar RPM (CRPM_ RT) (RPM) 0 400	PKPK_RPM (Stick_RT) 0 (RPM) 400	Standpipe Pressure (SPPA) 0 (PSI) 5000
					TUR_RPM (TRPM_RT) 0 (RPM) 5000
					T_FLOW (TFLO) 0 (GPM) 800