



Potassium	%	n/a									
<b>Environmental data</b>											
<b>GR</b>											
Mud weight	ppg	10.7									
Bit size	in.	8.5									
<b>Resistivity</b>											
<b>Neutron porosity</b>											
Hole Size	in.	8.5									
Mud weight	ppg	10.7									
Temperature	°C	93									
Mud salinity	ppk	57.5									
Formation salinity		n/a									
Recording rate 1	SEC	5 (ADN, SON)									
Recording rate 2	SEC	6 (ARC)									
Filtering GR		3 pts									
Filtering density		3 pts									
Filtering Neutron		3 pts									
Company representative	G. Doty	G. Campbell									
Schlumberger D&M Personnel	M. Y. Tan	C. Skiba	C. Hibberson	C. Soper	M. How						

<div>DISCLAIMER</div> <div>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</div>		
OTHER SERVICES FOR RUN2 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 2 Depth is referenced to Driller's Depth.  Gamma ray is corrected to mud weight, tool size and bit size.  Resistivity is borehole compensated and environmentally corrected.  Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure).  Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3.  POOH due to reaching TD of FTA A9b.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION		
RUN2	RUN	RUN
<div>DOWNHOLE EQUIPMENT</div>		

DOWNHOLE EQUIPMENT

6-3/4" adnVISION*	Neutron F	35.53	
	Neutron N	35.37	37.14
DHS: V8.3A02	Density S	34.42	
Blade OD: 8-1/4"	Density L	34.32	
S/N: 373	UltraSonic	33.94	
	R-O Port	33.17	
6-3/4" sonicVISION"			31.16
DHS: V6.6B04			
S/N: 649	Delta-T	27.90	
	R-O port	27.50	
8-3/8" ILS			23.71
S/N: OSS060187F			
6-3/4" Telescope*			22.82
MDC: FA27			
MEC: 373			
MDI: 1565	D&I	18.48	
MVC: 282	MVC	17.83	
8-3/8" ILS	R-O Port	11.50	
S/N: OSS0701135	T5	11.40	14.82
	T3	11.09	
6-3/4" arcVISION*	T1	10.79	
DHS: V9.3B13	Gamma Ray	10.43	13.82
S/N: FY68	Receiver	10.38	
	T2	10.13	
	T4	9.82	
ARC APRS		9.67	
6-3/4" PowerDrive Xceed*			7.91
S/N: 162			
8-1/2" Reed-Hycalog PDC Bit		0.00	0.25
S/N: 214577			

Maximum string diameter 8-1/2 in.  
All lengths in Meters

Variable Name	Variable Description	Run Name & Value
Run Number		2
General Information		
BHT_RM	Bottom Hole Temperature (RM)	93.000000
BSAL_RM	Mud Salinity (RM)	57.508289
BS_RM	Bit Size (RM)	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000
C_WS	Overpressure correction to Sw and M	1.000000
FEXP	Formation Factor Exponent (RM)	2.000000
FNUM	Formation Factor Enumerator (RM)	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT
MST_RM	Mud Sample temperature (RM)	75.000000
MW_RM	Mud Weight (RM)	10.700000
OBMF_RM	Oil Based Mud (RM)	YES
RHOF_RM	Mud Filtrate Density (RM)	1.000000
RHOM_RM	Matrix density (RM)	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	1000.000000
RWA_COMP_M	Rwa computation model	BASIC
RWA_DEN_AD	Rwa Density Input ADN	ROBB
RWA_DEN_CD	Rwa Density Input CDN	RHOB
RWA_DEN_IN	Rwa Density Input	ROBE
RWA_FORM_M	Rwa computation formation model	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	P34H
RWS_RM	Resistivity of Connate Water (RM)	1.000000
SHT_RM	Surface Hole Temperature (RM)	10.000000
TD_RM	Total Measured Depth (RM)	3746.000000
TWS_RM	Temperature of Connate Water (RM)	75.000000
VF_ILLI	Fraction of illite in shales	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000
ARC		
LWD_RM/STATION	FILE/PARAMETER	Station Time-frame file name Station
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	8.980860
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	8.986440
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	5.964700
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	5.966310
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	5.607090
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	5.602970
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	3.871990
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	3.869330
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	4.157310
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	4.162690
ABNT	Abnormal Transmitter Indicator	No_Tx_Failed
ADHS	ARC Down Hole Software Version	No_Tx_Failed
ANISO_COMP	Anisotropy Computation Option	YES
APICG	ARC5 Gamma Ray Gain Factor	1.039250
APIG	ARC Gamma Ray API Gain Factor	-1.000000
ATMP_ARC	ARC Select Temperature Channel	Annulus_Temp
ATRN	ARC Tool Run Number	2
ATSN	ARC Tool Serial Number	FY68
AZMF	Formation DIP Azimuth	0.000000
BH_COMPUTE	Borehole Inversion Computation Option	YES
CALG	ARC Gamma Ray Cal Gain Factor	1.039250
CALI_SLCT	ARC Caliper Selection	BITSIZE
CDPTH_ARC	Process Start Depth	100.000000
DIELEC_COM	Dielectric Computation Option	YES
DIPF	Formation DIP Angle	0.000000
ERRCT	Percentage Error Cutoff	4.500000
GRSH	GR Shale (Invasion Computation Cutoff)	1000.000000
HIGH_BLEND	High Resistivity Threshold for Blending	2.000000
INCLIN_B0	ARC Bias Constant (mg)	0.000000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	0.000000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	0.000000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	0.000000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	1.000000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	0.000000
INVAS_COMP	Invasion Computation Option	YES
JSD_ARC	ARC Acquisition start date	YES
KPER	Potassium Concentration (RM)	0.000000
LOW_BLEND	Low Resistivity Threshold for Blending	1.000000
MSWS	ARC Wizard Model Switch Window	5.000000
MULTIEFFEC	Multi Effect Option	YES
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	1.019090
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	-0.350909
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	-0.927967
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	0.284876
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	0.923579
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	-0.322901
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	-0.977645
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	0.287438
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	0.906331
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	-0.357818
POFFSET_AR	ARC: Pressure Offset	0.000000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	P34B
PSOF_ADJ T	ARC: User Input Phase offset	0.000000

RESTIK	ARC resistivity tick source	Phase
SHIG	ARC High Shock Risk Level	0.500000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	50.000000
SMED	ARC Medium Shock Risk Level	0.330000
SMIN	ARC Minimum Shock Risk Level	0.160000
SUPD	ARC Real Time Shock Update Rate	30.000000
TCODE_ARC	ARC Tool File Code	30.000000
TSIZ_ARC	ARC Tool Size	6.750000
UNIFORM_CO	Uniform Rock Option	YES
VERS_ARC	ARC Down hole software version Number	9.300000
WRK	Way to Report Potassium Concentration (RM)	K_by_Wgt_%

### ISONIC

FP_SD	First Sample delay	400.00
STC_CF	Center frequency of Filter	13.00
STC_BW	Bandwidth (kHz)	Default
STC_RWI	Receiver waveform ignored	None
PM_TOFF	Tool Time offset from surface system	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70
PPC_PF	Porosity Formula	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA
PPC_MDT	Matrix Delta-T	47.60
PPC_FDT	Fluid Delta-T	189.00

### ADN

ADN_CHASSI	ADN Chassis Type String	ADN
ADN_COLLAR	ADN Collar Type String	ADN
ADN_STAB_S	ADN Stabilizer Type String	ADN
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	YES
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	YES
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES
A_DHS	ADN Down Hole Software Version String	YES
CHI_RM	Caliper High limit from BS (RM)	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000
DEVI	Well Section Deviation	48.272999
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ
DTMUD	Delta-T for Mud	212.289993
DYN_IMG_CO	Generate Dynamic Normalized Image?	YES
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES
EVRL	EVR Process averaging number of samples (RM)	49
FCD	Future Casing (Outer) Diameter	0.000000
GCSE	Generalized Caliper Selection	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO
IBS	Intergal Blade Stabilizer Collar?	YES
IDQT	Image Derived Quality Threshold	1.000000
IHVS	Integrated Hole Volume Start Value(RM)	0.000000
IMAGE_MAX	Image SOA (Quadrant) Right Scale	2.500000
IMAGE_MAX	Image PEF(Segment) Right Scale	6.000000
IMAGE_MAX	Image RHOB(Segment) Right Scale	2.650000
IMAGE_MIN	Image SOA (Quadrant) Left Scale	0.000000
IMAGE_MIN	Image PEF(Segment) Left Scale	2.000000
IMAGE_MIN	Image RHOB(Segment) Left Scale	2.050000
JSD_ADN	ADN Acquisition start date	2.050000
LITHO_TYPE	Lithology (RM)	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11
SOCNL	Standoff Distance of the CNL Tool	1.000000
SSIZ_ADN	ADN Stabilizer Size	8.250000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.180000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES
VERS_ADN	ADN Downhole Software Version	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software vers:

## True Vertical Depth Log

IDEAL Version: ID12\_0C\_11


IDF


Format: VISION Service RM Log

Vertical Scale: 1:200

Graphics File Created: 29-Aug-2007 14:47


		ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)			
0.2		(OHMM)		2000	
ARC Gamma Ray (GR_ARC)		ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)		Thermal Neutron Porosity (TNPH)	
(GAPI)		(OHMM)		(PU)	
0		0.2		45	
200		2000		-15	






1150  
TVD

1175  
TVD







1200  
TVD

1225  
TVD

1250  
TVD









1275  
TVD


1300  
TVD






1325  
TVD


1350  
TVD






1375  
TVD

1400  
TVD







1425  
TVD

1450  
TVD

1475







1475  
TVD

1500  
TVD


1525  
TVD






1550  
TVD



1575  
TVD






1600  
TVD



1625  
TVD






1650  
TVD

1675  
TVD









1700  
TVD

1725  
TVD


1750  
TVD






1775  
TVD


1800  
TVD






1825  
TVD


1850  
TVD






1875  
TVD

1900  
TVD







1925  
TVD

1950  
TVD


1975  
TVD






2000  
TVD


2025  
TVD






2050  
TVD


2075  
TVD






2100  
TVD

2125  
TVD









2150  
TVD

2175  
TVD


2200  
TVD






2225  
TVD


2250  
TVD






2275  
TVD


2300  
TVD






2325  
TVD

2350  
TVD







2375  
TVD

2400  
TVD

2425








2425  
TVD

2450  
TVD

2475  
TVD





<div>Density Time After Bit (TAB_DEN) (HR)</div> <div>010</div>	<div>ADN Rotational Speed (RPM_ADN) (RPM)</div> <div>0250</div>	<div>ARC Phase-Shift Resistivity 16-in. at 2 MHz (P16H)</div> <div>0.2(OHMM)2000</div>	<div>Bulk Density Correction, Bottom (DRHB)</div> <div>-0.75(G/C3)0.25</div>
<div>Horizontal Hole Diameter (HORD) (IN)</div> <div>616</div>		<div>ARC Phase-Shift Resistivity 22-in. at 2 MHz (P22H)</div> <div>0.2(OHMM)2000</div>	<div>Photoelectric Factor, Bottom (PEB) (----</div> <div>010</div>
<div>Vertical Hole Diameter (VERD) (IN)</div> <div>616</div>		<div>ARC Phase-Shift Resistivity 28-in. at 2 MHz (P28H)</div> <div>0.2(OHMM)2000</div>	<div>Bulk Density, Bottom (ROBB) (G/C3)</div> <div>1.852.85</div>
<div>ARC Gamma Ray (GR_ARC) (GAPI)</div> <div>0200</div>		<div>ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)</div> <div>0.2(OHMM)2000</div>	<div>Thermal Neutron Porosity (TNPH) (PU)</div> <div>45-15</div>
		<div>ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)</div> <div>0.2(OHMM)2000</div>	

IDEAL Version: ID12\_0C\_11  
IDF

## True Vertical Depth Log

### 6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:  
Tool Name and Serial Number  
Collar Type and Serial Number  
Chassis Type and Serial Number  
Stabilizer Type and Serial Number  
Neutron Logging Source  
Density Logging Source  
Stabilizer Size  
Calibration Status

ADN6 - CA 373  
ADDC - AA  
ADSE - EA  
IES  
NSR - M 181  
GSR - J/Z 2152  
6.75 - in.  
Valid

Master: 6-Jul-2007 23:40

### 6.75-in. Azimuthal Density Neutron Calibration

#### Density: Magnesium Block




Phase	LS window 3 - Mg CPS	Value	Phase	SS window 1 - Mg CPS	Value	Phase	SS window 3 - Mg CPS	Value
Master	<div>250.041258000 (Minimum)(Nominal)(Maximum)</div>	1234	Master	<div>700.0935018000 (Minimum)(Nominal)(Maximum)</div>	3101	Master	<div>25002375045000 (Minimum)(Nominal)(Maximum)</div>	7425



Master: 6-Jul-2007 23:40

























### 6.75-in. Azimuthal Density Neutron Calibration


#### Density: Aluminum Block

Phase	LS window 3 - Al CPS	Value	Phase	SS window 1 - Al CPS	Value	Phase	SS window 3 - Al CPS	Value
Master	<div>50.00725.01400 (Minimum)(Nominal)(Maximum)</div>	183.8	Master	<div>500.042508000 (Minimum)(Nominal)(Maximum)</div>	1555	Master	<div>15001575030000 (Minimum)(Nominal)(Maximum)</div>	4633

Master: 6-Jul-2007 23:40														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Background														
Phase	LS window 3 – Background		CPS	Value	Phase	SS window 1 – Background		CPS	Value	Phase	SS window 3 – Background		CPS	Value
Master				50.04	Master				117.0	Master				519.0
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

Master: 6-Jul-2007 23:40										
6.75-in. Azimuthal Density Neutron Calibration										
Density: Water Block Check										
Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value	
Master				1.040	Master				1.151	
	1.024 (Minimum)	1.039 (Nominal)	1.054 (Maximum)			1.096 (Minimum)	1.126 (Nominal)	1.156 (Maximum)		

Master: 6-Jul-2007 23:40														
6.75-in. Azimuthal Density Neutron Calibration														
Neutron: 3-Point Calibration														
Phase	Far 1 tube 1	Air Point Measure	CPS	Value	Phase	Far 1 tube 1	Rod Point Measure	CPS	Value	Phase	Far 1 tube 1	H2O Point Measure	CPS	Value
Master				17.64	Master				4.361	Master				2.045
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 2	Air Point Measure	CPS	Value	Phase	Far 1 tube 2	Rod Point Measure	CPS	Value	Phase	Far 1 tube 2	H2O Point Measure	CPS	Value
Master				18.63	Master				4.548	Master				2.193
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 3	Air Point Measure	CPS	Value	Phase	Far 1 tube 3	Rod Point Measure	CPS	Value	Phase	Far 1 tube 3	H2O Point Measure	CPS	Value
Master				17.55	Master				4.417	Master				2.165
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 1	Air Point Measure	CPS	Value	Phase	Far 2 tube 1	Rod Point Measure	CPS	Value	Phase	Far 2 tube 1	H2O Point Measure	CPS	Value
Master				17.33	Master				4.720	Master				2.210
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 2	Air Point Measure	CPS	Value	Phase	Far 2 tube 2	Rod Point Measure	CPS	Value	Phase	Far 2 tube 2	H2O Point Measure	CPS	Value
Master				18.63	Master				4.693	Master				2.260
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 3	Air Point Measure	CPS	Value	Phase	Far 2 tube 3	Rod Point Measure	CPS	Value	Phase	Far 2 tube 3	H2O Point Measure	CPS	Value
Master				17.85	Master				4.397	Master				2.199
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Near 1 tube 1	Air Point Measure	CPS	Value	Phase	Near 1 tube 1	Rod Point Measure	CPS	Value	Phase	Near 1 tube 1	H2O Point Measure	CPS	Value
Master				478.6	Master				763.5	Master				336.3
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)	
Phase	Near 2 tube 1	Air Point Measure	CPS	Value	Phase	Near 2 tube 1	Rod Point Measure	CPS	Value	Phase	Near 2 tube 1	H2O Point Measure	CPS	Value
Master				484.6	Master				758.4	Master				337.5
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)	

Master: 6-Jul-2007 23:40			
6.75-in. Azimuthal Density Neutron Calibration			
Neutron: Water Block Check			
Phase	Far Neutron water porosity PU		Value
Master			99.51
	90.00 (Minimum)	100.0 (Nominal)	125.0 (Maximum)



## 6.75-in. Array Resistivity Compensated / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

ARC6 – BA

460











ARC675 Calibration Status

Valid

Master: 6-Jul-2007 11:12

## 6.75-in. Array Resistivity Compensated Calibration











Resistivity: Air

Phase	Phase-Shift T1	Value	Phase	Phase-Shift T2	Value	Phase	Phase-Shift T3	Value
Master		1.019	Master		-0.9280	Master		0.9236
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T4	Value	Phase	Phase-Shift T5	Value	Phase	Phase-Shift T1 at 400KHz	Value
Master		-0.9776	Master		0.9063	Master		-0.3509
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T2 at 400KHz	Value	Phase	Phase-Shift T3 at 400KHz	Value	Phase	Phase-Shift T4 at 400KHz	Value
Master		0.2849	Master		-0.3229	Master		0.2874
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T5 at 400KHz	Value						
Master		-0.3578						
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)							

Master: 6-Jul-2007 11:12

## 6.75-in. Array Resistivity Compensated Calibration


Resistivity: Air

Phase	Attenuation T1	Value	Phase	Attenuation T2	Value	Phase	Attenuation T3	Value
Master		8.981	Master		5.965	Master		5.607
	6.500 (Minimum)      8.500 (Nominal)      10.50 (Maximum)			4.500 (Minimum)      6.500 (Nominal)      8.500 (Maximum)			2.500 (Minimum)      4.500 (Nominal)      6.500 (Maximum)	
Phase	Attenuation T4	Value	Phase	Attenuation T5	Value	Phase	Attenuation T1 at 400KHz	Value
Master		3.872	Master		4.157	Master		8.986
	2.600 (Minimum)      4.600 (Nominal)      6.600 (Maximum)			1.600 (Minimum)      3.600 (Nominal)      5.600 (Maximum)			6.500 (Minimum)      8.500 (Nominal)      10.50 (Maximum)	
Phase	Attenuation T2 at 400KHz	Value	Phase	Attenuation T3 at 400KHz	Value	Phase	Attenuation T4 at 400KHz	Value
Master		5.966	Master		5.603	Master		3.869
	4.500 (Minimum)      6.500 (Nominal)      8.500 (Maximum)			2.500 (Minimum)      4.500 (Nominal)      6.500 (Maximum)			2.600 (Minimum)      4.600 (Nominal)      6.600 (Maximum)	
Phase	Attenuation T5 at 400KHz	Value						
Master		4.163						
	1.600 (Minimum)      3.600 (Nominal)      5.600 (Maximum)							

Master: 6-Jul-2007 11:59

## 6.75-in. Array Resistivity Compensated Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS	Value
Master		4.988
	2.780 (Minimum)      4.800 (Nominal)      6.000 (Maximum)	

SCHLUMBERGER

Survey report

29-Aug-2007 17:51:47

Page 1 of 4

Client.....: ESSO Australia Pty Ltd

Field.....: Postage

Well.....: FTA A9B  
API number.....  
Engineer.....: MYT/CH/CS  
  
RIG:.....: ISDL 175  
STATE:.....: Victoria

Spud date.....: 15-Aug-07  
Last survey date.....: 29-Aug-07  
Total accepted surveys....: 88  
MD of first survey.....: 1391.00 m  
MD of last survey.....: 3746.00 m

----- Survey calculation methods-----  
Method for positions.....: Minimum curvature  
Method for DLS.....: Mason & Taylor

----- Geomagnetic data -----  
Magnetic model.....: BGGM version 2007  
Magnetic date.....: 15-Aug-2007  
Magnetic field strength...: 1199.46 HCNT  
Magnetic dec (+E/W-).....: 13.21 degrees  
Magnetic dip.....: -68.86 degrees

----- Depth reference -----  
Permanent datum.....: Mean Sea Level  
Depth reference.....: Driller's Depth  
GL above permanent.....: -69.00 m  
KB above permanent.....: Top Drive  
DF above permanent.....: 42.50 m

----- MWD survey Reference Criteria -----  
Reference G.....: 1000.04 mGal  
Reference H.....: 1199.46 HCNT  
Reference Dip.....: -68.86 degrees  
Tolerance of G.....: (+/-) 2.50 mGal  
Tolerance of H.....: (+/-) 6.00 HCNT  
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Vertical section origin-----  
Latitude (+N/S-).....: -2.00 m  
Departure (+E/W-).....: 2.24 m

----- Platform reference point-----  
Latitude (+N/S-).....  
Departure (+E/W-).....

----- Corrections -----  
Magnetic dec (+E/W-).....: 13.21 degrees  
Grid convergence (+E/W-)..: -0.79 degrees  
Total az corr (+E/W-).....: 14.00 degrees  
(Total az corr = magnetic dec - grid conv)

Survey Correction Type ...:  
I=Sag Corrected Inclination  
M=Schlumberger Magnetic Correction  
S=Shell Magnetic Correction  
F=Failed Axis Correction  
R=Magnetic Resonance Tool Correction  
D=Dmag Magnetic Correction

Azimuth from Vsect Origin to target: 166.15 degrees

[[c)2007 IDEAL ID12\_OC\_11]  
SCHLUMBERGER Survey Report

29-Aug-2007 17:51:47

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
1	1391.00	57.26	189.80	0.00	1006.42	724.28	-784.59	-146.28	798.11	190.56	0.00	TIP	None
2	1395.50	56.52	188.54	4.50	1008.88	727.75	-788.31	-146.88	801.88	190.55	8.73	GYR	None
3	1405.70	57.13	185.07	10.20	1014.46	735.74	-796.79	-147.89	810.40	190.52	8.87	GYR	None
4	1410.15	57.12	185.58	4.45	1016.88	739.27	-800.51	-148.24	814.12	190.49	2.93	GYR	None
5	1440.10	57.19	179.49	29.95	1033.13	763.39	-825.63	-149.35	839.03	190.25	5.21	GYR	None
6	1466.10	54.87	178.36	26.00	1047.66	784.42	-847.18	-148.95	860.18	189.97	2.93	GYR	None
7	1485.40	52.97	175.01	19.30	1059.03	799.75	-862.75	-148.05	875.36	189.74	5.22	GYR	None
8	1505.40	52.50	170.13	20.00	1071.14	815.56	-878.53	-146.00	890.57	189.44	5.96	GYR	None
9	1530.80	51.90	168.37	25.40	1086.71	835.60	-898.24	-142.25	909.44	189.00	1.82	GYR	None
10	1550.60	51.50	168.28	19.80	1098.98	851.12	-913.46	-139.11	923.99	188.66	0.63	GYR	None
11	1564.95	51.16	168.45	14.35	1107.95	862.32	-924.43	-136.85	934.51	188.42	0.78	PUP	None
12	1593.30	50.17	168.48	28.35	1125.92	884.23	-945.92	-132.47	955.15	187.97	1.06	PUP	None
13	1621.71	50.05	166.75	28.41	1144.14	906.02	-967.21	-127.79	975.61	187.53	1.43	PUP	None
14	1650.61	49.25	165.08	28.90	1162.85	928.04	-988.57	-122.43	996.12	187.06	1.59	PUP	None
15	1679.24	49.93	162.42	28.63	1181.41	949.82	-1009.49	-116.33	1016.17	186.57	2.27	PUP	None
16	1707.31	51.98	160.05	28.07	1199.09	971.53	-1030.13	-109.31	1035.91	186.06	2.99	PUP	None
17	1735.98	53.13	156.95	28.67	1216.53	994.09	-1051.30	-100.97	1056.14	185.49	2.89	PUP	None
18	1764.43	53.16	154.58	28.45	1233.59	1016.48	-1072.06	-91.63	1075.96	184.89	2.03	PUP	None
19	1793.28	52.50	153.99	28.85	1251.02	1038.97	-1092.77	-81.65	1095.81	184.27	0.86	PUP	None
20	1821.77	50.97	154.49	28.49	1268.67	1060.86	-1112.91	-71.93	1115.24	183.70	1.69	PUP	None
21	1849.83	50.44	154.56	28.06	1286.44	1082.13	-1132.52	-62.59	1134.25	183.16	0.58	PUP	None
22	1877.48	50.75	154.34	27.65	1303.99	1103.05	-1151.79	-53.37	1153.03	182.65	0.39	PUP	None
23	1905.89	51.30	153.13	28.41	1321.86	1124.62	-1171.60	-43.60	1172.41	182.13	1.17	PUP	None
24	1934.47	50.53	152.72	28.58	1339.88	1146.21	-1191.35	-33.50	1191.82	181.61	0.89	PUP	None
25	1963.14	50.86	153.66	28.67	1358.04	1167.83	-1211.15	-23.50	1211.38	181.11	0.85	PUP	None
26	1991.60	50.93	152.39	28.46	1375.99	1189.34	-1230.83	-13.48	1230.91	180.63	1.06	PUP	None
27	2019.95	50.02	151.80	28.35	1394.03	1210.55	-1250.16	-3.25	1250.16	180.15	1.09	PUP	None
28	2048.43	50.25	152.25	28.48	1412.29	1231.75	-1269.46	7.01	1269.48	179.68	0.44	PUP	None
29	2076.87	50.61	152.51	28.44	1430.40	1253.05	-1288.89	17.17	1289.00	179.24	0.44	PUP	None
30	2105.24	50.21	151.98	28.37	1448.48	1274.27	-1308.23	27.35	1308.52	178.80	0.61	PUP	None

[[c)2007 IDEAL ID12\_OC\_11]  
SCHLUMBERGER Survey Report

29-Aug-2007 17:51:47

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
31	2133.88	50.49	152.25	28.64	1466.76	1295.66	-1327.73	37.66	1328.26	178.38	0.37	PUP	None
32	2161.97	50.61	151.95	28.09	1484.61	1316.70	-1346.89	47.81	1347.74	177.97	0.28	PUP	None
33	2190.45	50.34	152.03	28.48	1502.73	1338.00	-1366.29	58.13	1367.53	177.56	0.30	PUP	None
34	2219.15	50.36	152.00	28.70	1521.05	1359.43	-1385.80	68.50	1387.49	177.17	0.03	PUP	None
35	2247.45	50.83	151.97	28.30	1539.01	1380.63	-1405.11	78.77	1407.31	176.79	0.51	PUP	None
36	2275.68	50.35	151.56	28.23	1556.93	1401.76	-1424.32	89.09	1427.11	176.42	0.62	PUP	None
37	2304.24	49.92	152.29	28.56	1575.24	1423.01	-1443.66	99.41	1447.08	176.06	0.75	PUP	None
38	2332.69	50.24	152.55	28.45	1593.50	1444.20	-1463.00	109.51	1467.10	175.72	0.40	PUP	None
39	2361.45	50.40	152.55	28.76	1611.86	1465.72	-1482.65	119.71	1487.47	175.38	0.17	PUP	None
40	2390.06	50.52	152.43	28.61	1630.07	1487.16	-1502.22	129.90	1507.82	175.06	0.16	PUP	None

41	2419.00	50.35	152.30	28.94	1648.51	1508.83	-1521.98	140.25	1528.43	174.74	0.21	PUP	None
42	2447.71	50.15	152.71	28.71	1666.87	1530.28	-1541.56	150.44	1548.88	174.43	0.40	PUP	None
43	2476.11	50.35	152.71	28.40	1685.03	1551.51	-1560.97	160.45	1569.19	174.13	0.21	PUP	None
44	2504.23	50.14	152.17	28.12	1703.01	1572.52	-1580.13	170.45	1589.30	173.84	0.50	PUP	None
45	2532.23	50.27	152.37	27.88	1720.93	1593.39	-1600.17	180.46	1609.32	173.56	0.22	PUP	None

45	2532.22	50.27	152.57	27.99	1720.92	1593.39	-1599.17	180.48	1809.32	173.58	0.22	PUP	None
46	2560.17	50.22	153.20	27.95	1738.80	1614.30	-1618.28	190.29	1629.42	173.29	0.70	PUP	None
47	2588.65	50.02	152.83	28.48	1757.06	1635.58	-1637.75	200.20	1649.94	173.03	0.37	PUP	None
48	2616.70	49.87	152.56	28.05	1775.11	1656.46	-1656.83	210.05	1670.09	172.77	0.28	PUP	None
49	2645.11	50.39	152.68	28.41	1793.32	1677.66	-1676.19	220.08	1690.58	172.52	0.57	PUP	None
50	2673.81	50.13	153.10	28.70	1811.67	1699.14	-1695.83	230.14	1711.38	172.27	0.44	PUP	None
51	2702.36	49.76	153.18	28.55	1830.04	1720.43	-1715.33	240.01	1732.04	172.03	0.40	PUP	None
52	2730.45	50.49	152.89	28.09	1848.05	1741.43	-1734.54	249.79	1752.44	171.81	0.82	PUP	None
53	2758.87	49.72	153.61	28.42	1866.28	1762.68	-1754.01	259.60	1773.12	171.58	1.01	PUP	None
54	2787.31	50.01	153.70	28.44	1884.62	1783.91	-1773.50	269.25	1793.82	171.37	0.32	PUP	None
55	2815.54	50.27	154.24	28.23	1902.71	1805.09	-1792.97	278.76	1814.51	171.16	0.53	PUP	None
56	2843.71	49.97	153.55	28.17	1920.77	1826.21	-1812.38	288.27	1835.16	170.96	0.66	PUP	None
57	2870.87	50.40	153.49	27.16	1938.16	1846.57	-1831.05	297.57	1855.08	170.77	0.49	PUP	None
58	2898.99	50.90	152.48	28.12	1955.99	1867.74	-1850.42	307.45	1875.79	170.57	1.01	PUP	None
59	2926.96	50.29	152.82	27.97	1973.75	1888.76	-1869.62	317.38	1896.37	170.37	0.72	PUP	None
60	2955.05	50.59	152.90	28.09	1991.64	1909.83	-1888.89	327.26	1917.03	170.17	0.33	PUP	None

[(c)2007 IDEAL ID12\_OC\_11]  
SCHLUMBERGER Survey Report

29-Aug-2007 17:51:47

Page 4 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
61	2984.07	50.78	152.44	29.02	2010.02	1931.67	-1908.84	337.57	1938.46	169.97	0.42	PUP	None
62	3012.59	50.74	152.25	28.52	2028.06	1953.12	-1928.40	347.82	1959.52	169.78	0.16	PUP	None
63	3040.88	50.62	153.05	28.29	2045.99	1974.40	-1947.84	357.87	1980.44	169.59	0.68	PUP	None
64	3069.76	51.15	152.81	28.88	2064.21	1996.21	-1967.79	368.07	2001.92	169.41	0.59	PUP	None
65	3097.97	50.44	152.91	28.21	2082.04	2017.49	-1987.25	378.04	2022.89	169.23	0.77	PUP	None
66	3127.12	50.57	152.75	29.15	2100.58	2039.38	-2007.26	388.31	2044.47	169.05	0.19	PUP	None
67	3155.30	50.47	153.18	28.18	2118.50	2060.55	-2026.63	398.20	2065.38	168.88	0.37	PUP	None
68	3184.13	50.50	152.96	28.83	2136.84	2082.22	-2046.46	408.27	2086.79	168.72	0.18	PUP	None
69	3213.06	50.46	152.82	28.93	2155.25	2103.94	-2066.33	418.44	2108.27	168.55	0.12	PUP	None
70	3241.26	50.87	152.80	28.20	2173.13	2125.16	-2085.73	428.41	2129.27	168.39	0.44	PUP	None
71	3269.92	50.80	152.65	28.66	2191.23	2146.78	-2105.48	438.59	2150.67	168.23	0.14	PUP	None
72	3299.21	50.53	152.99	29.29	2209.79	2168.82	-2125.63	448.94	2172.52	168.07	0.39	PUP	None
73	3327.58	50.79	153.09	28.37	2227.78	2190.19	-2145.19	458.89	2193.72	167.93	0.29	PUP	None
74	3356.24	50.41	153.01	28.66	2245.97	2211.76	-2164.93	468.93	2215.13	167.78	0.41	PUP	None
75	3384.82	50.52	152.47	28.58	2264.16	2233.20	-2184.52	479.02	2236.43	167.63	0.46	PUP	None
76	3413.39	51.31	152.51	28.57	2282.17	2254.75	-2204.19	489.26	2257.84	167.48	0.84	PUP	None
77	3442.33	50.42	152.03	28.94	2300.44	2276.54	-2224.06	499.71	2279.51	167.34	1.02	PUP	None
78	3471.14	50.92	152.85	28.81	2318.70	2298.19	-2243.82	510.02	2301.05	167.19	0.85	PUP	None
79	3499.59	50.60	152.96	28.45	2336.69	2319.64	-2263.43	520.05	2322.41	167.06	0.35	PUP	None
80	3527.61	50.89	153.65	28.02	2354.42	2340.79	-2282.82	529.80	2343.49	166.93	0.66	PUP	None
81	3556.38	50.20	153.74	28.77	2372.71	2362.48	-2302.73	539.65	2365.12	166.81	0.73	PUP	None
82	3584.17	50.55	153.39	27.79	2390.43	2383.37	-2321.90	549.17	2385.96	166.69	0.48	PUP	None
83	3611.78	50.47	153.61	27.61	2407.99	2404.16	-2340.97	558.68	2406.71	166.58	0.21	PUP	None
84	3640.27	50.51	152.95	28.49	2426.11	2425.59	-2360.60	568.57	2428.11	166.46	0.55	PUP	None
85	3668.34	50.44	152.85	28.07	2443.98	2446.67	-2379.87	578.43	2449.16	166.34	0.11	PUP	None
86	3696.75	50.01	153.08	28.41	2462.15	2467.93	-2399.32	588.35	2470.41	166.22	0.50	PUP	None
87	3726.16	50.34	152.87	29.41	2480.99	2489.92	-2419.44	598.62	2492.40	166.10	0.38	PUP	None
88	3746.00	50.83	153.19	19.84	2493.59	2504.85	-2433.10	605.57	2507.33	166.02	0.84	Projection to TD	

[(c)2007 IDEAL ID12\_OC\_11]

Company:
**ESSO Australia Pty Ltd**

Well:
**FTA A9b**

Field:
**Fortescue**

Rig:
**ISDL 175**

State:
**Victoria**

**8.5 in. Section**

**Schlumberger**

**VISION Service**  
**1:200 True Vertical Depth**  
**Recorded Mode Log (Trip-Out)**

