

ESSO Australia Pty Ltd

8.5 in. Section

FTA A10AST1

Fortescue

ISDL 175 State: Victoria

Rig:		ISDL 175	
Field:		Fortescue	
Location:		Bass Strait	
Well:		FTA A10AST1	
Company:		ESSO Australia Pty Ltd	
<div>VISION Resistivity 1:200 True Vertical Depth Recorded Mode Log</div>			
Location			
Total depth:	4410.3 m	K.B. Top Drive	
Spud date:	23-Jul-07	G.L. -69.0 m	
Runs:	2 To 2	D.F. 42.5 m	
		Elevation	
Permanent datum:	Mean Sea Level	Elev.: 0.0 m	
Log measured from:	Drill Floor	42.5 m above Perm. datum	
Depth reference:	Driller's Depth		
Service Order no.	X = E 611,592.48 m	Longitude	Latitude
07ASQ0018	Y = N 5,748,242.46 m	E 148° 16' 41.149"S	38° 24' 25.529"

Depth logged:	2920.0 m	To 4400.3 m	Mag decl:	13.210° deg.	Other services:	
Date logged:	29-Jul-07	To 01-Aug-07	Mag dip:	-68.862° deg.	See Remarks	
Bore hole record			Casing record			
Hole size	from	to	Size	Density	from	to
8.5 in.	2780.0 m	4410.3 m	9.63 in.	43.5 lb/ft	21.0 m	2780.0 m
Type		Mud record				
	from	to	Min	Max	from	to
Accolade SBM	2780.0 m	4410.3 m	56.52 deg	66.41 deg	2780.0 m	2960.0 m
			61.15 deg	66.89 deg	2960.0 m	4410.3 m
Surface equipment		Software record				
Unit	Esso Office Unit	IDEAL Wis	ID12_0c_11			
Depth system	PDA	SPM	hspm12_0c_04			
		LWD	See Remarks			
		MWD	See Remarks			

Bit Run Summary


Run number		2								
Bit size	in.	8.5								
Bit start depth	m	2958.0								
Bit end depth	m	4410.3								
Top interval logged	m	2920.0								
Bottom interval logged	m	4400.3								
Begin log: time		15:40								
Begin log: date		29-Jul-07								
End log: time		21:18								
End log: date		01-Aug-07								
Mud data										
Depth	m	4410.3								
Type		Accolade SBM								
Mud weight	ppg	11.3								
Solids	%	16.6								
Chlorides	mg/L	47,966								
Rm	ohm.m@°C	n/a								
Rmf	ohm.m@°C	n/a								
Rmc	ohm.m@°C	n/a								

Potassium	%	n/a									
Environmental data											
GR											
Mud weight	ppg	11.3									
Bit size	in.	8.5									
Resistivity											
Neutron porosity											
Hole Size	in.	8.5									
Mud weight	ppg	11.3									
Temperature	°C	100									
Mud salinity	ppk	59.4									
Formation salinity		n/a									
Recording rate 1	SEC	5 (ADN, SON)									
Recording rate 2	SEC	6 (ARC)									
Filtering GR		3 pts									
Filtering density		3 pts									
Filtering Neutron		3 pts									
Company representative	G. Campbell	R. Spence	M. Calcicutt								
Schlumberger D&M Personnel	B. Pattarakorn	A. Kohli	M. Lu	C. Cocks	M. How						

<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
OTHER SERVICES FOR RUN2 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 2 Depth is referenced to Driller's Depth. Gamma ray readings are corrected for mud weight, tool size and bit size. Resistivity is borehole compensated and environmentally corrected. Neutron Porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity and mud hydrogen index (a factor of mud weight, mud temperature and pressure). Neutron Porosity is calculated using a limestone matrix density of 2.71 g/cm3. Delta-T is borehole compensated. POOH due to reaching TD of FTA A10AST1.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION		
RUN2	RUN	RUN
DOWNHOLE EQUIPMENT		

DOWNHOLE EQUIPMENT



Maximum string diameter 8.50 in.
All lengths in Meters

Variable Name	Variable Description	Run Name & Value
Run Number		2
General Information		
BHT_RM	Bottom Hole Temperature (RM)	100.000000
BSAL_RM	Mud Salinity (RM)	59.400000
BS_RM	Bit Size (RM)	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000
C_WS	Overpressure correction to Sw and M	1.000000
FEXP	Formation Factor Exponent (RM)	2.000000
FNUM	Formation Factor Enumerator (RM)	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT
MST_RM	Mud Sample temperature (RM)	20.000000
MW_RM	Mud Weight (RM)	11.300000
OBMF_RM	Oil Based Mud (RM)	YES
RHOF_RM	Mud Filtrate Density (RM)	1.000000
RHOM_RM	Matrix density (RM)	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	1000.000000
RWA_COMP_M	Rwa computation model	BASIC
RWA_DEN_AD	Rwa Density Input ADN	RHOB
RWA_DEN_CD	Rwa Density Input CDN	RHOB
RWA_DEN_IN	Rwa Density Input	RHOB
RWA_FORM_M	Rwa computation formation model	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	RT
RWS_RM	Resistivity of Connate Water (RM)	1.000000
SHT_RM	Surface Hole Temperature (RM)	
TD_RM	Total Measured Depth (RM)	4410.000000
TWS_RM	Temperature of Connate Water (RM)	23.000000
VF_ILLI	Fraction of illite in shales	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000
ARC		
LWD_RM/STATION_FILE/	PARAMETERStation Time-frame file name	Station
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	8.454470
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	8.428760
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	6.487210
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	6.520190
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	5.081830
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	5.049050
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	4.393750
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	4.421190
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	3.633010
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	3.610840
ABNT	Abnormal Transmitter Indicator	No_Tx_Failed
ADHS	ARC Down Hole Software Version	No_Tx_Failed
ANISO_COMP	Anisotropy Computation Option	YES
APICG	ARC5 Gamma Ray Gain Factor	1.070470
APIG	ARC Gamma Ray API Gain Factor	-1.000000
ATMP_ARC	ARC Select Temperature Channel	Annulus_Temp
ATRN	ARC Tool Run Number	2
ATSN	ARC Tool Serial Number	Annulus_Temp
AZMF	Formation DIP Azimuth	0.000000
BH_COMPUTE	Borehole Inversion Computation Option	YES
CALG	ARC Gamma Ray Cal Gain Factor	1.070470
CALI_SLCT_	ARC Caliper Selection	BITSIZE
CDPTH_ARC	Process Start Depth	100.000000
DIELEC_COM	Dielectric Computation Option	YES
DIPF	Formation DIP Angle	0.000000
ERRCT	Percentage Error Cutoff	4.500000
GRSH	GR Shale (Invasion Computation Cutoff)	1000.000000
HIGH_BLEND	High Resistivity Threshold for Blending	2.000000
INCLIN_B0	ARC Bias Constant (mg)	0.000000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	0.000000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	0.000000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	0.000000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	1.000000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	0.000000
INVAS_COMP	Invasion Computation Option	YES
JSD_ARC	ARC Acquisition start date	YES
KPER	Potassium Concentration (RM)	0.000000
LOW_BLEND	Low Resistivity Threshold for Blending	1.000000
MSWS	ARC Wizard Model Switch Window	5.000000
MULTIEFFEC	Multi Effect Option	YES
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	1.806140
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	-0.319793
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	-1.722540
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	0.224298
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	1.739660
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	-0.287066
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	-1.763690
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	0.206005
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	1.719260
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	-0.300926
POFFSET_AR	ARC: Pressure Offset	0.000000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	P34B
PSOF_ADJ_T	ARC: User Input Phase offset	0.000000

RESTIK	ARC resistivity tick source	Phase
SHIG	ARC High Shock Risk Level	0.500000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore) (RM)	50.000000
SMED	ARC Medium Shock Risk Level	0.330000
SMIN	ARC Minimum Shock Risk Level	0.160000
SUPD	ARC Real Time Shock Update Rate	30.000000
TCODE_ARC	ARC Tool File Code	30.000000
TSIZ_ARC	ARC Tool Size	6.750000
UNIFORM_CO	Uniform Rock Option	YES
VERS_ARC	ARC Down hole software version Number	9.300000
WRK	Way to Report Potassium Concentration (RM)	K_by_Wgt_%

ISONIC

FP_SD	First Sample delay	400.00
STC_CF	Center frequency of Filter	13.00
STC_BW	Bandwidth (kHz)	Default
STC_RWI	Receiver waveform ignored	None
PM_TOFF	Tool Time offset from surface system	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70
PPC_PF	Porosity Formula	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA
PPC_MDT	Matrix Delta-T	47.60
PPC_FDT	Fluid Delta-T	189.00

ADN

ADN_CHASSI	ADN Chassis Type String	ADN
ADN_COLLAR	ADN Collar Type String	ADN
ADN_STAB_S	ADN Stabilizer Type String	ADN
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	YES
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	YES
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES
A_DHS	ADN Down Hole Software Version String	YES
CHI_RM	Caliper High limit from BS (RM)	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000
DEVI	Well Section Deviation	56.070000
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ
DTMUD	Delta-T for Mud	216.800003
DYN_IMG_CO	Generate Dynamic Normalized Image?	NO
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES
EVRL	EVR Process averaging number of samples (RM)	49
FCD	Future Casing (Outer) Diameter	0.000000
GCSE	Generalized Caliper Selection	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO
IBS	Intergal Blade Stabilizer Collar?	YES
IDQT	Image Derived Quality Threshold	2.000000
IHVS	Integrated Hole Volume Start Value(RM)	0.000000
IMAGE_MAX_	Image SOA (Quadrant) Right Scale	2.500000
IMAGE_MAX_	Image PEF(Segment) Right Scale	6.000000
IMAGE_MAX_	Image RHOB(Segment) Right Scale	2.650000
IMAGE_MIN_	Image SOA (Quadrant) Left Scale	0.000000
IMAGE_MIN_	Image PEF(Segment) Left Scale	2.000000
IMAGE_MIN_	Image RHOB(Segment) Left Scale	2.050000
JSD_ADN	ADN Acquisition start date	2.050000
LITHO_TYPE	Lithology (RM)	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11
SOCNL	Standoff Distance of the CNL Tool	1.000000
SSIZ_ADN	ADN Stabilizer Size	8.170000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.300000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES
VERS_ADN	ADN Downhole Software Version	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software version 2.0c

IDEAL Version: ID12_OC_11





IDF


ARC6A-AA	id12_Oc_01	ADN	id12_Oc_01
----------	------------	-----	------------

Format: VISION Resistivity 2MHz	Vertical Scale: 1:200	Graphics File Created: 07-Aug-2007 16:06
---------------------------------	-----------------------	--

ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)		ARC Attenuation Resistivity 40-in. at 2 MHz (A40H)	
0.2	(OHMM) 2000	0.2	(OHMM) 2000
ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)		ARC Attenuation Resistivity 34-in. at 2 MHz (A34H)	
0.2	(OHMM) 2000	0.2	(OHMM) 2000
ARC Phase-Shift Resistivity 28-in. at 2 MHz (P28H)		ARC Attenuation Resistivity 28-in. at 2 MHz (A28H)	


Rate of Penetration, Averaged over Last






1900
TVD

1925
TVD






1950
TVD


1975
TVD






2000
TVD


2025
TVD






2050
TVD

2075
TVD







2100
TVD

2125
TVD


2150
TVD






2175
TVD


2200
TVD






2225
TVD


2250
TVD






2275
TVD

2300
TVD







2325
TVD

2350
TVD


2375
TVD







2400
TVD



2425
TVD





2450
TVD

2475
TVD



			ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)	ARC Attenuation Resistivity 40-in. at 2 MHz (A40H)
			0.2 (OHMM) 2000	0.2 (OHMM) 2000

IDEAL Version: ID12_0C_11
IDF

ARC6A-AA	id12_0c_01	ADN	id12_0c_01
----------	------------	-----	------------

6.75-in. Azimuthal Density Neutron / Equipment Identification

Primary Equipment:		
Tool Name and Serial Number	ADN6 - CA	437
Collar Type and Serial Number	ADDC - AA	
Chassis Type and Serial Number	ADSE - EA	
Stabilizer Type and Serial Number	IBS	AD41
Neutron Logging Source	NSR - M	181
Density Logging Source	GSR - J/Z	2152
Stabilizer Size	8.25 - in.	
Calibration Status	Valid	

Master: 5-Jun-2007 22:52														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Magnesium Block														
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value	Phase	SS window 3 – Mg CPS			Value
Master				1260	Master				3103	Master				7772
250.0 4125 8000 (Minimum) (Nominal) (Maximum)					700.0 9350 18000 (Minimum) (Nominal) (Maximum)					2500 23750 45000 (Minimum) (Nominal) (Maximum)				











Master: 5-Jun-2007 22:52														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				190.0	Master				1596	Master				4930
50.00 725.0 1400 (Minimum) (Nominal) (Maximum)					500.0 4250 8000 (Minimum) (Nominal) (Maximum)					1500 15750 30000 (Minimum) (Nominal) (Maximum)				


Master: 5-Jun-2007 22:52														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Background														
Phase	LS window 3 – Background CPS			Value	Phase	SS window 1 – Background CPS			Value	Phase	SS window 3 – Background CPS			Value
Master				46.17	Master				130.4	Master				560.4
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

Master: 5-Jun-2007 22:52													
6.75-in. Azimuthal Density Neutron Calibration													
Density: Water Block Check													
Phase	Long spacing water density G/C3					Value	Phase	Short spacing water density G/C3					Value
Master						1.040	Master						1.135
	1.024 (Minimum)		1.039 (Nominal)		1.054 (Maximum)			1.096 (Minimum)		1.126 (Nominal)		1.156 (Maximum)	

Master: 5-Jun-2007 22:52														
6.75-in. Azimuthal Density Neutron Calibration														
Neutron: 3-Point Calibration														
Phase	Far 1 tube 1 Air	Point Measure	CPS	Value	Phase	Far 1 tube 1 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 1 H2O	Point Measure	CPS	Value
Master				22.54	Master				5.441	Master				2.677
13.30 19.05 24.70 (Minimum) (Nominal) (Maximum)					3.400 4.857 6.200 (Minimum) (Nominal) (Maximum)					1.600 2.363 3.100 (Minimum) (Nominal) (Maximum)				
Phase	Far 1 tube 2 Air	Point Measure	CPS	Value	Phase	Far 1 tube 2 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 2 H2O	Point Measure	CPS	Value
Master				23.65	Master				5.587	Master				2.757
13.30 19.05 24.70 (Minimum) (Nominal) (Maximum)					3.400 4.857 6.200 (Minimum) (Nominal) (Maximum)					1.600 2.363 3.100 (Minimum) (Nominal) (Maximum)				
Phase	Far 1 tube 3 Air	Point Measure	CPS	Value	Phase	Far 1 tube 3 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 3 H2O	Point Measure	CPS	Value
Master				23.24	Master				5.623	Master				2.714
13.30 19.05 24.70 (Minimum) (Nominal) (Maximum)					3.400 4.857 6.200 (Minimum) (Nominal) (Maximum)					1.600 2.363 3.100 (Minimum) (Nominal) (Maximum)				

Master: 7-May-2007 12:04

Resistivity: Air														
Phase	Attenuation T1			Value	Phase	Attenuation T2			Value	Phase	Attenuation T3			Value
Master				8.454	Master				6.487	Master				5.082
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)			2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		
Phase	Attenuation T4			Value	Phase	Attenuation T5			Value	Phase	Attenuation T1 at 400KHz			Value
Master				4.394	Master				3.633	Master				8.429
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)			6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)		
Phase	Attenuation T2 at 400KHz			Value	Phase	Attenuation T3 at 400KHz			Value	Phase	Attenuation T4 at 400KHz			Value
Master				6.520	Master				5.049	Master				4.421
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)			2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)		
Phase	Attenuation T5 at 400KHz			Value										
Master				3.611										
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)											

Master: 7-May-2007 10:29			
6.75-in. Array Resistivity Compensated Calibration			
Gamma Ray: Blanket			
Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS		Value
Master			5.138
	2.780 (Minimum)	4.800 (Nominal)	6.000 (Maximum)

SCHLUMBERGER

Survey report

2-Aug-2007 05:34:29

Page 1 of 3

Client..... ESSO Australia Pty Ltd
Field..... Fortescue

Well..... FTA A10AST1
API number..... 07ASQ0018
Engineer..... BP/AK/ML

Spud date..... 23-Jul-07
Last survey date..... 02-Aug-07
Total accepted surveys... 60
MD of first survey..... 2780.00 m
MD of last survey..... 4410.00 m

Rig:..... ISDL 175
State:..... Victoria

----- Survey calculation methods-----
Method for positions..... Minimum curvature
Method for DLS..... Mason & Taylor

----- Depth reference -----
Permanent datum..... Mean Sea Level
Depth reference..... Driller's Depth
GL above permanent..... -69.00 m
KB above permanent..... Top Drive
DF above permanent..... 42.50 m

----- Vertical section origin-----
Latitude (+N/S-)..... -1.90 m
Departure (+E/W-)..... 4.37 m

----- Geomagnetic data -----
Magnetic model..... BGGM version 2007
Magnetic date..... 24-Jul-2007
Magnetic field strength... 1199.50 HCNT
Magnetic dec (+E/W-)..... 13.21 degrees
Magnetic dip..... -68.86 degrees

----- MWD survey Reference Criteria -----
Reference G..... 1000.04 mGal
Reference H..... 1199.50 HCNT
Reference Dip..... -68.86 degrees
Tolerance of G..... (+/-) 2.50 mGal
Tolerance of H..... (+/-) 6.00 HCNT
Tolerance of Dip..... (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-)..... 13.21 degrees
Grid convergence (+E/W-).. -0.79 degrees
Total az corr (+E/W-)..... 14.00 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2007 IDEAL ID12_0C_11]
SCHLUMBERGER Survey Report

2-Aug-2007 05:34:29

Page 2 of 3

Seq	Measured depth	Incl angle	Azimuth angle	Course length	TVD depth	Vertical section	Displ +N/S-	Displ +E/W-	Total displ	At Azim	DLS (deg/100f)	Srvy tool type	Tool Corr
#	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(m)	(deg)			(deg)
1	2780.00	56.52	353.72	0.00	1766.63	1941.12	1862.19	-588.22	1952.88	342.47	0.00	TIP	None
2	2787.92	59.39	352.18	7.92	1770.83	1947.82	1868.85	-589.05	1959.48	342.51	12.13	GYR	None
3	2825.40	66.41	356.27	37.48	1787.90	1981.03	1902.02	-592.36	1992.13	342.70	6.43	GYR	None
4	2855.50	65.35	356.43	30.10	1800.20	2008.31	1929.44	-594.11	2018.83	342.89	1.08	GYR	None
5	2885.20	64.56	357.26	29.70	1812.77	2034.99	1956.30	-595.59	2044.96	343.07	1.12	GYR	None
6	2898.90	63.11	357.38	13.70	1818.81	2047.17	1968.58	-596.17	2056.88	343.15	3.23	GYR	None

7	2937.15	60.27	356.53	38.25	1836.95	2080.55	2002.21	-597.95	2089.59	343.37	2.34	PUP	None
8	2953.67	60.38	356.27	16.52	1845.13	2094.80	2016.53	-598.85	2103.58	343.46	0.46	PUP	None
9	2982.87	61.15	358.04	29.20	1859.39	2120.05	2041.98	-600.12	2128.34	343.62	1.80	PUP	None
10	3011.63	63.13	0.63	28.76	1872.83	2145.09	2067.40	-600.41	2152.82	343.81	3.21	PUP	None
11	3040.02	63.90	2.08	28.39	1885.50	169.95	2092.80	-599.81	2177.06	344.01	1.62	PUP	None
12	3068.87	64.15	1.21	28.85	1898.13	2195.30	2118.73	-599.06	2201.79	344.21	0.87	PUP	None
13	3097.14	65.64	359.83	28.27	1910.13	2220.42	2144.33	-598.83	2226.37	344.40	2.10	PUP	None
14	3125.96	66.67	359.38	28.82	1921.78	2246.37	2170.68	-599.01	2251.82	344.57	1.17	PUP	None
15	3153.83	66.89	358.11	27.87	1932.77	2271.64	2196.29	-599.57	2276.66	344.73	1.30	PUP	None
16	3182.85	65.89	357.76	29.02	1944.39	2297.94	2222.86	-600.53	2302.55	344.88	1.10	PUP	None
17	3210.95	64.25	358.49	28.10	1956.23	2323.13	2248.33	-601.37	2327.37	345.03	1.92	PUP	None
18	3239.64	63.16	359.34	28.69	1968.94	2348.50	2274.05	-601.85	2352.34	345.18	1.41	PUP	None
19	3268.11	63.16	359.50	28.47	1981.80	2373.52	2299.45	-602.11	2376.97	345.33	0.15	PUP	None
20	3297.21	63.19	0.12	29.10	1994.93	2399.06	2325.42	-602.20	2402.12	345.48	0.58	PUP	None
21	3325.97	63.39	0.22	28.76	2007.85	2424.30	2351.11	-602.12	2426.98	345.64	0.23	PUP	None
22	3354.40	63.35	0.44	28.43	2020.60	2449.26	2376.52	-601.98	2451.58	345.79	0.22	PUP	None
23	3382.78	63.89	1.82	28.38	2033.21	2474.16	2401.94	-601.47	2476.10	345.94	1.45	PUP	None
24	3411.63	64.95	0.92	28.85	2045.67	2499.62	2427.95	-600.85	2501.20	346.10	1.41	PUP	None
25	3440.50	64.95	1.08	28.87	2057.89	2525.24	2454.10	-600.40	2526.48	346.25	0.15	PUP	None
26	3469.03	64.76	359.67	28.53	2070.01	2550.60	2479.93	-600.23	2551.53	346.39	1.38	PUP	None
27	3497.85	64.60	359.00	28.82	2082.34	2576.26	2505.98	-600.53	2576.93	346.52	0.66	PUP	None
28	3526.23	64.31	357.54	28.38	2094.58	2601.56	2531.57	-601.30	2602.00	346.64	1.45	PUP	None
29	3554.53	64.09	356.75	28.30	2106.89	2626.81	2557.02	-602.57	2627.06	346.74	0.80	PUP	None
30	3582.91	63.64	357.01	28.38	2119.39	2652.07	2582.46	-603.96	2652.14	346.84	0.54	PUP	None
[(c)2007 IDEAL ID12_OC_11]													
SCHLUMBERGER Survey Report													
2-Aug-2007 05:34:29													
Page 3 of 3													
Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
31	3610.60	63.26	357.65	27.69	2131.77	2676.61	2607.20	-605.11	2676.50	346.93	0.76	PUP	None
32	3637.87	63.58	357.68	27.27	2143.97	2700.75	2631.57	-606.10	2700.47	347.03	0.36	PUP	None
33	3667.13	64.57	358.10	29.26	2156.77	2726.78	2657.87	-607.07	2726.31	347.13	1.10	PUP	None
34	3695.23	64.37	357.93	28.10	2168.88	2751.85	2683.21	-607.95	2751.22	347.23	0.27	PUP	None
35	3724.36	64.22	358.14	29.13	2181.51	2777.80	2709.44	-608.85	2777.01	347.34	0.25	PUP	None
36	3752.52	63.45	357.51	28.16	2193.93	2802.80	2734.69	-609.81	2801.86	347.43	1.03	PUP	None
37	3780.64	62.94	358.13	28.12	2206.61	2827.63	2759.77	-610.76	2826.55	347.52	0.82	PUP	None
38	3808.97	62.90	1.05	28.33	2219.51	2852.46	2784.99	-610.95	2851.22	347.63	2.80	PUP	None
39	3837.82	63.45	1.11	28.85	2232.53	2877.68	2810.74	-610.46	2876.26	347.75	0.58	PUP	None
40	3866.50	63.89	2.35	28.68	2245.25	2902.79	2836.43	-609.68	2901.21	347.87	1.27	PUP	None
41	3894.55	64.79	1.46	28.05	2257.40	2927.48	2861.70	-608.84	2925.75	347.99	1.31	PUP	None
42	3922.77	64.66	2.71	28.22	2269.44	2952.38	2887.20	-607.92	2950.50	348.11	1.23	PUP	None
43	3951.31	64.25	3.20	28.54	2281.75	2977.41	2912.91	-606.59	2975.40	348.24	0.64	PUP	None
44	3979.33	64.15	2.89	28.02	2293.95	3001.93	2938.10	-605.25	2999.80	348.36	0.32	PUP	None
45	4008.07	64.39	1.76	28.74	2306.42	3027.17	2963.97	-604.20	3024.93	348.48	1.11	PUP	None
46	4036.03	64.95	359.78	27.96	2318.39	3051.95	2989.24	-603.86	3049.62	348.58	2.04	PUP	None
47	4064.93	65.52	357.29	28.90	2330.49	3077.86	3015.47	-604.53	3075.47	348.66	2.46	PUP	None
48	4093.51	66.09	357.87	28.58	2342.21	3103.66	3041.52	-605.63	3101.23	348.74	0.83	PUP	None
49	4121.30	65.29	357.86	27.79	2353.65	3128.72	3066.83	-606.58	3126.24	348.81	0.88	PUP	None
50	4149.87	64.69	357.13	28.57	2365.73	3154.35	3092.69	-607.71	3151.83	348.88	0.95	PUP	None
51	4178.61	64.95	356.34	28.74	2377.96	3180.15	3118.66	-609.19	3177.60	348.95	0.81	PUP	None
52	4207.11	64.15	357.06	28.50	2390.20	3205.68	3144.35	-610.67	3203.10	349.01	1.10	PUP	None
53	4235.94	64.15	357.77	28.83	2402.77	3231.37	3170.27	-611.84	3228.77	349.08	0.68	PUP	None
54	4263.05	64.28	359.31	27.11	2414.57	3255.48	3194.67	-612.46	3252.85	349.15	1.57	PUP	None
55	4291.35	64.12	359.40	28.30	2426.88	3280.57	3220.15	-612.75	3277.93	349.23	0.19	PUP	Npne
56	4319.88	64.09	358.97	28.53	2439.34	3305.87	3245.81	-613.11	3303.21	349.30	0.41	PUP	None
57	4347.72	64.15	358.85	27.84	2451.49	3330.58	3270.85	-613.59	3327.91	349.38	0.14	PUP	None
58	4376.37	63.94	358.35	28.65	2464.03	3356.01	3296.61	-614.22	3353.34	349.45	0.53	PUP	None
59	4390.93	64.09	359.36	14.56	2470.41	3368.92	3309.69	-614.48	3366.25	349.48	1.93	PUP	None
60	4410.00	64.28	0.64	19.07	2478.72	3385.79	3326.86	-614.48	3383.13	349.54	1.87	Projected to TD	
[(c)2007 IDEAL ID12_OC_11]													

Company:

ES

SO

Australia Pty Ltd

Well:

FTA

A10AST1

Field:

Fortescue

Rig:

ISDL 175

8.5 in. Section

State:

Victoria

VISION Resistivity

1:200 True Vertical Depth

Recorded Mode Log

Schlumberger

