

Reeves

Compact

Dual Laterolog
Gamma Ray
1:200 TVD

COMPANY	ESSO AUSTRALIA PTY. LTD.		
WELL	MARLIN A24A		
FIELD	TURRUM		
PROVINCE/COUNTY	BASS STRAIT		
COUNTRY/STATE	AUSTRALIA		
LOCATION	38Deg13'49.203"S, 148Deg13'15.554"E N 5767923.720 m, E 606865.170 m		
LSD	SEC	TWP	RGE
API Number	Other Services		Photo Density
Permit Number VIC/L11	Compensated Neutron		Compensated Sonic
Permanent Datum MSL	, Elevation 0.0 metres		
Log Measured From RT@27.91 m	above Permanent Datum		
Drilling Measured From RT			
Date	5-MAY-2004		
Run Number	ONE		
Depth Driller	2676.90	metres	
Depth Logger	2672.90	metres	
First Reading	2672.50	metres	
Last Reading	1702.40	metres	
Casing Driller	633.50	metres	
Casing Logger			
Bit Size	8.50	inches	
Hole Fluid Type	KCL/GLY/PPHA		
Density / Viscosity	10.15 lb/USg	30.00 CP	
PH / Fluid Loss	8.90	3.00 ml/30Min	
Sample Source	PRESS		
Rm @ Measured Temp	0.137 @ 25.0	ohm-m	
Rmf @ Measured Temp	0.098 @ 25.0	ohm-m	
Rmc @ Measured Temp	0.236 @ 25.0	ohm-m	
Source Rmf / Rmc	FLOW	FLOW	
Rm @ BHT	0.066 @ 75.0	ohm-m	
Time Since Circulation	36 HRS		
Max Recorded Temp	90.60	deg C	
Equipment Name	CWS/CML		
Equipment / Base	1	SALE	
Recorded By	G. MCMANUS, N. PATMAN		
Witnessed By	C. MENHENNIT, L. CULLEN		
Circ. Stopped	1400 4-MAY		

FINAL PRINT

Elevations:
KB 27.91 metres
DF 27.91 metres
GL -59.00 metres

BOREHOLE RECORD

Bit Size inches	Depth From metres	Depth To metres
8.500	653.000	3275.000

CASING RECORD

Type	Size inches	Depth From metres	Shoe Depth metres	Weight pounds/ft
SURFACE	13.375	0.000	653.000	0.00
L80	9.625	0.000	653.000	47.00

REMARKS

Miss Run - No data collected above 2008.5 m MD Due To Battery Failure

Rig Nabors 453

5" SHUTTLE - MEMORY LOGGING

5-MAY-04

Crew: G McManus, N Patman, M Susa, B Goodwin

Logs depth corrected -1.1m to correlate with Anadrill gamma log.

AVERAGE INCLINATION: 38° FROM WINDOW TO TD

MAXIMUM INCLINATION: 42.38° @ 3162.70 mMD

MAXIMUM DOGLEG SERVERITY: 5.53°/30m @ 780.54


MAXIMUM TEMPERATURE: 90.6°C @ 2654.30 mMD


All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not, guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions in our price schedule.


MAIN LOG 1:200

Depth Based Data - Maximum Sampling Increment 10.0cm

Plotted on 24-SEP-2004 13:22







1800
TVD

1810
TVD

87°

1820
TVD

1830
TVD


88°


1840
TVD


600

1850
TVD

1500







1920
TVD

1930
TVD

89°

1940
TVD


1950
TVD



1960
TVD



1300
89°



1970
TVD



1980


















2350
TVD

2360
TVD

89°

2370
TVD



200



2380
TVD



500
89°



2390
TVD



2400
TVD











General Constants All 000

General Parameters

Mud Resistivity	0.119	ohm-metres
Mud Resistivity Temperature	25.000	degrees C
Water Level	0.000	metres
Density/Neutron Processing	Wet Hole	

Hole/Annular Volume and Differential Caliper Parameters

HVOL Caliper 1	Density Caliper	
HVOL Caliper 2	Density Caliper	
Annular Volume Diameter	7.000	inches
Caliper for Differential Caliper	Density Caliper	

Rwa Parameters

Porosity used	Base Density Porosity	
Resistivity used	Deep Induction	
RWA Constant A	0.610	
RWA Constant M	2.150	

Gamma Calibration MCG 098

Field Calibration on 3-MAY-2004 11:25

	Measured	Calibrated (API)
Background	8	5
Calibrator (Gross)	1371	914
Calibrator (Net)	1363	909

Gamma Constants MCG 098

Gamma Calibrator Number	60	
Mud Density	1.00	gm/cc
Caliper Source for Processing	Bit Size	
Tool Position	Eccentred	
Concentration of KCl	0.00	kppm

High Resolution Temperature Calibration MCG 098

Field Calibration on 3-MAY-2004,11:21

	Measured	Calibrated(Deg C)
Lower	0.00	0.00
Upper	100.00	100.00

High Resolution Temperature Constants MCG 098

Pre-filter Length	11
-------------------	----

Caliper Calibration MPD 083

Base Calibration on 20-APR-2004 12:25

Field Calibration on 3-MAY-2004 10:29

Base Calibration

Reading No	Measured	Calibrator Size (in)
1	13792	4.01
2	23424	5.99
3	33363	7.98
4	43344	9.94
5	54608	12.01
6	N/A	N/A

Field Calibration

Measured Caliper (in)	Actual Caliper (in)
7.96	7.98

Laterolog Calibration MLE 017

Base Calibration on 16-APR-2004 15:30

Field Check on 3-MAY-2004,11:45

Base Calibration

		Measured	Calibrated (ohm-m)	
Channel	Resistor 1	Resistor 2	Resistor 1	Resistor 2
Shallow	9.7	969.1	13.2	1321.0
Deep	9.7	969.2	7.5	755.0
Groningen	9.7	970.5	8.5	854.0

Channel	Base Check (ohm-m)	Field Check (ohm-m)
Shallow	49.0	49.0
Deep	28.0	28.0
Groningen	253.1	253.2

Laterolog Constants MLE 017

Squasher Start	40000	ohm-m
Shallow Laterolog K Factor	1.3210	
Deep Laterolog K Factor	0.7550	
Groningem Laterolog K Factor	0.8540	
Interference Rejection	50 Hz	
SP Connection	SP Bridle Electrode	
Groningen Connection	Groningen Electrode	

DOWNHOLE EQUIPMENT

C:\Marlin\MLA A24a\Final Data Presentations\Black & White Prints\MLA A24A MAIN LOG MDL.dta

Compact Swivel Head Adaptor
SHA 63 Length: 0.83 m Weight: 26.5 lb

Compact Knuckle Joint
SKJ 49 Length: 0.66 m Weight: 24.3 lb

Compact Battery Sub.
MBS 99 Length: 4.34 m Weight: 88.2 lb

Compact Inline Standoff B
MIS 141 Length: 0.65 m Weight: 15.4 lb

Compact Stiff Bridle Electrode Sub.
MBE 18 Length: 3.76 m Weight: 94.8 lb

Compact Inline Standoff B
MIS 127 Length: 0.65 m Weight: 15.4 lb

Compact Stiff Bridle Electrode Sub.
MBE 19 Length: 3.76 m Weight: 94.8 lb

Compact Knuckle Joint
SKJ 110 Length: 0.66 m Weight: 24.3 lb

Thrid Bridle MBE 20
MLK 111 Length: 3.76 m Weight: 94.8 lb

Compact Gamma
MCG 98 Length: 2.65 m Weight: 63.9 lb



32.22 m GGCE - Borehole Corrected Gamma
31.33 m CGXT - MCG External Temperature

Compact Memory Sub.
MMS 24 Length: 0.95 m Weight: 22.0 lb

Compact Knuckle Joint
SKJ 48 Length: 0.66 m Weight: 24.3 lb

Compact Swivel Head Adaptor
SHA 28 Length: 0.83 m Weight: 26.5 lb

Compact Inline Bowspring A
MIS 95 Length: 1.74 m Weight: 33.1 lb

Compact Neutron
MDN 85 Length: 1.53 m Weight: 50.7 lb

Compact Density/Caliper
MPD 83 Length: 2.92 m Weight: 90.4 lb

Compact Inline Bowspring A
MIS 94 Length: 1.74 m Weight: 33.1 lb

Compact Swivel Head Adaptor
SHA 71 Length: 0.83 m Weight: 26.5 lb


Compact Knuckle Joint
SKJ 44 Length: 0.66 m Weight: 24.3 lb

Compact Inline Standoff B
MIS 128 Length: 0.65 m Weight: 15.4 lb

Compact Upper Guard Sub.
MUG 5 Length: 2.74 m Weight: 68.3 lb

Compact Inline Standoff B
MIS 135 Length: 0.65 m Weight: 15.4 lb

Compact Laterolog Electrode Sub.
MLE 17 Length: 3.76 m Weight: 92.6 lb



Compact Inline Standoff B
MIS 31 Length: 0.65 m Weight: 15.4 lb

Compact Lower Guard Sub.
MLG 7 Length: 2.44 m Weight: 55.1 lb

Compact Inline Standoff B
MIS 140 Length: 0.65 m Weight: 15.4 lb

Compact Sonic
MSS 47 Length: 3.82 m Weight: 72.8 lb

Compact Inline Standoff B
MIS 73 Length: 0.65 m Weight: 15.4 lb

Compact Induction
MAI 39 Length: 3.29 m Weight: 48.5 lb

Pressure Bung + Hole Finder
HFS 3 Length: 0.28 m Weight: 6.6 lb

Total Length: 53.18 m Weight: 1294.1 lb



Tool Zero (0.32m from bottom)

All measurements relative to tool zero.

COMPANY	ESSO AUSTRALIA PTY. LTD.
WELL	MARLIN A24A
FIELD	TURRUM
PROVINCE/COUNTY	BASS STRAIT
COUNTRY/STATE	AUSTRALIA

Elevation Kelly Bushing	metres	First Reading	2672.50	metres
Elevation Drill Floor 27.91	metres	Depth Driller	2676.90	metres
Elevation Ground Level -59.00	metres	Depth Logger	2672.90	metres

Reeves
Compact

Dual Laterolog
Gamma Ray
1:200 TVD