

<p style="text-align: center;"><b>DISCLAIMER</b></p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
<p><b>OTHER SERVICES FOR RUN1</b></p> <p>Directional Drilling Directional Surveys</p>	<p><b>OTHER SERVICES FOR RUN2</b></p> <p>Directional Drilling Directional Surveys</p>	<p><b>OTHER SERVICES FOR RUN3</b></p> <p>Directional Drilling Directional Surveys</p>
<p><b>REMARKS: RUN NUMBER 1</b></p> <p>8-1/2 in. hole was drilled from 633.7 m to 646.3 m TVD.</p> <p>Depth is referenced to Driller's depth.</p> <p>Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.</p> <p>Mud type is KCL/PHPA/Glycol.</p>	<p><b>REMARKS: RUN NUMBER 2</b></p> <p>8-1/2 in. hole was drilled from 633.7 m to 1460.0 m TVD.</p> <p>Depth is referenced to Driller's depth.</p> <p>Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.</p> <p>Mud type is KCL/PHPA/Glycol.</p>	<p><b>REMARKS: RUN NUMBER 3</b></p> <p>8-1/2 in. hole was drilled from 1460.0 m to 1744.9 m TVD.</p> <p>Depth is referenced to Driller's depth.</p> <p>Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.</p> <p>Mud type is KCL/PHPA/Glycol.</p>

POOH for bit change.

POOH for bit change.

POOH for bit change.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

EQUIPMENT DESCRIPTION

RUN1




RUN2

RUN3

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT



6-1/2 in. PMDC S/N: 97081023  6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 1437 1.5 deg. Bent Housing 8-3/8 in. Motor Sleeve  REED Hycalog MT Bit OD: 8-1/2 in. XS4 S/N: 749555  Maximum string diameter 8.50 in. All lengths in Meters	7.92	6-1/2 in. PMDC S/N: 97081023  6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 1437 1.5 deg. Bent Housing 8-3/8 in. Motor Sleeve  REED Hycalog PDC Bit OD: 8-1/2 in. RSX192 S/N: 205899  Maximum string diameter 8.50 in. All lengths in Meters	7.88	6-1/2 in. PMDC S/N: 97081023  6-3/4 in. PowerPak* Motor A675XP 7850 S/N: 3604 0.78 deg. Bent Housing 8-3/8 in. Motor Sleeve  Security TCI Bit OD: 8-1/2 in. TD51AKPRDH S/N: M16961  Maximum string diameter 8.50 in. All lengths in Meters	7.92
--	------	--	------	---	------

#### DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES FOR RUN4 Directional Drilling Directional Surveys	OTHER SERVICES FOR RUN5 Directional Drilling Directional Surveys	OTHER SERVICES FOR RUN6 Directional Drilling Directional Surveys
REMARKS: RUN NUMBER 4 8-1/2 in. hole was drilled from 1744.9 m to 2073.9 m TVD.  Erratic GR data removed from 1731.6 m to 1776.4 m TVD. Erratic data was due to Incorrect Surface system initialization.  Depth is referenced to Driller's depth.  Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.  Mud type is KCL/PHPA/Glycol.  POOH for bit change.	REMARKS: RUN NUMBER 5 8-1/2 in. hole was drilled from 2073.9 m to 2409.8 m TVD.  Depth is referenced to Driller's depth.  Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.  Mud type is KCL/PHPA/Glycol.  POOH due to PowerPak* motor failure.	REMARKS: RUN NUMBER 6 8-1/2 in. hole was drilled from 2409.8 m to 2608.9 m TVD.  Depth is referenced to Driller's depth.  Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.  Mud type is KCL/PHPA/Glycol.  POOH for Coring run.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

Thank You for Choosing Schlumberger.

## EQUIPMENT DESCRIPTION

RUN4

RUN5

RUN6

### DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse\* 22.58  
MDC: 066-AB  
MEC: 212-BA  
MDI: 1096-BC  
MGR: 503-AA  
DH Software: V7.0 C00

D&I — 18.28  
GR — 17.63

6-1/2 in. PMDC 14.37  
S/N: ANA98-007

6-1/2 in. NM Roller Reamer 11.61  
S/N: GU2317R  
Reamer OD: 8-3/8 in.

6-1/2 in. PMDC 9.42  
S/N: 97081023

6-3/4 in. PowerPak\* Motor 7.90  
A675XP 7850  
S/N: 3604  
0.78 deg. Bent Housing

### DOWNHOLE EQUIPMENT

6-1/2 in. PowerPulse\* 22.45  
MDC: 066-AB  
MEC: 212-BA  
MDI: 1096-BC  
MGR: 503-AA  
DH Software: V7.0 C00

D&I — 18.15  
GR — 17.50

6-1/2 in. NM Roller Reamer 14.24  
S/N: GU2298  
Reamer OD: 8-3/8 in.

6-1/2 in. PDMC 12.16  
S/N: ANA98-007

6-1/2 in. PMDC 9.40  
S/N: 97081023

6-3/4 in. PowerPak\* Motor 7.88  
A675XP 7850  
S/N: 3604  
1.15 deg. Bent Housing

### DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse\* 22.49  
MDC: 066-AB  
MEC: 212-BA  
MDI: 1096-BC  
MGR: 503-AA  
DH Software: V7.0 C00







D&I — 18.19  
GR — 17.54

6-1/2 in. PMDC 14.28  
S/N: ANA98-007

6-1/2 in. NM Roller Reamer 11.52  
S/N: GU2298  
Reamer OD: 8-3/8 in.

6-1/2 in. PMDC 9.44  
S/N: 97081023

6-3/4 in. PowerPak\* Motor 7.92  
A675XP 7850  
S/N: ASQ0003  
0.78 deg. Bent Housing

<p>8-3/8 in. Motor Sleeve</p>  <p>Security TCI Bit OD: 8-1/2 in. SEB485 S/N: 10618321</p>  <p>___ 0.00 0.24</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>8-3/8 in. Motor Sleeve</p>  <p>REED Hycalog PDC Bit OD: 8-1/2 in. RSX162 S/N: 206711</p>  <p>___ 0.00 0.22</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>	<p>8-3/8 in. Motor Sleeve</p>  <p>Hughes TCI Bit OD: 8-1/2 in. MX_DSR20GDX S/N: 6007867</p>  <p>___ 0.00 0.22</p> <p>Maximum string diameter 8.50 in. All lengths in Meters</p>
--	--	--

<p style="text-align: center;"><b>DISCLAIMER</b></p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
<p>OTHER SERVICES FOR RUN7</p> <p>Directional Drilling Directional Surveys</p>	<p>OTHER SERVICES FOR RUN</p>	<p>OTHER SERVICES FOR RUN</p>
<p>REMARKS: RUN NUMBER 7</p> <p>8-1/2 in. hole was drilled from 2608.9 m to 2676.9 m TVD.</p> <p>Three Coring runs were carried out from 21:30 28-Apr-2004 to 08:15 02-May-2004.</p> <p>Reamed for GR data over Coring interval between 2588.8 m to 2608.9 m TVD. Reaming ROP did not exceed 55 m/hr.</p> <p>Depth is referenced to Driller's depth.</p> <p>Gamma Ray is corrected for Tool Size, Bit Size and Mud Weight.</p> <p>Mud type is KCL/PHPA/Glycol.</p> <p>POOH after reaching TD of MLA A24A, at 2676.9 m TVD.</p> <p>Thank You for Choosing Schlumberger.</p>	<p>REMARKS: RUN NUMBER</p>	<p>REMARKS: RUN NUMBER</p>

EQUIPMENT DESCRIPTION

RUN7

RUN

RUN

DOWNHOLE EQUIPMENT

6-3/4 in. PowerPulse\*  
MDC: Y927-AC  
MEC: 570-BA  
MDI: 586-BC  
MGR: 512-AA  
DH Software: V7.0 C00



23.39

D&I — 19.09  
GR — 18.44

6-1/2 in. PMDC  
S/N: ANA98-700



14.94

6-1/2 in. PMDC  
S/N: 97081023



12.18

6-1/2 in. NM Roller Reamer  
S/N: GU2298  
Reamer OD: 8-3/8 in.



10.66

Float Sub  
S/N: ASQ12141



8.58

6-3/4 in. PowerPak\* Motor  
A675XP 7850  
S/N: ASQ0003  
0.0 deg. Bent Housing  
8-3/8 in. Motor Sleeve



7.93

1001


[illegible]

Filtering Neutron	n/a	n/a	n/a	n/a	n/a	n/a	n/a			
Company representative	Bim Steel	Brian Davis	Roger Bain	G.Campbell	Ross Morris					
Anadrill personnel	K.Handley	D.Hastie	C.Soper	T.Auger	J.Dolan					


# MLA A24A RT GR 1:200TVD

IDEAL Version: ID8 1C 01 <TVD> Vertical Scale: 1:200

Graphics File Created: 10-May-2004 17:21














675  
TVD



700  
TVD































1150  
TVD





1175  
TVD




1200  
TVD


1225  
TVD









1300  
TVD




1325  
TVD



1350  
TVD





1375  
TVD



1400  
TVD

1425  
TVD







Run 3

1450  
TVD

1475  
TVD









1500  
TVD


1525  
TVD






1550  
TVD


1575  
TVD








1600  
TVD


1625  
TVD








Erratic GR Data removed from 1731.6m to 1776.4m. Erratic data was due to incorrect Surface system initialization.




Run 4

1750  
TVD

1775  
TVD






Erratic GR data removed from  
1731.6 m to 1776.4 m TVD.





1800  
TVD



1825  
TVD




















2050  
TVD

Run 5


2075  
TVD










2100  
TVD

2125  
TVD



















2350  
TVD


2375  
TVD














2550  
TVD


2575  
TVD

Run 7


2600  
TVD







2675  
TVD



ROP\*5 (ROP5)  
(M/HR)

GR(TM) (GRM1)  
(GAPI)

## SCHLUMBERGER

Survey report 6-May-2004 05:21:03 Page 1 of 5

Client.....: ESSO Australia Pty. Ltd.  
Field.....: Turrum

Well.....: MLA A24A Spud date.....: 8-April-2004  
API number.....: Last survey date.....: 05-May-04  
Engineer.....: James Dolan Total accepted surveys...: 99  
MD of first survey.....: 655.00 m  
Rig.....: ISDL 453 MD of last survey.....: 3275.00 m  
STATE.....: Victoria

----- Survey calculation methods -----  
Method for positions.....: Minimum curvature  
Method for DLS.....: Mason & Taylor  
----- Depth reference -----  
Permanent datum.....: Mean Sea Level  
Depth reference.....: Driller's depth  
GL above permanent.....: -59.00 m  
KB above permanent.....: 27.91 m  
DF above permanent.....: 27.91 m  
----- Vertical section origin -----  
Latitude (+N/S-).....: 0.00 m  
Departure (+E/W-).....: 0.00 m  
----- Platform reference point -----  
Latitude (+N/S-).....: 5767927.00 m  
Departure (+E/W-).....: 606840.63 m  
----- Geomagnetic data -----  
Magnetic model.....: BGGM version 2003  
Magnetic date.....: 12-Apr-2004  
Magnetic field strength...: 1199.81 HCNT  
Magnetic dec (+E/W-).....: 13.13 degrees  
Magnetic dip.....: -68.73 degrees  
----- MWD survey Reference Criteria -----  
Reference G.....: 1000.03 mGal  
Reference H.....: 1199.81 HCNT  
Reference Dip.....: -68.73 degrees  
Tolerance of G.....: (+/-) 2.50 mGal  
Tolerance of H.....: (+/-) 6.00 HCNT  
Tolerance of Dip.....: (+/-) 0.45 degrees  
----- Corrections -----  
Magnetic dec (+E/W-).....: 13.13 degrees  
Grid convergence (+E/W-).....: -0.76 degrees  
Total az corr (+E/W-).....: 13.89 degrees  
Azimuth from rotary table to target: 172.07 degrees  
(Total az corr = magnetic dec - grid conv)  
Survey Correction Type



Survey Correction Type  
 I=Sag Corrected Inclination  
 M=Schlumberger Magnetic Correction  
 S=Shell Magnetic Correction  
 F=Failed Axis Correction  
 R=Magnetic Resonance Tool Correction  
 D=Dmag Magnetic Correction

[(c)2004 IDEAL ID8\_1C\_01]  
 SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 2 of 5

Seq	Measured depth	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	100f	type	(deg)	
1	655.00	33.20	210.13	0.00	633.73	96.52	-100.74	-23.64	103.48	193.21	0.00	TIP	None
2	660.00	32.99	210.13	5.00	637.92	98.66	-103.10	-25.01	106.09	193.64	1.28	GYR	None
3	665.00	33.29	210.01	5.00	642.11	100.82	-105.47	-26.38	108.72	194.04	1.87	GYR	None
4	670.00	33.73	209.91	5.00	646.27	103.00	-107.86	-27.76	111.37	194.43	2.70	GYR	None
5	675.00	34.09	209.86	5.00	650.42	105.20	-110.28	-29.15	114.06	194.81	2.20	GYR	None
6	680.00	34.69	210.12	5.00	654.55	107.43	-112.72	-30.56	116.79	195.17	3.77	GYR	None
7	685.00	35.40	210.66	5.00	658.64	109.68	-115.20	-32.01	119.56	195.53	4.72	GYR	None
8	689.10	35.51	210.76	4.10	661.98	111.54	-117.24	-33.23	121.86	195.82	0.92	GYR	None
9	717.50	34.70	205.96	28.40	685.22	124.69	-131.60	-40.99	137.84	197.30	3.09	GYR	None
10	752.43	33.40	195.32	34.93	714.19	141.79	-149.83	-47.88	157.30	197.72	5.32	MWD	None
11	780.54	33.91	186.00	28.11	737.60	156.52	-165.10	-50.75	172.73	197.09	5.62	MWD	None
12	810.03	35.97	177.85	29.49	761.79	173.13	-181.95	-51.29	189.04	195.74	5.27	MWD	None
13	838.48	36.64	170.20	28.45	784.73	189.94	-198.67	-49.53	204.75	194.00	4.90	MWD	None
14	866.83	37.47	166.76	28.35	807.36	206.98	-215.41	-46.11	220.29	192.08	2.40	MWD	None
15	895.45	37.83	165.95	28.62	830.02	224.38	-232.39	-41.99	236.16	190.24	0.65	MWD	None
16	924.14	38.25	166.46	28.69	852.61	241.96	-249.56	-37.77	252.40	188.61	0.56	MWD	None
17	952.81	39.64	166.66	28.67	874.91	259.90	-267.09	-33.58	269.19	187.17	1.48	MWD	None
18	981.60	38.22	166.49	28.79	897.30	277.91	-284.69	-29.38	286.20	185.89	1.51	MWD	None
19	1010.23	38.58	167.73	28.63	919.74	295.63	-302.02	-25.42	303.09	184.81	0.91	MWD	None
20	1039.20	38.55	167.51	28.97	942.39	313.63	-319.66	-21.55	320.39	183.86	0.15	MWD	None
21	1067.89	39.01	167.54	28.69	964.76	331.54	-337.21	-17.66	337.67	183.00	0.49	MWD	None
22	1096.72	39.89	167.06	28.83	987.02	349.80	-355.08	-13.64	355.34	182.20	0.98	MWD	None
23	1125.44	40.57	166.90	28.72	1008.95	368.27	-373.15	-9.46	373.27	181.45	0.73	MWD	None
24	1154.05	39.92	166.98	28.61	1030.78	386.68	-391.15	-5.28	391.19	180.77	0.69	MWD	None
25	1183.04	39.68	166.86	28.99	1053.06	405.17	-409.23	-1.08	409.23	180.15	0.26	MWD	None
26	1211.66	38.68	166.97	28.62	1075.24	423.17	-426.84	3.01	426.85	179.60	1.07	MWD	None
27	1240.27	38.47	166.82	28.61	1097.61	440.94	-444.21	7.06	444.27	179.09	0.24	MWD	None
28	1269.13	37.72	166.70	28.86	1120.32	458.67	-461.55	11.14	461.68	178.62	0.80	MWD	None
29	1297.80	38.60	167.43	28.67	1142.86	476.32	-478.81	15.10	479.05	178.19	1.05	MWD	None
30	1326.36	37.70	167.36	28.56	1165.32	493.90	-496.03	18.95	496.39	177.81	0.96	MWD	None

[(c)2004 IDEAL ID8\_1C\_01]  
 SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 3 of 5

Seq	Measured depth	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (deg)	At Azim (deg)	DLS (deg)	Srvy Tool	Tool Corr
-	(m)	(deg)	(deg)	(m)	(m)	(m)	(m)	(m)	(deg)	100f	type	(deg)	
31	1355.04	38.68	167.70	28.68	1187.86	511.58	-513.34	22.78	513.85	177.46	1.07	MWD	None
32	1384.27	37.81	167.57	29.23	1210.82	529.61	-531.02	26.65	531.68	177.13	0.91	MWD	None
33	1412.38	37.40	167.34	28.11	1233.09	546.71	-547.76	30.38	548.60	176.83	0.47	MWD	None
34	1441.17	37.84	168.07	28.79	1255.89	564.24	-564.93	34.12	565.96	176.54	0.66	MWD	None
35	1469.79	38.56	168.51	28.62	1278.39	581.90	-582.26	37.71	583.48	176.29	0.82	MWD	None
36	1498.39	37.87	168.37	28.60	1300.86	599.55	-599.59	41.26	601.01	176.06	0.74	MWD	None
37	1527.11	38.56	168.93	28.72	1323.42	617.29	-617.01	44.75	618.63	175.85	0.82	MWD	None
38	1556.02	37.65	169.12	28.91	1346.17	635.10	-634.53	48.15	636.35	175.66	0.97	MWD	None
39	1584.67	36.76	168.55	28.65	1368.99	652.40	-651.52	51.50	653.56	175.48	1.02	MWD	None
40	1613.25	38.50	168.86	28.58	1391.62	669.82	-668.63	54.92	670.89	175.30	1.87	MWD	None
41	1642.10	37.91	168.79	28.85	1414.29	687.63	-686.14	58.38	688.62	175.14	0.63	MWD	None
42	1671.05	37.92	169.06	28.95	1437.13	705.39	-703.60	61.79	706.31	174.98	0.17	MWD	None
43	1699.71	38.03	168.86	28.66	1459.72	723.00	-720.91	65.17	723.85	174.83	0.18	MWD	None
44	1727.96	37.84	169.05	28.25	1482.01	740.34	-737.95	68.50	741.12	174.70	0.24	MWD	None
45	1756.81	38.27	169.04	28.85	1504.72	758.10	-755.41	71.88	758.82	174.56	0.45	MWD	None
46	1785.62	38.00	168.66	28.81	1527.38	775.87	-772.87	75.32	776.53	174.43	0.38	MWD	None
47	1814.15	37.10	168.75	28.53	1550.00	793.22	-789.92	78.72	793.83	174.31	0.96	MWD	None
48	1842.95	38.27	167.89	28.80	1572.79	810.79	-807.16	82.29	811.34	174.18	1.36	MWD	None
49	1871.75	38.45	168.39	28.80	1595.38	828.62	-824.65	85.96	829.12	174.05	0.38	MWD	None
50	1900.47	38.71	168.39	28.72	1617.83	846.50	-842.19	89.57	846.94	173.93	0.28	MWD	None

50	1999.47	38.71	168.88	28.72	1671.88	876.88	-872.18	93.87	876.87	173.88	0.28	MWD	None
51	1929.33	38.47	168.66	28.86	1640.39	864.46	-859.83	93.15	864.86	173.82	0.31	MWD	None
52	1958.22	37.87	169.39	28.89	1663.10	882.29	-877.36	96.55	882.66	173.72	0.79	MWD	None
53	1986.84	38.12	169.09	28.62	1685.65	899.89	-894.67	99.84	900.22	173.63	0.33	MWD	None
54	2015.48	39.37	167.94	28.64	1707.99	917.78	-912.23	103.41	918.07	173.53	1.54	MWD	None
55	2044.61	38.98	168.11	29.13	1730.57	936.13	-930.23	107.23	936.39	173.42	0.42	MWD	None
56	2071.77	38.59	168.98	27.16	1751.74	953.11	-946.91	110.61	953.34	173.34	0.75	MWD	None
57	2101.85	37.10	168.96	30.08	1775.50	971.54	-965.02	114.14	971.75	173.25	1.51	MWD	None
58	2130.54	37.51	168.59	28.69	1798.32	988.90	-982.08	117.52	989.08	173.18	0.50	MWD	None
59	2159.14	38.47	167.19	28.60	1820.86	1006.45	-999.29	121.22	1006.61	173.08	1.37	MWD	None
60	2187.44	38.03	166.74	28.30	1843.08	1023.90	-1016.35	125.17	1024.03	172.98	0.56	MWD	None

[(c)2004 IDEAL ID8\_1C\_01]  
SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 4 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool	Tool Corr
61	2216.29	38.41	166.91	28.85	1865.75	1041.68	-1033.73	129.24	1041.78	172.87	0.42	MWD	None
62	2245.08	38.93	167.52	28.79	1888.23	1059.60	-1051.28	133.22	1059.68	172.78	0.68	MWD	None
63	2273.90	38.02	167.87	28.82	1910.79	1077.48	-1068.80	137.04	1077.54	172.69	0.99	MWD	None
64	2302.68	38.81	168.30	28.78	1933.34	1095.32	-1086.29	140.73	1095.37	172.62	0.88	MWD	None
65	2331.35	38.78	168.59	28.67	1955.68	1113.25	-1103.89	144.33	1113.29	172.55	0.20	MWD	None
66	2359.88	38.33	168.94	28.53	1977.99	1131.00	-1121.33	147.79	1131.03	172.49	0.53	MWD	None
67	2388.53	38.91	168.96	28.65	2000.38	1148.85	-1138.88	151.22	1148.88	172.44	0.62	MWD	None
68	2417.21	38.59	168.82	28.68	2022.74	1166.78	-1156.50	154.68	1166.80	172.38	0.35	MWD	None
69	2445.97	39.26	168.62	28.76	2045.12	1184.82	-1174.22	158.21	1184.83	172.33	0.72	MWD	None
70	2474.75	38.92	168.19	28.78	2067.46	1202.93	-1191.99	161.86	1202.93	172.27	0.46	MWD	None
71	2503.39	39.80	167.74	28.64	2089.60	1221.04	-1209.76	165.65	1221.05	172.20	0.98	MWD	None
72	2531.95	39.39	167.17	28.56	2111.61	1239.19	-1227.53	169.60	1239.19	172.13	0.58	MWD	None
73	2560.51	40.01	166.69	28.56	2133.58	1257.36	-1245.30	173.73	1257.36	172.06	0.74	MWD	None
74	2589.43	40.85	166.60	28.92	2155.60	1276.03	-1263.54	178.06	1276.03	171.98	0.89	MWD	None
75	2617.92	41.96	167.22	28.49	2176.96	1294.79	-1281.90	182.33	1294.80	171.91	1.27	MWD	None
76	2646.67	41.96	167.88	28.75	2198.34	1313.96	-1300.67	186.47	1313.97	171.84	0.47	MWD	None
77	2675.56	41.93	168.44	28.89	2219.83	1333.22	-1319.57	190.43	1333.24	171.79	0.40	MWD	None
78	2703.70	41.03	168.90	28.14	2240.91	1351.83	-1337.84	194.10	1351.85	171.75	1.03	MWD	None
79	2732.45	40.27	169.62	28.75	2262.73	1370.53	-1356.24	197.59	1370.56	171.71	0.95	MWD	None
80	2760.98	39.81	169.96	28.53	2284.57	1388.87	-1374.31	200.84	1388.90	171.69	0.54	MWD	None
81	2789.98	38.64	171.44	29.00	2307.03	1407.20	-1392.40	203.81	1407.24	171.67	1.57	MWD	None
82	2818.82	38.83	171.71	28.84	2329.53	1425.25	-1410.25	206.45	1425.28	171.67	0.27	MWD	None
83	2847.42	38.91	171.07	28.60	2351.80	1443.20	-1428.00	209.14	1443.23	171.67	0.44	MWD	None
84	2875.94	39.73	171.25	28.52	2373.86	1461.26	-1445.85	211.91	1461.30	171.66	0.88	MWD	None
85	2904.56	40.43	171.37	28.62	2395.76	1479.69	-1464.07	214.70	1479.73	171.66	0.75	MWD	None
86	2933.12	40.91	171.26	28.56	2417.42	1498.30	-1482.47	217.51	1498.34	171.65	0.52	MWD	None
87	2961.50	41.59	171.60	28.38	2438.76	1517.01	-1500.97	220.30	1517.05	171.65	0.77	MWD	None
88	2990.42	39.85	170.94	28.92	2460.68	1535.88	-1519.62	223.16	1535.92	171.65	1.89	MWD	None
89	3019.22	39.73	171.29	28.80	2482.81	1554.30	-1537.83	226.00	1554.35	171.64	0.27	MWD	None
90	3048.40	39.90	171.55	29.18	2505.22	1572.99	-1556.30	228.79	1573.03	171.64	0.25	MWD	None

[(c)2004 IDEAL ID8\_1C\_01]  
SCHLUMBERGER Survey Report

6-May-2004 05:21:03

Page 5 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool	Tool Corr
91	3076.98	39.84	171.60	28.58	2527.16	1591.31	-1574.43	231.48	1591.35	171.64	0.07	MWD	None
92	3104.57	40.18	172.01	27.59	2548.29	1609.05	-1591.99	234.00	1609.09	171.64	0.48	MWD	None
93	3134.13	41.41	172.07	29.57	2570.67	1628.37	-1611.12	236.68	1628.41	171.64	1.27	MWD	None
94	3162.70	42.38	172.49	28.56	2591.93	1647.44	-1630.02	239.24	1647.48	171.65	1.08	MWD	None
95	3191.43	42.22	172.43	28.73	2613.18	1666.77	-1649.19	241.78	1666.81	171.66	0.18	MWD	None
96	3219.74	41.68	172.83	28.31	2634.24	1685.70	-1667.95	244.21	1685.74	171.67	0.65	MWD	None
97	3248.88	38.89	174.72	29.14	2656.46	1704.52	-1686.68	246.26	1704.56	171.69	3.19	MWD	None
98	3255.01	38.38	174.78	6.13	2661.25	1708.35	-1690.49	246.61	1708.38	171.70	2.54	MWD	None
99	3275.00	38.38	174.78	19.99	2676.92	1720.75	-1702.85	247.74	1720.78	171.72	0.00	Projection to TD	

[(c)2004 IDEAL ID8\_1C\_01]

**Company: ESSO Australia Pty. Ltd.**

**Schlumberger**

**Well: MLA A24A**

**Field: Turrum**

**Rig: ISDL 453**

**State: Victoria**

**Gamma Ray Service  
1:200 True Vertical Depth  
Real Time Log**