




FTA A30A DrillMech RM Depth 500MD Log


IDEAL Version: ID12_OC_13 <MD> Vertical Scale: 1:500


Graphics File Created: 28-Oct-2007 01:20





















































ROP*5 (ROP5) 200 (M/HR)	Local comp 1 6in (LCOMP1) (PSI)	MWD Lateral Vib (VIBLAT_RT) (G)	Surface RPM (RPM)	CONT_INC (INCL_CONT_ RT) (DEG)	Equivalent Circulating Density (ECD) (LB/G)
0	0	5	0	90	9
0	100000	0	200	90	14

Gamma Ray, Average (GRMA)	MWD Vib X-Axis (VIBX_ RT)	STOR (TQA)	MWD Shock Peak (SHKP)	CONT_AZIM (AZIM_CONT_ RT)	Downhole Annulus Temperature (DHAT)
------------------------------	------------------------------	------------	--------------------------------	------------------------------	--

0	Average (SRMA) (GAPI) 200	5	(G)	0	0	(KFLB) 50	(SHRP K_RT) (G) 0 200	-180	(RT) (DEG) 180	0	(CHRT) (DEGC) 200
							MWD Collar RPM (CRPM _RT) (RPM) 0 400		PKPK_RPM (Stick_RT) (RPM) 400	0	Standpipe Pressure (SPPA) (PSI) 5000
											TUR_RPM (TRPM_RT) (RPM) 5000
											T_FLOW (TFLO) (GPM) 800