

Potassium	%	n.a									
Environmental data											
GR											
Mud weight	ppg	11.30									
Bit size	in	8.50									
Resistivity											
Neutron porosity											
Hole Size	in	8.50									
Mud weight	ppg	11.30									
Temperature	°C	108.00									
Mud salinity	ppk	54.352									
Formation salinity		n.a									
Recording rate 1	SEC	5									
Recording rate 2	SEC	n.a									
Filtering GR		3 pts.									
Filtering density		3 pts.									
Filtering Neutron		3 pts.									
Company representative		D. Daniels	R. Spence	Mark C							
Anadrill personnel		Mewan A	M. Sihite	J. Ikeda	C. Soper	M. How					

<div>DISCLAIMER</div> <div>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</div>		
OTHER SERVICES FOR RUN5 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 5 Depth is referenced to Driller's Depth. Gamma ray is corrected for mud weight, tool size and bit size. Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure). Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3. POOH due to reaching coring TD of SNA A21A.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION		
RUN 5	RUN	RUN

DOWNHOLE EQUIPMENT

6-3/4" adnVISION*
DHS: 8.3A02
Blade OD: 8-1/4"
S/N: 40778

- Neutron F — 20.22
- Neutron N — 20.05
- Density S — 19.10
- Density L — 19.01
- UltraSonic — 18.63
- R-O Port — 17.86

6-3/4" PowerPulse*
MDC: FA28
MEC: 1533
MDI: 1820
MGR: 322

- D&I — 11.60
- GR — 10.96
- APWD — 8.35

8-3/8" Roller Reamer
S/N: GU2317R

6-3/4" NM Pony
S/N: SBD4464

8-3/8" Roller Reamer
S/N: GU2945

8-1/2" Reed Hycalog PDC Bit
S/N: 218088

Maximum string diameter 8.50 in.
All lengths in Meters

Variable Name	Variable Description	Run Name & Value	
	Run Number	5	
	General Information		
BHT_RM	Bottom Hole Temperature (RM)	DEGC	108.000
BSAL_RM	Mud Salinity (RM)	PPK	54.352
BS_RM	Bit Size (RM)	IN	8.500
COEF_M	User Defined FEXP in Clean Sand	----	1.650
C_WS	Overpressure correction to Sw and M	----	1.000
FEXP	Formation Factor Exponent (RM)	----	2.000
FNUM	Formation Factor Enumerator (RM)	----	1.000
FPHI_RM	Formation Factor Porosity Source (RM)	----	XPLOT
MST_RM	Mud Sample temperature (RM)	DEGC	23.889
MW_RM	Mud Weight (RM)	LB/G	11.300
OBMF_RM	Oil Based Mud (RM)	----	YES
RHOF_RM	Mud Filtrate Density (RM)	G/C3	1.000
RHOM_RM	Matrix density (RM)	G/C3	2.710
RMS_RM	Resistivity of Mud Sample (RM)	OHMM	1000.00
RWA_COMP_M	Rwa computation model		
RWA_DEN_AD	Rwa Density Input ADN		
RWA_DEN_CD	Rwa Density Input CDN		
RWA_DEN_IN	Rwa Density Input		
RWA_FORM_M	Rwa computation formation model		
RWA_RES_IN	Rwa computation resistivity input		
RWS_RM	Resistivity of Connate Water (RM)	OHMM	1.000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore) (RM)	DEGC	10.000
TD_RM	Total Measured Depth (RM)	M	2931.0
TWS_RM	Temperature of Connate Water (RM)	DEGC	23.889
VF_ILLI	Fraction of illite in shales	----	0.500
VF_KAOL	Fraction of kaolinite in shales	----	0.500
VF_MONT	Fraction of montmorillonite in shales	----	0.000
XPDM_RM	Cross plot density porosity multiplier	----	0.675
XPNM_RM	Cross plot neutron porosity multiplier	----	0.325
RSD	LWD run start date dd-mmm-yy		28-02-08
RWA_COMP_MOD	Rwa computation model	----	BASIC
RWA_DEN_ADN	Rwa Density Input	----	RHOB
RWA_DEN_CDN	Rwa Density Input	----	RHOB
RWA_DEN_INPUT	Rwa Density Input	----	RHOB
RWA_FORM_MOD	Rwa computation formation model	----	CLASTIC
RWA_RES_INPUT	Rwa computation resistivity input	----	RT
	ADN		
ADN_CHASSIS_STR	Type String	Chassis	ADN
ADN_COLLAR_STR	Type String	Collar	ADN
ADN_DATA_FIX	ADN: Create A Corrected ADN Time Data File	----	NO
ADN_DATA_LTB	ADN: Create An ADN LTB Data File	----	NO
ADN_STAB_STR	ADN Stabilizer Type String	----	IBS
ALPHA_COMPUTE_D	Perform Density Enhanced Vertical Resolution process ?	----	YES
ALPHA_COMPUTE_N	Perform Neutron Enhanced Vertical Resolution process ?	----	YES
AVE ADN	ADN/Array Channels: perform averaging (RM) :	----	YES
A_DHS	ADN Down Hole Software Version String	----	YES
CHI_RM	Caliper High limit from BS (RM)	IN	3.000
CLO_RM	Caliper Low limit from BS (RM)	IN	0.000
DEVI	Well Section Deviation	DEG	0.690
DTIK_SEL	ADN: Density Tick Channel Name	----	LSAZ
DTMUD	Delta-T for Mud	US/F	211.110
DYN_IMG_COMPUTE	Generate Dynamic Normalized Image?	----	YES
ECC_CORR_ADN	Perform Eccentering Correction for TNPH?	----	YES
ENVCOR	Neutron Processing: Environmental Correction?	----	NO
EVRL	EVR Process averaging number of samples (RM)	----	49
FCD	Future Casing (Outer) Diameter	IN	7.000
GCSE	Generalized Caliper Selection	----	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	----	NO
IBS	Intergal Blade Stabilizer Collar?	----	YES
IDQT	Image Derived Quality Threshold	----	2.000
IHVS	Integrated Hole Volume Start Value (RM)	M3	0.000
IMAGE_MAX_SOA	Image SOA (Quadrant) Right Scale	IN	2.500
IMAGE_MAX_SPEF	Image PEF (Segment) Right Scale	----	6.000
IMAGE_MAX_SRHOB	Image RHOB (Segment) Right Scale	G/C3	2.650
IMAGE_MIN_SOA	Image SOA (Quadrant) Left Scale	IN	0.000
IMAGE_MIN_SPEF	Image PEF (Segment) Left Scale	----	2.000
IMAGE_MIN_SRHOB	Image RHOB (Segment) Left Scale	G/C3	2.050
JSD ADN	ADN Acquisition start date	G/C3	2.050
LITHO_TYPE ADN	Lithology (RM)	----	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	----	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	----	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	----	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	----	FR11
SOCNL	Standoff Distance of the CNL Tool	----	1.000
SSIZ ADN	ADN Stabilizer Size	IN	8.346
STOH	ADN Density Top of Hole Sector (Left Boundary):	-----SECTOR	0
TRPM_RM	Average Tool Rotational Speed	RPM	20.000
USMIN_RM	ADN: Minimum Ultrasonic standoff (RM)	IN	0.180
USWF_RM	ADN: Process Ultrasonic Waveform?	----	YES
VERS_ADN	ADN Downhole Software Version	----	8.300
WSDI	Window Size of Dynamic Normalization Image	M	15.240
Schlumberger Drilling & Measurements			
ID13 Parameter Insert Header Software version 3.0c			

IDEAL Version: ID13_0C_06

IDF

MWD_10 id13_0c_02 ADN id13_0c_02

Format: VISION Density Neutron Log Vertical Scale: 1:500 Graphics File Created: 05-Mar-2008 21:32

PIP SUMMARY

Neutron Ticks, 0.1 ft

GR(TM) PIP Density Ticks, 0.1 ft

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)
200 (M/HR) 0

GR(TM) (GRM1)
0 (GAPI) 200

Vertical Hole Diameter (VERD)
6 (IN) 16

Horizontal Hole Diameter (HORD)
6 (IN) 16

Photoelectric Factor (PEF) Bulk Density Correction (DRHO)
0 (----) 10 -0.75 (G/C3) 0.25

Thermal Neutron Porosity (TNPH)
45 (PU) -15


Density Time After Bit (TAB_DEN)
0 (HR) 10


ADN
Rotational
Speed
(RPM_ADN)
(RPM)
0 200


Bulk Density (RHOB)
1.85 (G/C3) 2.85




Casing Shoe @2517m MD

2550

















Primary Equipment:
Tool Name and Serial Number
Collar Type and Serial Number
Chassis Type and Serial Number
Stabilizer Type and Serial Number
Neutron Logging Source
Density Logging Source
Stabilizer Size
Calibration Status





ADN6 – CA
ADDC – AA
ADSE – EA
IBS
NSR – M
GSR – J/Z
8.35 – in.
Valid



373
40778

























202
1994







Master: 15–Jan–2008 23:42									
6.75–in. Azimuthal Density Neutron Calibration									
Density: Magnesium Block									
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value
Master				1039	Master				2672
	250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)			700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)	
Phase	SS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value
Master				6394	Master				2672
	2500 (Minimum)	23750 (Nominal)	45000 (Maximum)			700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)	


Master: 15–Jan–2008 23:42									
6.75–in. Azimuthal Density Neutron Calibration									
Density: Aluminum Block									
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value
Master				156.2	Master				1355
	50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)			500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)	
Phase	SS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value
Master				4015	Master				1355
	1500 (Minimum)	15750 (Nominal)	30000 (Maximum)			500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)	

Master: 15–Jan–2008 23:42									
6.75–in. Azimuthal Density Neutron Calibration									
Density: Background									
Phase	LS window 3 – Background CPS			Value	Phase	SS window 1 – Background CPS			Value
Master				49.65	Master				117.5
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)	
Phase	SS window 3 – Background CPS			Value	Phase	SS window 1 – Background CPS			Value
Master				513.5	Master				117.5
	150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)	

Master: 15–Jan–2008 23:42									
6.75–in. Azimuthal Density Neutron Calibration									
Density: Water Block Check									
Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value
Master				1.034	Master				1.143
	1.024 (Minimum)	1.039 (Nominal)	1.054 (Maximum)			1.096 (Minimum)	1.126 (Nominal)	1.156 (Maximum)	

Master: 15–Jan–2008 23:42									
6.75–in. Azimuthal Density Neutron Calibration									
Neutron: 3–Point Calibration									
Phase	Far 1 tube 1 Air Point Measure CPS			Value	Phase	Far 1 tube 1 Rod Point Measure CPS			Value
Master				17.03	Master				4.292
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 1 tube 1 H2O Point Measure CPS			Value	Phase	Far 1 tube 1 Rod Point Measure CPS			Value
Master				2.103	Master				4.292
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 1 tube 2 Air Point Measure CPS			Value	Phase	Far 1 tube 2 Rod Point Measure CPS			Value
Master				17.96	Master				4.380
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 1 tube 2 H2O Point Measure CPS			Value	Phase	Far 1 tube 2 Rod Point Measure CPS			Value
Master				2.166	Master				4.380
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 1 tube 3 Air Point Measure CPS			Value	Phase	Far 1 tube 3 Rod Point Measure CPS			Value
Master				16.34	Master				4.008
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 1 tube 3 H2O Point Measure CPS			Value	Phase	Far 1 tube 3 Rod Point Measure CPS			Value
Master				1.956	Master				4.008
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 1 Air Point Measure CPS			Value	Phase	Far 2 tube 1 Rod Point Measure CPS			Value
Master				16.32	Master				4.328
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 1 H2O Point Measure CPS			Value	Phase	Far 2 tube 1 Rod Point Measure CPS			Value
Master				2.075	Master				4.328
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 2 Air Point Measure CPS			Value	Phase	Far 2 tube 2 Rod Point Measure CPS			Value
Master				17.92	Master				4.511
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 2 H2O Point Measure CPS			Value	Phase	Far 2 tube 2 Rod Point Measure CPS			Value
Master				2.168	Master				4.511
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 3 Air Point Measure CPS			Value	Phase	Far 2 tube 3 Rod Point Measure CPS			Value
Master				17.33	Master				4.319
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	
Phase	Far 2 tube 3 H2O Point Measure CPS			Value	Phase	Far 2 tube 3 Rod Point Measure CPS			Value
Master				2.045	Master				4.319
	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	

(Minimum)	(Nominal)	(Maximum)		(Minimum)	(Nominal)	(Maximum)		(Minimum)	(Nominal)	(Maximum)	
Phase	Near 1 tube 1 Air Point Measure	CPS	Value	Phase	Near 1 tube 1 Rod Point Measure	CPS	Value	Phase	Near 1 tube 1 H2O Point Measure	CPS	Value
Master			454.5	Master			735.4	Master			325.4
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)		535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)		230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)
Phase	Near 2 tube 1 Air Point Measure	CPS	Value	Phase	Near 2 tube 1 Rod Point Measure	CPS	Value	Phase	Near 2 tube 1 H2O Point Measure	CPS	Value
Master			462.0	Master			725.7	Master			326.1
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)		535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)		230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)

Master: 15-Jan-2008 23:42			
6.75-in. Azimuthal Density Neutron Calibration			
Neutron: Water Block Check			
Phase	Far Neutron water porosity PU		Value
Master			98.07
	90.00 (Minimum)	100.0 (Nominal)	125.0 (Maximum)

SCHLUMBERGER

Survey report 18-Mar-2008 05:20:22

Client.....: ESSO Australia Pty Ltd
Field.....: Snapper

Well.....: SNA A21A
Service Order no.....: 07ASQ0022
Engineer.....: MS

COUNTY.....: ISLD 175
STATE.....: Victoria

Spud date.....: 05-Feb-08
Last survey date.....: 18-Mar-08
Total accepted surveys....: 91
MD of first survey.....: 625.00 m
MD of last survey.....: 3346.89 m

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's Depth
GL above permanent.....: -55.00 m
KB above permanent.....: Top Drive
DF above permanent.....: 41.70 m

----- Vertical section origin-----
Latitude (+N/S-).....: -3.69 m
Departure (+E/W-).....: 4.78 m

----- Platform reference point-----
Latitude (+N/S-).....:
Departure (+E/W-).....:

Azimuth from Vsect Origin to target: 312.96 degrees

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2007
Magnetic date.....: 25-Feb-2008
Magnetic field strength...: 1197.81 HCNT
Magnetic dec (+E/W-).....: 13.01 degrees
Magnetic dip.....: -68.71 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.02 mGal
Reference H.....: 1197.81 HCNT
Reference Dip.....: -68.71 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 13.01 degrees
Grid convergence (+E/W-)..: -0.63 degrees
Total az corr (+E/W-).....: 13.64 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2008 IDEAL ID13_OC_06]
SCHLUMBERGER Survey Report

18-Mar-2008 05:20:22

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	625.00	1.38	351.20	0.00	623.39	27.34	32.16	0.80	32.17	1.42	0.00	TIP	None
2	652.41	5.45	320.65	27.41	650.75	28.89	33.49	-0.08	33.49	359.87	4.80	MWD	None
3	705.85	12.48	317.04	53.44	703.50	37.18	39.69	-5.63	40.09	351.93	4.02	MWD	None
4	725.21	13.02	315.52	19.36	722.38	41.44	42.78	-8.58	43.63	348.66	1.00	MWD	None
5	754.52	14.44	311.84	29.31	750.86	48.40	47.57	-13.62	49.48	344.03	1.73	MWD	None
6	784.09	16.51	312.18	29.57	779.35	56.28	52.85	-19.48	56.33	339.77	2.14	MWD	None
7	813.12	18.78	313.53	29.03	807.02	65.08	58.84	-25.92	64.30	336.22	2.42	MWD	None
8	842.44	21.59	313.20	29.32	834.53	75.20	65.78	-33.28	73.72	333.17	2.92	MWD	None
9	871.68	24.22	311.73	29.24	861.46	86.58	73.46	-41.68	84.46	330.43	2.81	MWD	None
10	900.94	26.82	310.10	29.26	887.87	99.17	81.71	-51.21	96.43	327.92	2.81	MWD	None

11	930.15	29.84	307.85	29.21	913.58	113.00	90.42	-61.99	109.63	325.56	3.34	MWD	None
12	959.50	32.87	307.23	29.35	938.64	128.20	99.72	-74.10	124.23	323.38	3.16	MWD	None
13	989.11	33.88	307.39	29.61	963.36	144.41	109.59	-87.06	139.96	321.54	1.04	MWD	None
14	1018.15	34.17	307.26	29.04	987.43	160.58	119.44	-99.98	155.76	320.07	0.31	MWD	None
15	1047.09	34.15	308.61	28.94	1011.38	176.76	129.43	-112.79	171.68	318.93	0.80	MWD	None
16	1078.04	34.14	309.60	30.95	1037.00	194.10	140.39	-126.27	188.82	318.03	0.55	MWD	None
17	1107.99	33.85	312.28	29.95	1061.83	210.83	151.36	-138.92	205.45	317.45	1.55	MWD	None
18	1137.64	34.20	312.71	29.65	1086.40	227.42	162.57	-151.15	221.98	317.08	0.44	MWD	None
19	1165.35	34.55	312.45	27.71	1109.27	243.06	173.15	-162.67	237.58	316.79	0.42	MWD	None
20	1195.05	34.67	311.75	29.70	1133.72	259.93	184.46	-175.19	254.40	316.48	0.43	MWD	None
21	1223.98	34.59	311.04	28.93	1157.52	276.36	195.33	-187.52	270.78	316.17	0.43	MWD	None
22	1253.83	34.61	311.01	29.85	1182.09	293.30	206.46	-200.31	287.66	315.87	0.03	MWD	None
23	1283.30	35.06	310.70	29.47	1206.28	310.13	217.47	-213.04	304.43	315.59	0.50	MWD	None
24	1311.04	35.22	310.15	27.74	1228.97	326.08	227.82	-225.20	320.34	315.33	0.39	MWD	None
25	1339.83	34.49	309.08	28.79	1252.59	342.50	238.31	-237.87	336.71	315.05	1.01	MWD	None
26	1368.38	34.54	308.77	28.55	1276.11	358.64	248.48	-250.46	352.80	314.77	0.19	MWD	None
27	1398.22	34.75	309.47	29.84	1300.66	375.56	259.18	-263.62	369.69	314.51	0.46	MWD	None
28	1427.62	33.94	311.69	29.40	1324.94	392.13	269.97	-276.21	386.23	314.34	1.55	MWD	None
29	1457.22	33.59	312.30	29.60	1349.55	408.58	280.97	-288.44	402.67	314.25	0.50	MWD	None
30	1486.18	33.57	312.37	28.96	1373.67	424.60	291.76	-300.28	418.68	314.18	0.05	MWD	None
31	1515.35	34.00	311.71	29.17	1397.92	440.82	302.62	-312.33	434.89	314.10	0.59	MWD	None
32	1545.07	34.17	310.50	29.72	1422.53	457.46	313.57	-324.88	451.52	313.99	0.72	MWD	None
33	1573.99	33.63	309.97	28.92	1446.54	473.58	323.99	-337.19	467.62	313.86	0.65	MWD	None
34	1602.74	32.45	310.56	28.75	1470.64	489.23	334.12	-349.15	483.27	313.74	1.30	MWD	None
35	1632.66	31.89	310.51	29.92	1495.96	505.15	344.47	-361.26	499.17	313.64	0.57	MWD	None
36	1661.99	30.57	310.54	29.33	1521.04	520.34	354.36	-372.82	514.36	313.55	1.37	MWD	None
37	1691.42	28.92	310.18	29.43	1546.59	534.93	363.81	-383.95	528.94	313.46	1.72	MWD	None
38	1720.46	27.60	309.76	29.04	1572.17	548.66	372.64	-394.48	542.66	313.37	1.40	MWD	None
39	1750.04	26.32	309.58	29.58	1598.54	562.05	381.21	-404.80	556.04	313.28	1.32	MWD	None
40	1779.99	24.23	309.89	29.95	1625.62	574.81	389.38	-414.64	568.81	313.20	2.13	MWD	None
41	1808.98	22.83	310.45	28.99	1652.20	586.37	396.84	-423.48	580.36	313.14	1.49	MWD	None
42	1837.32	20.99	310.77	28.34	1678.49	596.94	403.72	-431.51	590.93	313.09	1.98	MWD	None
43	1867.39	18.74	310.60	30.07	1706.77	607.15	410.39	-439.26	601.14	313.05	2.28	MWD	None
44	1897.11	16.67	309.64	29.72	1735.08	616.17	416.21	-446.17	610.16	313.01	2.14	MWD	None
45	1926.28	15.62	309.74	29.17	1763.10	624.27	421.39	-452.41	618.26	312.97	1.10	MWD	None
46	1955.02	13.10	310.42	28.74	1790.94	631.39	425.98	-457.86	625.38	312.93	2.68	MWD	None
47	1984.70	10.07	310.16	29.68	1820.01	637.34	429.83	-462.41	631.33	312.91	3.11	MWD	None
48	2013.75	7.32	312.94	29.05	1848.72	641.73	432.73	-465.70	635.72	312.90	2.92	MWD	None
49	2044.10	4.92	317.60	30.35	1878.90	644.96	435.01	-468.00	638.95	312.91	2.46	PUP	None
50	2073.22	3.32	318.41	29.12	1907.94	647.05	436.56	-469.40	641.03	312.92	1.68	PUP	None
51	2102.90	1.71	322.36	29.68	1937.59	648.34	437.56	-470.24	642.33	312.94	1.66	PUP	None
52	2131.95	0.17	329.67	29.05	1966.64	648.81	437.94	-470.53	642.80	312.95	1.62	PUP	None
53	2161.88	0.06	37.16	29.93	1996.57	648.85	437.99	-470.54	642.84	312.95	0.16	PUP	None
54	2191.09	0.14	285.89	29.21	2025.78	648.89	438.01	-470.57	642.87	312.95	0.18	PUP	None
55	2220.65	0.11	151.26	29.56	2055.34	648.89	438.00	-470.59	642.88	312.95	0.24	PUP	None
56	2249.63	0.14	116.42	28.98	2084.32	648.83	437.96	-470.54	642.82	312.95	0.08	PUP	None
57	2279.10	0.14	131.90	29.47	2113.79	648.76	437.92	-470.48	642.75	312.95	0.04	PUP	None
58	2308.26	0.14	57.11	29.16	2142.95	648.72	437.91	-470.43	642.70	312.95	0.18	PUP	None
59	2337.63	0.17	15.68	29.37	2172.32	648.73	437.97	-470.38	642.71	312.96	0.12	PUP	None
60	2366.99	0.17	15.68	29.37	2201.70	648.73	437.97	-470.38	642.71	312.96	0.12	PUP	None
61	2396.35	0.17	15.68	29.37	2231.08	648.73	437.97	-470.38	642.71	312.96	0.12	PUP	None
62	2425.71	0.17	15.68	29.37	2260.46	648.73	437.97	-470.38	642.71	312.96	0.12	PUP	None
63	2454.71	0.29	12.45	28.97	2289.40	648.74	438.05	-470.32	642.72	312.97	0.28	PUP	None
64	2483.64	0.18	307.41	28.93	2318.33	648.82	438.15	-470.34	642.81	312.97	0.28	PUP	None
65	2511.29	0.17	271.05	27.65	2345.98	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
66	2540.65	0.17	271.05	27.65	2375.36	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
67	2569.99	0.17	271.05	27.65	2404.74	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
68	2599.35	0.17	271.05	27.65	2434.12	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
69	2628.71	0.17	271.05	27.65	2463.50	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
70	2658.07	0.17	271.05	27.65	2492.88	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
71	2687.43	0.17	271.05	27.65	2522.26	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
72	2716.79	0.17	271.05	27.65	2551.64	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
73	2746.15	0.17	271.05	27.65	2581.02	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
74	2775.51	0.17	271.05	27.65	2610.40	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
75	2804.87	0.17	271.05	27.65	2639.78	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
76	2834.23	0.17	271.05	27.65	2669.16	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
77	2863.59	0.17	271.05	27.65	2698.54	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
78	2892.95	0.17	271.05	27.65	2727.92	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
79	2922.31	0.17	271.05	27.65	2757.30	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
80	2951.67	0.17	271.05	27.65	2786.68	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
81	2981.03	0.17	271.05	27.65	2816.06	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
82	3010.39	0.17	271.05	27.65	2845.44	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
83	3039.75	0.17	271.05	27.65	2874.82	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
84	3069.11	0.17	271.05	27.65	2904.20	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
85	3098.47	0.17	271.05	27.65	2933.58	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
86	3127.83	0.17	271.05	27.65	2962.96	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
87	3157.19	0.17	271.05	27.65	2992.34	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
88	3186.55	0.17	271.05	27.65	3021.72	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
89	3215.91	0.17	271.05	27.65	3051.10	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
90	3245.27	0.17	271.05	27.65	3080.48	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
91	3274.63	0.17	271.05	27.65	3109.86	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
92	3303.99	0.17	271.05	27.65	3139.24	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
93	3333.35	0.17	271.05	27.65	3168.62	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
94	3362.71	0.17	271.05	27.65	3198.00	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
95	3392.07	0.17	271.05	27.65	3227.38	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
96	3421.43	0.17	271.05	27.65	3256.76	648.89	438.18	-470.42	642.88	312.97	0.12	PUP	None
97	3450.79	0.17	271.05	27.65	3286.14	648.89	438.18	-470.42	642.88	312.97	0.12		

Company:

ESSO Australia Pty Ltd

Schlumberger

Well:

SNA A21A

Field:

Snapper

Rig:

ISDL 175

8.50 in. Section

State:

Victoria

VISION Density Neutron

1:500 Measured Depth

Recorded Mode Log