

JSA ANALYSIS



Authors: C.J.Riggs	DST Tool Nubbins	Job Safety Analysis Number: DST/JSA-04
Date Issued: 1/8/06		Areas: All Locations
Required Personal Protective Equipment: Long sleeve shirt (coveralls), safety boots, hard hat, safety glasses, gloves, (gas monitor)		

Sequence of Job Steps	Potential Hazards	Recommended Action or Procedure
Entry to lease.	Undermined site, soft edges, boggy ground	Visually inspect the proposed location for ground stability.
Safety Meeting	Lack of dissemination of information for job at hand	Inform all as to procedure, knowledge of operation & objective important base for achievement of same. Question time important for all.
Use of Nubbins	Applicable to all nubbins Pinched, squashed fingers Loss of control	1.Lift into position using sling / elevators 2.Do not screw nubbin in while hanging in elevators, 3.Always release elevators & lift elevators out of the way into . derrick. 4.Screw in by hand 5. Makeup with chain tong 6. Mark with chalk/crayon/paint pen
Using Tugger	Frayed wire. Pinch points Mechanical problems. Loss of control. Trapped by, Crushed by,	Complete a thorough inspection of all equipment to be used before starting job. Visually inspect all lifting chains/slings for certification and wear. Always keep area between operator & tools clear. Look up & watch out for others. Designate specific parts of the operation to floormen. Ensure communication to all. DST PIC only person to give directions. Essential persons only all others to vacate area.