

Depth logged:	675.0 m To 2929.0 m	Mag decl:	13.248 deg.	Other services:
Date logged:	12-May-06 To 25-May-06	Mag dip:	-69.064 deg.	Directional Drilling, D&I



















Bit Run Summary

Run number	1	2	3	4						
Bit size	in.	8.5	8.5	8.5	8.5					
Bit start depth	m	675.0	2511.0	2890.0	2946.0					
Bit end depth	m	2511.0	2890.0	2946.0	2946.0					
Top interval logged	m	675.0	2511.0	2871.9	2871.9					
Bottom interval logged	m	2511.0	2871.9	2871.9	2929.0					
Begin log: time		21:31	16:41	N/A	06:00					
Begin log: date		12-May-06	19-May-06	N/A	25-May-06					
End log: time		09:04	17:26	N/A	08:00					
End log: date		18-May-06	21-May-06	N/A	25-May-06					
Mud data										
Depth	m	2511.0	2890.0	2946.0	2946.0					
Type		KCl/PHPA/Gly	KCl/PHPA/Gly	KCl/PHPA/Gly	KCl/PHPA/Gly					
Mud weight	ppg	9.50	9.70	9.80	9.80					
Solids	%	5.0	6.2	6.6	6.6					
Chlorides	mg/l	37000	39000	40000	40000					
Rm		N/A	N/A	N/A	N/A					
Rmf		N/A	N/A	N/A	N/A					
Rmc		N/A	N/A	N/A	N/A					

Potassium	%	3.80	4.09	4.09	4.09						
Environmental data											
GR											
Mud weight	ppg	9.50	9.70	9.80	9.80						
Bit size	in.	8.5	8.5	8.5	8.5						
Resistivity											
Neutron porosity											
Hole Size		N/A	N/A	N/A	N/A						
Mud weight		N/A	N/A	N/A	N/A						
Temperature		N/A	N/A	N/A	N/A						
Mud salinity		N/A	N/A	N/A	N/A						
Formation salinity		N/A	N/A	N/A	N/A						
Recording rate 1	SEC	3.83	3.83	3.83	3.83						
Recording rate 2	SEC	N/A	N/A	N/A	N/A						
Filtering GR		3 pt.	3 pt.	3 pt.	3 pt.						
Filtering density		N/A	N/A	N/A	N/A						
Filtering Neutron		N/A	N/A	N/A	N/A						
Company representative		G. Campbell	B. Steel	J. Bennett							
Schlumberger D&M Personnel		B. Pattarakorn	C. Skiba	M. McDermott	C. Soper	A. Tovar	R. Burns	C. Cocks			

<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
OTHER SERVICES FOR RUN1 Directional Drilling Directional Surveys D&I	OTHER SERVICES FOR RUN2 Directional Drilling Directional Surveys D&I	OTHER SERVICES FOR RUN3 Directional Drilling Directional Surveys D&I
REMARKS: RUN NUMBER 1 Depth is referenced to Driller's Depth. All data presented is from Real-Time Transmission. Environmental Corrections:-- Gamma Ray was corrected for Mud Weight, Tool size and Bit size. Gamma Ray is not corrected for Potassium. 8.5 in. hole was drilled from 675.0m to 2511.0m MD. Due to a Depth sensor failure, Gamma Ray data was lost from 917.0m to 939.0m and ROP data was lost from 928.0m to 958.0m. Due to high ROP, Gamma Ray data is coarse from 910.0m to 917.0m MD, and from 1256.0m to 1284.0m MD. ROP data was lost due to rig power shut down from 1275.0m to 1303.0m MD, and 1337.6m to 1360.9m MD. POOH for Bit Change.	REMARKS: RUN NUMBER 2 Depth is referenced to Driller's Depth. All data presented is from Real-Time Transmission. Environmental Corrections:-- Gamma Ray was corrected for Mud Weight, Tool size and Bit size. Gamma Ray is not corrected for Potassium. 8.5 in. hole was drilled from 2511.0m to 2890.0m MD. POOH for Bit Change.	REMARKS: RUN NUMBER 3 Depth is referenced to Driller's Depth. All data presented is from Real-Time Transmission. No Gamma Ray Data provided as PowerPulse ceased to transmit at 2890.0m MD. 8.5 in. hole was drilled from 2890.0m to 2946.0m MD. POOH at TD of WKF W20A.

EQUIPMENT DESCRIPTION		
RUN1	RUN2	RUN3
DOWNHOLE EQUIPMENT	DOWNHOLE EQUIPMENT	DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT			DOWNHOLE EQUIPMENT			DOWNHOLE EQUIPMENT		
6-3/4 in. PowerPulse* MDC: V875 MEC: 064 MDI: 738 MGR: AA 503 DHS: V80C02 OD 6.89		23.42	6-3/4 in. PowerPulse* MDC: V875 MEC: 064 MDI: 738 MGR: AA 503 DHS: V80C02 OD 6.89		23.46	6-3/4 in. PowerPulse* MDC: V875 MEC: 064 MDI: 738 MGR: AA 503 DHS: V80C02 OD 6.89		23.52
	D&I — 19.07			D&I — 19.11			D&I — 19.17	
	GR — 18.42			GR — 18.46			GR — 18.52	
6-5/8 in. NM Pony S/N: 97081023		14.93	6-5/8 in. NM Pony S/N: 97081023		14.97	6-5/8 in. NM Pony S/N: 97081023		15.03
6-5/8 in. NM Roller Reamer S/N: GU2317R		13.69	6-5/8 in. NM Roller Reamer S/N: GU2317R		13.73	6-5/8 in. NM Roller Reamer S/N: GU2317R		13.79
6-5/8 in. NM Pony wFloat S/N: ANA98-007		11.70	6-5/8 in. NM Pony wFloat S/N: ANA98-007		11.74	6-5/8 in. NM Pony wFloat S/N: ANA98-007		11.80
7 in. PowerPak* Motor A700GT 7:8 S/N: N7310 1.5 deg. Bent Housing		9.09	7 in. PowerPak* Motor A700GT 7:8 S/N: N7310 1.5 deg. Bent Housing		9.13	7 in. PowerPak* Motor A700GT 7:8 S/N: N7311 0 deg. Bent Housing		9.19
	0.00			0.00			0.00	
Smith PDC Bit OD: 8-1/2 in. S73PX S/N: JT6967		0.22	Smith TCI Bit OD: 8-1/2 in. GF11YODV S/N: MR5166		0.26	Smith PDC Bit OD: 8-1/2 in, S73PX S/N: JT6968A		0.22
Maximum string diameter 8.50 in.			Maximum string diameter 8.50 in.			Maximum string diameter 8.50 in.		
All lengths in Meters			All lengths in Meters			All lengths in Meters		


DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.


OTHER SERVICES FOR RUN4 Directional Drilling Directional surveys D&I	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 4 Depth is referenced to Driller's Depth. All data presented is from Real-Time Transmission. Environmental Correction:-- Gamma Ray was corrected for Mud weight, Tool size and Bit size. Gamma Ray is not corrected for Potassium. 8.5 in. hole was reamed up from 2946.0 m to 2890.0m MD. Gamma Ray data is spliced from 2890.0m to last reading at 2929.0m	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER



EQUIPMENT DESCRIPTION


RUN4	RUN	RUN
<div>DOWNHOLE EQUIPMENT</div> <div><div>6-3/4 in. PowerPulse*23.54</div><div>MDC: FA28</div><div>MEC: 1542</div><div>MDI: 1559</div><div>MGR: 295</div><div>DHS: V80B96</div><div>OD 6.89</div><div><div>D&I19.17</div><div>GR18.52</div></div></div>		



WKF W20A RT 1:200 TVD










700
TVD

725
TVD










800
TVD

825
TVD

850
TVD









925
TVD


950
TVD






975
TVD

1000
TVD







1025
TVD

1050
TVD


1075







1150
TVD

1175
TVD









1300
TVD

1325
TVD


1350
TVD






1425
TVD


1450
TVD






1475
TVD

1500
TVD







1525
TVD

1550
TVD


1575
TVD






1600
TVD

1625
TVD







1750
TVD

1775
TVD


1800
TVD






1825
TVD


1850
TVD






1875
TVD

1900
TVD







1975
TVD

2000
TVD

2025







2025
TVD

2050
TVD


2075
TVD






2100
TVD


2125
TVD






2150
TVD


2175
TVD







2200
TVD

2225
TVD







SCHLUMBERGER

Survey report

25-May-2006 12:53:48

Page 1 of 4

Client..... ESSO Australia Pty. Ltd.
Field..... West Kingfish

Well..... WKF W20A
Service Order number..... 06ASQ0005
Engineer..... B. Pattarakorn/ C. Skiba

Rig..... ISDL 453
STATE..... Victoria

Spud date..... 12 May 06
Last survey date..... 25-May-06
Total accepted surveys... 81
MD of first survey..... 674.53 m
MD of last survey..... 2946.00 m

----- Survey calculation methods-----
Method for positions..... Minimum curvature
Method for DLS..... Mason & Taylor

----- Depth reference -----
Permanent datum..... Mean Sea Level
Depth reference..... Driller's Depth
GL above permanent..... -76.13 m
KB above permanent..... 0.00 m
DF above permanent..... 33.43 m

----- Vertical section origin-----
Latitude (+N/S-)..... -4.35 m
Departure (+E/W-)..... 1.93 m

----- Platform reference point-----
Latitude (+N/S-)..... 5727806.50 m
Departure (+E/W-)..... 596265.00 m

Azimuth from Vsect Origin to target: 245.69 degrees

----- Geomagnetic data -----
Magnetic model..... BGGM version 2005
Magnetic date..... 11-May-2006
Magnetic field strength... 1202.51 HCNT
Magnetic dec (+E/W-)..... 13.25 degrees
Magnetic dip..... -69.06 degrees

----- MWD survey Reference Criteria -----
Reference G..... 1000.06 mGal
Reference H..... 1202.51 HCNT
Reference Dip..... -69.06 degrees
Tolerance of G..... (+/-) 2.50 mGal
Tolerance of H..... (+/-) 6.00 HCNT
Tolerance of Dip..... (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-)..... 13.25 degrees
Grid convergence (+E/W-).. -0.69 degrees
Total az corr (+E/W-)..... 13.94 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[(c)2006 IDEAL ID11_0C_01]
SCHLUMBERGER Survey Report

25-May-2006 12:53:48

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool Corr (deg)
1	674.53	46.50	253.23	0.00	622.76	189.41	-54.07	-183.45	191.25	253.58	0.00	TIP	None
2	706.79	50.72	241.60	32.26	644.13	213.52	-63.41	-205.69	215.24	252.87	3.00	MWD	None
3	735.63	50.08	239.53	28.84	662.51	235.65	-74.32	-225.04	237.00	251.72	0.60	MWD	None
4	763.06	46.38	238.21	27.43	680.78	255.96	-84.89	-242.55	256.98	250.71	1.40	MWD	None
5	792.99	42.30	236.90	29.93	702.18	276.67	-96.10	-260.21	277.39	249.73	1.40	MWD	None
6	823.14	38.13	237.55	30.15	725.20	295.91	-106.64	-276.57	296.42	248.91	1.39	MWD	None
7	850.62	34.44	237.39	27.48	747.35	312.01	-115.39	-290.28	312.37	248.32	1.34	MWD	None
8	878.86	33.78	237.13	28.24	770.73	327.67	-123.95	-303.60	327.93	247.79	0.24	MWD	None
9	907.36	33.51	236.86	28.50	794.46	343.28	-132.55	-316.84	343.45	247.30	0.11	MWD	None
10	936.95	32.59	238.86	29.59	819.26	359.27	-141.14	-330.50	359.38	246.88	0.48	MWD	None
11	964.80	32.38	238.93	27.85	842.75	374.12	-148.87	-343.31	374.19	246.56	0.08	MWD	None
12	993.42	31.99	238.25	28.62	866.97	389.25	-156.81	-356.32	389.30	246.25	0.19	MWD	None
13	1022.94	31.42	238.40	29.52	892.09	404.63	-164.96	-369.52	404.67	245.94	0.19	MWD	None
14	1051.55	30.85	238.27	28.61	916.58	419.30	-172.72	-382.11	419.34	245.68	0.20	MWD	None
15	1080.53	31.49	240.83	28.98	941.37	434.21	-180.32	-395.04	434.25	245.47	0.51	MWD	None
16	1109.94	31.23	240.18	29.41	966.49	449.46	-187.86	-408.36	449.50	245.30	0.15	MWD	None
17	1137.96	31.49	240.60	29.42	994.47	463.90	-195.08	-420.99	463.94	245.14	0.10	MWD	None
18	1167.96	31.49	240.60	29.42	1022.47	478.41	-202.30	-433.62	478.45	245.14	0.10	MWD	None

17	1137.96	31.08	240.62	28.02	990.47	463.89	-195.02	-420.97	463.94	245.14	0.10	MWD	None
18	1166.87	29.62	244.25	28.91	1015.42	478.47	-201.56	-434.01	478.53	245.09	1.11	MWD	None
19	1195.61	27.77	247.96	28.74	1040.63	492.27	-206.93	-446.72	492.32	245.15	0.70	MWD	None
20	1224.36	28.76	248.27	28.75	1065.95	505.87	-212.00	-459.35	505.92	245.23	0.35	MWD	None
21	1252.66	30.06	245.24	28.30	1090.60	519.76	-217.43	-472.12	519.80	245.27	0.70	MWD	None
22	1281.95	29.22	244.60	29.29	1116.06	534.24	-223.63	-485.24	534.29	245.26	0.31	MWD	None
23	1309.53	27.80	244.86	27.58	1140.29	547.40	-229.25	-497.14	547.45	245.24	0.52	MWD	None
24	1338.89	29.19	244.81	29.36	1166.10	561.41	-235.21	-509.82	561.46	245.23	0.47	MWD	None
25	1368.17	30.13	244.69	29.28	1191.54	575.90	-241.39	-522.92	575.95	245.22	0.32	MWD	None
26	1396.84	28.90	244.52	28.67	1216.49	590.02	-247.45	-535.68	590.07	245.21	0.43	MWD	None
27	1425.16	30.13	245.91	28.32	1241.13	603.97	-253.29	-548.35	604.02	245.21	0.50	MWD	None
28	1453.53	28.98	245.99	28.37	1265.81	617.96	-258.99	-561.13	618.01	245.22	0.41	MWD	None
29	1482.63	27.29	246.23	29.10	1291.47	631.68	-264.55	-573.67	631.73	245.24	0.58	MWD	None
30	1511.25	28.23	245.43	28.62	1316.80	645.01	-270.01	-585.83	645.06	245.25	0.35	MWD	None

[[c)2006 IDEAL ID11_OC_01]
SCHLUMBERGER Survey Report

25-May-2006 12:53:48

Page

3

of

4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool Corr (deg)
31	1539.77	27.46	245.23	28.52	1342.02	658.33	-275.57	-597.94	658.38	245.26	0.27	MWD	None
32	1568.45	28.58	244.22	28.68	1367.33	671.80	-281.33	-610.12	671.86	245.25	0.42	MWD	None
33	1597.09	27.80	243.57	28.64	1392.58	685.33	-287.28	-622.27	685.38	245.22	0.29	MWD	None
34	1625.48	30.45	244.68	28.39	1417.38	699.14	-293.30	-634.70	699.20	245.20	0.95	MWD	None
35	1654.41	30.47	244.59	28.93	1442.31	713.80	-299.58	-647.95	713.86	245.19	0.02	MWD	None
36	1682.43	30.24	244.31	28.02	1466.49	727.96	-305.69	-660.73	728.02	245.17	0.10	MWD	None
37	1711.73	29.39	244.52	29.30	1491.91	742.52	-311.98	-673.87	742.59	245.16	0.29	MWD	None
38	1740.32	28.62	245.05	28.59	1516.92	756.38	-317.89	-686.41	756.45	245.15	0.28	MWD	None
39	1769.67	28.24	245.59	29.35	1542.73	770.36	-323.72	-699.11	770.42	245.15	0.16	MWD	None
40	1798.67	27.48	245.37	29.00	1568.37	783.91	-329.35	-711.44	783.97	245.16	0.26	MWD	None
41	1827.64	29.57	244.90	28.97	1593.82	797.74	-335.17	-723.99	797.81	245.16	0.73	MWD	None
42	1855.91	29.01	245.48	28.27	1618.47	811.57	-340.97	-736.54	811.64	245.16	0.22	MWD	None
43	1884.87	28.52	245.00	28.96	1643.86	825.51	-346.81	-749.20	825.57	245.16	0.19	MWD	None
44	1913.53	27.59	244.89	28.66	1669.15	838.98	-352.52	-761.41	839.05	245.16	0.32	MWD	None
45	1942.40	26.83	244.54	28.87	1694.83	852.18	-358.15	-773.34	852.25	245.15	0.27	MWD	None
46	1971.75	27.82	244.37	29.35	1720.90	865.65	-363.96	-785.50	865.72	245.14	0.34	MWD	None
47	2000.10	27.44	244.07	28.35	1746.02	878.79	-369.68	-797.34	878.87	245.13	0.14	MWD	None
48	2028.99	26.94	244.59	28.89	1771.72	891.99	-375.40	-809.23	892.07	245.11	0.19	MWD	None
49	2057.82	29.28	244.92	28.83	1797.14	905.57	-381.19	-821.52	905.65	245.11	0.81	MWD	None
50	2086.13	28.98	244.47	28.31	1821.87	919.35	-387.08	-833.98	919.43	245.10	0.13	MWD	None
51	2114.27	28.28	244.27	28.14	1846.57	932.83	-392.92	-846.14	932.91	245.09	0.25	MWD	None
52	2143.80	27.40	244.34	29.53	1872.68	946.62	-398.89	-858.56	946.70	245.08	0.30	MWD	None
53	2171.65	28.15	244.42	27.85	1897.32	959.59	-404.51	-870.26	959.68	245.07	0.27	MWD	None
54	2201.22	28.95	246.24	29.57	1923.30	973.72	-410.40	-883.11	973.81	245.07	0.40	MWD	None
55	2230.09	28.34	245.38	28.87	1948.64	987.56	-416.07	-895.73	987.65	245.08	0.26	MWD	None
56	2258.89	27.57	245.72	28.80	1974.08	1001.06	-421.66	-908.02	1001.15	245.09	0.27	MWD	None
57	2287.33	30.20	247.14	28.44	1998.98	1014.80	-427.15	-920.61	1014.88	245.11	0.96	MWD	None
58	2316.69	31.70	246.61	29.36	2024.15	1029.89	-433.08	-934.50	1029.97	245.14	0.52	MWD	None
59	2345.46	34.08	245.32	28.77	2048.31	1045.51	-439.45	-948.76	1045.59	245.15	0.86	MWD	None
60	2373.81	35.28	245.70	28.35	2071.62	1061.64	-446.13	-963.44	1061.72	245.15	0.43	MWD	None

[[c)2006 IDEAL ID11_OC_01]
SCHLUMBERGER Survey Report

25-May-2006 12:53:48

Page

4

of

4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 10m)	Srvy tool type	Tool Corr (deg)
61	2402.35	37.26	246.37	28.54	2094.63	1078.53	-452.99	-978.87	1078.60	245.17	0.71	MWD	None
62	2431.27	40.90	245.77	28.92	2117.08	1096.75	-460.38	-995.53	1096.83	245.18	1.27	MWD	None
63	2459.03	42.82	245.76	27.76	2137.75	1115.28	-467.99	-1012.42	1115.35	245.19	0.69	MWD	None
64	2488.00	45.39	245.34	28.97	2158.55	1135.44	-476.33	-1030.77	1135.51	245.20	0.89	MWD	None
65	2517.61	49.71	246.31	29.61	2178.53	1157.28	-485.27	-1050.70	1157.35	245.21	1.48	MWD	None
66	2546.73	55.95	247.91	29.12	2196.12	1180.47	-494.28	-1072.07	1180.53	245.25	2.19	MWD	None
67	2575.77	60.70	246.52	29.04	2211.37	1205.16	-503.86	-1094.85	1205.22	245.29	1.69	MWD	None
68	2604.45	64.45	246.50	28.68	2224.57	1230.61	-514.00	-1118.19	1230.67	245.31	1.31	MWD	None
69	2633.12	67.90	248.28	28.67	2236.15	1256.82	-524.08	-1142.40	1256.88	245.36	1.33	MWD	None
70	2661.54	70.43	248.39	28.42	2246.26	1283.35	-533.88	-1167.08	1283.40	245.42	0.89	MWD	None
71	2690.06	72.05	247.45	28.52	2255.43	1310.34	-544.03	-1192.11	1310.38	245.47	0.65	MWD	None
72	2719.33	74.27	244.91	29.27	2263.91	1338.35	-555.35	-1217.73	1338.39	245.48	1.12	MWD	None
73	2747.50	74.93	244.96	28.17	2271.39	1365.50	-566.85	-1242.33	1365.54	245.47	0.23	MWD	None
74	2776.37	75.40	244.92	28.87	2278.79	1393.41	-578.68	-1267.61	1393.45	245.46	0.16	MWD	None
75	2805.15	75.49	245.23	28.78	2286.02	1421.26	-590.42	-1292.87	1421.31	245.46	0.11	MWD	None
76	2833.96	75.62	245.27	28.81	2293.20	1449.16	-602.10	-1318.21	1449.21	245.45	0.05	MWD	None
77	2862.67	75.70	245.06	28.71	2300.32	1476.97	-613.78	-1343.45	1477.02	245.45	0.08	MWD	None
78	2889.43	76.06	246.10	26.76	2306.84	1502.93	-624.51	-1367.08	1502.97	245.45	0.40	MWD	None
79	2919.19	77.19	245.82	29.76	2313.73	1531.88	-636.30	-1393.52	1531.92	245.46	0.39	MWD	None
80	2926.49	77.73	245.56	7.30	2315.31	1539.00	-639.23	-1400.02	1539.05	245.46	0.82	MWD	None
81	2946.00	78.20	245.25	19.51	2319.38	1558.08	-647.18	-1417.37	1558.13	245.46	0.29	Proj.	to TD

[[c)2006 IDEAL ID11_OC_01]

Company: **ESSO Australia Pty. Ltd.**

Schlumberger

Well: **WKF W20A**

Field: **West Kingfish**

Rig: **ISDL 453**

State: **Victoria**

Gamma Ray Service

1:200 True Vertical Depth

Real Time Log