

Essential Petroleum Resources Limited		<b>CASING RUNNING LIST</b>					<b>FORM CT-CRL KDC-SRF-01</b>		
		WELL NAME:		CASING TYPE:					
		KILLARNEY EPSL-1		Surface					
EPSL REP(S) : V. Ozolins		DEPTH: 257.83		SHOE AT : 255.83		DATE: 10/06/2004			
Joint Number		Depth		CASING			MAKE UP TORQUE		
From	To	From	To	Size	Grade	Weight	Maximum	Minimum	Optimum
1	20	250	4.5	9-5/8"	K55	40			
21	25			9-5/8"	K55	36			
ITEM	ITEM LENGTH	LENGTH RUN	JNT TOP OFF BTM	RUN YES / NO	COMMENTS				
					<i>Fm Tops running in</i> <input type="text"/> <i>Fm Tops @ Shoe Depth</i> <input type="text"/>				
			255.83		Shoe depth - Casing setting depth.				
Shoe	0.43	0.43	255.40		Top of Float Shoe, type : Halliburton PDC Drillable				
2	11.80	12.23	243.60						
Float	0.34	12.57	243.26		Top of Float Collar, type : Halliburton PDC Drillable				
1	11.98	24.55	231.28						
3	12.04	36.59	219.24						
4	12.05	48.64	207.19						
5	11.97	60.61	195.22						
6	12.01	72.62	183.21						
7	12.02	84.64	171.19						
8	12.04	96.68	159.15						
9	12.02	108.70	147.13						
10	12.03	120.73	135.10						
11	12.04	132.77	123.06						
12	11.99	144.76	111.07						
13	12.01	156.77	99.06						
14	12.01	168.78	87.05						
15	11.11	179.89	75.94						
16	11.86	191.75	64.08						
17	12.02	203.77	52.06						
18	11.82	215.59	40.24						
19	11.75	227.34	28.49						
20	11.95	239.29	16.54						
21	12.04	251.33	4.50						
22	12.04	263.37	-7.54	No	*Note: After Joint #21, run Landing Joint with 1.53m Stick-up.				
23	12.19	275.56	-19.73	No					
24	12.20	287.76	-31.93	No					
25	11.72	299.48	-43.65	No					
26									
27									
28									
29									
30									
31									
32									
33									
34									
35									
36									
37									
38									
39									