

PORT FAIRY #1 9 5/8" SURFACE CASING RUNNING TALLY

Joint No.	Joint Length (meters)	Cumulative Length (meters)	Depth Landed 812.00m	Capacity (bbls) 0.07324bbl/ft	Displacement (bbls) 0.08117bbl/ft	String Weight klb 47.00lb/ft	Remarks
Shoe & Jt	12.82	12.82	812.00	3.08 bbl	3.41 bbl	1.977	shoe length 0.52m float length 0.35m
Float & Jt	12.52	25.34	799.18	3.01 bbl	6.75 bbl	3.907	
3	12.20	37.54	786.66	5.94 bbl	10.00 bbl	5.789	
4	12.12	49.66	774.46	8.85 bbl	13.22 bbl	7.657	
5	11.88	61.54	762.34	11.71 bbl	16.39 bbl	9.489	
6	11.77	73.31	750.46	14.54 bbl	19.52 bbl	11.304	
7	12.29	85.60	738.69	17.49 bbl	22.79 bbl	13.199	
8	11.93	97.53	726.40	20.35 bbl	25.97 bbl	15.039	
9	11.78	109.31	714.47	23.19 bbl	29.11 bbl	16.855	
10	12.51	121.82	702.69	26.19 bbl	32.44 bbl	18.784	
11	11.77	133.59	690.18	29.02 bbl	35.57 bbl	20.599	
12	12.22	145.81	678.41	31.96 bbl	38.83 bbl	22.484	
13	11.28	157.09	666.19	34.67 bbl	41.83 bbl	24.223	
14	11.14	168.23	654.91	37.34 bbl	44.80 bbl	25.941	
15	11.86	180.09	643.77	40.19 bbl	47.96 bbl	27.769	
16	11.07	191.16	631.91	42.85 bbl	50.90 bbl	29.476	
17	11.36	202.52	620.84	45.58 bbl	53.93 bbl	31.228	
18	12.41	214.93	609.48	48.56 bbl	57.23 bbl	33.142	
19	12.08	227.01	597.07	51.47 bbl	60.45 bbl	35.004	
20	12.44	239.45	584.99	54.46 bbl	63.76 bbl	36.923	
21	12.82	252.27	572.55	57.54 bbl	67.18 bbl	38.899	
22	12.00	264.27	559.73	60.42 bbl	70.37 bbl	40.750	
23	12.02	276.29	547.73	63.31 bbl	73.57 bbl	42.603	
24	12.34	288.63	535.71	66.27 bbl	76.86 bbl	44.506	
25	10.97	299.60	523.37	68.91 bbl	79.78 bbl	46.198	
26	12.18	311.78	512.40	71.84 bbl	83.02 bbl	48.076	
27	12.08	323.86	500.22	74.74 bbl	86.24 bbl	49.938	
28	11.84	335.70	488.14	77.58 bbl	89.39 bbl	51.764	
29	12.60	348.30	476.30	80.61 bbl	92.75 bbl	53.707	
30	11.60	359.90	463.70	83.40 bbl	95.84 bbl	55.496	
31	11.15	371.05	452.10	86.08 bbl	98.81 bbl	57.215	
32	12.09	383.14	440.95	88.98 bbl	102.03 bbl	59.079	
33	12.21	395.35	428.86	91.92 bbl	105.28 bbl	60.962	
34	12.42	407.77	416.65	94.90 bbl	108.59 bbl	62.877	
35	11.79	419.56	404.23	97.74 bbl	111.73 bbl	64.695	
36	12.10	431.66	392.44	100.64 bbl	114.95 bbl	66.561	
37	12.11	443.77	380.34	103.55 bbl	118.17 bbl	68.428	
38	11.98	455.75	368.23	106.43 bbl	121.36 bbl	70.276	
39	12.22	467.97	356.25	109.37 bbl	124.62 bbl	72.160	
40	11.55	479.52	344.03	112.14 bbl	127.69 bbl	73.941	
41	12.52	492.04	332.48	115.15 bbl	131.03 bbl	75.871	
42	11.65	503.69	319.96	117.95 bbl	134.13 bbl	77.668	
43	12.14	515.83	308.31	120.87 bbl	137.36 bbl	79.540	
44	11.83	527.66	296.17	123.71 bbl	140.51 bbl	81.364	
45	12.41	540.07	284.34	126.69 bbl	143.82 bbl	83.277	
46	11.58	551.65	271.93	129.47 bbl	146.90 bbl	85.063	
47	11.58	563.23	260.35	132.26 bbl	149.98 bbl	86.849	
48	10.99	574.22	248.77	134.90 bbl	152.91 bbl	88.543	
49	12.49	586.71	237.78	137.90 bbl	156.24 bbl	90.469	
50	12.08	598.79	225.29	140.80 bbl	159.45 bbl	92.332	
51	12.34	611.13	213.21	143.77 bbl	162.74 bbl	94.235	
52	11.91	623.04	200.87	146.63 bbl	165.91 bbl	96.071	
53	11.99	635.03	188.96	149.51 bbl	169.10 bbl	97.920	
54	12.21	647.24	176.97	152.44 bbl	172.35 bbl	99.803	
55	12.24	659.48	164.76	155.39 bbl	175.61 bbl	101.690	
56	12.42	671.90	152.52	158.37 bbl	178.92 bbl	103.605	
57	11.81	683.71	140.10	161.21 bbl	182.07 bbl	105.426	
58	12.19	695.90	128.29	164.14 bbl	185.31 bbl	107.306	
59	12.36	708.26	116.10	167.11 bbl	188.60 bbl	109.212	
60	12.54	720.80	103.74	170.12 bbl	191.94 bbl	111.146	
61	12.37	733.17	91.20	173.09 bbl	195.24 bbl	113.053	
62	12.59	745.76	78.83	176.12 bbl	198.59 bbl	114.994	
63	12.35	758.11	66.24	179.08 bbl	201.88 bbl	116.899	
64	12.52	770.63	53.89	182.09 bbl	205.21 bbl	118.829	

PORT FAIRY #1 9 5/8" SURFACE CASING RUNNING TALLY

Joint No.	Joint Length	Cumulative Length	Depth Landed	Capacity (bbls)	Displacement (bbls)	String Weight klb	Remarks
65	12.51	783.14	41.37	185.10 bbl	208.54 bbl	120.758	
66	11.97	795.11	28.86	187.98 bbl	211.73 bbl	122.604	
67	12.09	807.20	16.89	190.88 bbl	214.95 bbl	124.468	
Lnd Jt	7.50	814.70	4.80	192.68 bbl	216.95 bbl	125.625	Landing joint
68	12.54	827.24	-2.70	195.70 bbl	220.29 bbl	127.558	OUT
69	13.10	840.34	-15.24	198.84 bbl	223.78 bbl	129.578	OUT
70	13.02	853.36	-28.34	201.97 bbl	227.24 bbl	131.586	OUT
71	12.68	866.04	-41.36	205.02 bbl	230.62 bbl	133.541	OUT
72	12.64	878.68	-54.04	208.06 bbl	233.98 bbl	135.490	OUT
73	12.47	891.15	-66.68	211.05 bbl	237.31 bbl	137.413	OUT
74	12.39	903.54	-79.15	214.03 bbl	240.60 bbl	139.324	OUT
75	12.35	915.89	-91.54	217.00 bbl	243.89 bbl	141.228	OUT
Stick up above RT		<u>-2.70m</u>					

CASING RUN SUMMARY

Drill to 821m. Run survey. POOH.
 Conduct pre-casing meeting.
 Rig up to run casing.
 Run shoe followed by next 5 joints of casing. (13.3/8" K-55 BTC Casing)
 Tag bottom. Pick up of bottom to cement.
 Prepare for cementing.
 Conduct pre-cementing meeting.
 Commence cement job.