



**LAKES OIL
WOMBAT # 2
DST REPORTS**



**DST # 1
REPORT**



COMPANY: Lakes Oil **State:** Vict **Date:** 16/04/2004
Well Name: Wombat # 2 **KB Elev:** 14.65 m **Ticket No:** 573
Well Loc: PEP 157 **GR Elev:** 11 m **DST No:** 1
Interval: 1355.64 - 1390 m **T.D. (m):** 1390 m **Test Type:** Conventional bottom hole

RECORDER DATA :

Rec #	6883	3149	6886	6885
Range lbs	10 k	3800	10 k	10 k
Clock hrs	Battery	24	Battery	Battery
Depth m	1341.69	1348.24	1349.8	1372.63
	PSI	PSI	PSI	PSI
Initial Hydrostatic			2432.86	2450.49
Initial Prewflow			188.53	196.65
Final Prewflow			576.93	729.99
Initial Shutin				
Initial Flow				
Final Flow				
Final Shutin		493.65	1887.03	1898.2
Final Hydrostatic			2414.25	2439.63
Inside / Outside	Fluid	Fluid	In	In
				Out

TIME DATA :

		Time Start	Time End
Prewflow	15 mins	2:45	3:00
Initial Shutin	30 mins	3:00	3:30
Initial Flow	30 mins	3:30	4:00
Final Shutin	30 mins	4:00	4:30

Time Start 20:00 **On Bottom** 2:43 **Time Open** 2:45 **Time Pulled** 4:30 **Time Out** 13:30

	COMPANY: Lakes Oil WELL NAME: Wombat # 2 FORMATION: Golden Beach TESTER: Chad McGuinn / Jason Noud	DATE: 15/04/2004 DST # 1
	Total Tool To Bottom Packer 18.58 Tool Interval 16.10 Total Tool 34.68	
	H.W. In Interval 1 std 18.26 Drill Collars Above Tool 6 stds + 1 122.79 Jars 9.59 HWDP Above Tool 1 9.50 Drill Pipe Above Tool 1198.20 Pup Joint/s Above Tool 63 stds + 1 0 Total 1393.02	
	STICK UP -2.02 Drill Pipe 63 stds + 1 1198.2 -2.02 Pup Jt/s 1196.18 Drill Pipe 1196.18 H.W. Drill Pipe 1 9.50 1196.18 Drill Collars 1 st + 1 28.14 1205.68 Jars 9.59 1233.82 Drill Collars 4 stds 75.80 1243.41 Pump Out Sub 0.30 1319.21 Drill Collar 1 9.49 1319.51 Drop Bar Sub 0.30 1329.00 Drill Collar 1 9.36 1329.30 Cross Over 0.40 1338.66 Spacing 3.63 1339.06 Fluid Electronic Rec Carrier 1.55 1342.69 Shut in Tool 1.70 1344.24 Sampler 1.20 1345.94 Travel Sub 0.46 1347.14 Hyd Tool 1.68 1347.60 Inside Mechanical Rec Carrier 1.52 1349.28 Inside Electronic Rec Carrier 1.83 1350.80 Jars 0.00 1352.63 Safety Joint 0.66 1352.63 Packer 2.31 1353.29 Packer 1.04 1355.60	
	DEPTH 1356.64 Stick Down 1.01 1356.64 Perf 6.08 1357.65 Outside Electronic Rec Carrier 1.52 1363.73 Perf 4.56 1365.25 Cross Over 0.40 1369.81 H.W. Drill Pipe 1 std 18.26 1370.21 Cross Over 0.40 1388.47 Perf 1.52 1388.87 Bullnose 0.61 1390.39 TOTAL DEPTH 1391.00	




DST # 1
PLOTS AND DATA

Lakes Oil
Gauge set @ 1372.63m
Start Test Date: 2004/04/15

Outside recor


Wombat # 2 DST # 1



Lakes Oil

Gauge set @ 1349.8m
Start Test Date: 2004/04/15


Wombat # 2 DST # 1



Fluid E

Lakes Oil
gauge set @1342.69m
Start Test Date: 2004/04/15

Wombat # 1 DST # 1





**DST # 1A
REPORT**



Company: Lakes Oil **State:** Vict **Date:** 17/04/2004
Well Name: Wombat # 2 **KB Elev:** 14.65 m **Ticket No:** 574
Well Loc: Pep 157 **GR Elev:** 11 m **DST No:** 1A
Interval: 1328.29 - 1391 m **T.D. (m)** 1391 m **Test Type:** Conventional bottom hole

RECORDER DATA:

Rec #	6883		6886	6883
Range lbs	10 k		10 k	10 k
Clock hrs	Battery		Battery	Battery
Depth m	1311.92		1319.8	1339.94
	PSI	PSI	PSI	PSI
Initial Hydrostatic			2338.39	2375.31
Initial Preflow				
Final Preflow				
Initial Shutin				
Initial Flow			1483.83	1618.05
Final Flow			1837.17	1866.06
Final Shutin			1840.52	1869.35
Final Hydrostatic	1812.64		2325.56	2359.27
Temperature	143 F		143 F	143 F
	<i>Fluid</i>	<i>Fluid</i>	<i>In</i>	<i>Out</i>

TIME DATA:

		<u>Time Start</u>	<u>Time End</u>
Preflow	_____ mins	_____	_____
Initial Shutin	_____ mins	_____	_____
Initial Flow	240 mins	6:40	10:40
Final Shutin	60 mins	10:40	11:40

Time Start 0:00 **On Bottom** 6:38 **Time Open** 6:40 **Time Pulled** _____ **Time Out** _____

TOOL DATA:

Tool Weight: 7 k lbs
Weight Set on Packers: 40 k lbs
Weight Pulled Loose: 105 k lbs
Initial String Weight: 90 k lbs
Hole Size: 8.5 ins
Bottom Hole Choke: 0.75 ins

	<u>ID</u>	<u>Length</u>
Drill Pipe:	3 5/6	103.94m
HW Drill Pipe:	3	0m
Drill Collars:	2 7/8	1208.65 m

FLUID RECOVERY:

_____ (m) of _____
 _____ (m) of _____
 _____ (m) of _____
 _____ (m) of _____

Total Fluid 1275 m of formation water

MUD DATA:

Mud Type	Kcl / polymer
Weight	10.4
Vis.	44
W.L.	6.4
F.C.	1\32
Mud Drop	Nil

BLOW DESCRIPTION AND REMARKS:

GAS FLOW RATES:

Comments

	<u>TIME (mins)</u>	<u>CHOKE</u>	<u>PSI</u>	<u>M CF/D</u>
Tool open bubble on bucket strong .	6:40			
	6:45 .		8	
Open thru 1/4 choke @ 12 psi .	6:48	1/4	12	
	6:50 .		14	
	6:55		10	
	7:00		4	
Gas to surface 1/2 / 1 m lazy flare .	7:05		1	
Open manifold thru centre valve approx 13/16	7:15			
Surging bubble on top of bucket / lazy 1 m flare @ 0 psi			0	
Shut in manifold & bubble hose .	8:40			
Bleed off pressure . 1m flare dies immediately.	10:37		14	
Shut in tool	10:40			
Sample Chamber Recovery - gas cut water @ 300 psi				

GENERAL DATA:

Amount of Fill (m):	0	Cushion Amount (m):	Nil	Tester:	Chad McGuinn/Jason Noud
Bottom Hole Temp (F):	143	Cushion Type:	N.A.	Company Rep:	Lou De Vattimo
Hole Condition:	Good	Reversed Out:	Yes	Contractor:	Hunt
Packer Size:	7 1/2	Tool Chased:	No	Rig Number:	2
Number of Packers:	2				

	COMPANY: Lakes Oil	DATE: 17/04/2004		
	WELL NAME: Wombat # 2	DST # 1A		
	FORMATION: Golden Beach			
	TESTER: Chad McGuinn / Jason Noud			
	Total Tool To Bottom Packer		20.15	
	Tool Interval		16.10	
	Total Tool :		36.25	
	H.W. + D.Cs. In Interval		46.61	
	Drill Collars Above Tool	5std + 1	103.94	
	Jars		0	
	HWDP Above Tool		0.00	
	Drill Pipe Above Tool	64 stds	1208.65	
	Pup Joint/s Above Tool		0	
	Total :		1395.45	
	STICK UP :		-4.45	
	Drill Pipe	64 stds	1208.65	-4.45
	Pup Jt/s			1204.20
	Drill Pipe			1204.20
	H.W. Drill Pipe	0.00		1204.20
	Drill Collars	0		1204.20
Jars	0		1204.20	
Drill Collars	4stds + 1	84.95	1204.20	
Pump Out Sub		0.30	1289.15	
Drill Collar	1	9.45	1289.45	
Drop Bar Sub		0.30	1298.90	
Drill Collar	1	9.54	1299.20	
Cross Over		0.40	1308.74	
Spacing		2.78	1309.14	
Fluid Electronic Rec Carrier		1.52	1311.92	
Shut in Tool		1.64	1313.44	
Sampler		1.02	1315.08	
Travel Sub		0.46	1316.10	
Hyd Tool		1.68	1316.56	
Inside Mechanical Rec Carrier		1.56	1318.24	
Inside Electronic Rec Carrier		1.78	1319.80	
Jars		2.70	1321.58	
Safety Joint		0.66	1324.28	
Packer		2.31	1324.94	
Packer		1.04	1327.25	
DEPTH :		1328.29		
Stick Down		1.01	1328.29	
Perf		6.08	1329.30	
Perf		4.56	1335.38	
Outside Electronic Rec Carrier		1.52	1339.94	
Cross Over		0.40	1341.46	
3 H.W. + Std D.Cs.		46.61	1341.86	
Cross Over		0.40	1388.47	
Perf		1.52	1388.87	
Bullnose		0.61	1390.39	
TOTAL DEPTH :		1391.00		




**DST # 1A
PLOTS AND DATA**

Lakes Oil
 Gauge set @1339.94m
 Start Test Date: 2004/04/16

Outside E


Wombat # 2 DST # 1a



Lakes Oil
Gauge set @ 1319.8m
Start Test Date: 2004/04/16

Inside E


Wombat # 2 DST # 1a



Lakes Oil
Gauge set @ 1311.92m
Start Test Date: 2004/04/16

Fluid E

Wombat # 2 DST # 1A





**DST # 2
REPORT**



COMPANY: Lakes Oil **State:** Vict **Date:** 18/04/2004
Well Name: Wombat # 1 **KB Elev:** 14.65 m **Ticket No:** 575
Well Loc: Pep 157 **GR Elev:** 11 m **DST No:** 2
Interval: 1399.72 - 1428 m **T.D. (m):** 1428 **Test Type:** Conventional bottom hole

RECORDER DATA:

Rec #	6886		6883	6885
Range lbs	10 k		10 k	10 k
Clock hrs	Battery		Battery	Battery
Depth m	1386.05		1393.93	1403.77
	PSI	PSI	PSI	PSI
Initial Hydrostatic			2498.51	2498.93
Initial Prewell				
Final Prewell				
Initial Shutin				
Initial Flow			201.25	201.25
Final Flow			225.79	222.69
Final Shutin	117.67		1994.89	1986.81
Final Hydrostatic			2490.03	2479.92
Temperature				
	Fluid	Fluid	In	In
				Out

TIME DATA:

		<u>Time Start</u>	<u>Time End</u>
Prewell	mins		
Initial Shutin	mins		
Initial Flow	257 mins	18:28	22:15
Final Shutin	120 mins	22:15	0:15

Time Start: 13:00 **On Bottom:** 18:25 **Time Open:** 18:28 **Time Pulled:** 0:15 **Time Out:** 8:00

**CALCULATION OF GAS FLOWS FROM FLOW PRESSURE
BEHIND SURFACE CHOKE:**



Gas Flow = 0.0555*C*(Pressure+15)

1/4 choke

Coefficient Table	
Choke Size (in)	Coefficient (C)
1/8	6.25
3/16	14.44
1/4	26.51
5/16	43.64
3/8	61.21
7/16	85.13
1/2	112.72
5/8	179.74
3/4	260.99

	Pressure (psi g)	Gas Flow (Mmcf/d)
18:28	24	0.057
18:29	34	0.072
18:30	40	0.081
:31	54	0.102
:32	60	0.110
:34	78	0.137
:36	88	0.152
:37	92	0.157
:39	102	0.172
:41	108	0.181
:43	112	0.187
:44	116	0.193
:46	120	0.199
:48	124	0.205
:52	128	0.210
:53	129	0.212
:56	132	0.216
:59	134	0.219
19:04	136	0.222
:09	138	0.225
:24	138	0.225

STILL INCREASES IN G
↓

**CALCULATION OF GAS FLOWS FROM FLOW PRESSURE
BEHIND SURFACE CHOKE:**



Gas Flow = 0.0555*C*(Pressure+15)

1/2 choke

Coefficient Table	
Choke Size (in)	Coefficient (C)
1/8	6.25
3/16	14.44
1/4	26.51
5/16	43.64
3/8	61.21
7/16	85.13
1/2	112.72
5/8	179.74
3/4	260.99

	Pressure (psi g)	Gas Flow (Mmcf/d)
19:24	118	0.832
:25	114	0.807
:26	0	0.094
:27	96	0.694
:28	78	0.582
:30	62	0.482
:32	54	0.432
:34	46	0.382
:36	40	0.344
:38	38	0.332
:41	32	0.294
:45	30	0.282
:47	28	0.269
:54	26	0.256

↓
DEPRESSING

	Drill Pipe	COMPANY: Lakes Oil	DATE: 18/04/2004
	Pup Joint	WELL NAME: Wombat # 2	DST # 2
	Drill Pipe	FORMATION: Golden Beach	
	HWDP	TESTER: Chad McGuinn / Jason Noud	
	Drill Collars		
		Total Tool To Bottom Packer	14.67
		Tool Interval	10.02
	Drill Collars	Total Tool :	24.69
	Pump out sub	H.W. In Interval	1 std 18.26
		Drill Collars Above Tool	6 stds + 1 122.79
	Jars	9.59	
Drill Collars	Hev - Waite Above Tool	1 9.50	
	Drill Pipe Above Tool	1246.47	
Drop bar sub	Pup Joint/s Above Tool	63 stds + 1 0	
	Total :	1431.30	
Drill collar	STICK UP:	-3.30	
	Drill Pipe	66 stds 1246.47 -3.30	
X-over	Pup Jt/s	1243.17	
	Drill Pipe	1243.17	
Rec.carrier	H.W. Drill Pipe	1 9.50 1243.17	
	Drill Collars	1 st + 1 28.14 1252.67	
Rec.carrier	Jars	9.59 1280.81	
	Drill Collars	4 stds 75.80 1290.40	
Shut-in tool	Pump Out Sub	0.30 1366.20	
	Drill Collar	1 9.49 1366.50	
Sampler	Drop Bar Sub	0.30 1375.99	
	Drill Collar	1 9.36 1376.29	
Travel sub	Cross Over	0.40 1385.65	
	Spacing	0.00 1386.05	
	Fluid Electronic Rec Carrier	1.52 1386.05	
Hydraulic tool	Shut in Tool	1.64 1387.57	
	Sampler	1.02 1389.21	
Rec Carrier	Travel Sub	0.46 1390.23	
Rec Carrier	Hyd Tool	1.68 1390.69	
Jar	Inside Mechanical Rec Carrier	1.56 1392.37	
Safety joint	Inside Electronic Rec Carrier	1.78 1393.93	
Packer	Jars	0.00 1395.71	
	Safety Joint	0.66 1395.71	
Packer	Packer	2.31 1396.37	
Stick Down	Packer	1.04 1398.68	
Perf	DEPTH	1399.72	
	Stick Down	1.01 1399.72	
Rec Carrier	Perf	3.04 1400.73	
	Outside Electronic Rec Carrier	1.52 1403.77	
X- Over	Perf	3.04 1405.29	
1 Std HWDP	Cross Over	0.40 1408.33	
X- Over	H.W. Drill Pipe	1 std 18.26 1408.73	
Perf	Cross Over	0.40 1426.99	
	Perf	0.00 1427.39	
Bull Nose	Bullnose	0.61 1427.39	
	TOTAL DEPTH	1428.00	



DST # 2
PLOTS AND DATA


Lakes Oil

Gauge set @ 1403.77m

Start Test Date: 2004/04/18

Outside E


Wombat # 2 DST # 2



Lakes Oil
 Gauge set @1393.93m
 Start Test Date: 2004/04/18

Inside E


Wombat # 2 DST # 2



Lakes Oil
Gauge set @1386.05m
Start Test Date: 2004/04/18

Fluid E

Wombat # 2 DST # 2





**DST # 3
REPORT**



COMPANY: Lakes Oil **State:** Vict **Date:** 20/04/2004
Well Name: Wombat # 1 **KB Elev:** 14.65 m **Ticket No:** 576
Well Loc: Pep 157 **GR Elev:** 11 m **DST No:** 3
Interval: 1463.85 - 1497 m **T.D. (m):** 1497 m **Test Type:** Conventional bottom hole

RECORDER DATA:

Rec #	6886		6883	6885
Range lbs	10 k		10 k	10 k
Clock hrs	Battery		Battery	Battery
Depth m	1450.18	1456.5	1458.06	1475.5
	PSI	PSI	PSI	PSI
Initial Hydrostatic			2633.92	2672.73
Initial Preflow			336.86	374.07
Final Preflow			409.85	434.4
Initial Shutin			2049.22	2059.91
Initial Flow			360.07	380.71
Final Flow			414.99	429.24
Final Shutin	232.21		1902.26	1913.24
Final Hydrostatic			2617.19	2655.05
Temperature			141 F	143 F
	Fluid	Fluid	In	Out

TIME DATA:

		<u>Time Start</u>	<u>Time End</u>
Preflow	11 mins	18:04	18:15
Initial Shutin	45 mins	18:15	19:00
Initial Flow	60 mins	19:00	20:00
Final Shutin	180 mins	20:00	23:00

Time Start 12:40 **On Bottom** 18:00 **Time Open** 18:04 **Time Pulled** 23:00 **Time Out** 11:00

**CALCULATION OF GAS FLOWS FROM FLOW PRESSURE
BEHIND SURFACE CHOKE :**



Gas Flow = 0.0555*C*(Pressure+15)

Coefficient Table	
Choke Size (in)	Coefficient (C)
1/8	6.25
3/16	14.44
1/4	26.51
5/16	43.64
3/8	61.21
7/16	85.13
1/2	112.72
5/8	179.74
3/4	260.99

1/4 choke		
	Pressure (psi g)	Gas Flow (Mmcf/d)
18:04	60	0.110
:06	80	0.140
:07	108	0.181
:08	122	0.202
:09	156	0.252
:11	200	0.316
:13	210	0.331
:14	230	0.360
Shut in		0.022
19:00	10	0.037
:01	100	0.169
:02	190	0.302
:03	240	0.375
:04	250	0.390
:05	260	0.405
:07	270	0.419
:09	280	0.434
:12	290	0.449
:15	300	0.463
:18	305	0.471
:21	306	0.472
:24	307	0.474
:27	305	0.471
:30	302	0.466
:33	300	0.463
:37	295	0.456
:40	290	0.449
:45	285	0.441
:50	275	0.427
:55	265	0.412
20:00	260	0.405

	Drill Pipe	COMPANY: Lakes Oil	DATE: 20/04/2004
	Pup Joint	WELL NAME: Wombat # 2	DST # 3
	Drill Pipe	FORMATION: Strzelecki	
	HWDP	TESTER: Chad McGuinn / Jason Noud	
	Drill Collars	Total Tool To Bottom Packer	14.67
	Jar	Tool Interval	14.89
	Drill Collars	Total Tool :	29.56
	Pump out sub	H.W. In Interval	1 std 18.26
	Drill Collars	Drill Collars Above Tool	7 stds + 1 141.50
	Drop bar sub	Jars	9.59
	Drill collar	Hev - Waite Above Tool	1 9.50
	X-over	Drill Pipe Above Tool	68+1 stds 1293.95
	Rec.carrier	Pup Joint/s Above Tool	0
	Rec.carrier	Total :	1502.36
	Shut-in tool	STICK UP :	-5.36
	Sampler	Drill Pipe	68 + 1 stds 1293.95 -5.36
	Travel sub	Pup Jt/s	1288.59
	Hydraulic tool	Drill Pipe	1288.59
	Rec Carrier	H.W. Drill Pipe	1 9.50 1288.59
	Rec Carrier	Drill Collars	1 9.38 1298.09
Safety joint	Jars	9.59 1307.47	
Packer	Drill Collars	6 stds 113.27 1317.06	
Packer	Pump Out Sub	0.30 1430.33	
Perf	Drill Collar	1 9.49 1430.63	
Rec Carrier	Drop Bar Sub	0.30 1440.12	
Rec Carrier	Drill Collar	1 9.36 1440.42	
Perf	Cross Over	0.40 1449.78	
X-Over	Spacing	0.00 1450.18	
HWDP	Fluid Electronic Rec Carrier	1.52 1450.18	
X-Over	Shut in Tool	1.64 1451.70	
Perf	Sampler	1.02 1453.34	
Bull Nose	Travel Sub	0.46 1454.36	
	Hyd Tool	1.68 1454.82	
	Inside Mechanical Rec Carrier	1.56 1456.50	
	Inside Electronic Rec Carrier	1.78 1458.06	
	Jars	0.00 1459.84	
	Safety Joint	0.66 1459.84	
	Packer	2.31 1460.50	
	Packer	1.04 1462.81	
	DEPTH :	1463.85	
	Stick Down	1.01 1463.85	
	Perf	6.08 1464.86	
	Perf	4.56 1470.94	
	Outside Electronic Rec Carrier	1.83 1475.50	
	Cross Over	0.40 1477.33	
	H.W. Drill Pipe	1 std 18.26 1477.73	
	Cross Over	0.40 1495.99	
	Perf	0.00 1496.39	
	Bullnose	0.61 1496.39	
	TOTAL DEPTH :	1497.00	

cr52004




**DST # 3
PLOTS AND DATA**

Lakes Oil
 Gauge set @1475.5m
 Start Test Date: 2004/04/20

Wombat # 2 DST # 3


OUT E



Lakes Oil
Gauge set @ 1458.06m
Start Test Date: 2004/04/20

IN E


Wombat # 2 DST # 3



Lakes Oil
Gauge set @1450.18m
Start Test Date: 2004/04/20

FLUID E

Wombat # 2 DST # 3





**CORE # 1
BHA/REPORT**


AUSTRALIAN D.S.T. AUSTRALASIA PTY. LTD.

COMPANY: Lakes Oil **BIT TYPE:** Diamant Boart CD 93 **m CORED:** 9 **TIME START:** 19:40
WELL: Wombat # 2 **SERIEL #:** Bel 7970035 **m RECOVERED:** 4.84 **TIME END:** 0:25
CORE #: 1 **BIT SIZE:** 8.5 x 4 in **% RECOVERY:** 53.70% **DATE:** 21/04/2004

CORED BY: Chad McGuinn

LINER TYPE: 5.5

DEPTH m	ROP mins / mt	WOB lbs	RPM	SPM	GPM	PUMP psi	MW ppg
1497	0	0	0	0			10.4
1498	29.26	15 k	50	32	185	482	
1499	22.72	20 k	80	35	204	507	
1500	41.37	20k	100	36	214	501	
1501	60.6	25k	120	39	232	523	
1502	37.03	20k	120	44	258	533	
1503	32.6	20k	120	43	253	550	
1504	18.57	15k	100	32	184	602	
1505	20.1	15k	100	32	184	600	
1506	24.5	15k	100	32	184	610	
1507							
1508							
1509							
1510							
1511							
1512							
1513							
1514							
1515							





Wombat # 2 Core # 1

1322.44	70 stds d/p	Core Bit :	Type	CD 93
3.86	Pony d/c		Serial #	Bel 7970035
27.76	3 H.W.		Size	8.5 x 4 in
131.99	7 stds d/c			
0.21	upper safety joint			
0.39	lower safety joint			
0.61	stab			
8.53	core barrel			
0.61	stab			
0.31	core head			
1496.71	Total Length			