



Company: **ESSO Australia Pty Ltd**

8.5 in. Section

Well: **FTA A12A**

Field: Fortescue

Rig: ISDL 175

State:

Victoria

VISION Resistivity	
1:200 Measured Depth	
Recorded Mode Log	
Location	
Total depth:	4040.0 m
Spud date:	11-Mar-07
Runs:	4 To 5
Permanent datum:	Mean Sea Level
Log measured from:	Drill Floor
Depth reference:	Driller's Depth
Service Order No.	X = E 61'1596.75 m
07ASQ0013	Y = N 57'48242.67 m
Longitude	Latitude
E 148° 16' 41.325"	S 38° 24' 25.521"

[illegible]

Bit Run Summary

Run number		4	5							
Bit size	in	8.5	8.5							
Bit start depth	m	983.0	1409.0							
Bit end depth	m	1409.0	4040.0							
Top interval logged	m	947.5	1373.5							
Bottom interval logged	m	1373.5	4029.6							
Begin log: time		14:35	14:27							
Begin log: date		20-Mar-07	30-Mar-07							
End log: time		20:12	13:37							
End log: date		21-Mar-07	30-Mar-07							
Mud data										
Depth	m	1408.0	4040							
Type		Accolade SBM	Accolade SBM							
Mud weight	ppg	8.9	10.5							
Solids	%	4.7	13.4							
Chlorides	mg/L	41250	57500							
Rm	ohm.m@°C	n/a	n/a							
Rmf	ohm.m@°C	n/a	n/a							
Rmc	ohm.m@°C	n/a	n/a							











Potassium	%	n/a	n/a								
Environmental data											
GR											
Mud weight	ppg	8.9	10.5								
Bit size	in	8.5	8.5								
Resistivity											
Neutron porosity											
Hole Size	in	8.5	8.5								
Mud weight	ppg	8.9	10.5								
Temperature	°C	65.0	101.0								
Mud salinity	ppk	54.2	66.0								
Formation salinity		n/a	n/a								
Recording rate 1	SEC	5 (ADN, SON)	5 (ADN, SON)								
Recording rate 2	SEC	6 (ARC)	6 (ARC)								
Filtering GR		3 pts	3 pts								
Filtering density		3 pts	3 pts								
Filtering Neutron		3 pts	3 pts								
Company representative		B. Davis	B. Steel	R. Spence	G. Doty	T. Bassett					
Schlumberger D&M Personnel		M. Y. Tan	M. Amarasena	C. Hibberson	C. Soper	L. Muskett					

<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>											
OTHER SERVICES FOR RUN 4 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations				OTHER SERVICES FOR RUN 5 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations				OTHER SERVICES FOR RUN			
REMARKS: RUN NUMBER 4 Gamma Ray is corrected for mud weight, tool size, and bit size. Resistivity is borehole compensated and environmentally corrected. Neutron Porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure). Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3. Delta-T is borehole compensated. POOH due to bell nipple seal leakage.				REMARKS: RUN NUMBER 5 Gamma Ray is corrected for mud weight, tool size, and bit size. Resistivity is borehole compensated and environmentally corrected. Neutron Porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure). Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3. Delta-T is borehole compensated. sonicVISION* recorded mode data was acquired at 1s record rate while tripping out. POOH due to reaching TD of FTA A12A.				REMARKS: RUN NUMBER			

EQUIPMENT DESCRIPTION											
RUN4				RUN5				RUN			
DOWNHOLE EQUIPMENT				DOWNHOLE EQUIPMENT				DOWNHOLE EQUIPMENT			

DOWNHOLE EQUIPMENT

DOWNHOLE EQUIPMENT



Maximum string diameter 8-1/2 in.
All lengths in Meters

Maximum string diameter 8-1/2 in.
All lengths in Meters

Variable Name	Variable Description	Run Name & Value	
Run Number		4	5
General Information			
BHT_RM	Bottom Hole Temperature (RM)	64.999960	100.999900
BSAL_RM	Mud Salinity (RM)	54.224964	65.967598
BS_RM	Bit Size (RM)	8.500000	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000	1.650000
C_WS	Overpressure correction to Sw and M	1.000000	1.000000
FEXP	Formation Factor Exponent (RM)	2.000000	2.000000
FNUM	Formation Factor Enumerator (RM)	1.000000	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT	XPLOT
MST_RM	Mud Sample temperature (RM)	75.000000	75.000000
MW_RM	Mud Weight (RM)	9.850000	10.500000
OBFM_RM	Oil Based Mud (RM)	YES	YES
RHOF_RM	Mud Filtrate Density (RM)	1.000000	1.000000
RHOM_RM	Matrix density (RM)	2.710000	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	1000.000000	1.000000
RWA_COMP_M	Rwa computation model	BASIC	BASIC
RWA_DEN_AD	Rwa Density Input ADN	ROBB	ROBB
RWA_DEN_CD	Rwa Density Input CDN	RHOB	RHOB
RWA_DEN_IN	Rwa Density Input	ROBB	ROBB
RWA_FORM_M	Rwa computation formation model	CLASTIC	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	P34H	P34H
RWS_RM	Resistivity of Connate Water (RM)	1.000000	1.000000
SHT_RM	Surface Hole Temperature (RM)	10.000000	10.000000
TD_RM	Total Measured Depth (RM)	1409.000000	4040.000000
TWS_RM	Temperature of Connate Water (RM)	75.000000	75.000000
VF_ILLI	Fraction of illite in shales	0.500000	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000	0.325000
ADN			
LWD_RM/STATION_FILE/	PARAMETERStation Time-frame file name	Station	Station
ADN_CHASSI	ADN Chassis Type String	ADN	ADN
ADN_COLLAR	ADN Collar Type String	ADN	ADN
ADN_STAB_S	ADN Stabilizer Type String	ADN	ADN
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	YES	YES
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	YES	YES
AVE ADN	ADN/Array Channels: perform averaging (RM) :	YES	YES
A_DHS	ADN Down Hole Software Version String	YES	YES
CHI_RM	Caliper High limit from BS (RM)	3.000000	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000	0.000000
DEVI	Well Section Deviation	38.139999	51.840000
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ	LSAZ
DTMUD	Delta-T for Mud	218.360001	222.029999
DYN_IMG_CO	Generate Dynamic Normalized Image?	YES	YES
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES	YES
EVRL	EVR Process averaging number of samples (RM)	49	49
FCD	Future Casing (Outer) Diameter	0.000000	0.000000
GCSE	Generalized Caliper Selection	BS	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO	NO
IBS	Intergal Blade Stabilizer Collar?	YES	YES
IDQT	Image Derived Quality Threshold	1.000000	1.000000
IHVS	Integrated Hole Volume Start Value (RM)	0.000000	0.000000
IMAGE_MAX_	Image SOA (Quadrant) Right Scale	2.500000	2.500000
IMAGE_MAX_	Image PEF(Segment) Right Scale	6.000000	6.000000
IMAGE_MAX_	Image RHOB(Segment) Right Scale	2.650000	2.650000
IMAGE_MIN_	Image SOA (Quadrant) Left Scale	0.000000	0.000000
IMAGE_MIN_	Image PEF(Segment) Left Scale	2.000000	2.000000
IMAGE_MIN_	Image RHOB(Segment) Left Scale	2.050000	2.050000
JSD ADN	ADN Acquisition start date	2.050000	2.050000
LITHO_TYPE	Lithology (RM)	LIME	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11	FR11
SHT_RM	Ground Level Temperature (Mud-Line When Offshore) (RM)	50.000000	50.000000
SOCNL	Standoff Distance of the CNL Tool	1.000000	1.000000
SSIZ ADN	ADN Stabilizer Size	8.250000	8.250000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.180000	0.180000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES	YES
VERS_ADN	ADN Downhole Software Version	8.300000	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000	15.000000
ARC			
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	8.454500	8.454500
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	8.429340	8.429340
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	6.486760	6.486760
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	6.520790	6.520790
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	5.081880	5.081880
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	5.049710	5.049710
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	4.393790	4.393790
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	4.422380	4.422380
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	3.632990	3.632990
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	3.610050	3.610050

ABNT	Abnormal Transmitter Indicator	No_Tx_Failed	No_Tx_Failed
ADHS	ARC Down Hole Software Version	YES	YES
ANISO_COMP	Anisotropy Computation Option	1.063480	1.063480
APICG	ARC5 Gamma Ray Gain Factor	-1.000000	-1.000000
APIG	ARC Gamma Ray API Gain Factor	Annulus_Temp	Annulus_Temp
ATMP_ARC	ARC Select Temperature Channel	4	5
ATRN	ARC Tool Run Number	Annulus_Temp	Annulus_Temp
ATSN	ARC Tool Serial Number	0.000000	0.000000
AZMF	Formation DIP Azimuth	YES	YES
BH_COMPUTE	Borehole Inversion Computation Option	1.063480	1.063480
CALG	ARC Gamma Ray Cal Gain Factor	BITSIZE	BITSIZE
CALI_SLCT	ARC Caliper Selection	100.000000	100.000000
CDPTH_ARC	Process Start Depth	YES	YES
DIELEC_COM	Dielectric Computation Option	0.000000	0.000000
DIPF	Formation DIP Angle	4.500000	4.500000
ERRCT	Percentage Error Cutoff	1000.000000	1000.000000
GRSH	GR Shale (Invasion Computation Cutoff)	2.000000	2.000000
HIGH_BLEND	High Resistivity Threshold for Blending	0.000000	0.000000
INCLIN_B0	ARC Bias Constant (mg)	0.000000	0.000000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	0.000000	0.000000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	0.000000	0.000000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	0.000000	0.000000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	1.000000	1.000000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	0.000000	0.000000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	0.000000	0.000000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	0.000000	0.000000
INVAS_COMP	Invasion Computation Option	YES	YES
JSD_ARC	ARC Acquisition start date	YES	YES
KPER	Potassium Concentration (RM)	0.000000	0.000000
LOW_BLEND	Low Resistivity Threshold for Blending	1.000000	1.000000
MSWS	ARC Wizard Model Switch Window	5.000000	5.000000
MULTIEFFEC	Multi Effect Option	YES	YES
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	1.807390	1.807390
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	-0.316562	-0.316562
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	-1.724300	-1.724300
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	0.225322	0.225322
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	1.742660	1.742660
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	-0.284950	-0.284950
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	-1.764980	-1.764980
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	0.212175	0.212175
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	1.721960	1.721960
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	-0.301446	-0.301446
POFFSET_AR	ARC: Pressure Offset	0.000000	0.000000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	P34B	P34B
PSOF_ADJ_T	ARC: User Input Phase offset	0.000000	0.000000
RESTIK	ARC resistivity tick source	Phase	Phase
SHIG	ARC High Shock Risk Level	0.500000	0.500000
SMED	ARC Medium Shock Risk Level	0.330000	0.330000
SMIN	ARC Minimum Shock Risk Level	0.160000	0.160000
SUPD	ARC Real Time Shock Update Rate	30.000000	30.000000
TCODE_ARC	ARC Tool File Code	30.000000	30.000000
TSIZ_ARC	ARC Tool Size	6.750000	6.750000
UNIFORM_CO	Uniform Rock Option	YES	YES
VERS_ARC	ARC Down hole software version Number	9.300000	9.300000
WRK	Way to Report Potassium Concentration (RM)	K_by_Wgt_%	K_by_Wgt_%

ISONIC

FP_SD	First Sample delay	400.00	400.00
STC_CF	Center frequency of Filter	13.00	13.00
STC_BW	Bandwidth (kHz)	6.25 kHz	6.25 kHz
STC_RWI	Receiver waveform ignored	None	None
PM_TOFF	Tool Time offset from surface system	0.00	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70	0.70
PPC_PF	Porosity Formula	Raymer-Hunt	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA	DTRA
PPC_MDT	Matrix Delta-T	47.60	47.60
PPC_FDT	Fluid Delta-T	189.00	189.00

Schlumberger Drilling & Measurements

Parameter Insert Header Software version 2.0c

IDEAL Version: ID12_OC_06

IDF


ARC6A-AA	id12_Oc_01	MWD_10	id12_Oc_01
SON675	id12_Oc_01	ADN	id12_Oc_01



Format: VISION Resistivity 2MHz Vertical Scale: 1:200 Graphics File Created: 04-Apr-2007 11:33



PIP SUMMARY



└ ARC Gamma Ray Samples
└ ARC Resistivity Samples



ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)		ARC Attenuation Resistivity 40-in. at 2 MHz (A40H)	
0.2	(OHMM)	0.2	(OHMM)
2000		2000	
ARC Phase-Shift Resistivity 24 in. at 2 MHz (P24H)		ARC Attenuation Resistivity 24 in. at 2 MHz (A24H)	
0.2	(OHMM)	0.2	(OHMM)
2000		2000	






















1275


1300



1325


























1725

1750









1775

1800

1825









1900


1925





1950



1975






TAB ARC RES

P16H

A16H








2175

2200



P16H

P22H

P28H

P34H

P40H



A16H



A22H


A28H

A34H

A40H














2350



2375
















2625

2650





2675

2700

TAB_ARC_RES

GR_ARC

ROP5_RM

P16H

P22H

P28H

P34H

P40H


A16H

A22H

A28H

A34H


A40H







2725



2750



2775

























3075


3100


















3300



3325














































ARC Gamma Ray (GR_ARC) (GAPI)		ARC Phase-Shift Resistivity 16-in. at 2 MHz (P16H)		ARC Attenuation Resistivity 16-in. at 2 MHz (A16H)	
0	200	0.2	2000	0.2	2000
ARC Resistivity Time After Bit (TAB_ ARC_RES)		ARC Phase-Shift Resistivity 22-in. at 2 MHz (P22H)		ARC Attenuation Resistivity 22-in. at 2 MHz (A22H)	
0	10	0.2	2000	0.2	2000
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)		ARC Phase-Shift Resistivity 28-in. at 2 MHz (P28H)		ARC Attenuation Resistivity 28-in. at 2 MHz (A28H)	
200	0	0.2	2000	0.2	2000
		ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)		ARC Attenuation Resistivity 34-in. at 2 MHz (A34H)	
		0.2	2000	0.2	2000
		ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)		ARC Attenuation Resistivity 40-in. at 2 MHz (A40H)	
		0.2	2000	0.2	2000

PIP SUMMARY




└ ARC Gamma Ray Samples




└ ARC Resistivity Samples




6.75-in. Azimuthal Density Neutron / Equipment Identification



Primary Equipment:
 Tool Name and Serial Number
 Collar Type and Serial Number
 Chassis Type and Serial Number
 Stabilizer Type and Serial Number
 Neutron Logging Source
 Density Logging Source
 Stabilizer Size
 Calibration Status



















ADN6 – CA 373
 ADDC – AA
 ADSE – EA
 IBS
 NSR – M 181
 CSR – J/Z 2152
 8.25 – in.
 Valid

Master: 2-Jan-2007 10:39														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Magnesium Block														
Phase	LS window 3 – Mg CPS			Value	Phase	SS window 1 – Mg CPS			Value	Phase	SS window 3 – Mg CPS			Value
Master				1199	Master				3083	Master				7329
	250.0 (Minimum)	4125 (Nominal)	8000 (Maximum)		700.0 (Minimum)	9350 (Nominal)	18000 (Maximum)		2500 (Minimum)	23750 (Nominal)	45000 (Maximum)			

Master: 2-Jan-2007 10:39														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Aluminum Block														
Phase	LS window 3 – Al CPS			Value	Phase	SS window 1 – Al CPS			Value	Phase	SS window 3 – Al CPS			Value
Master				179.6	Master				1555	Master				4550
	50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)			500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)			1500 (Minimum)	15750 (Nominal)	30000 (Maximum)	

Master: 2-Jan-2007 10:39														
6.75-in. Azimuthal Density Neutron Calibration														
Density: Background														
Phase	LS window 3 – Background		CPS	Value	Phase	SS window 1 – Background		CPS	Value	Phase	SS window 3 – Background		CPS	Value
Master				51.01	Master				121.0	Master				522.4
	15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)			40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)			150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

Master: 2-Jan-2007 10:39									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Water Block Check									
Phase	Long spacing water density G/C3		Value	Phase	Short spacing water density G/C3		Value		
Master			1.033	Master			1.145		
	1.024 (Minimum)	1.039 (Nominal)	1.054 (Maximum)		1.096 (Minimum)	1.126 (Nominal)	1.156 (Maximum)		

Master: 2-Jan-2007 10:39														
6.75-in. Azimuthal Density Neutron Calibration														
Neutron: 3-Point Calibration														
Phase	Far 1 tube 1	Air Point Measure	CPS	Value	Phase	Far 1 tube 1	Rod Point Measure	CPS	Value	Phase	Far 1 tube 1	H2O Point Measure	CPS	Value
Master				17.97	Master				4.439	Master				2.178
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 2	Air Point Measure	CPS	Value	Phase	Far 1 tube 2	Rod Point Measure	CPS	Value	Phase	Far 1 tube 2	H2O Point Measure	CPS	Value
Master				19.00	Master				4.791	Master				2.320
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 3	Air Point Measure	CPS	Value	Phase	Far 1 tube 3	Rod Point Measure	CPS	Value	Phase	Far 1 tube 3	H2O Point Measure	CPS	Value
Master				17.92	Master				4.493	Master				2.245
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 1	Air Point Measure	CPS	Value	Phase	Far 2 tube 1	Rod Point Measure	CPS	Value	Phase	Far 2 tube 1	H2O Point Measure	CPS	Value
Master				17.60	Master				4.833	Master				2.283
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 2	Air Point Measure	CPS	Value	Phase	Far 2 tube 2	Rod Point Measure	CPS	Value	Phase	Far 2 tube 2	H2O Point Measure	CPS	Value
Master				19.02	Master				4.883	Master				2.407
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 3	Air Point Measure	CPS	Value	Phase	Far 2 tube 3	Rod Point Measure	CPS	Value	Phase	Far 2 tube 3	H2O Point Measure	CPS	Value
Master				17.92	Master				4.493	Master				2.245
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	

Master	<div><div></div></div>	18.28	Master	<div><div></div></div>	4.647	Master	<div><div></div></div>	2.280						
13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)	3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)	1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)						
Phase	Near 1 tube 1 Air	Point Measure	CPS	Value	Phase	Near 1 tube 1 Rod	Point Measure	CPS	Value	Phase	Near 1 tube 1 H2O	Point Measure	CPS	Value
Master	<div><div></div></div>			488.6	Master	<div><div></div></div>			786.7	Master	<div><div></div></div>			352.0
345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)		
Phase	Near 2 tube 1 Air	Point Measure	CPS	Value	Phase	Near 2 tube 1 Rod	Point Measure	CPS	Value	Phase	Near 2 tube 1 H2O	Point Measure	CPS	Value
Master	<div><div></div></div>			497.1	Master	<div><div></div></div>			780.0	Master	<div><div></div></div>			353.1
345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)		

Master: 2–Jan–2007 10:39														
6.75–in. Azimuthal Density Neutron Calibration														
Neutron: Water Block Check														
Phase	Far Neutron water porosity PU												Value	
Master	<div><div></div></div>													100.4
	90.00 (Minimum)					100.0 (Nominal)							125.0 (Maximum)	

6.75–in. Array Resistivity Compensated / Equipment Identification														
Primary Equipment:														
Tool Name and Serial Number										ARC6 – BA 1708				
ARC675 Calibration Status										Valid				

Master: 20–Feb–2007 12:55														
6.75–in. Array Resistivity Compensated Calibration														
Resistivity: Air														
Phase	Phase–Shift T1			Value	Phase	Phase–Shift T2			Value	Phase	Phase–Shift T3			Value
Master	<div><div></div></div>			1.807	Master	<div><div></div></div>			–1.724	Master	<div><div></div></div>			1.743
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)	
Phase	Phase–Shift T4			Value	Phase	Phase–Shift T5			Value	Phase	Phase–Shift T1 at 400KHz			Value
Master	<div><div></div></div>			–1.765	Master	<div><div></div></div>			1.722	Master	<div><div></div></div>			–0.3166
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)	
Phase	Phase–Shift T2 at 400KHz			Value	Phase	Phase–Shift T3 at 400KHz			Value	Phase	Phase–Shift T4 at 400KHz			Value
Master	<div><div></div></div>			0.2253	Master	<div><div></div></div>			–0.2849	Master	<div><div></div></div>			0.2122
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)			–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)	
Phase	Phase–Shift T5 at 400KHz			Value										
Master	<div><div></div></div>			–0.3014										
	–3.900 (Minimum)	0.1000 (Nominal)	4.100 (Maximum)											

Master: 20–Feb–2007 12:55														
6.75–in. Array Resistivity Compensated Calibration														
Resistivity: Air														
Phase	Attenuation T1			Value	Phase	Attenuation T2			Value	Phase	Attenuation T3			Value
Master	<div><div></div></div>			8.455	Master	<div><div></div></div>			6.487	Master	<div><div></div></div>			5.082
	6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)			4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)			2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)	
Phase	Attenuation T4			Value	Phase	Attenuation T5			Value	Phase	Attenuation T1 at 400KHz			Value
Master	<div><div></div></div>			4.394	Master	<div><div></div></div>			3.633	Master	<div><div></div></div>			8.429
	2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)			1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)			6.500 (Minimum)	8.500 (Nominal)	10.50 (Maximum)	
Phase	Attenuation T2 at 400KHz			Value	Phase	Attenuation T3 at 400KHz			Value	Phase	Attenuation T4 at 400KHz			Value

Master			6.521	Master			5.050	Master			4.422
	4.500 (Minimum)	6.500 (Nominal)	8.500 (Maximum)		2.500 (Minimum)	4.500 (Nominal)	6.500 (Maximum)		2.600 (Minimum)	4.600 (Nominal)	6.600 (Maximum)
Phase	Attenuation T5 at 400KHz		Value								
Master			3.610								
	1.600 (Minimum)	3.600 (Nominal)	5.600 (Maximum)								

Master: 20-Feb-2007 10:26											
6.75-in. Array Resistivity Compensated Calibration											
Gamma Ray: Blanket											
Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS									Value	
Master										5.105	
	2.780 (Minimum)			4.800 (Nominal)					6.000 (Maximum)		

SCHLUMBERGER

Survey report 30-Mar-2007 18:03:55 Page 1 of 5

Client.....: ESSO Australia
Field.....: Fortescue

Well.....: FTA-A12A
API number.....:
Engineer.....: MYT/MA/CH

Rig:.....: ISDL 175
STATE:.....: Victoria

Spud date.....: 11-Mar-07
Last survey date.....: 30-Mar-07
Total accepted surveys...: 112
MD of first survey.....: 910.00 m
MD of last survey.....: 4040.00 m

----- Survey calculation methods-----
Method for positions.....: Minimum curvature
Method for DLS.....: Mason & Taylor

----- Depth reference -----
Permanent datum.....: Mean Sea Level
Depth reference.....: Driller's Depth
GL above permanent.....: 69.00 m
KB above permanent.....: Top Drive
DF above permanent.....: 42.50 m

----- Vertical section origin-----
Latitude (+N/S-).....: -1.69 m
Departure (+E/W-).....: 8.64 m

----- Platform reference point-----
Latitude (+N/S-).....:
Departure (+E/W-).....:

Azimuth from Vsect Origin to target: 32.14 degrees

----- Geomagnetic data -----
Magnetic model.....: BGGM version 2006
Magnetic date.....: 03-Mar-2007
Magnetic field strength..: 1200.01 HCNT
Magnetic dec (+E/W-).....: 13.24 degrees
Magnetic dip.....: -68.92 degrees

----- MWD survey Reference Criteria -----
Reference G.....: 1000.05 mGal
Reference H.....: 1200.01 HCNT
Reference Dip.....: -68.92 degrees
Tolerance of G.....: (+/-) 2.50 mGal
Tolerance of H.....: (+/-) 6.00 HCNT
Tolerance of Dip.....: (+/-) 0.45 degrees

----- Corrections -----
Magnetic dec (+E/W-).....: 13.24 degrees
Grid convergence (+E/W-)..: -0.79 degrees
Total az corr (+E/W-).....: 14.03 degrees
(Total az corr = magnetic dec - grid conv)
Survey Correction Type ...:
 I=Sag Corrected Inclination
 M=Schlumberger Magnetic Correction
 S=Shell Magnetic Correction
 F=Failed Axis Correction
 R=Magnetic Resonance Tool Correction
 D=Dmag Magnetic Correction

[(c)2007 IDEAL ID12_OC_06]
SCHLUMBERGER Survey Report

30-Mar-2007 18:03:55 Page 2 of 5

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	910.00	48.66	34.62	0.00	852.42	213.73	164.42	146.00	219.89	41.60	0.00	TIP	None
2	939.58	56.35	29.78	29.58	870.42	237.17	184.28	158.45	243.03	40.69	8.85	PUP	None
3	967.92	57.99	29.13	28.34	885.78	260.95	205.02	170.16	266.43	39.69	1.86	PUP	None
4	998.17	58.33	28.90	30.25	901.74	286.61	227.49	182.62	291.72	38.76	0.40	PUP	None
5	1027.14	58.95	28.24	28.97	916.82	311.30	249.21	194.45	316.10	37.96	0.88	PUP	None
6	1054.86	59.94	28.06	27.72	930.91	335.12	270.26	205.71	339.65	37.28	1.10	PUP	None
7	1081.21	59.75	27.38	26.35	944.15	357.83	290.43	216.31	362.13	36.68	0.71	PUP	None
8	1109.93	58.85	26.48	28.72	958.81	382.42	312.45	227.49	386.49	36.06	1.26	PUP	None
9	1139.43	57.61	26.85	29.50	974.34	407.39	334.86	238.75	411.26	35.49	1.32	PUP	None
10	1167.88	57.22	28.15	28.45	989.66	431.28	356.12	249.82	435.01	35.05	1.25	PUP	None
11	1196.14	56.67	29.76	28.26	1005.08	454.93	376.85	261.28	458.57	34.74	1.57	PUP	None
12	1224.27	58.09	30.36	28.13	1020.24	478.61	397.35	273.15	482.18	34.51	1.63	PUP	None
13	1252.25	60.61	32.20	27.98	1034.50	502.67	417.92	285.65	506.21	34.35	3.24	PUP	None
14	1280.12	62.54	33.07	27.87	1047.77	527.18	438.56	298.87	530.71	34.27	2.27	PUP	None
15	1309.38	64.12	32.60	29.26	1060.90	553.32	460.53	313.05	556.85	34.21	1.70	PUP	None
16	1336.81	63.88	31.30	27.43	1072.93	577.98	481.44	326.09	581.48	34.11	1.33	PUP	None
17	1364.88	63.16	30.22	28.07	1085.44	603.09	503.03	338.94	606.57	33.97	1.31	PUP	None
18	1393.82	61.89	29.64	28.94	1098.80	628.75	525.28	351.75	632.18	33.81	1.44	PUP	None
19	1422.27	59.94	29.32	28.45	1112.63	653.58	546.93	363.99	656.98	33.64	2.11	PUP	None
20	1450.54	58.77	30.00	28.27	1127.04	677.88	568.06	376.02	681.24	33.50	1.41	PUP	None
21	1478.10	58.94	32.14	28.65	1141.86	702.40	588.95	388.86	705.74	33.44	2.86	PUP	None

21	1479.19	58.94	33.14	28.65	1141.88	702.40	588.95	388.86	705.74	33.44	2.86	PUP	None
22	1507.06	60.51	34.94	27.87	1155.91	726.45	608.89	402.33	729.81	33.46	2.42	PUP	None
23	1536.05	61.68	35.62	28.99	1169.92	751.79	629.61	416.99	755.17	33.52	1.38	PUP	None
24	1564.67	61.97	33.93	28.62	1183.43	776.99	650.33	431.38	780.39	33.56	1.62	PUP	None
25	1593.07	61.98	32.43	28.40	1196.78	802.05	671.31	445.10	805.46	33.55	1.42	PUP	None
26	1622.00	61.50	30.07	28.93	1210.48	827.53	693.09	458.32	830.92	33.48	2.25	PUP	None
27	1649.69	60.99	29.67	27.69	1223.80	851.79	714.14	470.41	855.15	33.37	0.68	PUP	None
28	1678.34	60.72	29.92	28.65	1237.75	876.79	735.86	482.84	880.13	33.27	0.37	PUP	None
29	1706.82	60.44	30.08	28.48	1251.74	901.58	757.34	495.25	904.89	33.18	0.33	PUP	None
30	1735.78	60.16	30.15	28.96	1266.09	926.72	779.10	507.87	930.01	33.10	0.30	PUP	None
[[c)2007 IDEAL ID12_OC_06] SCHLUMBERGER Survey Report													
						30-Mar-2007 18:03:55		Page		3 of 5			
Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
31	1764.33	59.73	30.16	28.55	1280.39	951.41	800.47	520.28	954.69	33.02	0.46	PUP	None
32	1793.47	59.15	30.45	29.14	1295.20	976.49	822.13	532.94	979.76	32.95	0.66	PUP	None
33	1822.07	58.57	30.52	28.60	1309.99	1000.96	843.23	545.36	1004.21	32.89	0.62	PUP	None
34	1851.06	58.06	30.60	28.99	1325.22	1025.62	864.47	557.90	1028.86	32.84	0.54	PUP	None
35	1878.81	56.98	30.59	27.75	1340.12	1049.02	884.62	569.82	1052.26	32.79	1.19	PUP	None
36	1907.06	56.15	30.92	28.25	1355.69	1072.59	904.88	581.87	1075.82	32.74	0.94	PUP	None
37	1934.67	56.93	31.64	27.61	1370.91	1095.62	924.56	593.83	1098.84	32.71	1.09	PUP	None
38	1963.06	57.74	32.89	28.39	1386.23	1119.52	944.77	606.59	1122.74	32.70	1.43	PUP	None
39	1991.56	58.68	33.48	28.50	1401.25	1143.74	965.04	619.85	1146.96	32.71	1.14	PUP	None
40	2019.42	60.15	34.51	27.86	1415.42	1167.71	984.93	633.26	1170.94	32.74	1.88	PUP	None
41	2047.80	61.16	34.12	28.38	1429.33	1192.43	1005.36	647.21	1195.67	32.77	1.14	PUP	None
42	2076.31	62.12	33.28	28.51	1442.87	1217.51	1026.23	661.13	1220.75	32.79	1.30	PUP	None
43	2105.22	62.67	32.69	28.91	1456.27	1243.13	1047.72	675.07	1246.37	32.79	0.80	PUP	None
44	2134.03	62.26	32.67	28.81	1469.59	1268.67	1069.22	688.87	1271.92	32.79	0.43	PUP	None
45	2162.40	61.25	32.89	28.37	1483.01	1293.66	1090.24	702.40	1296.91	32.79	1.10	PUP	None
46	2190.18	60.06	32.82	27.78	1496.63	1317.87	1110.58	715.53	1321.13	32.79	1.31	PUP	None
47	2218.83	59.30	33.05	28.65	1511.09	1342.60	1131.33	728.98	1345.86	32.80	0.84	PUP	None
48	2248.01	58.10	33.10	29.18	1526.25	1367.53	1152.23	742.59	1370.79	32.80	1.25	PUP	None
49	2274.95	58.10	31.81	26.94	1540.49	1390.40	1171.52	754.86	1393.66	32.80	1.24	PUP	None
50	2303.36	57.91	29.81	28.41	1555.54	1414.49	1192.22	767.20	1417.74	32.76	1.83	PUP	None
51	2332.15	58.11	27.95	28.79	1570.79	1438.86	1213.60	778.99	1442.10	32.70	1.68	PUP	None
52	2361.11	57.32	27.68	28.96	1586.26	1463.28	1235.25	790.42	1466.49	32.61	0.87	PUP	None
53	2389.54	56.45	28.20	28.43	1601.79	1487.03	1256.29	801.57	1490.23	32.54	1.04	PUP	None
54	2417.92	56.65	28.84	28.38	1617.44	1510.66	1277.09	812.88	1513.85	32.48	0.61	PUP	None
55	2446.41	57.69	29.55	28.49	1632.88	1534.57	1297.99	824.56	1537.75	32.43	1.28	PUP	None
56	2474.84	58.92	30.20	28.43	1647.82	1558.74	1318.97	836.61	1561.92	32.39	1.45	PUP	None
57	2502.80	59.92	30.64	27.96	1662.04	1582.80	1339.72	848.80	1585.97	32.36	1.17	PUP	None
58	2531.73	61.02	31.76	28.93	1676.30	1607.96	1361.25	861.84	1611.14	32.34	1.55	PUP	None
59	2560.19	62.04	31.58	28.46	1689.87	1632.98	1382.54	874.97	1636.15	32.33	1.11	PUP	None
60	2588.71	63.57	30.43	28.52	1702.90	1658.34	1404.29	888.04	1661.51	32.31	1.97	PUP	None
[[c)2007 IDEAL ID12_OC_06] SCHLUMBERGER Survey Report													
						30-Mar-2007 18:03:55		Page		4 of 5			
Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
61	2617.47	64.39	28.46	28.76	1715.52	1684.16	1426.79	900.74	1687.33	32.26	2.07	PUP	None
62	2645.77	64.27	26.73	28.30	1727.78	1709.58	1449.40	912.55	1712.75	32.19	1.68	PUP	None
63	2673.99	62.11	25.56	28.22	1740.51	1734.63	1472.00	923.65	1737.79	32.11	2.59	PUP	None
64	2702.18	61.26	25.34	28.19	1753.88	1759.28	1494.41	934.32	1762.45	32.01	0.94	PUP	None
65	2729.72	60.71	26.99	27.54	1767.24	1783.23	1516.03	944.94	1786.40	31.94	1.71	PUP	None
66	2757.98	59.79	29.25	28.26	1781.26	1807.70	1537.66	956.50	1810.88	31.88	2.34	PUP	None
67	2785.86	59.95	29.55	27.88	1795.26	1831.79	1558.67	968.33	1834.97	31.85	0.33	PUP	None
68	2814.79	59.62	29.52	28.93	1809.82	1856.76	1580.42	980.66	1859.95	31.82	0.35	PUP	None
69	2842.54	59.19	29.29	27.75	1823.94	1880.62	1601.23	992.39	1883.82	31.79	0.52	PUP	None
70	2871.26	58.45	29.42	28.72	1838.81	1905.16	1622.65	1004.43	1908.37	31.76	0.79	PUP	None
71	2899.68	58.31	29.57	28.42	1853.71	1929.34	1643.71	1016.35	1932.55	31.73	0.20	PUP	None
72	2928.04	58.05	30.04	28.36	1868.66	1953.41	1664.62	1028.32	1956.63	31.71	0.51	PUP	None
73	2956.20	57.61	29.95	28.16	1883.66	1977.23	1685.27	1040.24	1980.46	31.69	0.48	PUP	None
74	2984.50	58.49	30.50	28.30	1898.63	2001.23	1706.02	1052.33	2004.47	31.67	1.07	PUP	None
75	3013.11	60.08	31.18	28.61	1913.24	2025.82	1727.13	1064.94	2029.06	31.66	1.80	PUP	None
76	3041.64	61.35	31.73	28.53	1927.20	2050.70	1748.36	1077.92	2053.94	31.66	1.45	PUP	None
77	3069.56	60.41	31.97	27.92	1940.79	2075.09	1769.08	1090.79	2078.33	31.66	1.05	PUP	None
78	3098.04	59.96	32.25	28.48	1954.95	2099.80	1790.01	1103.93	2103.04	31.66	0.55	PUP	None
79	3128.87	59.73	32.38	30.83	1970.43	2126.46	1812.54	1118.18	2129.70	31.67	0.25	PUP	None
80	3156.53	59.50	32.54	27.66	1984.43	2150.32	1832.67	1130.99	2153.56	31.68	0.30	PUP	None
81	3184.41	59.38	32.63	27.88	1998.60	2174.33	1852.90	1143.91	2177.56	31.69	0.16	PUP	None
82	3213.54	58.79	32.83	29.13	2013.57	2199.32	1873.92	1157.43	2202.55	31.70	0.64	PUP	None
83	3242.31	58.28	33.14	28.77	2028.58	2223.85	1894.51	1170.79	2227.08	31.72	0.61	PUP	None
84	3270.77	59.47	32.47	28.46	2043.29	2248.22	1914.98	1183.98	2251.44	31.73	1.41	PUP	None
85	3298.54	61.34	31.20	27.77	2057.01	2272.36	1935.50	1196.72	2275.58	31.73	2.38	PUP	None
86	3327.20	62.47	30.54	28.66	2070.51	2297.64	1957.20	1209.69	2300.86	31.72	1.35	PUP	None
87	3355.99	61.91	30.64	28.79	2083.94	2323.09	1979.12	1222.65	2326.32	31.71	0.60	PUP	None
88	3384.31	61.58	31.29	28.32	2097.34	2348.03	2000.51	1235.48	2351.27	31.70	0.71	PUP	None
89	3412.22	61.09	31.57	27.91	2110.73	2372.52	2021.41	1248.25	2375.76	31.70	0.60	PUP	None
90	3440.85	60.09	30.98	28.63	2124.79	2397.46	2042.72	1261.20	2400.70	31.69	1.20	PUP	None
[[c)2007 IDEAL ID12_OC_06] SCHLUMBERGER Survey Report													
						30-Mar-2007 18:03:55		Page		5 of 5			

Seq # -	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/ 100f)	Srvy tool type	Tool Corr (deg)
91	3468.88	58.26	28.83	28.03	2139.15	2421.51	2063.58	1273.20	2424.75	31.67	2.83	PUP	None
92	3497.54	56.85	27.50	28.66	2154.53	2445.63	2084.90	1284.62	2448.89	31.64	1.92	PUP	None
93	3526.24	56.29	27.94	28.70	2170.34	2469.51	2106.10	1295.76	2472.79	31.60	0.71	PUP	None
94	3554.70	56.56	29.74	28.46	2186.08	2493.18	2126.87	1307.20	2496.47	31.58	1.63	PUP	None
95	3583.41	57.35	32.06	28.71	2201.74	2517.24	2147.52	1319.56	2520.53	31.57	2.23	PUP	None
96	3611.63	57.04	32.55	28.22	2217.03	2540.96	2167.57	1332.24	2544.25	31.58	0.56	PUP	None
97	3639.74	57.10	33.12	28.11	2232.31	2564.55	2187.39	1345.03	2567.84	31.59	0.52	PUP	None
98	3668.41	57.31	32.85	28.67	2247.84	2588.65	2207.61	1358.15	2591.93	31.60	0.33	PUP	None
99	3696.55	57.48	32.21	28.14	2263.00	2612.35	2227.59	1370.90	2615.63	31.61	0.61	PUP	None
100	3723.95	55.20	33.73	27.40	2278.19	2635.16	2246.73	1383.30	2638.43	31.62	2.90	PUP	None
101	3751.97	53.21	34.99	28.02	2294.58	2657.86	2265.49	1396.13	2661.13	31.64	2.43	PUP	None
102	3780.39	51.73	36.35	28.42	2311.89	2680.36	2283.80	1409.27	2683.61	31.68	1.96	PUP	None
103	3809.63	50.20	37.30	29.24	2330.30	2702.99	2301.98	1422.88	2706.23	31.72	1.77	PUP	None
104	3837.45	47.53	39.32	27.82	2348.60	2723.82	2318.42	1435.86	2727.04	31.77	3.37	PUP	None
105	3864.95	45.46	41.51	27.50	2367.54	2743.56	2333.61	1448.78	2746.76	31.83	2.89	PUP	None
106	3893.77	44.28	42.83	28.82	2387.96	2763.58	2348.68	1462.43	2766.77	31.91	1.59	PUP	None
107	3922.37	43.94	43.20	28.60	2408.50	2783.13	2363.24	1476.01	2786.30	31.99	0.45	PUP	None
108	3950.43	43.62	43.55	28.06	2428.75	2802.17	2377.35	1489.34	2805.34	32.07	0.44	PUP	None
109	3978.86	41.90	42.29	28.43	2449.63	2821.13	2391.48	1502.49	2824.30	32.14	2.06	PUP	None
110	4007.47	40.30	41.13	28.61	2471.19	2839.67	2405.52	1515.00	2842.84	32.20	1.89	PUP	None
111	4021.05	39.80	40.48	13.58	2481.58	2848.31	2412.13	1520.71	2851.48	32.23	1.46	PUP	None
112	4040.00	39.50	40.00	18.95	2496.17	2860.28	2421.36	1528.52	2863.46	32.26	0.69	Projection to TD	

[(c)2007 IDEAL ID12_0C_06]

Company: **ESSO Australia Pty Ltd****Schlumberger**Well: **FTA A12A**Field: **Fortescue**Rig: **ISDL 175****8.5 in. Section**State: **Victoria****VISION Resistivity
1:200 Measured Depth
Recorded Mode Log**