FTA A28B DrillMech 200MD

IDEAL Version: ID12_0C_09 <MD > Vertical Scale: 1:200 Graphics File Created: 25−Apr−2007 03:15

Isonic Shock, Real−Time (SHK_ISONIC_RT)								
0 (−−−− 4								
ADN Shock, Real−Time (SHK_ADN_RT)								
0 (−−−− 4								
ARC Gamma Ray, Real−Time (ARC_GR_RT)								
0 (GAPI) 200								
MWD Shock Risk (SHKRSK_RT)						T_FLOW (TFLO)		
0 (−−−− 4						0 (GPM) 1000		
MWD Shock Peak (SHKPK_RT)	STOR (TQA)			Surface RPM (RPM)		PUMPPRS (SPPA)		ARC Equivalent Circulating density (ECD_ARC_RT)
0 (G) 200	0 (KFLB) 50			0 (RPM) 300		0 (PSI) 5000		10 (LB/G) 15
ARC Shock Level, Real−Time (SHK2_RT)	HKLD (HKLD)		MWD Lateral Vib (VIBLAT_RT)	MWD Collar RPM (CRPM_RT)		TUR_RPM (TRPM_RT)		ARC Annulus Pressure (APRS_RT)
0 (−−−− 4	0 (KLBF) 500		0 (G) 50	0 (RPM) 300		0 (RPM) 5000		0 (PSI) 6000
ROP*5 (ROP5)	SWOB (SWOB)		MWD Vib X−Axis (VIBX_RT)	PKPK_RPM (Stick_RT)		CRS_TRPM (TRPM)		ARC Annulus Temperature (ATMP_RT)
200 (M/HR) 0	0 (KLBF) 100		0 (G) 50	0 (RPM) 300		0 (RPM) 5000		0 (DEGC) 200




1625
1650


1675
1700


1725
1750


1775
1800
1825


1850
1875


1900
1925


1950
1975


2000
2025


2050
2075
2100


2125
2150


2175
2200


2225
2250


2275
2300
2325


2350
2375


2400
2425


2450
2475


2500
2525
2550


2575
2600


2625
2650


2675
2700


2725
2750
2775


2800
2825


2850
2875


2900
2925


2950
2975


3000
3025
3050


3075
3100


3125
3150


3175
3200


3225
3250
3275


3300
3325


3350
3375


3400
3425


3450
3475
3500


3525
3550


3575
3600


3625
3650


3675
3700
3725


3750
3775


3800
3825


3850
3875


3900
3925


3950
3975
4000



ROP*5 (ROP5) 200 (M/HR) 0	SWOB (SWOB) 0 (KLBF) 100	MWD Vib X−Axis (VIBX_RT) 0 (G) 50	PKPK_RPM (Stick_RT) 0 (RPM) 300	CRS_TRPM (TRPM) 0 (RPM) 5000	ARC Annulus Temperature (ATMP_RT) 0 (DEGC) 200
ARC Shock Level, Real−Time (SHK2_RT) 0 (---- 4	HKLD (HKLD) 0 (KLBF) 500	MWD Lateral Vib (VIBLAT_RT) 0 (G) 50	MWD Collar RPM (CRPM_RT) 0 (RPM) 300	TUR_RPM (TRPM_RT) 0 (RPM) 5000	ARC Annulus Pressure (APRS_RT) 0 (PSI) 6000
MWD Shock Peak (SHKPK_RT) 0 (G) 200	STOR (TQA) 0 (KFLB) 50		Surface RPM (RPM) 0 (RPM) 300	PUMPPRS (SPPA) 0 (PSI) 5000	ARC Equivalent Circulating density (ECD_ARC_RT) 10 (LB/G) 15
MWD Shock Risk (SHKRSK_RT) 0 (---- 4				T_FLOW (TFLO) 0 (GPM) 1000	
ARC Gamma Ray, Real−Time (ARC_GR_RT) 0 (GAPI) 200					
ADN Shock, Real−Time (SHK_ADN_RT) 0 (---- 4					
Isonic Shock, Real−Time (SHK_ISONIC_RT) 0 (---- 4					