

Rig: **ISDL 175**  
State: **Victoria**

Rig:		ISDL 175	
Field:		Fortescue	
Location:		Bass Strait	
Well:		FTA A4c	
Company:		ESSO Australia Pty Ltd	
<div>VISION Service</div> <div>1:500 Measured Depth</div> <div>Recorded Mode Log</div>			
Location			
Total depth:	3314.0 m	K.B. Top Drive	
Spud date:	09-Jul-07	G.L. -69.0 m	
Runs:	1 To 1	D.F. 42.5 m	
Permanent datum:	Mean Sea Level	Elev.: 0.0 m	
Log measured from:	Drill Floor	42.5 m above Perm. datum	
Depth reference:	Driller's Depth		
Service Order no.	X = E 611,594.50 m	Longitude	Latitude
07ASQ0017	Y = N 5,748,244.68 m	E 148° 16' 41.231"	S 38° 24' 25.457"

Depth logged:		2071.0 m	To	3303.6 m		Mag decl:	13.210° deg.	Other services:
Date logged:	12-Jul-07	To	15-Jul-07		Mag dip:	-68.862° deg.	See Remarks	
Bore hole record				Casing record				
Hole size	from	to	Size	Density	from	to		
8.5 in.	2071.0 m	3314.0 m	10.75 in.	40.5 lb/ft	21.0 m	2071.0 m		
Type	Mud record from	to	Min	Borehole deviation Max	from	to		
Accolade SBM	2071.0 m	3314.0 m	27.26 deg.	60.74 deg.	2071.0 m	3314.0 m		
Surface equipment			Software record					
Unit	Esso Office Unit	IDEAL WIS	ID12_0c_11					
Depth system	PDA	SPM	hspm12_0c_04					
		LWD	See Remarks					
		MWD	See Remarks					

## Bit Run Summary

Run number		1								
Bit size	in.	8.5								
Bit start depth	m	2070.0								
Bit end depth	m	3314.0								
Top interval logged	m	2069.0								
Bottom interval logged	m	3303.6								
Begin log: time		12:40								
Begin log: date		12-Jul-07								
End log: time		13:14								
End log: date		15-Jul-07								
Mud data										
Depth	m	3314.0								
Type		Accolade SBM								
Mud weight	ppg	10.5								
Solids	%	13.7								
Chlorides	mg/L	47178								
Rm	ohm.m@°C	n/a								
Rmf	ohm.m@°C	n/a								
Rmc	ohm.m@°C	n/a								

Potassium	%	n/a									
<b>Environmental data</b>											
<b>GR</b>											
Mud weight	ppg	10.5									
Bit size	in.	8.5									
<b>Resistivity</b>											
<b>Neutron porosity</b>											
Hole Size	in.	8.5									
Mud weight	ppg	10.5									
Temperature	°C	88.0									
Mud salinity	ppk	64.4									
Formation salinity		n/a									
Recording rate 1	SEC	5 (ADN, SON)									
Recording rate 2	SEC	6 (ARC)									
Filtering GR		3 pts									
Filtering density		3 pts									
Filtering Neutron		3 pts									
Company representative	D. Bareswill	R. Spence	M. Calicutt								
Schlumberger D&M Personnel	M. Y. Tan	A. Kohli	M. Lu	C. Soper	M. How						

<div>DISCLAIMER</div> <div>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</div>		
OTHER SERVICES FOR RUN 1 Directional Drilling Directional Surveys Annular Pressure & Temperature Shock & Vibrations	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
REMARKS: RUN NUMBER 1 Depth is referenced to Driller's Depth.  Gamma ray is corrected for mud weight, tool size and bit size.  Resistivity is borehole compensated and environmentally corrected.  Neutron porosity is corrected for the effects of borehole size (bit size), temperature, mud salinity, and mud hydrogen index (a factor of mud weight, mud temperature and pressure).  Neutron porosity is calculated using a limestone matrix density of 2.71 g/cm3.  POOH due to reaching TD of FTA A4c.	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION		
RUN 1	RUN	RUN

DOWNHOLE EQUIPMENT

6-3/4" adnVISION\* Neutron F 35.47 37.30  
DHS: V8.3A02 Neutron N 35.31  
Blade OD: 8-1/4" Density S 34.36  
S/N: AD41 Density L 34.27  
UltraSonic 33.88  
R-O Port 33.12




6-3/4" sonicVISION\* 31.10  
DHS: V6.6b04  
S/N: 649  
Delta-T 27.83  
R-O port 27.43



8-3/8" ILS 23.64  
S/N: S31746-1




6-3/4" TeleScope\* 22.75  
MDC: FA27  
MEC: 373  
MDI: 1565  
MVC: 282  
D&I 18.39  
MVC 17.74




8-3/8" ILS 14.73  
S/N: OSS0701135B  
T5 11.48  
T3 11.38  
T1 11.07



6-3/4" arcVISION\* 13.72  
DHS: V9.3b13  
S/N: 1191  
Gamma Ray 10.77  
Receiver 10.41  
T2 10.36  
T4 10.11  
ARC APRS 9.80  
9.65



6-3/4" PowerDrive Xceed\* 7.88  
S/N: 109



8-1/2" Reed-Hycalog PDC Bit 0.00 0.22  
S/N: 214576



Maximum string diameter 8-1/2 in.  
All lengths in Meters

Variable Name	Variable Description	Run Name & Value
Run Number		1
General Information		
BHT_RM	Bottom Hole Temperature (RM)	88.000000
BSAL_RM	Mud Salinity (RM)	64.402878
BS_RM	Bit Size (RM)	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000
C_WS	Overpressure correction to Sw and M	1.000000
FEXP	Formation Factor Exponent (RM)	2.000000
FNUM	Formation Factor Enumerator (RM)	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT
MST_RM	Mud Sample temperature (RM)	75.000000
MW_RM	Mud Weight (RM)	10.500000
OBMF_RM	Oil Based Mud (RM)	YES
RHOF_RM	Mud Filtrate Density (RM)	1.000000
RHOM_RM	Matrix density (RM)	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	1000.000000
RWA_COMP_M	Rwa computation model	BASIC
RWA_DEN_AD	Rwa Density Input ADN	ROBB
RWA_DEN_CD	Rwa Density Input CDN	RHOB
RWA_DEN_IN	Rwa Density Input	ROBE
RWA_FORM_M	Rwa computation formation model	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	P34H
RWS_RM	Resistivity of Connate Water (RM)	1.000000
SHT_RM	Surface Hole Temperature (RM)	10.000000
TD_RM	Total Measured Depth (RM)	3314.000000
TWS_RM	Temperature of Connate Water (RM)	75.000000
VF_ILLI	Fraction of illite in shales	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000
ARC		
LWD_RM/STATION_FILE/	PARAMETERStation Time-frame file name	Station
A12A	ARC Air Cal Attenuation From T1 at 2 MHz	8.454470
A14A	ARC Air Cal Attenuation From T1 at 400 KHz	8.428760
A22A	ARC Air Cal Attenuation From T2 at 2 MHz	6.487210
A24A	ARC Air Cal Attenuation From T2 at 400 KHz	6.520190
A32A	ARC Air Cal Attenuation From T3 at 2 MHz	5.081830
A34A	ARC Air Cal Attenuation From T3 at 400 KHz	5.049050
A42A	ARC Air Cal Attenuation From T4 at 2 MHz	4.393750
A44A	ARC Air Cal Attenuation From T4 at 400 KHz	4.421190
A52A	ARC Air Cal Attenuation From T5 at 2 MHz	3.633010
A54A	ARC Air Cal Attenuation From T5 at 400 KHz	3.610840
ABNT	Abnormal Transmitter Indicator	No_Tx_Failed
ADHS	ARC Down Hole Software Version	No_Tx_Failed
ANISO_COMP	Anisotropy Computation Option	YES
APICG	ARC5 Gamma Ray Gain Factor	1.070470
APIG	ARC Gamma Ray API Gain Factor	-1.000000
ATMP_ARC	ARC Select Temperature Channel	Annulus_Temp
ATRN	ARC Tool Run Number	1
ATSN	ARC Tool Serial Number	Annulus_Temp
AZMF	Formation DIP Azimuth	0.000000
BH_COMPUTE	Borehole Inversion Computation Option	YES
CALG	ARC Gamma Ray Cal Gain Factor	1.070470
CALI_SLCT	ARC Caliper Selection	BITSIZE
CDPTH_ARC	Process Start Depth	100.000000
DIELEC_COM	Dielectric Computation Option	YES
DIPF	Formation DIP Angle	0.000000
ERRCT	Percentage Error Cutoff	4.500000
GRSH	GR Shale (Invasion Computation Cutoff)	1000.000000
HIGH_BLEND	High Resistivity Threshold for Blending	2.000000
INCLIN_B0	ARC Bias Constant (mg)	0.000000
INCLIN_B1	ARC Bias First-order Coefficient (mg/degC)	0.000000
INCLIN_B2	ARC Bias Secod-order Coeeficient (mg/degC)	0.000000
INCLIN_B3	ARC Bias Third-order Coeeficient (mg/degC)	0.000000
INCLIN_C0	ARC Current Scale Factor Constant (mA/g)	1.000000
INCLIN_C1	ARC Scale First-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C2	ARC Scale Second-order Coeeficient (mA/g/degC)	0.000000
INCLIN_C3	ARC Scale Third-order Coeeficient (mA/g/degC)	0.000000
INVAS_COMP	Invasion Computation Option	YES
JSD_ARC	ARC Acquisition start date	YES
KPER	Potassium Concentration (RM)	0.000000
LOW_BLEND	Low Resistivity Threshold for Blending	1.000000
MSWS	ARC Wizard Model Switch Window	5.000000
MULTIEFFEC	Multi Effect Option	YES
P12A	ARC Air Cal Phase-Shift From T1 at 2 MHz	1.806140
P14A	ARC Air Cal Phase-Shift From T1 at 400 KHz	-0.319793
P22A	ARC Air Cal Phase-Shift From T2 at 2 MHz	-1.722540
P24A	ARC Air Cal Phase-Shift From T2 at 400 KHz	0.224298
P32A	ARC Air Cal Phase-Shift From T3 at 2 MHz	1.739660
P34A	ARC Air Cal Phase-Shift From T3 at 400 KHz	-0.287066
P42A	ARC Air Cal Phase-Shift From T4 at 2 MHz	-1.763690
P44A	ARC Air Cal Phase-Shift From T4 at 400 KHz	0.206005
P52A	ARC Air Cal Phase-Shift From T5 at 2 MHz	1.719260
P54A	ARC Air Cal Phase-Shift From T5 at 400 KHz	-0.300926
POFFSET_AR	ARC: Pressure Offset	0.000000
PRTD	Preferred Resistivity Log for Rt Display while Multi-Effects	P34B
PSOF_ADJ_T	ARC: User Input Phase offset	0.000000

RESTIK	ARC resistivity tick source	Phase
SHIG	ARC High Shock Risk Level	0.500000
SHT_RM	Ground Level Temperature (Mud-Line When Offshore ) (RM)	50.000000
SMED	ARC Medium Shock Risk Level	0.330000
SMIN	ARC Minimum Shock Risk Level	0.160000
SUPD	ARC Real Time Shock Update Rate	30.000000
TCODE_ARC	ARC Tool File Code	30.000000
TSIZ_ARC	ARC Tool Size	6.750000
UNIFORM_CO	Uniform Rock Option	YES
VERS_ARC	ARC Down hole software version Number	9.300000
WRK	Way to Report Potassium Concentration (RM)	K_by_Wgt_%

## ISONIC

FP_SD	First Sample delay	400.00
STC_CF	Center frequency of Filter	13.00
STC_BW	Bandwidth (kHz)	Default
STC_RWI	Receiver waveform ignored	None
PM_TOFF	Tool Time offset from surface system	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70
PPC_PF	Porosity Formula	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA
PPC_MDT	Matrix Delta-T	47.60
PPC_FDT	Fluid Delta-T	189.00

## ADN

ADN_CHASSI	ADN Chassis Type String	ADN
ADN_COLLAR	ADN Collar Type String	ADN
ADN_STAB_S	ADN Stabilizer Type String	IBS
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	YES
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	YES
AVE_ADN	ADN/Array Channels: perform averaging(RM) :	YES
A_DHS	ADN Down Hole Software Version String	YES
CHI_RM	Caliper High limit from BS (RM)	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000
DEVI	Well Section Deviation	41.450001
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ
DTMUD	Delta-T for Mud	209.160004
DYN_IMG_CO	Generate Dynamic Normalized Image?	YES
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES
EVRL	EVR Process averaging number of samples (RM)	49
FCD	Future Casing (Outer) Diameter	0.000000
GCSE	Generalized Caliper Selection	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO
IBS	Intergal Blade Stabilizer Collar?	YES
IDQT	Image Derived Quality Threshold	1.000000
IHVS	Integrated Hole Volume Start Value(RM)	0.000000
IMAGE_MAX	Image SOA (Quadrant) Right Scale	2.500000
IMAGE_MAX	Image PEF(Segment) Right Scale	6.000000
IMAGE_MAX	Image RHOB(Segment) Right Scale	2.650000
IMAGE_MIN	Image SOA (Quadrant) Left Scale	0.000000
IMAGE_MIN	Image PEF(Segment) Left Scale	2.000000
IMAGE_MIN	Image RHOB(Segment) Left Scale	2.050000
JSD_ADN	ADN Acquisition start date	11-Jul-2007
LITHO_TYPE	Lithology (RM)	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11
SOCNL	Standoff Distance of the CNL Tool	1.000000
SSIZ_ADN	ADN Stabilizer Size	8.250000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.180000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES
VERS_ADN	ADN Downhole Software Version	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software vers:

## IDEAL Version: ID12\_OC\_11

IDF

Format: VISION Service RM Log Vertical Scale: 1:500 Graphics File Created: 17-Jul-2007 21:48

### PIP SUMMARY

Density Samples +

Neutron Samples +

+ ARC Gamma Ray Samples

+ ARC Resistivity Samples

Rate of Penetration, Averaged over Last  
5ft (ROP5\_RM)


200 (M/HR) 0


ARC Phase-Shift Resistivity 40-in. at 2  
MHz (P40H)


0.2 (OHMM) 2000

ARC Phase-Shift Resistivity 34-in. at 2


Thermal Neutron Porosity (TNPH)






























Density Time After Bit (TAB_DEN) (HR)	ADN Rotational Speed (RPM_ADN) (RPM)	ARC Phase-Shift Resistivity 16-in. at 2 MHz (P16H)	Bulk Density Correction, Bottom (DRHB)
0-----10	0-----250	0.2-----2000 (OHMM)	-0.75-----0.25 (G/C3)
Horizontal Hole Diameter (HORD) (IN)		ARC Phase-Shift Resistivity 22-in. at 2 MHz (P22H)	Photoelectric Factor, Bottom (PEB)
6-----16		0.2-----2000 (OHMM)	0-----10 (-----)
Vertical Hole Diameter (VERD) (IN)		ARC Phase-Shift Resistivity 28-in. at 2 MHz (P28H)	Bulk Density, Bottom (ROBB)
6-----16		0.2-----2000 (OHMM)	1.85-----2.85 (G/C3)
ARC Gamma Ray (GR_ARC) (GAPI)		ARC Phase-Shift Resistivity 34-in. at 2 MHz (P34H)	Thermal Neutron Porosity (TNPH)
0-----200		0.2-----2000 (OHMM)	45-----15 (PU)
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)		ARC Phase-Shift Resistivity 40-in. at 2 MHz (P40H)	
200-----0 (M/HR)		0.2-----2000 (OHMM)	

PIP SUMMARY	
Density Samples	Neutron Samples
ARC Gamma Ray Samples	
ARC Resistivity Samples	




IDEAL Version: ID12\_0C\_11  
IDF




6.75-in. Azimuthal Density Neutron / Equipment Identification		
Primary Equipment:	ADN6 - CA	437
Tool Name and Serial Number	ADDC - AA	
Collar Type and Serial Number	ADSE - EA	
Chassis Type and Serial Number	IBS	AD41
Stabilizer Type and Serial Number	NSR - M	181
Neutron Logging Source	GSR - JZ	2152
Density Logging Source	8.25-in.	
Stabilizer Size	Valid	
Calibration Status		



Master: 5-Jun-2007 22:52									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Magnesium Block									
Phase	LS window 3 - Mg CPS	Value	Phase	SS window 1 - Mg CPS	Value	Phase	SS window 3 - Mg CPS	Value	
Master		1260	Master		3103	Master		7772	
	250.0 (Minimum) 4125 (Nominal) 8000 (Maximum)			700.0 (Minimum) 9350 (Nominal) 18000 (Maximum)			2500 (Minimum) 23750 (Nominal) 45000 (Maximum)		

























Master: 5-Jun-2007 22:52									
6.75-in. Azimuthal Density Neutron Calibration									
Density: Aluminum Block									
Phase	LS window 3 - Al CPS	Value	Phase	SS window 1 - Al CPS	Value	Phase	SS window 3 - Al CPS	Value	




Master		190.0	Master		1596	Master		4930
50.00 (Minimum)	725.0 (Nominal)	1400 (Maximum)	500.0 (Minimum)	4250 (Nominal)	8000 (Maximum)	1500 (Minimum)	15750 (Nominal)	30000 (Maximum)

Master: 5-Jun-2007 22:52											
6.75-in. Azimuthal Density Neutron Calibration											
Density: Background											
Phase	LS window 3 – Background CPS		Value	Phase	SS window 1 – Background CPS		Value	Phase	SS window 3 – Background CPS		Value
Master			46.17	Master			130.4	Master			560.4
15.00 (Minimum)	82.50 (Nominal)	150.0 (Maximum)		40.00 (Minimum)	220.0 (Nominal)	400.0 (Maximum)		150.0 (Minimum)	825.0 (Nominal)	1500 (Maximum)	

Master: 5-Jun-2007 22:52											
6.75-in. Azimuthal Density Neutron Calibration											
Density: Water Block Check											
Phase	Long spacing water density G/C3			Value	Phase	Short spacing water density G/C3			Value		
Master				1.040	Master				1.135		
1.024 (Minimum)		1.039 (Nominal)		1.054 (Maximum)	1.096 (Minimum)		1.126 (Nominal)		1.156 (Maximum)		

Master: 5-Jun-2007 22:52														
6.75-in. Azimuthal Density Neutron Calibration														
Neutron: 3-Point Calibration														
Phase	Far 1 tube 1 Air	Point Measure	CPS	Value	Phase	Far 1 tube 1 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 1 H2O	Point Measure	CPS	Value
Master				22.54	Master				5.441	Master				2.677
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 2 Air	Point Measure	CPS	Value	Phase	Far 1 tube 2 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 2 H2O	Point Measure	CPS	Value
Master				23.65	Master				5.587	Master				2.757
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 1 tube 3 Air	Point Measure	CPS	Value	Phase	Far 1 tube 3 Rod	Point Measure	CPS	Value	Phase	Far 1 tube 3 H2O	Point Measure	CPS	Value
Master				23.24	Master				5.623	Master				2.714
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 1 Air	Point Measure	CPS	Value	Phase	Far 2 tube 1 Rod	Point Measure	CPS	Value	Phase	Far 2 tube 1 H2O	Point Measure	CPS	Value
Master				22.73	Master				5.656	Master				2.671
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 2 Air	Point Measure	CPS	Value	Phase	Far 2 tube 2 Rod	Point Measure	CPS	Value	Phase	Far 2 tube 2 H2O	Point Measure	CPS	Value
Master				24.00	Master				5.803	Master				2.779
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Far 2 tube 3 Air	Point Measure	CPS	Value	Phase	Far 2 tube 3 Rod	Point Measure	CPS	Value	Phase	Far 2 tube 3 H2O	Point Measure	CPS	Value
Master				22.27	Master				5.432	Master				2.612
	13.30 (Minimum)	19.05 (Nominal)	24.70 (Maximum)			3.400 (Minimum)	4.857 (Nominal)	6.200 (Maximum)			1.600 (Minimum)	2.363 (Nominal)	3.100 (Maximum)	
Phase	Near 1 tube 1 Air	Point Measure	CPS	Value	Phase	Near 1 tube 1 Rod	Point Measure	CPS	Value	Phase	Near 1 tube 1 H2O	Point Measure	CPS	Value
Master				556.2	Master				876.7	Master				379.2
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)	
Phase	Near 2 tube 1 Air	Point Measure	CPS	Value	Phase	Near 2 tube 1 Rod	Point Measure	CPS	Value	Phase	Near 2 tube 1 H2O	Point Measure	CPS	Value
Master				558.1	Master				871.4	Master				378.3
	345.0 (Minimum)	487.5 (Nominal)	595.0 (Maximum)			535.0 (Minimum)	768.8 (Nominal)	925.0 (Maximum)			230.0 (Minimum)	343.7 (Nominal)	430.0 (Maximum)	

Master: 5-Jun-2007 22:52											
6.75-in. Azimuthal Density Neutron Calibration											
Neutron: Water Block Check											
Phase	Far Neutron water porosity PU								Value		
Master									92.72		
	90.00 (Minimum)			100.0 (Nominal)				125.0 (Maximum)			



6.75-in. Array Resistivity Compensated / Equipment Identification

Primary Equipment:

Tool Name and Serial Number

ARC6 – BA

1708











ARC675 Calibration Status

Valid

Master: 7-May-2007 12:04

6.75-in. Array Resistivity Compensated Calibration











Resistivity: Air

Phase	Phase-Shift T1	Value	Phase	Phase-Shift T2	Value	Phase	Phase-Shift T3	Value
Master		1.806	Master		-1.723	Master		1.740
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T4	Value	Phase	Phase-Shift T5	Value	Phase	Phase-Shift T1 at 400KHz	Value
Master		-1.764	Master		1.719	Master		-0.3198
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T2 at 400KHz	Value	Phase	Phase-Shift T3 at 400KHz	Value	Phase	Phase-Shift T4 at 400KHz	Value
Master		0.2243	Master		-0.2871	Master		0.2060
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)			-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)	
Phase	Phase-Shift T5 at 400KHz	Value						
Master		-0.3009						
	-3.900 (Minimum)      0.1000 (Nominal)      4.100 (Maximum)							

Master: 7-May-2007 12:04

6.75-in. Array Resistivity Compensated Calibration


Resistivity: Air

Phase	Attenuation T1	Value	Phase	Attenuation T2	Value	Phase	Attenuation T3	Value
Master		8.454	Master		6.487	Master		5.082
	6.500 (Minimum)      8.500 (Nominal)      10.50 (Maximum)			4.500 (Minimum)      6.500 (Nominal)      8.500 (Maximum)			2.500 (Minimum)      4.500 (Nominal)      6.500 (Maximum)	
Phase	Attenuation T4	Value	Phase	Attenuation T5	Value	Phase	Attenuation T1 at 400KHz	Value
Master		4.394	Master		3.633	Master		8.429
	2.600 (Minimum)      4.600 (Nominal)      6.600 (Maximum)			1.600 (Minimum)      3.600 (Nominal)      5.600 (Maximum)			6.500 (Minimum)      8.500 (Nominal)      10.50 (Maximum)	
Phase	Attenuation T2 at 400KHz	Value	Phase	Attenuation T3 at 400KHz	Value	Phase	Attenuation T4 at 400KHz	Value
Master		6.520	Master		5.049	Master		4.421
	4.500 (Minimum)      6.500 (Nominal)      8.500 (Maximum)			2.500 (Minimum)      4.500 (Nominal)      6.500 (Maximum)			2.600 (Minimum)      4.600 (Nominal)      6.600 (Maximum)	
Phase	Attenuation T5 at 400KHz	Value						
Master		3.611						
	1.600 (Minimum)      3.600 (Nominal)      5.600 (Maximum)							

Master: 7-May-2007 10:29

6.75-in. Array Resistivity Compensated Calibration

Gamma Ray: Blanket

Phase	Gamma ray factor (equals Calibration Gain multiplied by API Gain Factor) CPS	Value
Master		5.138
	2.780 (Minimum)      4.800 (Nominal)      6.000 (Maximum)	

Client..... ESSO Australia Pty Ltd  
Field..... Fortescue

Well..... FTA A4c  
API number.....  
Engineer..... MYT/AK/ML

RIG..... ISDL 175  
STATE..... Victoria

Spud date..... 09-Jul-07  
Last survey date..... 15-Jul-07  
Total accepted surveys... 46  
MD of first survey..... 2070.00 m  
MD of last survey..... 3314.00 m

----- Survey calculation methods-----  
Method for positions..... Minimum curvature  
Method for DLS..... Mason & Taylor

----- Depth reference -----  
Permanent datum..... Mean Sea Level  
Depth reference..... Driller's Depth  
GL above permanent..... -69.00 m  
KB above permanent..... Top Drive  
DF above permanent..... 42.50 m

----- Vertical section origin-----  
Latitude (+N/S-)..... 0.32 m  
Departure (+E/W-)..... 6.39 m

----- Platform reference point-----  
Latitude (+N/S-).....  
Departure (+E/W-).....

Azimuth from Vsect Origin to target: 80.33 degrees

----- Geomagnetic data -----  
Magnetic model..... BGGM version 2007  
Magnetic date..... 09-Jul-2007  
Magnetic field strength... 1199.52 HCNT  
Magnetic dec (+E/W-)..... 13.21 degrees  
Magnetic dip..... -68.86 degrees

----- MWD survey Reference Criteria -----  
Reference G..... 1000.04 mGal  
Reference H..... 1199.52 HCNT  
Reference Dip..... -68.86 degrees  
Tolerance of G..... (+/-) 2.50 mGal  
Tolerance of H..... (+/-) 6.00 HCNT  
Tolerance of Dip..... (+/-) 0.45 degrees

----- Corrections -----  
Magnetic dec (+E/W-)..... 13.21 degrees  
Grid convergence (+E/W-).. -0.79 degrees  
Total az corr (+E/W-)..... 14.00 degrees  
(Total az corr = magnetic dec - grid conv)  
Survey Correction Type ...:  
I=Sag Corrected Inclination  
M=Schlumberger Magnetic Correction  
S=Shell Magnetic Correction  
F=Failed Axis Correction  
R=Magnetic Resonance Tool Correction  
D=Dmag Magnetic Correction

[(c)2007 IDEAL ID12\_OC\_11]  
SCHLUMBERGER Survey Report

15-Jul-2007 19:28:05

Page 2 of 3

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
1	2070.00	60.46	69.02	0.00	1455.44	1215.21	440.78	1164.06	1244.72	69.26	0.00	TIP	None
2	2075.22	60.74	68.64	5.22	1458.00	1219.66	442.42	1168.30	1249.27	69.26	2.53	PUP	None
3	2104.04	57.41	70.90	28.82	1472.81	1243.96	450.98	1191.49	1273.98	69.27	4.07	PUP	None
4	2132.38	52.95	73.86	28.34	1488.99	1266.99	458.03	1213.65	1297.20	69.32	5.46	PUP	None
5	2160.80	50.00	75.47	28.42	1506.69	1289.11	463.92	1235.09	1319.34	69.41	3.44	PUP	None
6	2189.09	47.83	78.49	28.29	1525.29	1310.39	468.73	1255.85	1340.48	69.53	3.39	PUP	None
7	2217.82	46.12	81.05	28.73	1544.89	1331.39	472.47	1276.52	1361.15	69.69	2.69	PUP	None
8	2246.55	44.28	83.19	28.73	1565.14	1351.76	475.27	1296.71	1381.06	69.87	2.53	PUP	None
9	2275.38	42.35	84.89	28.83	1586.11	1371.50	477.32	1316.38	1400.24	70.07	2.38	PUP	None
10	2303.78	40.31	86.91	28.40	1607.44	1390.16	478.67	1335.08	1418.30	70.28	2.62	PUP	None
11	2332.03	38.31	88.99	28.25	1629.29	1407.90	479.32	1352.96	1435.36	70.49	2.58	PUP	None
12	2360.24	36.01	91.52	28.21	1651.78	1424.68	479.25	1370.00	1451.40	70.72	2.98	PUP	None
13	2388.62	33.42	94.08	28.38	1675.10	1440.46	478.48	1386.14	1466.39	70.96	3.19	PUP	None
14	2417.82	31.95	98.61	29.20	1699.68	1455.61	476.75	1401.80	1480.65	71.22	2.98	PUP	None
15	2446.19	32.67	103.27	28.37	1723.66	1469.79	473.86	1416.68	1493.83	71.51	2.78	PUP	None
16	2474.01	32.66	109.44	27.82	1747.09	1483.27	469.64	1431.07	1506.16	71.83	3.65	PUP	None
17	2502.20	32.12	111.79	28.19	1770.90	1496.31	464.33	1445.20	1517.96	72.19	1.48	PUP	None
18	2530.84	32.51	112.70	28.64	1795.10	1509.30	458.53	1459.37	1529.71	72.56	0.66	PUP	None
19	2560.27	30.91	113.14	29.43	1820.14	1522.34	452.51	1473.62	1541.53	72.93	1.67	PUP	None
20	2587.96	30.34	113.08	27.69	1843.96	1534.19	446.97	1486.59	1552.33	73.27	0.63	PUP	None
21	2616.18	28.63	112.81	28.22	1868.53	1545.89	441.56	1499.38	1563.05	73.59	1.85	PUP	None
22	2644.36	27.26	112.58	28.18	1893.42	1557.05	436.46	1511.56	1573.32	73.89	1.49	PUP	None
23	2673.59	27.96	112.94	29.23	1919.32	1568.48	431.22	1524.05	1583.89	74.20	0.75	PUP	None
24	2701.68	27.66	114.31	28.09	1944.17	1579.43	425.97	1536.06	1594.03	74.50	0.77	PUP	None
25	2730.47	27.94	114.54	28.79	1969.64	1590.55	420.42	1548.29	1604.35	74.81	0.32	PUP	None
26	2758.02	27.99	116.31	27.55	1993.97	1601.12	414.87	1559.95	1614.18	75.11	0.92	PUP	None
27	2786.20	27.96	116.83	28.18	2018.86	1611.78	408.96	1571.78	1624.11	75.42	0.27	PUP	None
28	2814.56	28.63	116.45	28.36	2043.83	1622.62	402.93	1583.79	1634.24	75.73	0.75	PUP	None
29	2842.84	28.02	116.43	28.28	2068.72	1633.46	396.96	1595.81	1644.44	76.03	0.66	PUP	None
30	2870.59	28.39	115.85	27.75	2093.18	1644.09	391.18	1607.58	1654.49	76.32	0.51	PUP	None

[(c)2007 IDEAL ID12\_OC\_11]  
SCHLUMBERGER Survey Report

15-Jul-2007 19:28:05

Page 3 of 3

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/100f)	Srvy tool type	Tool Corr (deg)
31	2898.01	27.75	115.66	27.42	2117.37	1654.61	385.57	1619.20	1664.47	76.61	0.72	PUP	None
32	2926.40	28.41	115.58	28.39	2142.42	1665.51	379.79	1631.25	1674.88	76.89	0.71	PUP	None
33	2955.11	28.90	115.68	28.71	2167.61	1676.75	373.84	1643.66	1685.64	77.19	0.52	PUP	None
34	2983.52	28.14	114.45	28.41	2192.58	1687.90	368.09	1655.95	1696.37	77.47	1.03	PUP	None
35	3011.74	28.49	114.59	28.22	2217.42	1698.97	362.53	1668.13	1707.07	77.74	0.38	PUP	None
36	3040.18	28.03	115.28	28.44	2242.47	1710.05	356.86	1680.34	1717.81	78.01	0.60	PUP	None
37	3069.23	28.34	115.61	29.05	2268.07	1721.28	350.96	1692.73	1728.73	78.29	0.36	PUP	None
38	3097.40	27.85	113.97	28.17	2292.93	1732.21	345.40	1704.77	1739.41	78.55	0.99	PUP	None
39	3125.64	28.02	114.12	28.24	2317.87	1743.22	340.01	1716.85	1750.19	78.80	0.20	PUP	None
40	3154.09	27.97	114.63	28.45	2343.00	1754.28	334.50	1729.01	1761.07	79.05	0.26	PUP	None

41	3182.78	28.67	115.11	28.69	2368.25	1765.49	328.77	1741.36	1772.13	79.31	0.78	PUP	None
42	3211.72	28.19	115.42	28.94	2393.70	1776.79	322.89	1753.82	1783.30	79.57	0.53	PUP	None
43	3239.94	28.28	114.88	28.22	2418.56	1787.75	317.22	1765.91	1794.17	79.82	0.29	PUP	None
44	3268.27	28.12	115.16	28.33	2443.53	1798.76	311.56	1778.04	1805.13	80.06	0.22	PUP	None
45	3294.80	28.05	115.59	26.53	2466.94	1808.98	306.21	1789.32	1815.33	80.29	0.25	PUP	None
46	3314.00	28.00	115.89	19.20	2483.89	1816.33	302.29	1797.45	1822.69	80.45	0.24	Projection to TD	
[(c)2007 IDEAL ID12_0C_11]													

Company:

ESSO Australia Pty Ltd

Well:

FTA A4c

Field:

Fortescue

Rig:

ISDL 175

State:

Victoria

VISION Service

1:500 Measured Depth

Recorded Mode Log

Schlumberger

8.5 in. Section