

Potassium	%	4.2									
Environmental data											
GR											
Mud weight	ppg	9.75									
Bit size	in.	8.5									
Resistivity											
Neutron porosity											
Hole Size	in	8.5									
Mud weight	ppg	9.75									
Temperature	°C	83									
Mud salinity	ppk	66.87									
Formation salinity		n/a									
Recording rate 1	SEC	5									
Recording rate 2	SEC	10									
Filtering GR		3pt									
Filtering density		3pt									
Filtering Neutron		3pt									
Company representative	R.Spence	G.Campbell	T.Bassett								
Schlumberger D&M Personnel	G.Sparrow	A.Kohli	C.Hibberson	C.Cocks	M.How						

<p style="text-align: center;">DISCLAIMER</p> <p>THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.</p>		
<p>OTHER SERVICES FOR RUN 2</p> <p>Directional Drilling Directional Surveys Annulus Pressure & Temperature</p>	OTHER SERVICES FOR RUN	OTHER SERVICES FOR RUN
<p>REMARKS: RUN NUMBER 2</p> <p>Depth is reference to Driller's Depth.</p> <p>Gamma Ray is corrected for mud weight, tool size and bit size.</p> <p>Resistivity is borehole compensated and environmentally corrected.</p> <p>Neutron Porosity is corrected for the effects of borehole size, bit size, temperature mud salinity and mud hydrogen index, (a factor of mud weight, mud temperature and pressure).</p> <p>Neutron Porosity is calculated using a limestone matrix density of 2.71 g/cm3.</p> <p>Delta-T is borehole compensated.</p> <p>POOH upon reaching TD of HLA-A7A</p>	REMARKS: RUN NUMBER	REMARKS: RUN NUMBER

EQUIPMENT DESCRIPTION		
RUN2	RUN	RUN

Maximum string diameter 8.50 in.

6–3/4 in. adnVISION*	Neutron F	35.05	37.02
DHS: 8.3A02	Neutron N	34.90	
BladeOD: 8–1/4 in.	Density S	34.03	
S/N: AD09	Density L	33.93	
	UltraSonic	33.55	
	R-O Port	32.79	

6-3/4 in. sonicVISION®
DHS: 6.6b04
S/N: 607

Delta-T — 27.42
R-O port — 27.02

6-5/8 in. ILS
S/N: OSS061160C

6-7/8 in. PowerPulse*		22.33
MDC: V875		
MEC: 1281		
MDI: 1751		
MGR: 146		
DHS: 8.0C03		
	D&I	18.08
	APWD	14.83

6-3/4 in. GeoVISION*
DHS: 6.2B01
Blade OD: 8-1/8 in.
S/N: 41876

Shallow 12.44
Medium 12.32
Deep 12.14
Ring Res 11.97
R-O port 11.83
GR 11.61

13.94

7 in. PowerPak* Motor	10.28
A700GT 7:8	
S/N: N7411	
0 deg. Bent Housing	
Bit Res	5.55

8-1/2 in. Smith PDC Bit

S/N: 212954

 0.00

0.22

All lengths in Meters

Variable Name	Variable Description	Run Name & Value
Run Number		2
General Information		
BHT_RM	Bottom Hole Temperature (RM)	82.999994
BSAL_RM	Mud Salinity (RM)	74.300003
BS_RM	Bit Size (RM)	8.500000
COEF_M	User Defined FEXP in Clean Sand	1.650000
C_WS	Overpressure correction to Sw and M	1.000000
FEXP	Formation Factor Exponent(RM)	2.000000
FNUM	Formation Factor Enumerator(RM)	1.000000
FPHI_RM	Formation Factor Porosity Source (RM)	XPLOT
MST_RM	Mud Sample temperature (RM)	21.49999
MW_RM	Mud Weight (RM)	9.750000
OBMF_RM	Oil Based Mud (RM)	NO
RHOF_RM	Mud Filtrate Density (RM)	1.000000
RHOM_RM	Matrix density (RM)	2.710000
RMS_RM	Resistivity of Mud Sample (RM)	0.109900
RWA_COMP_M	Rwa computation model	BASIC
RWA_DEN_AD	Rwa Density Input ADN	RHOB
RWA_DEN_CD	Rwa Density Input CDN	RHOB
RWA_DEN_IN	Rwa Density Input	RHOB
RWA_FORM_M	Rwa computation formation model	CLASTIC
RWA_RES_IN	Rwa computation resistivity input	RT
RWS_RM	Resistivity of Connate Water (RM)	1.000000
SHT_RM	Surface Hole Temperature (RM)	
TD_RM	Total Measured Depth (RM)	3038.000000
TWS_RM	Temperature of Connate Water (RM)	75.000000
VF_ILLI	Fraction of illite in shales	0.500000
VF_KAOL	Fraction of kaolinite in shales	0.500000
VF_MONT	Fraction of montmorillonite in shales	0.000000
XPDM_RM	Cross plot density porosity multiplier	0.675000
XPNM_RM	Cross plot neutron porosity multiplier	0.325000
ISONIC		
FP_SD	First Sample delay	400.00
STC_CF	Center frequency of Filter	13.00
STC_BW	Bandwidth (kHz)	Default
STC_RWI	Receiver waveform ignored	None
PM_TOFF	Tool Time offset from surface system	0.00
DT_COH	Delta-T Coherence Cutoff Value	0.70
PPC_PF	Porosity Formula	Raymer-Hunt
PPC_PS	Sonic Porosity Source	DTRA
PPC_MDT	Matrix Delta-T	47.60
PPC_FDT	Fluid Delta-T	189.00
RAB		
LWD_RM/STATION_FILE/PARAMETER	Station Time-frame file name	Station
RAB/BTN_SLV_SIZE/PARAMETER	RAB: Button Sleeve Diameter	RAB6:
RAB/STAB_SIZE/PARAMETER	RAB: Stabilizer Diameter	RAB6:
BDBHCA	RAB: Button Deep Borehole A Factor	0.003550
BDBHCB	RAB: Button Deep Borehole B Factor	0.000000
BHA_COEF_V	RAB: BHA Coef Generator Version	62012.000000
BITBHCA	RAB: Bit A Borehole Factor	0.057576
BITBHCB	RAB: Bit B Borehole Factor	0.000000
BIT_K_FACT	RAB: Bit K Factor	14.546491
BMBHCA	RAB: Button Medium Borehole A Factor	0.022474
BMBHCB	RAB: Button Medium Borehole B Factor	0.000000
BSBHCA	RAB: Button Shallow Borehole A Factor	0.021984
BSBHCB	RAB: Button Shallow Borehole B Factor	0.000000
BUT_KIMP_A	RAB: Button Impedance Coeff A	0.000000
BUT_KIMP_B	RAB: Button Impedance Coeff B	0.000000
DBUTTON_K	RAB: Button Deep K factor	0.004594
DHS_VERSION	RAB: DownHole Software Version	6.200100
GR_BHC_TOO	RAB: Gamma-Ray Borehole Coeff 1	6.750000
HI_CSDEPTH	RAB: Allow Hi-Resolution CS_DEPTH Image Data Output	NO
HI_DLIS_OU	RAB: Allow Hi-Resolution DLIS Image Data Output	NO
HI_RIVER_O	RAB: Allow Hi-Resolution River for Image Data Output	NO
IMAGE_MAX	RAB: GR Image Maximum Scale Value	120.000000
IMAGE_MAX	RAB: Image Maximum Resistivity Value	100.000000
IMAGE_MIN	RAB: GR Image Minimum Scale Value	20.000000
IMAGE_MIN	RAB: Image Minimum Resistivity Value	1.000000
JSD_RAB	RAB Acquisition start date	1.000000
MAG_DECL_R	RAB: Magnetic Declination	13.229998
MAG_INCL_R	RAB: Magnetic Dip	-68.859993
MBUTTON_K	RAB: Button Medium K Factor	0.005264
OBM	RAB: Oil base Mud	NO
ORIENTATIO	Rab Image Orientation	TOH
RABBD A0	RAB: Button Deep A0 Coeff	-0.049562
RABBD A1	RAB: Button Deep A1 Coeff	0.019485
RABBD A2	RAB: Button Deep A2 Coeff	-0.004357
RABBD A3	RAB: Button Deep A3 Coeff	0.000455
RABBD A4	RAB: Button Deep A4 Coeff	-0.000017
RABBD A5	RAB: Button Deep A5 Coeff	0.000000
RABBD MIN	RAB: Button Deep Minimum Value	0.051084
RABBITA0	RAB: Bit A0 Coeff	3.851055
RABBITA1	RAB: Bit A1 Coeff	-4.225814
RABBITA2	RAB: Bit A2 Coeff	11.365308
RABBITA3	RAB: Bit A3 Coeff	-11.825766
RABBITA4	RAB: Bit A4 Coeff	4.766129
RABBITA5	RAB: Bit A5 Coeff	0.000000

RABBITMIN	RAB: Bit Minimum Value	21.114918
RABBMA0	RAB: Button Medium A0 Coeff	-0.059887
RABBMA1	RAB: Button Medium A1 Coeff	0.025592
RABBMA2	RAB: Button Medium A2 Coeff	-0.005948
RABBMA3	RAB: Button Medium A3 Coeff	0.000628
RABBMA4	RAB: Button Medium A4 Coeff	-0.000024
RABBMA5	RAB: Button Medium A5 Coeff	0.000000
RABBMIN	RAB: Button Medium Minimum Value	0.059503
RABBSA0	RAB: Button Shallow A0 Coeff	-0.071674
RABBSA1	RAB: Button Shallow A1 Coeff	0.030295
RABBSA2	RAB: Button Shallow A2 Coeff	-0.006843
RABBSA3	RAB: Button Shallow A3 Coeff	0.000699
RABBSA4	RAB: Button Shallow A4 Coeff	-0.000026
RABBSA5	RAB: Button Shallow A5 Coeff	0.000000
RABBSMIN	RAB: Button Shallow Minimum Value	0.086483
RABDHS	RAB Down Hole Software	4.000000
RABEC	RAB: Resistivity Env-Cor	YES
RABRNGA0	RAB: RING A0 Coeff	-0.045451
RABRNGA1	RAB: RING A1 Coeff	0.017730
RABRNGA2	RAB: RING A2 Coeff	-0.004016
RABRNGA3	RAB: RING A3 Coeff	0.000426
RABRNGA4	RAB: RING A4 Coeff	-0.000016
RABRNGA5	RAB: RING A5 Coeff	0.000000
RABRNGMIN	RAB: Ring Minimum Value	1.696958
RAB_BIT_EC	Bit Resistivity for ECAL_RAB?	YES
RAB_BIT_IN	Input Bit Resistivity for Inversion? (Recommended at the bit)	YES
RAB_CALIPE	Compute ECAL_RAB?	NO
RAB_DEEPBT	Deep Button Resistivity for ECAL_RAB?	YES
RAB_DEEPBT	Input Deep Button Resistivity for Inversion?	YES
RAB_INVERS	Perform Rt Inversion?	NO
RAB_INVERS	RAB Bit Sensor Weight for Inversion[0,1]	1.000000
RAB_INVERS	Ending Depth for GR Cutoff in Zone1	100000.000000
RAB_INVERS	Continuity Multiplier[0,1]	0.500000
RAB_INVERS	RAB Deep Button Sensor Weight for Inversion[0,1]	1.000000
RAB_INVERS	RAB inversion for Dh?	YES
RAB_INVERS	RAB inversion for Di?	YES
RAB_INVERS	GR Cutoff for Shale Formation	75.000000
RAB_INVERS	GR Cutoff for Shale Formation in Zone1	75.000000
RAB_INVERS	GR Cutoff in Zone10	75.000000
RAB_INVERS	GR Cutoff in Zone2	75.000000
RAB_INVERS	GR Cutoff in Zone3	75.000000
RAB_INVERS	GR Cutoff in Zone4	75.000000
RAB_INVERS	GR Cutoff in Zone5	75.000000
RAB_INVERS	GR Cutoff in Zone6	75.000000
RAB_INVERS	GR Cutoff in Zone7	75.000000
RAB_INVERS	GR Cutoff in Zone8	75.000000
RAB_INVERS	GR Cutoff in Zone9	75.000000
RAB_INVERS	RAB Medium Button Sensor Weight for Inversion[0,1]	1.000000
RAB_INVERS	Resistivity Cutoff for Shale Formation	2.000000
RAB_INVERS	Resistive Invasion Allowed	NO
RAB_INVERS	RAB Ring Sensor Weight for Inversion[0,1]	1.000000
RAB_INVERS	RAB inversion for Rmud?	NO
RAB_INVERS	RAB inversion for Rt?	YES
RAB_INVERS	Rt to R-deepest separation penalty multiplier[0,1]	0.500000
RAB_INVERS	RAB inversion for Rxo?	YES
RAB_INVERS	RAB Shallow Button Sensor Weight for Inversion[0,1]	1.000000
RAB_INVERS	Inversion Threshold[0, 0.3]	0.010000
RAB_INVERS	Formation Water Resistivity	0.100000
RAB_INVERS	Formation Water Temperature	150.000000
RAB_MEDIUM	Medium Button Resistivity for ECAL_RAB?	YES
RAB_MEDIUM	Input Medium Button Resistivity for Inversion?	YES
RAB_QUAD	RAB: Process Quadrant data ?	YES
RAB_RIGMOD	Bit on Bottom?	YES
RAB_RING_E	Ring Resistivity for ECAL_RAB?	YES
RAB_RING_I	Input RING Resistivity for Inversion?	YES
RAB_SHALLO	Shallow Button Resistivity for ECAL_RAB?	YES
RAB_SHALLO	Input Shallow Button Resistivity for Inversion?	YES
RAB_TAB	RAB: Compute TAB ?	YES
RAB_TECHLO	RAB: Generate Techlog ?	YES
RAB_TEMP_S	RAB Temperature Selection	MEASURED
RAB_TICKS	RAB: Generate Ticks ?	YES
READOUT_PO	RAB: ROP to Bit Face Distance	38.812336
RINGBHCA	RAB: Ring Borehole A Factor	0.159086
RINGBHCB	RAB: Ring Borehole B Factor	0.000000
RING_KIMP_	RAB: Ring Impedance Coeff A	0.000000
RING_KIMP_	RAB: Ring Impedance Coeff B	0.000000
RING_K_FAC	RAB: Ring K Factor	0.153558
SBUTTON_K	RAB: Button Shallow K Factor	0.007135
SCALE_IMAG	RAB: Process Image Data	YES
SHT_RM	Ground Level Temperature (Mud-Line When Offshore) (RM)	25.000000
STAB	RAB: Run with Stabilizer	YES
TFF_OFFSET	RAB Time-Frame File Time Offset	0.000000
TIMEFRAME_	RAB: Time Frame File Name	0.000000
TOOLTYPE	RAB: Azimuthal Tool	YES
TS_VERSION	RAB: ToolScope Software Version	0.000000
VRAB6	Rab Tool type (ENP/PILOT)	RAB6_C_SERIES
WIN_SIZE_D	RAB: Window Size for Scaling Dynamic Image	3.000000

ADN

ADN_CHASSI	ADN Chassis Type String	ADN
ADN_COLLAR	ADN Collar Type String	ADN
ADN_STAB_S	ADN Stabilizer Type String	ADN
ALPHA_COMP	Perform Density Enhanced Vertical Resolution process ?	NO
ALPHA_COMP	Perform Neutron Enhanced Vertical Resolution process ?	NO
AVE ADN	ADN/Array Channels: perform averaging (RM) :	YES
A_DHS	ADN Down Hole Software Version String	YES

A_DNS	ADN Down Hole Software Version String	1.25
CHI_RM	Caliper High limit from BS (RM)	3.000000
CLO_RM	Caliper Low limit from BS (RM)	0.000000
DEVI	Well Section Deviation	35.820000
DTIK_SEL	ADN: Density Tick Channel Name	LSAZ
DTMUD	Delta-T for Mud	188.449997
DYN_IMG_CO	Generate Dynamic Normalized Image?	YES
ECC_CORR_A	Perform Eccentering Correction for TNPH?	YES
ENVCOR	Neutron Quadrant Processing: Environmental Correction?	YES
EVRL	EVR Process averaging number of samples (RM)	49
FCD	Future Casing (Outer) Diameter	0.000000
GCSE	Generalized Caliper Selection	BS
HPS	ADSE-EB (High Pressure Inconel Chassis)?	NO
IBS	Intergal Blade Stabilizer Collar?	YES
IDQT	Image Derived Quality Threshold	2.000000
IHVS	Integrated Hole Volume Start Value (RM)	0.000000
IMAGE_MAX	Image SOA (Quadrant) Right Scale	2.500000
IMAGE_MAX	Image PEF(Segment) Right Scale	6.000000
IMAGE_MAX	Image RHOB(Segment) Right Scale	2.650000
IMAGE_MIN	Image SOA (Quadrant) Left Scale	0.000000
IMAGE_MIN	Image PEF(Segment) Left Scale	2.000000
IMAGE_MIN	Image RHOB(Segment) Left Scale	2.050000
LITHO_TYPE	Lithology (RM)	LIME
N1FTU_6_RM	ADN: Neutron Bank 1 Far Tubes used :	1-2-3
N2FTU_6_RM	ADN: Neutron Bank 2 Far Tubes used :	1-2-3
NNTU_RM	ADN Neutron Near Banks Used	1-2
NTIK_SEL	ADN: Neutron Tick Channel Name	FR11
SOCNL	Standoff Distance of the CNL Tool	1.000000
SSIZ_ADN	ADN Stabilizer Size	8.250000
STOH	ADN Density Top of Hole Sector (Left Boundary):	SECTOR_0
TRPM_RM	Average Tool Rotational Speed	20.000000
USMIN_RM	ADN:Minimum Ultrasonic standoff (RM)	0.180000
USWF_RM	ADN:Process Ultrasonic Waveform?	YES
VERS_ADN	ADN Downhole Software Version	8.300000
WSDI	Window Size of Dynamic Normalization Image	15.000000

Schlumberger Drilling & Measurements

Parameter Insert Header Software version 2.0c

IDEAL Version: ID12_0C_09

IDF

RAB	id12_0c_01	MWD_10	id12_0c_01
SON675	id12_0c_01	ADN	id12_0c_01

Format: GeoVISION Density Neutron Log_1 Vertical Scale: 1:200 Graphics File Created: 06-Jun-2007 20:07

PIP SUMMARY

Neutron Samples

Density Samples

Rate of Penetration, Averaged over Last
5ft (ROP5_RM)

200 (M/HR) 0

RAB Gamma Ray (GR_RAB)

0 (GAPI) 200

Vertical Hole Diameter (VERD)

6 (IN) 16

Horizontal Hole Diameter (HORD)

6 (IN) 16

Thermal Neutron Porosity (TNPH)

45 (PU) -15

Bulk Density, Bottom (ROBB)

1.85 (G/C3) 2.85

Density Time After Bit (TAB_DEN)

0 (HR) 10

ADN
Rotational
Speed
(RPM_ADN)
(RPM)

0 250

Photoelectric Factor, Bottom (PEB)



0 (----) 10


Bulk Density Correction, Bottom



(DRHB)
(G/C3) -0.75 0.25



First reading



First reading









































Density Time After Bit (TAB_DEN) (HR)		ADN Rotational Speed (RPM_ADN) (RPM)	Photoelectric Factor, Bottom (PEB) (-----)	Bulk Density Correction, Bottom (DRHB) (G/C3)
0	10	0	10	-0.75
		250		0.25


Neutron: 3-Point Calibration									
Phase	Far 1 tube 1	Air Point Measure	CPS	Value	Phase	Far 1 tube 1	Rod Point Measure	CPS	Value
Master				17.74	Master				4.514
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Far 1 tube 2	Air Point Measure	CPS	Value	Phase	Far 1 tube 2	Rod Point Measure	CPS	Value
Master				18.39	Master				4.543
	16.00 (Minimum)	19.05 (Nominal)	22.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Far 1 tube 3	Air Point Measure	CPS	Value	Phase	Far 1 tube 3	Rod Point Measure	CPS	Value
Master				17.65	Master				4.641
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Far 2 tube 1	Air Point Measure	CPS	Value	Phase	Far 2 tube 1	Rod Point Measure	CPS	Value
Master				18.10	Master				4.770
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Far 2 tube 2	Air Point Measure	CPS	Value	Phase	Far 2 tube 2	Rod Point Measure	CPS	Value
Master				17.65	Master				4.512
	16.00 (Minimum)	19.05 (Nominal)	22.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Far 2 tube 3	Air Point Measure	CPS	Value	Phase	Far 2 tube 3	Rod Point Measure	CPS	Value
Master				17.20	Master				4.435
	15.00 (Minimum)	19.05 (Nominal)	21.00 (Maximum)			4.000 (Minimum)	4.857 (Nominal)	5.500 (Maximum)	
Phase	Near 1 tube 1	Air Point Measure	CPS	Value	Phase	Near 1 tube 1	Rod Point Measure	CPS	Value
Master				472.7	Master				753.5
	400.0 (Minimum)	487.5 (Nominal)	540.0 (Maximum)			610.0 (Minimum)	768.8 (Nominal)	850.0 (Maximum)	
Phase	Near 2 tube 1	Air Point Measure	CPS	Value	Phase	Near 2 tube 1	Rod Point Measure	CPS	Value
Master				460.7	Master				728.3
	400.0 (Minimum)	487.5 (Nominal)	540.0 (Maximum)			610.0 (Minimum)	768.8 (Nominal)	850.0 (Maximum)	

Master: 20-Mar-2007 21:54									
6.75-in. Azimuthal Density Neutron Calibration									
Neutron: Water Block Check									
Phase	Far Neutron water porosity PU							Value	
Master									105.9
	90.00 (Minimum)					100.0 (Nominal)			125.0 (Maximum)

6.75-in. Resistivity At-the-Bit / Equipment Identification									
Primary Equipment: Tool Name and Serial Number Calibration Status									
RAB6 - CA AUTO - 242									

Master: 23-Apr-2007 14:58									
6.75-in. Resistivity At-the-Bit Calibration									
Resistivity: Fixture									
Phase	Ring/T1 factor ----			Value	Phase	Ring/T2 factor ----			Value
Master				1.008	Master				1.002
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)			0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	
Phase	M0/T2 factor ----			Value	Phase	M2/T1 factor ----			Value
Master				1.001	Master				1.008
	0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)			0.9750 (Minimum)	1.000 (Nominal)	1.025 (Maximum)	
Phase	BTN shallow/T1 factor ----			Value	Phase	BTN shallow/T2 factor ----			Value
Master				1.006	Master				0.9990
Phase	BTN medium/T1 factor ----			Value					
Master				1.016					

0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)				0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)				0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)									
Phase		BTN medium/T2 factor -----										Value		Phase		BTN deep/T1 factor -----										Value		Phase		BTN deep/T2 factor -----										Value	
Master												1.009		Master												1.015		Master												1.008	
0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)				0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)				0.9750 (Minimum)				1.000 (Nominal)				1.025 (Maximum)									

Master: Calibration date not found								
6.75-in. Resistivity At-the-Bit Calibration								
Gamma Ray: Blanket								
Phase	Gamma ray factor ----						Value	
Master							1.024	
	0.7500 (Minimum)		1.000 (Nominal)			1.250 (Maximum)		

SCHLUMBERGER

Survey report

5-Jun-2007 01:09:51

Page 1 of 4

Client..... ESSO Australia Pty. Ltd.
Field..... Halibut

Well..... HLA A7A
API number..... N/A
Engineer..... GHS/AK/CH

Spud date..... 19-May-2007
Last survey date..... 29-May-2007
Total accepted surveys... 84
MD of first survey..... 552.00 m
MD of last survey..... 3038.00 m

RIG..... ISDL 453
STATE..... Victoria

----- Survey calculation methods-----
Method for positions..... Minimum curvature
Method for DLS..... Mason & Taylor

----- Geomagnetic data -----
Magnetic model..... BGGM version 2006
Magnetic date..... 21-May-2007
Magnetic field strength... 1199.13 HCNT
Magnetic dec (+E/W-)..... 13.22 degrees
Magnetic dip..... -68.86 degrees

----- Depth reference -----
Permanent datum..... Mean Sea Level
Depth reference..... Drillers Depth
GL above permanent..... -73.00 m
KB above permanent..... TopDrive
DF above permanent..... 29.40 m

----- MWD survey Reference Criteria -----
Reference G..... 1000.04 mGal
Reference H..... 1199.13 HCNT
Reference Dip..... -68.86 degrees
Tolerance of G..... (+/-) 2.50 mGal
Tolerance of H..... (+/-) 6.00 HCNT
Tolerance of Dip..... (+/-) 0.45 degrees

----- Vertical section origin-----
Latitude (+N/S-)..... -5.21 m
Departure (+E/W-)..... 9.70 m

----- Corrections -----
Magnetic dec (+E/W-)..... 13.23 degrees
Grid convergence (+E/W-).. -0.82 degrees
Total az corr (+E/W-)..... 14.05 degrees
(Total az corr = magnetic dec - grid conv)

Azimuth from Vsect Origin to target: 164.58 degrees

Survey Correction Type ...:
I=Sag Corrected Inclination
M=Schlumberger Magnetic Correction
S=Shell Magnetic Correction
F=Failed Axis Correction
R=Magnetic Resonance Tool Correction
D=Dmag Magnetic Correction

[[c)2007 IDEAL ID12_OC_09]
SCHLUMBERGER Survey Report

5-Jun-2007 01:09:51

Page 2 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
1	552.00	17.11	141.77	0.00	547.71	41.16	-41.87	31.57	52.44	142.98	0.00	TIP	None
2	680.34	28.29	165.03	128.34	666.15	89.21	-86.31	51.21	100.35	149.32	1.10	MWD	None
3	709.44	29.61	165.51	29.10	691.61	103.30	-99.93	54.79	113.96	151.27	0.46	MWD	None
4	738.64	32.13	165.79	29.20	716.67	118.28	-114.44	58.50	128.53	152.93	0.86	MWD	None
5	767.94	33.00	166.40	29.30	741.37	134.04	-129.75	62.29	143.93	154.36	0.32	MWD	None
6	797.26	33.94	165.47	29.32	765.82	150.21	-145.44	66.22	159.80	155.52	0.37	MWD	None
11	943.43	33.02	164.23	29.42	887.80	230.74	-222.94	88.10	239.72	158.44	0.09	MWD	None
12	972.49	33.29	164.46	29.06	912.13	246.63	-238.25	92.39	255.53	158.80	0.10	MWD	None
13	1001.57	33.30	164.17	29.08	936.44	262.60	-253.62	96.71	271.43	159.13	0.05	MWD	None
14	1030.51	35.30	165.27	28.94	960.34	278.90	-269.35	101.00	287.66	159.44	0.72	MWD	None
15	1059.91	38.30	166.14	29.40	983.88	296.51	-286.41	105.34	305.17	159.81	1.04	MWD	None
16	1089.48	41.46	165.81	29.57	1006.57	315.46	-304.80	109.94	324.02	160.17	1.07	MWD	None
17	1118.56	41.79	165.62	29.08	1028.31	334.77	-323.52	114.71	343.26	160.48	0.12	MWD	None
18	1147.81	42.11	165.37	29.25	1050.06	354.32	-342.45	119.60	362.74	160.75	0.12	MWD	None
19	1177.07	42.24	164.11	29.26	1071.75	373.97	-361.40	124.77	382.34	160.95	0.29	MWD	None
20	1206.26	41.56	163.55	29.19	1093.47	393.46	-380.13	130.20	401.81	161.09	0.27	MWD	None
21	1235.41	41.52	163.70	29.15	1115.29	412.79	-398.67	135.65	421.12	161.21	0.04	MWD	None
22	1264.68	41.00	165.90	29.27	1137.29	432.09	-417.30	140.71	440.38	161.37	0.53	MWD	None
23	1293.45	40.97	165.76	28.77	1159.01	450.95	-435.59	145.33	459.20	161.55	0.03	MWD	None

24	1322.62	40.85	165.35	29.17	1181.06	470.05	-454.09	150.10	478.26	161.71	0.10	MWD	None
25	1351.88	41.75	165.88	29.26	1203.04	489.36	-472.80	154.89	497.52	161.86	0.33	MWD	None
26	1381.11	41.68	165.73	29.23	1224.86	508.81	-491.65	159.66	516.93	162.01	0.04	MWD	None
27	1410.48	41.62	165.83	29.37	1246.80	528.32	-510.57	164.46	536.41	162.15	0.03	MWD	None
28	1439.66	41.44	165.89	29.18	1268.65	547.66	-529.33	169.19	555.71	162.28	0.06	MWD	None
29	1468.60	42.24	165.47	28.94	1290.21	566.96	-548.04	173.96	574.99	162.39	0.29	MWD	None
30	1497.78	42.38	165.73	29.18	1311.79	586.60	-567.06	178.85	594.60	162.50	0.08	MWD	None

[(c)2007 IDEAL ID12_OC_09]
SCHLUMBERGER Survey Report

5-Jun-2007 01:09:51

Page 3 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
31	1527.56	42.72	165.81	29.78	1333.73	606.74	-586.58	183.80	614.70	162.60	0.12	MWD	None
32	1556.60	42.79	166.01	29.04	1355.05	626.45	-605.71	188.59	634.39	162.71	0.05	MWD	None
33	1585.63	42.76	165.16	29.03	1376.36	646.16	-624.80	193.50	654.08	162.79	0.20	MWD	None
34	1614.64	42.34	164.38	29.01	1397.73	665.77	-643.73	198.66	673.68	162.85	0.23	MWD	None
35	1643.92	41.77	163.89	29.28	1419.47	685.39	-662.59	204.02	693.29	162.89	0.22	MWD	None
36	1673.13	41.66	163.29	29.21	1441.27	704.82	-681.24	209.51	712.73	162.91	0.14	MWD	None
37	1702.00	41.12	163.82	28.87	1462.93	723.91	-699.55	214.91	731.81	162.92	0.22	MWD	None
38	1731.54	41.27	163.73	29.54	1485.16	743.36	-718.23	220.35	751.27	162.94	0.05	MWD	None
39	1760.34	41.34	163.49	28.80	1506.80	762.37	-736.46	225.71	770.28	162.96	0.06	MWD	None
40	1790.23	40.88	164.28	29.89	1529.32	782.02	-755.34	231.17	789.93	162.98	0.23	MWD	None
41	1819.22	40.91	165.98	28.99	1551.23	800.99	-773.69	236.04	808.89	163.03	0.38	MWD	None
42	1848.32	41.04	166.36	29.10	1573.20	820.07	-792.21	240.60	827.94	163.11	0.10	MWD	None
43	1877.46	41.80	166.71	29.14	1595.05	839.34	-810.96	245.09	847.19	163.18	0.27	MWD	None
44	1906.62	42.18	166.88	29.16	1616.73	858.83	-829.96	249.54	866.66	163.27	0.14	MWD	None
45	1935.86	42.33	165.89	29.24	1638.37	878.48	-849.06	254.17	886.29	163.33	0.23	MWD	None
46	1965.15	41.93	165.80	29.29	1660.09	898.12	-868.12	258.98	905.92	163.39	0.14	MWD	None
47	1994.33	41.59	165.57	29.18	1681.86	917.55	-886.95	263.78	925.34	163.44	0.13	MWD	None
48	2023.63	41.94	165.77	29.30	1703.71	937.07	-905.86	268.61	944.84	163.48	0.13	MWD	None
49	2052.91	41.60	166.22	29.28	1725.55	956.57	-924.78	273.33	964.33	163.53	0.15	MWD	None
50	2082.02	41.88	166.48	29.11	1747.27	975.94	-943.61	277.91	983.69	163.59	0.11	MWD	None
51	2111.07	41.44	165.65	29.05	1768.97	995.24	-962.35	282.56	1002.98	163.64	0.24	MWD	None
52	2140.43	41.49	165.44	29.36	1790.98	1014.68	-981.18	287.41	1022.41	163.67	0.05	MWD	None
53	2169.61	41.37	165.29	29.18	1812.85	1033.98	-999.86	292.29	1041.71	163.70	0.05	MWD	None
54	2199.00	41.28	165.36	29.39	1834.93	1053.39	-1018.64	297.20	1061.11	163.73	0.03	MWD	None
55	2228.01	41.21	164.90	29.01	1856.74	1072.51	-1037.12	302.11	1080.23	163.76	0.11	MWD	None
56	2256.68	41.72	165.89	28.67	1878.22	1091.50	-1055.49	306.90	1099.20	163.79	0.29	MWD	None
57	2286.49	41.77	165.89	29.81	1900.46	1111.34	-1074.74	311.74	1119.04	163.82	0.02	MWD	None
58	2314.89	41.71	166.05	28.40	1921.65	1130.24	-1093.08	316.32	1137.93	163.86	0.04	MWD	None
59	2344.75	41.75	165.91	29.86	1943.94	1150.11	-1112.37	321.13	1157.79	163.90	0.03	MWD	None
60	2373.85	41.67	165.80	29.10	1965.66	1169.47	-1131.14	325.87	1177.15	163.93	0.04	MWD	None

[(c)2007 IDEAL ID12_OC_09]
SCHLUMBERGER Survey Report

5-Jun-2007 01:09:51

Page 4 of 4

Seq #	Measured depth (m)	Incl angle (deg)	Azimuth angle (deg)	Course length (m)	TVD depth (m)	Vertical section (m)	Displ +N/S- (m)	Displ +E/W- (m)	Total displ (m)	At Azim (deg)	DLS (deg/10m)	Srvy tool type	Tool Corr (deg)
61	2403.24	41.63	165.76	29.39	1987.62	1189.00	-1150.08	330.66	1196.67	163.96	0.02	MWD	None
62	2432.55	41.61	165.56	29.31	2009.53	1208.46	-1168.94	335.49	1216.13	163.99	0.05	MWD	None
63	2461.53	41.50	165.17	28.98	2031.22	1227.68	-1187.54	340.34	1235.34	164.01	0.10	MWD	None
64	2490.81	41.94	165.15	29.28	2053.08	1247.17	-1206.37	345.33	1254.83	164.03	0.15	MWD	None
65	2520.14	41.75	165.39	29.33	2074.93	1266.73	-1225.29	350.31	1274.39	164.04	0.08	MWD	None
66	2549.14	41.61	165.11	29.00	2096.58	1286.01	-1243.94	355.22	1293.67	164.06	0.08	MWD	None
67	2578.40	41.49	164.85	29.26	2118.48	1305.42	-1262.69	360.25	1313.07	164.08	0.07	MWD	None
68	2607.57	41.91	165.27	29.17	2140.26	1324.82	-1281.44	365.25	1332.47	164.09	0.17	MWD	None
69	2636.75	41.85	165.11	29.18	2161.99	1344.30	-1300.27	370.23	1351.95	164.11	0.04	MWD	None
70	2665.91	41.73	165.00	29.16	2183.73	1363.73	-1319.04	375.24	1371.38	164.12	0.05	MWD	None
71	2678.92	41.58	165.07	13.01	2193.45	1372.38	-1327.40	377.47	1380.03	164.13	0.12	MWD	None
72	2695.05	41.49	164.79	16.13	2205.52	1383.08	-1337.73	380.25	1390.72	164.13	0.13	MWD	None
73	2724.67	41.37	165.09	29.62	2227.73	1402.68	-1356.65	385.35	1410.32	164.14	0.08	MWD	None
74	2752.94	41.14	165.43	28.27	2248.98	1421.32	-1374.68	390.09	1428.96	164.16	0.11	MWD	None
75	2782.04	40.96	165.71	29.10	2270.93	1440.42	-1393.19	394.85	1448.06	164.18	0.09	MWD	None
76	2810.51	40.76	165.74	28.47	2292.46	1459.04	-1411.24	399.44	1466.68	164.20	0.07	MWD	None
77	2839.39	40.92	165.91	28.88	2314.31	1477.93	-1429.55	404.07	1485.56	164.22	0.07	MWD	None
78	2868.67	41.23	165.97	29.28	2336.38	1497.16	-1448.21	408.74	1504.79	164.24	0.11	MWD	None
79	2897.47	41.60	166.15	28.80	2357.98	1516.20	-1466.70	413.33	1523.83	164.26	0.13	MWD	None
80	2926.34	42.00	166.28	28.87	2379.50	1535.44	-1485.39	417.92	1543.06	164.29	0.14	MWD	None
81	2955.29	41.78	166.14	28.95	2401.05	1554.76	-1504.16	422.53	1562.38	164.31	0.08	MWD	None
82	2984.43	41.64	165.94	29.14	2422.81	1574.14	-1522.98	427.20	1581.76	164.33	0.07	MWD	None
83	3013.60	42.16	166.05	29.17	2444.52	1593.62	-1541.88	431.92	1601.23	164.35	0.18	MWD	None
84	3038.00	42.20	166.05	24.40	2462.60	1610.00	-1557.78	435.87	1617.61	164.37	0.02	Proj.	to TD

[(c)2007 IDEAL ID12_OC_09]

Well: **HLA A7A**

Field: **Halibut**

Rig: **ISDL 453**

State: **Victoria**

GeoVISION Density–Neutron

1:200 Measured depth

Recorded Mode Log