

Company: Anzon

Well: Basker 3

Field: Basker

Rig: Ocean Patriot

Country: Australia

GR-CCL
Correlation Run 1:200
Suite4 ; Run1

Ocean Patriot
Basker
VIC/L26
Basker 3
Anzon

LOCATION	
VIC/L26	Elev.: K.B. 21.5 m
Northing : 5759552.0m	G.L. -155.5 m
Easting : 649256.8m	D.F. 21.5 m
Permanent Datum: _____	Mean Sea Level _____
Log Measured From: _____	Drill Floor _____
Drilling Measured From: _____	Drill Floor _____
State: Victoria	Max. Well Deviation 45.7 deg
	Longitude 148 42' 24.94" E
	Latitude 38 17' 58.97" S

Logging Date	4-Jul-2006				
Run Number	1				
Depth Driller	4086 m				
Schlumberger Depth	4076 m				
Bottom Log Interval	3530 m				
Top Log Interval	3484 m				
Casing Fluid Type	Well Fluid				
Salinity					
Density					
Fluid Level	0 m				
BIT/CASING/TUBING STRING					
Bit Size	8.500 in				
From	3520 m				
To	4125 m				
Casing/Tubing Size	4.500 in				
Weight	12.6 lbm/ft				
Grade	L-80				
From	0 m				
To	3555.4 m				
Maximum Recorded Temperatures					
Logger On Bottom	Time				
Unit Number	Location		5:41		
Recorded By	1909	AUSL			
Witnessed By	Kasian S. / Omar Tahmiscic				
	Stuart Thomson				

PVT DATA			
Oil Density	Run 1	Run 2	F
Water Salinity			
Gas Gravity			
Bo			
Bw			
1/Bg			
Bubble Point Pressure			
Bubble Point Temperature			
Solution GOR			
Maximum Deviation	45.7 deg		
CEMENTING DATA			
Primary/Squeeze	Primary		
Casing String No			
Lead Cement Type			
Volume			
Density			
Water Loss			
Additives			
Tail Cement Type			
Volume			
Density			
Water Loss			
Additives			
Expected Cement Top			
Logging Date			
Run Number			
Depth Driller			
Schlumberger Depth			
Bottom Log Interval			
Top Log Interval			
Casing Fluid Type			
Salinity			
Density			
Fluid Level			
BIT/CASING/TUBING STRING			
Bit Size			
From			
To			
Casing/Tubing Size			
Weight			
Grade			
From			
To			
Maximum Recorded Temperatures			
Logger On Bottom			
Unit Number	Location		
Recorded By			
Witnessed By			

Run 4

Date Created: 7-JUL-2006 10:46:11

Logging Cable

Type:	2-32ZT
Serial Number:	24187
Length:	6499.86 M
<hr/>	
Conveyance Method:	Wireline
Rig Type:	Offshore Floater with WMC






Reference Log Name: CBL-VDL-GR-CC
Reference Log Run Number: 1
Reference Log Date: 1-Jun-2006
Subsequent Trip Down Log Correction: 2.00 M


1. All Schlumberger depth control policy followed.
2. IDW used as a primary depth measurement.
3. Subsequent trip into the well, Log correlated to CBL-VDL-GR-CCL Dated: 1-Jun-01
- 4.
- 5.
- 6.

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

OTHER SERVICES2
OS1:
OS2:
OS3:
OS4:
OS5:

See remarks on the log.

DOWNHOLE EQUIPMENT		
MH-22 MH-22		9.76
EQF-41 EQF-41		9.28
EQF-41 EQF-41		8.06
EQF-46 EQF-46 6001		6.84
EQF-46 EQF-46 6002		5.01



Client: Anzon

Well: Basker-3

Field: Basker

State: Victoria

Country: Australia

Rig Name: Ocean Patriot


Reference Datum: Mean Sea Level

Elevation: 21.5 m

Drawing Date: 4/27/2006

API #:

Production String	(in) (m)			Well Schematic	(m) (in)			Casing String
	OD	ID	MD		MD	OD	ID	
Kelly Bushing Elevation			0.0					
Derrick Floor Elevation			0.0					
Mean Sea Level			21.5					
Tubing	4.500		0.0		207.9	30.000		Casing Shoe
					1102.3	13.375		Casing Shoe




All Depth as per driller’s depth





Correlation Pass (3485–3530m MD)
Scale 1:200

MAXIS Field Log

Company: Anzon					Well: Basker 3	
Output DLIS Files						
DEFAULT	PERFO_024LUP	FN:43	PRODUCER	04-Jul-2006 05:40	3534.9 M	3386.0 M
RT	PERFO_024LUP	FN:44	PRODUCER	04-Jul-2006 05:41	3534.9 M	3386.0 M
OP System Version: 14C0-302						
MCM						
SHM_GUN	14C0-302	PGGT-C		14C0-302		
PIP SUMMARY						
Time Mark Every 60 S						
Casing Collar Locator (CCL)		Raw Casing Collar Locator (RCCL)				
-19	(-----1	-3	(-----17			







PIP SUMMARY

Time Mark Every 60 S

Format: CCLLog Vertical Scale: 1:200 Graphics File Created: 04-Jul-2006 05:40

OP System Version: 14C0-302

MCM

SHM_GUN 14C0-302 PGGT-C 14C0-302

Output DLIS Files

DEFAULT	PERFO_024LUP	FN:43	PRODUCER	04-Jul-2006 05:40
RT	PERFO_024LUP	FN:44	PRODUCER	04-Jul-2006 05:41

Schlumberger

Correlation Pass (3484–3548m MD)
Scale 1:200 (Splicing)

MAXIS Field Log

Company: Anzon

Well: Basker 3

Input DLIS Files

DEFAULT	SPLICE_PERFO_043	FN:1	PRODUCER	04-Jul-2006 07:04	3552.0 M	3484.0 M
---------	------------------	------	----------	-------------------	----------	----------

Output DLIS Files


DEFAULT	PERFO_047PUP	FN:86	PRODUCER	04-Jul-2006 07:13	3551.2 M	3483.9 M
RT	PERFO_047PUP	FN:87	PRODUCER	04-Jul-2006 07:15	3551.2 M	3483.9 M


OP System Version: 14C0-302
MCM

SHM_GUN	14C0-302	PGGT-C	14C0-302
---------	----------	--------	----------

PIP SUMMARY

☒ Time Mark Every 60 S





PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
DO	System and Miscellaneous	
PP	Depth Offset for Playback Playback Processing	-0.7 M NORMAL

Format: CCLLog		Vertical Scale: 1:200		Graphics File Created: 04-Jul-2006 07:13		
OP System Version: 14C0-302						
MCM						
SHM_GUN	14C0-302	PGGT-C		14C0-302		
Input DLIS Files						
DEFAULT	SPLICE_PERFO_043	FN:1	PRODUCER	04-Jul-2006 07:04	3552.0 M	3484.0 M
Output DLIS Files						
DEFAULT	PERFO_047PUP	FN:86	PRODUCER	04-Jul-2006 07:13		
RT	PERFO_047PUP	FN:87	PRODUCER	04-Jul-2006 07:15		

Company:	Anzon	Schlumberger
Well:	Basker 3	
Field:	Basker	
Rig	Ocean Patriot	
Country:	Australia	
GR-CCL		
Correlation Run 1:200		
Suite4 ; Run1		