



# PRESSURE EVALUATION LOG

WELL : TREFOIL-2



FROM (m): 2500

TO (m): 3150

SCALE: 1/ 500

Country : AUSTRALIA  
Region : TASMANIA  
Field : TREFOIL  
Permit : T/18P  
Well Type : APPRAISAL  
Rig Name : KAN TAN 4

POSITION  
Latitude : 39 53' 07.93" S  
Longitude : 145 22' 14.62" E  
X (m) : 360690.389  
Y (m) : 5583676.588  
RT-Sealevel (m MSL) : 26  
RT-Seabed (m) : 95

CASING SHOE SIZE / DEPTH  
762mm (30") at (m MDRT) : 153.00  
340mm (13 3/8") at (m MDRT) : 930.00  
245mm (9 5/8") at (m MDRT) : 2520.00

Spud Date : 06-10-2009  
Total Depth Date :  
Total Depth (m MDRT) :  
Total Depth (m TVSS) :  
Status :

## ABBREVIATIONS


MW MUD WEIGHT  
FV FUNNEL VISCOSITY  
PV PLASTIC VISCOSITY  
YP YIELD POINT  
FC FILTER CAKE  
SOL SOLIDS  
CR CIRCULATE RETURNS  
SD SAND - %  
S SALINITY - PPM  
RM MUD RESISTIVITY  
RMF MUD FILTRATE  
C CARBIDE TEST  
LAT LOGGED AFTER TRIP  
DS DEVIATION SURVEY  
NB NEW BIT  
RR RERUN BIT  
CB CORE BIT  
WOB WEIGHT ON BIT  
RPM REVS PER MINUTE  
FLC FLOW CHECK  
WL FILTRATE  
PR POOR RETURNS  
NR NO RETURNS  
BG BACKGROUND GAS  
TG TRIP GAS  
STG SHORT TRIP GAS  
CG CONNECTION GAS  
SG SWAB GAS  
SVG SURVEY GAS

## LITHOLOGY LEGEND

	Dolomite		Claystone		Argil Siltstone		Calcareous
	Calcirudite		Siltstone		Sandy Siltstone		Dolomitic
	Calcarenite		Sandstone		Calcareous Siltstone		Fossils
	Calcsiltite		Coal		Argil Sandstone		Foraminiferae
	Calclutite		Intrusive Volcanics		Calcareous Sandstone		Carbonaceous
	Sandy Claystone		Volcaniclastics		Dolomitic Sandstone		Chert
	Silty Claystone		Tuff		Silty Sandstone		Pyrite
	Calcareous Claystone		Cement				Glauconite
	Argil Calclutite						Mica

## ENGINEERING

	Test
	FIT or LOT
	Mud loss
	Mud gain
	Deviation survey
	Core
	Shoe
	Calcimetry




WOB: 1-16 klbs  
RPM: 70-72  
GPM: 714-729  
SPP: 1523-1617 psi


WOB: 1-16 klbs  
RPM: 46-156  
GPM: 684-712  
SPP: 2328-2554 psi


MW: 9.4 EV: 68  
PV/VP: 11/26  
FC: 1/2  
SOL: 3.3% SAND: 0.25%  
CL: 41,500 mg/l

ROP DATA FROM 2523-2543 mMDRT  
FROM SPERRY DATABASE

DATA LOSS FROM 2523-2543 mMDRT  
DUE TO GEOSERVICES COMPUTER  
SOFTWARE MALFUNCTION







MW: 9.4 EV: 46  
PV/YP: 10/25  
FC: 1/2  
SOL: 3.3% SAND: 0.25%  
CL: 41,000 mg/l

